POWER EXTreme LOW-PROFILE, EXTREME HIGH-POWER/SIGNAL COMBO

FEATURES & BENEFITS

- 30 A per power blade and 1 A per signal pin
- Low 7.5 mm profile design (right-angle) for improved system airflow and space savings
- Double-stacked power blades per bank for increased density and power
- Ideal for coplanar and perpendicular applications
- Rugged guide posts are standard for blind mating assistance
- Socket available as vertical with press-fit tails and right-angle through-hole; mates with terminal or standard .062" (1.60 mm) PCB card

Standard Creepage*	5.63 mm	
Standard Clearance*	2.69 mm	

*Selectively loading contacts achieves customer specific creepage and clearance requrements Contact asp@samtec.com





MAX

KEY SPECIFICATIONS

PITCH INSULATOR TERMINAL MATERIAL MATERIAL		PLATING	OPERATING TEMP RANGE	VOLTAGE RATING	MATING CYCLES	LEAD-FREE SOLDERABLE	
(12.00 mm) .472" (pwr) (1.27 mm) .050" (sig)	Black LCP	Signal: Brass Power: Copper Alloy	Au or Sn over 50 μ" (1.27 μm) Ni	40 °C to +105 °C	250 VAC / 500 VDC	250 (MFG Tested)	Yes (RT1 & RT2 option)

Notes:

Notes: Series is rated up to 60 A per power bank. Some lengths, styles and options are non-standard, non-returnable. The Molex EXTreme LPHPower[™] line is a second source to the Samtec LPHT/LPHS Series. *EXTreme LPHPower[™] is a trademark of Molex Incorporated.



30 A SIGNAL/POWER COMBO SYSTEM

SERIES	POWER POSITIONS	SIGNAL POSITIONS	PLATING OPTION	TAIL – GP
LPHT	Total, 2 per power bank	Total	-L	_VP1
Terminal	-02, -04,	-16	= 10 μ" (0.25 μm) Gold on contact,	= Vertical Press-fit (LPHS only)
LPHS Socket	-06, -08, -10	-20	Matte Tin on tail	-RT1
		-24		= Right-angle Through-hole (Use with (1.60 mm) .062" thick board)
		-32		-RT2 = Right-angle Through-hole (Use with (2.36 mm) .093" thick board)

LPHT Board Mates: LPHS





SIGNAL	POWER POSITIONS								
POSITIONS	A (–02)	A (–04)	A (–06)	A (–08)	A (–10)				
-16	(33.97) 1.337	(45.97) 1.810	(57.97) 2.282	(69.97) 2.755	(81.97) 3.227				
-20	(36.51) 1.437	(48.51) 1.910	(60.51) 2.382	(72.51) 2.855	(84.51) 3.327				
-24	(39.05) 1.537	(51.05) 2.010	(63.05) 2.482	(75.05) 2.955	(87.05) 3.427				
-32	(44.13) 1.737	(56.13) 2.210	(68.13) 2.682	(80.13) 3.155	(92.13) 3.627				



View complete specifications at: samtec.com?LPHT

LPHS Board Mates: LPHT



	POWER POSITIONS									
SIGNAL POSITIONS	A (–02)	B (–02)	A (–04)	B (–04)	A (–06)	B (–06)	A (–08)	B (–08)	A (–10)	B (–10)
-16	(31.64)	(25.88)	(43.64)	(37.88)	(55.64)	(49.88)	(67.64)	(61.88)	(79.64)	(73.88)
	1.918	1.019	1.718	1.491	2.191	1.964	2.633	2.436	3.135	2.909
-20	(34.18)	(28.42)	(46.18)	(40.42)	(58.18)	(52.42)	(77.18)	(64.42)	(82.18)	(76.42)
	1.346	1.119	1.818	1.591	2.291	2.064	2.763	2.536	3.235	3.009
-24	(36.72)	(30.96)	(48.72)	(42.96)	(60.72)	(54.96)	(72.72)	(66.96)	(84.72)	(78.96)
	1.446	1.219	1.918	1.691	2.391	2.164	2.863	2.636	3.335	3.109
-32	(41.80)	(36.04)	(53.80)	(48.04)	(65.80)	(60.04)	(77.80)	(72.04)	(89.80)	(84.04)
	1.646	1.419	2.118	1.891	2.591	2.364	3.063	2.836	3.535	3.309





View complete specifications at: samtec.com?LPHS

samtec.com/extreme-lphpower

Unless otherwise approved in writing by Samtec, all parts and components are designed and built according to Samtec's specifications which are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by Samtec manufacturer:

Other Similar products are found below :

647757-1 6643411-1 6646058-2 6646137-1 6646138-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651788-1 696475-1 702-32-01109 703-25-02205 73000005059 73000005642 73080255059 73080965046 765-15-0080A 765-16-0080B 765-18-0080D 829992-1 902-77-02113 PS00/A0620/6300 PS25/A0420/63 129-1J 1409400 AN0024023 E6374G1 e6389g2 157-43GW8 MS3117-14AC 1643543-1 1650540-1 1651811-2 1766260-1 1766282-1 1766966-1 1791340000 NLDFT-3-BL-L-S120-M40A NLDFT-N-W-L-C240-M40B NLS-2-R-C240-M40B NLS-N-W-C240-M40B NPS-3-BL-T6 1986615-1 2-1589900-8 2199314-1 KA8102