





FSH-120-04-F-RA-SL



FSH-110-04-L-DH-SL




SFMH-130-02-L-D-LC



SFMH-105-02-L-D-LC



FSH-120-04-F-DH



SFMH-120-02-L-D

FSH, SFMH SERIES

(1.27 mm) .050"

HIGH-RELIABLE HORIZONTAL SMT

FSH Mates with:
SFMH
Mates with:
FTSH, FSH

SPECIFICATIONS

For complete specifications see www.samtec.com?FSH or www.samtec.com?SFMH

Insulator Material:
Black Liquid Crystal Polymer
Terminal Material:
Phosphor Bronze
Plating:
FSH =
Sn or Au over 50 μ" (1.27 μm) Ni
SFMH =
Au over 50 μ" (1.27 μm) Ni
Current Rating (FSH/SFMH):
2.6 A per pin
(2 pins powered)
Operating Temp Range:
-55 °C to +125 °C
Insertion Depth:
SFMH =
(3.35 mm) .132" to
(4.57 mm) .180"
RoHS Compliant:
Yes

PROCESSING

Lead-Free Solderable:
Yes (FSH)
SMT Lead Coplanarity:
(0.10 mm) .004" max (SFMH)
(0.15 mm) .006" max (FSH)*
*(.004" stencil solution may be available; contact IPG@samtec.com)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FSH	1	NO. PINS PER ROW	04	PLATING OPTION	ROW OPTION	OPTIONS
<p>05, 10, 15, 20, 25 (-DH Option)</p> <p>05, 10, 15, 20, 25, 30, 35, 40, 45 (-RA Option) (Standard sizes)</p>				<p>-F = Gold flash on post, Matte Tin on tail</p> <p>-L = 10 μ" (0.25 μm) Gold on post, Matte Tin on tail</p>	<p>-DH = Double Row Horizontal (Surface Mount)</p> <p>-RA = Right-angle (Through-hole)</p>	<p>-SL = Solder Locks</p> <p>-C = (4.50 mm) .177" DIA Polyimide film Pick & Place Pad (10 positions minimum) not available with -RA option</p> <p>-TR = Tape & Reel (Not available with -RA)</p> <p>-FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks) (Not available with -RA)</p>
<p>(No. of positions + 4) x (1.27) .050</p> <p>(3.43) .135</p> <p>(1.27) .050</p> <p>(1.27) .050</p> <p>(1.27) .050</p> <p>(1.27) .050</p> <p>(3.94) .155</p> <p>2 4</p> <p>1 3</p> <p>(0.41) .016 SQ</p> <p>No. of positions + 2 x (1.27) .050</p>		<p>(3.68) .145</p> <p>(1.27) .050</p> <p>(2.29) .090</p> <p>(1.27) .050</p> <p>(5.21) .205</p> <p>(0.89) .035</p> <p>(0.71) .028</p> <p>(2.16) .085</p>		<p>(3.68) .145</p> <p>(1.27) .050</p> <p>(2.29) .090</p> <p>(1.27) .050</p> <p>(5.21) .205</p> <p>(0.89) .035</p> <p>(0.71) .028</p> <p>(2.16) .085</p>		

SFMH	1	NO. PINS PER ROW	02	PLATING OPTION	D	OPTION
<p>05, 10, 15, 20, 25, 30, 35, 40, 45, 50</p>				<p>-L = 10 μ" (0.25 μm) Gold on contact, Gold flash on tail</p>	<p>-LC = Locking Clip (Manual placement required)</p> <p>-WT = Weld Tab (Not available with 35, 40, 45, 50 positions)</p> <p>-TR = Tape & Reel</p> <p>-FR = Full Reel Tape & Reel (must order max. quantity per reel; contact Samtec for quantity breaks)</p>	
<p>(0.64) .025 TYP</p> <p>(4.57) .180</p> <p>(1.65) .065</p> <p>(2.03) .080</p>		<p>(0.41) .016</p> <p>(1.50) .059</p>		<p>(1.41) .056 DIA</p> <p>(1.02) .040</p>		
<p>(3.43) .135</p> <p>(1.65) .065</p> <p>(1.27) .050</p> <p>(1.27) .050 + (1.65) .065</p>		<p>(0.41) .016</p> <p>(1.50) .059</p>		<p>(1.41) .056 DIA</p> <p>(1.02) .040</p>		



Note:
Some sizes, styles and options are non-standard, non-returnable.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [79531-3000](#) [FCN-](#)
[360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[801-93-011-10-001000](#)