

RUGGED TIGER EYE™ SYSTEMS

(1.27 mm) .050" PITCH













- Screw down, locking clip, friction latching and weld tab ruggedizing options
- · Shrouded, polarized and keyed
- Surface mount or through-hole tails
- High-density, four row design (FOLC/MOLC Series)
- Discrete wire assemblies available in single or double row, 28 and 30 AWG PVC or Teflon® wire; contact asp@samtec.com for custom solutions
- Cable components (ISDF/CC03) and tooling available

Dupont™ Teflon® is a registered trademark of the E.I. du Pont de Nemours and Company or its affiliates.



IDC cable assemblies with rugged strain relief (FFSD/FFMD, FFTP/FMTP)



Locking for increased unmating force (SFML/TFML)

KEY SPECIFICATIONS (TFM/SFM)

PITCH	STACK HEIGHTS	INSULATOR MATERIAL	CONTACT MATERIAL	PLATING	OPERATING TEMP RANGE	CURRENT RATING	VOLTAGE RATING	MAX CYCLES
1.27 mm	6 to 12 mm	Black LCP	BeCu (SFM) Phosphor Bronze (TFM)	Au or Sn over 50 μ" (1.27 μm) Ni	-55 °C to +125 °C	3.2 A per pin (2 pins powered)	250 VAC	10,000 with 30 μ" (0.76 μm) Au (Call Samtec for E.L.P. TM plating option)







(1.27 mm) .050" PITCH • SMT/THROUGH-HOLE SOCKET

SERIES **SFM** = Standard **SFML** = Locking

NO. PINS PER ROW

03, 04, 06, 08 (SFM only)

05, 07, 10, 15, 20, 25, 30, 35, 40, 45, 50 (Standard sizes)

LEAD STYLE

(Surface Mount) (Through-hole)

-02= Tiger Eye Contact (BeCu)

-L1, -L3 = Low Insertion Force **-L2** = Low Insertion Force Tiger Eye™ Tiger Eye Contact (BeCu) Contact (BeCu)

-T2 = Tiger Eye™ LITE Contact (Phosphor Bronze)

contact, Matte

_T1 = Tiger Eye™ LITE Contact (Phosphor

Bronze)

-01, -03

= Tiger Eye[™] Contact (BeCu)

PLATING OPTION

-L = 10 μ" (0.25 μm) Gold on (Call Samtec plating option)

ROW OPTION

-S = Single Row (SFM only)

-D = Double Row

-SH = Single Horizontal (05 thru 30 positions only) (SFM only) (Lead style –02 only)

-DH = Double Horizontal (05 thru 30 positions only) (SFM only) (Lead style -02 only)

Specify only A, LC or DS (Not available with –DH, –SH)

-A = Alignment Pin

-LC = Locking Clip (Manual placement required)

-DS = Dual Screw Down for (1.60 mm) .062" PCB (05 thru 40 positions only) (Lead styles –01 –02 & –03 only) (Requires -D

row option) (Not available with SFML) (Mates with TFM-DS option) (Not available with -A, -LC, -K, -P, -XR)

Specify only –K or –P (Lead styles –02, –L2, –T2 only)

OPTIONS

-K

= Polyimide film Pick & Place Pad (Not available with -DH, -SH)

= Plastic Pick & Place Pad (Not available with -DH, -SH)

Specify –TR or -FR last; Required for -DH & -SH. (Lead styles –02, –L2 & –T2 only)

> -TR = Tape & Reel

-FR = Full Reel Tape & Reel (must order max quantity per reel; contact Samtec for quantity breaks)


SFM


Board Mates: TFM

Cable Mates: TFSD, TFSS

SFML Board Mates:










(9.78) .385 -(3.37)


.133






(9.78) .385 -







LEAD STYLE	A	В
-01, -L1, -T1	(3.05) .120	(0.51) .020
-03, -L3	(1.91) .075	(0.41) .016

Note: Some lengths, styles and options are non-standard, non-returnable.

View complete specifications at: samtec.com?SFM & samtec.com?SFML

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Samtec manufacturer:

Other Similar products are found below:

892-18-020-10-001101 58102-G61-06LF 582553-1 0009485154 009176003701906 0050291907 LY20-4P-DT1-P1E-BR 02.125.8002.8
609-3404 61062-3 61082-181009 622-3653LF 63453-116 636-1030 636-1427 636-3427 636-4007 641938-9 641991-4 644827-2 65817010LF 65817-015LF 65863-015LF 66207-023LF 67095-007LF 67601157 68645-018 68648-049 70.362.1628.0 70-4210 70-4226B 704853B 707-5020 707-5028 71.350.2428.0 71918-208LF 71961-016LF 733-134 733-162 754199-000 760-3052 787-8014-00 79531-3000
FCN-360C032-B FCN-367T-T012/H FCN-723D010/2 80.063.4001.1 800-90-001-10-001000 800-90-010-10-002000 801-43-002-10-013000