

PXB Series

• 125°C 2,000~5,000Hrs assured.

Solvent-proof

WV ≤ 80V_{DC}

- Low impedance.
- Wide Temperature range.
- Long Life.
- Suitable to fit for automotive equipment.
- RoHS compliant.
- Halogen-free capacitors are also available.

PXA

PXB

Long Life

• AEC-Q200 compliant : Please contact us for more details, test data, information.




SPECIFICATIONS

Item	Characteristics																			
Rated Voltage Range	10 ~ 100 V _{DC}		160 ~ 400 V _{DC}		450 V _{DC}															
Operating Temperature Range	-40 ~ +125°C		-40 ~ +125°C		-25 ~ +125°C															
Capacitance Tolerance	±20% (M) (at 20°C, 120Hz)																			
Leakage Current	I = 0.03CV (μA) or 4μA, whichever is greater.		CV ≤ 1,000		CV > 1,000															
			I = 0.1CV + 40		I = 0.04CV + 100															
Dissipation Factor(Tan δ)	Where, I : Max. leakage current (μA) C: Nominal capacitance (μF)V: Rated voltage(V _{DC}) (at 20°C, 1 minute)																			
	Rated voltage(V _{DC})	10	16	25	35	50~63	80~100	160~250	350~450											
	Tanδ(Max.)	0.20	0.16	0.14	0.12	0.10	0.08	0.20	0.24											
	When the capacitance exceeds 1.000μF, 0.02 shall be added every 1.000μF increase. (at 20°C, 120Hz)																			
Temperature Characteristics (Max. Impedance ratio)	Rated Voltage(V _{DC})		10	16~35	50~80	100	160~250	350~400	450											
	Z(-25°C)/Z(+20°C)		3	2	3	3	3	6	6											
	Z(-40°C)/Z(+20°C)		6	4	5	6	6	10	-											
	(at 120Hz)																			
Load Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied at 125°C.						<table><tr><td>ø D</td><td>10~100V</td><td>160~450V</td></tr><tr><td>ø 5~6.3</td><td>2,000 hours</td><td>-</td></tr><tr><td>ø 8</td><td>3,000 hours</td><td>5,000 hours</td></tr><tr><td>ø 10~</td><td>5,000 hours</td><td></td></tr></table>		ø D	10~100V	160~450V	ø 5~6.3	2,000 hours	-	ø 8	3,000 hours	5,000 hours	ø 10~	5,000 hours	
	ø D	10~100V	160~450V																	
ø 5~6.3	2,000 hours	-																		
ø 8	3,000 hours	5,000 hours																		
ø 10~	5,000 hours																			
	Capacitance change ≤ ±30% of the initial value (where, ±20% for ≥ WV 160V _{DC}) Tanδ ≤ 300% of the initial specified value (where, 200% for ≥ WV 160V _{DC}) Leakage current ≤ The initial specified value																			
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 125°C without voltage applied. The rated voltage shall be applied to the capacitors for a minimum of 30 minutes, at least 24 hours and not more than 48 hours before the measurements.																			
	Capacitance change ≤ ±30% of the initial value (where, ±20% for ≥ WV 160V _{DC}) Tanδ ≤ 300% of the initial specified value (where, 200% for ≥ WV 160V _{DC}) Leakage current ≤ The initial specified value (where, 500% for ≥ WV 160V _{DC})																			
Others	Satisfied characteristics KS C IEC 60384-4																			

DIMENSIONS OF PXB Series

Unit(mm)



Marking : GREEN SLEEVE, BLACK INK

∅D	5	6.3	8	10	12.5	16
∅d	0.5	0.5	0.6	0.6	0.6	0.8
F	2.0	2.5	3.5	5.0	5.0	7.5
∅D'	∅D + 0.5 max.					
L'	L + 1.5 max.			L + 2.0 max.		

RATINGS OF PXB Series

V _{DC}	10			16			25			35		
Items μF	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)
		(20°C, 100kHz)	(125°C, 100kHz)		(20°C, 100kHz)	(125°C, 100kHz)		(20°C, 100kHz)	(125°C, 100kHz)		(20°C, 100kHz)	(125°C, 100kHz)
22										5 × 11	3.0	128
33							5 × 11	3.0	128	6.3 × 11	1.0	180
47				5 × 11	3.0	128	6.3 × 11	1.0	180	6.3 × 11	1.00	220
68	5 × 11	3.0	128	6.3 × 11	1.0	180	6.3 × 11	1.0	220	8 × 11.5	0.35	307
100	5 × 11	3.0	150	6.3 × 11	1.0	220	8 × 11.5	0.35	325	8 × 11.5	0.35	325
	6.3 × 11	1.0	180	8 × 11.5	0.35	325				10 × 12.5	0.25	480
220	6.3 × 11	1.0	220	8 × 11.5	0.35	368	10 × 12.5	0.25	480	10 × 16	0.15	625
	8 × 11.5	0.35	325	10 × 12.5	0.25	480						
330	10 × 12.5	0.25	480	10 × 12.5	0.25	480	10 × 16	0.15	625	10 × 20	0.11	799
470	10 × 12.5	0.25	480	10 × 16	0.15	625	10 × 20	0.11	799	12.5 × 20	0.068	997
1,000	10 × 20	0.11	799	12.5 × 20	0.068	997	12.5 × 25	0.058	1,121	16 × 25	0.040	1,426
2,200	12.5 × 25	0.058	997	16 × 25	0.040	1,426	16 × 31.5	0.034	1,595			
3,300	16 × 25	0.040	1,426	16 × 31.5	0.034	1,595						
4,700	16 × 31.5	0.034	1,595									

V _{DC}	50			63			80			100		
Items μF	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)	ø D × L (mm)	Imp. ($\varnothing$ max.)	Rated Ripple Current (mArms)
		(20°C, 100kHz)	(125°C, 100kHz)		(20°C, 100kHz)	(125°C, 100kHz)		(20°C, 100kHz)	(125°C, 100kHz)		(20°C, 100kHz)	(125°C, 100kHz)
1	5 × 11	5.2	29									
1.5	5 × 11	5.2	38									
2.2	5 × 11	5.2	45									
3.3	5 × 11	5.2	55									
4.7	5 × 11	5.2	67									
6.8	5 × 11	5.2	75									
10	5 × 11	2.5	92									
	8 × 11.5	0.75	180							8 × 11.5	1.7	140
22	5 × 11	2.5	162				8 × 11.5	1.5	150	10 × 12.5	0.94	440
	8 × 11.5	0.50	250									
33	8 × 11.5	0.50	280	8 × 11.5	1.5	150	10 × 12.5	0.80	480	10 × 12.5	0.94	440
47	8 × 11.5	0.50	280	10 × 12.5	0.80	480	10 × 12.5	0.80	480	10 × 16	0.68	600
100	10 × 12.5	0.25	480	10 × 16	0.58	650	10 × 20	0.39	790	12.5 × 20	0.32	870
220	10 × 20	0.15	625	12.5 × 20	0.27	950	12.5 × 25	0.18	1,240	16 × 25	0.14	1,320
330	12.5 × 20	0.081	990	12.5 × 25	0.18	1,240	12.5 × 30	0.16	1,390	16 × 31.5	0.12	1,400
470	12.5 × 25	0.059	1,150	12.5 × 30	0.16	1,390	16 × 25	0.11	1,500			
1,000	16 × 31.5	0.032	1,590	16 × 31.5	0.090	1,650						

V _{DC}	160		200		250		350		400		450	
Items μF	ø D × L (mm)	Rated Ripple Current (mArms)	ø D × L (mm)	Rated Ripple Current (mArms)	ø D × L (mm)	Rated Ripple Current (mArms)	ø D × L (mm)	Rated Ripple Current (mArms)	ø D × L (mm)	Rated Ripple Current (mArms)	ø D × L (mm)	Rated Ripple Current (mArms)
		(125°C, 120Hz)		(125°C, 120Hz)		(125°C, 120Hz)		(125°C, 120Hz)		(125°C, 120Hz)		(125°C, 120Hz)
3.3									8 × 11.5	48		
4.7			8 × 11.5	53			8 × 11.5	56	10 × 12.5	65		
6.8			8 × 15	71	8 × 11.5	70	8 × 15	75	10 × 16	86	10 × 16	80
10	8 × 11.5	80	8 × 15	86	10 × 12.5	91	10 × 16	105	10 × 20	112	10 × 20	108
15	8 × 15	108	10 × 12.5	110	10 × 16	115	10 × 20	139	12.5 × 20	153	12.5 × 20	150
22	10 × 12.5	135	10 × 20	159	12.5 × 20	167	12.5 × 25	204	12.5 × 25	202	16 × 25	242
	10 × 16	151							12.5 × 30	217		
33	10 × 20	204	12.5 × 20	216	12.5 × 25	223	16 × 25	276	16 × 25	273	16 × 31.5	321
47	12.5 × 20	242	12.5 × 25	281	16 × 25	294	16 × 31.5	355	16 × 31.5	351		
68	12.5 × 25	317	16 × 20	348	16 × 31.5	381						
100	16 × 25	424	16 × 25	452								
150	16 × 31.5	481										

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

(10 ~ 100V_{DC})

Cap. (μF) \ Freq. (Hz)	120	1k	10k	50k	100k
1 ~ 100	0.40	0.75	0.90	0.93	1.00
220 ~ 470	0.50	0.85	0.94	0.96	1.00
1,000	0.60	0.87	0.95	0.97	1.00
2,200 ~ 3,300	0.75	0.90	0.95	0.97	1.00
4,700	0.85	0.95	0.98	0.99	1.00

(160 ~ 450V_{DC})

Cap. (μF) \ Freq. (Hz)	120	1k	10k	50k	100k
3.3 ~ 33	1.00	1.50	1.75	1.76	1.80
47 ~ 150	1.00	1.30	1.40	1.43	1.50

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Electrolytic Capacitors - Radial Leaded](#) ***category:***

Click to view products by [SamYoung](#) ***manufacturer:***

Other Similar products are found below :

[NRELS102M35V16X16C.140LLF](#) [ESRG160ETC100MD07D](#) [227RZS050M](#) [335CKR250M](#) [476CKH100MSA](#) [477CKR100M](#)
[107CKR010M](#) [107CKH063MSA](#) [RJH-25V222MI9#](#) [RJH-35V221MG5#](#) [B43827A1106M8](#) [RJH-50V221MH6#](#) [EKYA500ELL470MF11D](#)
[B41022A5686M6](#) [ESRG250ELL101MH09D](#) [EKMA160EC3101MF07D](#) [RJB-10V471MG3#](#) [ESMG160ETD221MF11D](#)
[EKZH160ETD152MJ20S](#) [RJH-35V122MJ6#](#) [EGXF630ELL621ML20S](#) [RBD-25V100KE3#N](#) [EKMA350ELL100ME07D](#)
[ESMG160ETD101ME11D](#) [ELXY100ETD102MJ20S](#) [EGXF500ELL561ML15S](#) [EKMG350ETD471MJ16S](#) [35YXA330MEFC10X12.5](#)
[RXW471M1ESA-0815](#) [ELXZ630ELL221MJ25S](#) [ERR1HM1R0D11OT](#) [LPE681M30060FVA](#) [LPL471M22030FVA](#) [HFE221M25030FVA](#)
[LKMD1401H221MF](#) [B41888G6108M000](#) [EKMA160ETD470MF07D](#) [UHW1J102MHD6](#) [EKMG500ETD221MJC5S](#) [LKMK2502W101MF](#)
[LKMD1401H181MF](#) [LKMI2502G820MF](#) [LKMJ2001J122MF](#) [LKML2501C472MF](#) [LKMJ4002C681MF](#) [450MXH330MEFCSN25X45](#)
[450MXK330MA2RFC22X50](#) [63ZLH560MEFCG412.5X30](#) [ELH2DM331O25KT](#) [ELH2DM471P30KT](#)