

# Product data sheet

Specifications



## selector switch Ø 30 - 2 positions - maintained - LED

9001K11J35LLL

### Main

|                           |                             |
|---------------------------|-----------------------------|
| Range of product          | Harmony 9001K               |
| Product or component type | Illuminated selector switch |
| Device short name         | 9001K                       |
| Type of operator          | maintained                  |
| Operator profile          | Blue standard knob          |

### Complementary

|                               |                       |
|-------------------------------|-----------------------|
| Bezel material                | Chromium plated metal |
| Mounting diameter             | 30 mm                 |
| Product weight                | 0.245 kg              |
| Shape of signaling unit head  | Round                 |
| Operator position information | 2 positions           |
| Contacts type and composition | Without contact block |
| Mechanical durability         | 500000 cycles         |
| Light block supply            | Direct                |
| Light source                  | LED                   |
| Bulb base                     | BA 9s                 |
| [Us] rated supply voltage     | 24...28 V AC/DC       |
| Device presentation           | Basic element         |

### Environment

|                                       |                                                                                 |
|---------------------------------------|---------------------------------------------------------------------------------|
| Protective treatment                  | TC                                                                              |
| Ambient air temperature for storage   | -40...70 °C                                                                     |
| Ambient air temperature for operation | -25...70 °C                                                                     |
| Electrical shock protection class     | Class II conforming to IEC 61140                                                |
| IP degree of protection               | IP66 conforming to IEC 60529                                                    |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 6 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                        |                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------|
| Standards              | IEC 60947-5-4<br>UL 508<br>IEC 60947-1<br>JIS C 852<br>JIS C 4520<br>IEC 60947-5-1<br>CSA C22.2 No 14 |
| Product certifications | NEMA<br>UL 508                                                                                        |
| Vibration resistance   | 7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                      |
| Shock resistance       | 50 gn conforming to IEC 60068-2-27                                                                    |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 4.6 cm  |
| Package 1 Width              | 5.8 cm  |
| Package 1 Length             | 9.4 cm  |
| Package 1 Weight             | 163.3 g |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Selector Switches](#) category:*

*Click to view products by [Schneider](#) manufacturer:*

Other Similar products are found below :

[AS6Q-2Y2P](#) [ASD202NU-104](#) [TC-412N2](#) [508A229G01](#) [956-3127-BX](#) [25303A](#) [LBW6S-3T3](#) [ASS211N](#) [LB2S-2T1](#) [HA3S-2C6](#) [LB2S-2LT3](#)  
[Q25LWK1-GN/WB](#) [CW1S-2LE20](#) [CW1S-3E02](#) [52-435.036](#) [ASD311NU-203](#) [LB1F-3T63A](#) [ASLD22220DNUW](#) [HW1F-2F10QD-WA-12V](#)  
[LB1S-2T2](#) [1.10.021.005/0021](#) [50HA109659](#) [ASLW224620D-R](#) [50HA1E811R](#) [HA1S-2C6](#) [52SA2CABA2](#) [ASD3120NU](#) [HW1F-2P11Q4S](#)  
[HW4S-2LF10](#) [M22-WK](#) [M22-WKV](#) [M22-WRK](#) [M22-WRK3](#) [M22-WRLK3-Y](#) [M22-WRLK-R](#) [M22-WRLK-W](#) [M22S-WKV](#) [XB4BJ21](#)  
[XB4BJ33](#) [2441D](#) [3SU1100-2BF60-1BA0](#) [3SU1100-2BF60-1MA0](#) [3SU1100-2BL60-1NA0](#) [3SU1100-2BM60-1NA0](#) [3SU1150-2BF60-1BA0](#)  
[M22-WKV/K11](#) [XB4BK125B5](#) [LB6MF-2T64G](#) [LBW6S-2T6](#) [XB7ND21](#)