Product availability: Stock - Normally stocked in distribution facility



Main	
Range	TeSys
Product or component type	Auxiliary contact block
Device application	Signalling
Device short name	GV7AE
Range compatibility	TeSys TeSys GV7 motor circuit breaker TeSys TeSys GV5 motor circuit breaker TeSys TeSys GV6 motor circuit breaker
Auxiliary contact composition	1 C/O
Auxiliary contacts type	Standard contacts
[le] rated operational current	0.1 A AC-15 Ue: 660690 V conforming to IEC 60947-5-1 6 A AC-12 Ue: <= 690 V conforming to IEC 60947-5-1 6 A AC-15 Ue: <= 48 V conforming to IEC 60947-5-1 5 A AC-15 Ue: 110127 V conforming to IEC 60947-5-1 4 A AC-15 Ue: 230240 V conforming to IEC 60947-5-1 3 A AC-15 Ue: 380440 V conforming to IEC 60947-5-1 2.5 A DC-12 Ue: <= 48 V conforming to IEC 60947-5-1 0.8 A DC-12 Ue: 110 V conforming to IEC 60947-5-1 0.3 A DC-12 Ue: 250 V conforming to IEC 60947-5-1 1 A DC-14 Ue: <= 24 V conforming to IEC 60947-5-1 0.5 A DC-14 Ue: 48 V conforming to IEC 60947-5-1 0.5 A DC-14 Ue: 48 V conforming to IEC 60947-5-1 0.5 A DC-14 Ue: 110 V conforming to IEC 60947-5-1
	60947-5-1 0.05 A DC-14 Ue: 250 V conforming to IEC

60947-5-1

#### Complementary

Product weight	0.03 lb(US) (0.015 kg)
	end Screw clamps terminals 1 cable 1.5 mm² - cable stiffness: rigid
Connections - terminals	Screw clamps terminals 1 cable 1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screw clamps terminals 1 cable 1.5 mm <sup>2</sup> - cable stiffness: flexible - without cable
Minimum switching voltage	17 V
Minimum switching current	5 mA
Mechanical durability	50000 cycles
Protection type	GG fuse 10 A maximum GB2CB circuit breaker 10 A maximum
[Ith] conventional free air thermal current	6 A conforming to IEC 60947-5-1
System Voltage	<= 690 V AC 50/60 Hz <= 250 V DC
[Ui] rated insulation voltage	690 V - conforming to IEC 60947-1
Auxiliary contacts operation	Instantaneous
Mounting location	Inside the circuit breaker

## Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	l11
GTIN	00785901566908
Nbr. of units in pkg.	1
Package weight(Lbs)	5.9999999999998E-2
Returnability	Υ
Country of origin	FR
Package weight(Lbs) Returnability	Y

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0744 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.
More information	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8515.8640 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 84-8511.6320 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added