## XVLA135

pilot light Ø8 - IP40 - yellow - protruding LED included - 24V - faston





#### Main

Range of product	Harmony XVL
Product or component	LED pilot light with black bezel
type	
Component name	XVL
Mounting diameter	0.31 in (8 mm)
Light source	Protruding LED
Light block colour	Yellow
Protection type	Integral ballast resistor Built-in by diode
	Dulit-III by diode
[Us] rated supply voltage	24 V
IP degree of protection	IP40 IEC 60529 IP40 NF C 20-010

### Complementary

Supply circuit type	DC	
Connections - terminals	Tag for Faston connectors 2.8 x 0.5 mm Tag for soldering connectors	
Current consumption	18 mA	
[Ui] rated insulation voltage	50 V IEC 60947-1	
Bulb lifespan	100000 h	
Nominal voltage limit	0.81.1 Un	
Terminals description ISO n°1	(X1-X2)PL	
Height	0.47 in (12 mm)	
Width	0.47 in (12 mm)	
Depth	1.34 in (34 mm)	
Net weight	0.01 lb(US) (0.003 kg)	

#### **Environment**

Product certifications	UL CSA		
Protective treatment	TC		
Ambient air temperature for operation	-13158 °F (-2570 °C)		
Ambient air temperature for storage	-40158 °F (-4070 °C)		
Overvoltage category	Class 3 IEC 60536 Class 3 NF C 20-030		

### Ordering and shipping details

Category	22460 - PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2
GTIN	00785901247975
Package weight(Lbs)	0.01 lb(US) (0.00 kg)
Returnability	No
Country of origin	FR

## Offer Sustainability

Sustainable offer status	Green Premium product		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	₫Yes		
China RoHS Regulation	☑ China RoHS Declaration		
Environmental Disclosure	Product Environmental Profile		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.		

## Contractual warranty


Warranty	18 months
----------	-----------

# Product data sheet Dimensions Drawings

# XVLA135

## **LED Pilot Light**

### Dimensions



(1) Tags for Faston connectors or soldered connections

e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

С		Ø		
mm	in.	mm	in.	
32	1.26	12	0.47	

# Product data sheet Mounting and Clearance

# XVLA135

## LED Pilot Light

## Panel Drilling



Ø min	G min		n G min H min		
mm	in.	mm	in.	mm	in.
8.2	0.32	12.5	0.49	12.5	0.49

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Fixings category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

T92 1302030523 798204000 843187-000 843487-000 MOR05 GOUPILLE15X3G06 A22L01AT1 HG9Z-2K1 12C1055-1 12Q1452-2 1301260038 1437612-7 1530AABB B1440204 NALDENG-B-SPL PAPHC22 PAPLCONN PARR3 PAYPR6 K16-VP-NUT K18 K35 29Z2036-2 A2268 A3CT7122 SP12 2S09-09.0 2SS09-08.0 3-1437627-5 39C1008-2 MHU27 BP1440804 HWNP-SPL C0312.5 C0620 C0810 U10313 U1676 U369 U916 K36 K39 445360305 46W1133-1 03-0023 108565 U3402 W46 VVA9CMD-100