XVLA145

pilot light Ø8 - IP40 - yellow - protruding LED included - 48V - faston





Main

Range of product	Harmony XVL
Product or component	LED pilot light with black bezel
type	
Component name	XVL
Mounting diameter	0.31 in (8 mm)
Light source	Protruding LED
Light block colour	Yellow
Protection type	Integral ballast resistor
	Built-in by diode
[Us] rated supply voltage	48 V
IP degree of protection	IP40 IEC 60529 IP40 NF C 20-010

Complementary

Supply circuit type	DC		
Connections - terminals	Tag for Faston connectors 2.8 x 0.5 mm Tag for soldering connectors		
Current consumption	10 mA		
[Ui] rated insulation voltage	50 V IEC 60947-1		
Bulb lifespan	100000 h		
Nominal voltage limit	0.81.1 Un		
Terminals description ISO n°1	(X1-X2)PL		
Height	0.47 in (12 mm)		
Width	0.47 in (12 mm)		
Depth	1.34 in (34 mm)		
Net weight	0.01 lb(US) (0.003 kg)		

Environment

Product certifications	CSA UL		
Protective treatment	TC		
Ambient air temperature for operation	-13158 °F (-2570 °C)		
Ambient air temperature for storage	-40158 °F (-4070 °C)		
Overvoltage category	Class 3 IEC 60536 Class 3 NF C 20-030		

Ordering and shipping details

Category	22460 - PUSHBUTTONS 22MM (PLASTIC)		
Discount Schedule	CS2		
GTIN	03389110651164		
Returnability	No		
Country of origin	FR		

Offer Sustainability

Sustainable offer status	Green Premium product		
REACh Regulation	☑ REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	₫Yes		
China RoHS Regulation	China RoHS Declaration		
Environmental Disclosure	Product Environmental Profile		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.		

Contractual warranty


Warranty	18 months
----------	-----------

Product data sheet Dimensions Drawings

XVLA145

LED Pilot Light

Dimensions



(1) Tags for Faston connectors or soldered connections

e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

С		Ø		
mm	in.	mm	in.	
32	1.26	12	0.47	

Product data sheet Mounting and Clearance

XVLA145

LED Pilot Light

Panel Drilling



Ø min		G min		H min	
mm	in.	mm	in.	mm	in.
8.2	0.32	12.5	0.49	12.5	0.49

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by Schneider manufacturer:

Other Similar products are found below:

01-121.022 LW1A-P1-W LW1B-A0L 01-952.0 01-152.025 D38999/20FJ29PB L/C 704-6012 704-6020 704-6023 704-6026 73.362.4028.0 EUS-704.000.7 750-1520 9001OA120 99-450.837 99-455.837 99-458.837 99-486.837 99-901.9 99-902.9 99-908.0 99-909.4 99-909.5 A0244J1 A3DT-500Y AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-A APD106LN-G APN1126-G APS122DN-W ATN2100 AYLW4L-A 18-237.035 C0180AANAH HW1A-L1-GD HW1A-P2-GL HW1F-3G HW1R-2DF20-R HW1X-BM411-R HW2A-L1-GL HW2A-P1-GD HW4S-31L HWAZ1N-OB PA2200/1 PA2SHIELD 21-931.0 21-931.2 96-923.5