

2X Series 2.5 x 2.0 mm SMD Crystal

2 : 2.5×2.0×0.55 mm | SMD2520-4P X : Crystal Resonator

Feature

- AT-cut Crystal Construction
- Ultra miniature Ceramic surface mount with Metal Lid
- High temperature, high precision and reliability Characteristics
- Package Size:2.5 x 2.0 x 0.55mm
- Pb-free and RoHS/Green compliant

Applications

- Industrial applications
- Portable devices
- Short-range Wireless module
- Computers, Modems, Microprocessors



Electrical Specifications

Item	Symb.	Min.	Typ.	Max.	Unit	Notes
Frequency Range	Freq.	12.000		54.000	MHz	
Oscillation Mode		Fundamental (AT-cut)				
Frequency Tolerance	$\Delta f/f$			± 10	ppm	at 25°C±2°C
Operating Temperature	T _{use}	-20		70	°C	
		-40		85	°C	
StorageTemperature Range	T _{sta}	-55		125	°C	
Shunt Capacitance	C0			3	pF	
Drive Level	DL		10	100	μW	
Load Capacitance	CL	6		20	pF	
Insulation Resistance	IR			500	MΩ	at DC 100V
Aging	f _{age}			3	ppm	1st. Year at 25°C

Frequency Stability & Operating Temperature Range

Temp. \ FT	±10ppm	±15ppm	±20ppm	±30ppm
-20°C to +70°C	△	★	★	★
-40°C to +85°C		△	★	★

★: Available △: Conditional


Equivalent Series Resistance

Frequency Range	ESR(Max.)
12MHz≤ Freq. <16MHz	200 Ω
16MHz≤ Freq. <20MHz	80 Ω
20MHz≤ Freq. <30MHz	60 Ω
30MHz≤ Freq. <35MHz	50 Ω
35MHz≤ Freq. ≤54MHz	40 Ω


2X Series 2.5 x 2.0 mm SMD Crystal

2 : 2.5×2.0×0.55 mm | SMD2520-4P X : Crystal Resonator

Dimensions (UNIT:mm)



Solder pad layout (UNIT:mm)



Options and Part Identification : Example SX2B12.000F1010F30


Company	Ceramic Package	Frequency Code [MHZ]	Vibration Mode	Load Capacitance	Frequency Tolerance	Operating Temperature	Frequency Drift	
SX	2B	X.XXX	F	10	10	F	30	
		Frequency						
Code	Company	12.000	Code	Vibration Mode	Code	Frequency Tolerance	Code	Frequency Drift
SX	SCTF		F	AT - Fundamental	10	±10ppm	10	±10ppm
					20	±20ppm	15	±15ppm
							20	±20ppm
							30	±30ppm
Code	Ceramic Package			Code	Load Capacitance		Code	Operating Temperature
0B	1.6 x 1.2 x 0.35mm [4PAD]			S	Please specify CL in pF or S for series	E	-20°C ~ +70°C	
1B	2.0 x 1.6 x 0.45mm [4PAD]			06	6pF	F	-40°C ~ +85°C	
2B	2.5 x 2.0 x 0.55mm [4PAD]			08	8pF			
3B	3.2 x 2.5 x 0.7mm [4PAD]			10	10pF			
5B	5.0 x 3.2 x 0.8mm[4PAD]			12	12pF			
5A	5.0 x 3.2 x 0.8mm[2PAD]			20	20pF			
7B	7.0 x 5.0 x 1.0mm[4PAD]							

If you have other parameter requirements, you can contact **SCTF** at any time.

2X Series 2.5 x 2.0 mm SMD Crystal


2 : 2.5×2.0×0.55 mm | SMD2520-4P X : Crystal Resonator

Frequency Temperature Characteristics




Product Structure&Marking Information

Product Structure




Marking Information



2X Series 2.5 x 2.0 mm SMD Crystal

2 : 2.5×2.0×0.55 mm | SMD2520-4P X : Crystal Resonator

Suggested Reflow Profile






Profile Feature	Sn - Pb Eutectic Assembly	Preheat / Soak
Preheat / Soak ● Temperature Min (Ts min) ● Temperature Max (Ts max) ● Time (Ts min to Ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-120 seconds
Ramp - up rate (TL to Tp)	3°C/ second max.	3°C/ second max.
Time maintained above ● Liquidous temperature (TL) ● Time (tL) maintained above TL	183°C 60-150 seconds	217°C 60-150 seconds
Peak package body temperature (Tp)	235°C	260°C
Time within 5° C of the specified classification temperature (Tp)	20 seconds	30 seconds
Ramp - down rate (Tp to TL)	6°C/ second max.	6°C/ second max.
Time 25° C to peak temperature	6 minutes max.	8 minutes max.
Suggest reflow times	2 Times max.	

2X Series 2.5 x 2.0 mm SMD Crystal

2 : 2.5×2.0×0.55 mm | SMD2520-4P X : Crystal Resonator

Packaging Information

T=Tape and reel (3,000pcs/reel)



Pocket Tape Dimensions(mm)

Series	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
2X	0.25±0.05	2.25±0.1	0.8±0.1	8.0±0.1	3.5±0.1	2.25±0.1	4.0±0.1	4.0±0.1	2.0±0.1	φ1.5±0.1	2.0±0.2	4.0±1.0	φ13±0.5	φ60±1	φ180±1

Common Frequencies – MHz

2X Series				
12.000	12.288	14.31818	16.000	16.384
18.432	19.200	20.000	22.1184	22.5792
24.000	24.305	24.576	25.000	26.000
27.000	27.120	28.63636	30.000	32.000
37.400	38.400	40.000	48.000	50.000
52.000	54.000			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Crystals](#) category:

Click to view products by [SCTF](#) manufacturer:

Other Similar products are found below :

[CX3225GB25000M0PPSZ1](#) [FL2000085](#) [99-BU](#) [H10S-12.000-18-EXT-TR](#) [AB-11.0592MHZ](#) [ABC2-6.000MHZ-D4Z-T](#) [ABS071-](#)
[32.768KHZ-6-T](#) [R38-32.768-12.5-5PPM-NPB](#) [21U15A-21.4MHZ](#) [RTX-781DF1-S-20.950](#) [LFX TAL066198Cutt](#) [9C-14.31818MBBK-T](#) [A-](#)
[11.000MHZ-27](#) [ABL-27.000MHZ-B4Y-T](#) [ABM11-132-24.000MHZ-T3](#) [ABM3B1-25.000MHZ-D2Y-T](#) [SSPT7F-9PF20-R](#)
[LFX TAL065253Cutt](#) [LFX TAL066431Cutt](#) [XT9S20ANA14M7456](#) [7A-24.576MBBK-T](#) [CX2520DB16000H0HPQCC](#) [6504-202-1501](#) [6526-](#)
[202-1501](#) [ABM3B-24.000MHZ-R60-D1W-](#) [ABLS-12.000MHZ-B2Y-T](#) [SG636PCE-20.000MC](#) [3404](#) [CM315D32768EZFT](#) [C1E-](#)
[19.200-12-1530-X-R](#) [FL5000014](#) [EUCA18-3.1872M](#) [FX0800015](#) [425F35E027M0000](#) [FP0800018](#) [MS3V-T1R-32.768kHz-7pF-20PPM-TA-](#)
[QC-Au](#) [VXM7-1C1-16M000](#) [MS3V-T1R-32.768kHz-9pF-20PPM-TA-QC-Au](#) [17000](#) [17301](#) [GB1200038](#) [NTE661](#) [R38-32.768-12.5-EXT](#)
[4133-VBO-168.62MHZ](#) [4133-VBO-171.750MHZ](#) [NX8045GB-12M-STD-CSF-4](#) [FC1610AN](#) [32.7680KA-A3](#) [NX8045GB-5MHZ-STD-CSF-3](#)
[C1E-48.000-10-1530-X-R](#) [FC5BSHFEM25.0-T1](#)