

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-20V	16mΩ@-4.5V	-13A
	23mΩ@-2.5V	



合肥矽普半导体

Siliup Semiconductor Technology Co., Ltd

技术 品质 服务

www.siliup.com


Feature

- Low On-Resistance
- Low Input Capacitance


Application

- Power Management Functions
- DC-DC Converters


Package



Circuit diagram



Marking



2016
**

:Device Code
:Week Code

Order Information

Device	Package	Unit/Tape
SP2016NQ	PDFN2X2-6L	3000


Absolute maximum ratings (Ta=25°C unless otherwise noted)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	-16	A
Pulsed Drain Current	I_{DM}	-64	A
Power Dissipation	P_D	2.5	W
Thermal Resistance from Junction-to-Ambient	$R_{\theta JA}$	50	$^{\circ}\text{C}/\text{W}$
Operating Junction Temperature Range	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$
Storage Temperature Range	T_J	-55 ~ +150	$^{\circ}\text{C}$


Electrical characteristics (T_A=25 °C, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	VGS=0V , ID=-250uA	-20	-	-	V
Drain-Source Leakage Current	IDSS	VDS=-16V , VGS=0V , TJ=25℃	-	-	-1	uA
Gate-Source Leakage Current	IGSS	VGS=±12V , VDS=0V	-	-	±100	nA
Gate Threshold Voltage	VGS(th)	VGS=VDS , ID =-250uA	-0.4	-0.7	-1.0	V
Static Drain-Source On-Resistance	RDS(ON)	VGS =-4.5V, ID =-5A	-	16	20	mΩ
		VGS =-2.5V, ID =-4A	-	23	35	
Dynamic characteristics						
Input Capacitance	Ciss	VDS=-6V , VGS=0V , f=1MHz	-	1275	-	pF
Output Capacitance	Coss		-	255	-	
Reverse Transfer Capacitance	Crss		-	236	-	
Total Gate Charge	Qg	VDS=-6V , VGS=-4.5V , ID=-5A	-	14	-	nC
Gate-Source Charge	Qgs		-	2.3	-	
Gate-Drain Charge	Qgd		-	3.6	-	
Switching Characteristics						
Turn-On Delay Time	Td(on)	VDD=-6V VGS=-4.5V , RG=1Ω, ID=-4A	-	26	-	nS
Rise Time	Tr		-	24	-	
Turn-Off Delay Time	Td(off)		-	45	-	
Fall Time	Tf		-	20	-	
Diode Characteristics						
Diode Forward Voltage	VSD	VGS=0V , IS=-1A , TJ=25℃	-	-	-1.2	V


Typical Characteristics




Output Characteristics




Transfer Characteristics




Capacitance Characteristics




Gate Charge




Current dissipation




Power dissipation




$R_{DS(on)}$ VS Drain Current




Forward characteristics of reverse diode




Normalized breakdown voltage




Normalized Threshold voltage



Maximum Transient Thermal Impedance



Safe Operation Area

PDFN2X2-6L Package Information


BOTTOM VIEW

Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	0.70	0.75	0.80
A1		0.02	0.05
b	0.25	0.30	0.35
b1	0.20REF		
c	0.203REF		
D	1.90	2.00	2.10
D1	0.08	0.125	0.18
D2	0.85	0.90	0.95
D3	0.25	0.30	0.35
D4	0.33	0.375	0.43
e	0.65BSC		
Nd	1.30BSC		
E	1.90	2.00	2.10
E2	0.95	1.00	1.05
E3	0.55	0.60	0.65
L	0.20	0.25	0.30
h	0.25REF		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFETs](#) category:

Click to view products by [Siliup](#) manufacturer:

Other Similar products are found below :

[MCH3443-TL-E](#) [MCH6422-TL-E](#) [NTNS3A92PZT5G](#) [IRFD120](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [2SJ277-DL-E](#) [2SK2267\(Q\)](#) [MIC4420CM-TR](#) [IRFS350](#) [IPS70R2K0CEAKMA1](#) [AON6932A](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [SCM040600](#) [NTE2384](#) [2N7000TA](#) [DMN2080UCB4-7](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN13M9UCA6-7](#) [STU7N60DM2](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#) [2N7002W-G](#) [MCQ7328-TP](#) [IPB45P03P4L11ATMA2](#) [BXP4N65F](#) [BXP2N20L](#) [BXP2N65D](#) [TSM60NB380CP](#) [ROG](#) [SLF10N65ABV2](#) [IRF9395MTRPBF](#) [FCMT080N65S3](#) [NTD5C632NLT4G](#) [NTMFS0D55N03CGT1G](#) [NTMFS1D15N03CGT1G](#) [NTMTS0D4N04CTXG](#) [NTMYS2D1N04CLTWG](#) [NVD360N65S3T4G](#) [NVD5C464NLT4G](#) [NVMTS001N06CLTXG](#) [NVMTS1D1N04CTXG](#)