

# SIM7000E-N

NB-IoT Module



Quad-Band  
LTE

NB-IoT

LCC

SMS

Compact  
Size

UDP

TCP/IP

USB 2.0

FOTA

## Product Description

The SIM7000E-N is Quad-Band LTE-FDD NB-IoT module solution in a SMT type which supports LTE CAT NB-IoT up to 66 kbps data transfer.

It has strong extension capability with rich interfaces including UART, USB2.0, GPIO etc. The module provides much flexibility and ease of integration for customer's application.

The package of SIM7000E-N is compatible with SIM900 and SIM800F. AT commands of SIM7000E-N are mostly compatible with SIM800F. This also minimize the investments of customers, and enables a short time-to-market.

It is designed for applications that need low latency, medium throughput data communication in a variety of radio propagation conditions. Due to the unique combination of performance, security and flexibility, this module is ideally suited for M2M applications, such as metering, telematics, asset tracking, remote monitoring, E-health, mobile pos terminals and sharing bike.

## Key Benefits

- With Power Save Mode(PSM) and Extended Discontinuous Reception(eDRX), SIM7000E-N can extend battery life to 10 years
- SIM7000E-N provides deeper coverage enhancement compared to GSM
- The package and AT commands of SIM7000E-N mostly are compatible with SIM900 and SIM800F.

Smart machine Smart decision

Tel:86-21-32523300  
Fax:86-21-32523301  
simcom@sim.com  
www.simcomm2m.com

## General Features

Quad-Band FDD-LTE B3/B8/B20/B28  
Control Via AT Commands  
Supply voltage range: 3.0V~ 4.3V, Typ: 3.8V  
Operation temperature: -40°C to +85°C  
Dimensions: 24 X 24 X 2.6mm  
Weight: 3.0g

## Data

### NB-IoT

- Uplink up to 66kbps, Downlink up to 34kbps

## Specifications for SMS

Point to point MO and MT  
Text and PDU mode

## Other Features

USB Driver for Microsoft Windows XP/Vista/7/8  
USB Driver for Windows CE/Mobile  
USB Driver for Linux  
Firmware update via USB  
TCP/IP  
UDP  
PPP  
SMS  
FOTA \*

## Interfaces

USB2.0 x1 (high-speed)  
UART x2 (7-wire UART and 2-wire UART  
interface multiplex from GPIO)  
SIM card x1 (1.8V and 3V)  
I2C x1  
GPIO x5  
ADC x1

## Consumption

Power off: 7uA  
PSM: 9uA

## Certifications

CE\* / RoHS / REACH

**Smart machine Smart decision**

Tel:86-21-32523424

Fax:86-21-32523020

simcom@sim.com

www.simcomm2m.com

Copyright © 2017 SIMCom Wireless Solutions Co., Ltd. All Rights Reserved

Note: \* In Planning

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Modules](#) category:*

*Click to view products by [Simcom](#) manufacturer:*

Other Similar products are found below :

[HMC-C009](#) [HMC-C011](#) [nRF24L01P-MODULE-PCB](#) [HMC-C021](#) [HMC-C024](#) [XB9XT-DPRS-721](#) [XBP9B-DMUTB022](#) [nRF24L01P-MODULE-SMA](#) [CMD-KEY2-418-CRE](#) [XM-C92-2P-UA](#) [XB9XT-DPUS-721](#) [V640-A90](#) [HMC-C583](#) [MAAM-008818-TR3000](#) [MTSMC-H5-U](#) [SIMSA868-PRO](#) [SIMSA915C-PRO](#) [SIMSA868C-PRO](#) [SIMSA433C-PRO](#) [SIMSA915-PRO](#) [XBP9B-DMUT-042](#) [HMC-C582](#) [HMC-C022](#) [XBP9B-DPST-041](#) [XBP9B-DMWT-042](#) [SM-MN-00-HF-RC](#) [HMC-C031](#) [MT-02](#) [M1002GB](#) [702-W](#) [SIMSA868C-N-PRO](#) [SIMSA433C-N-PRO](#) [SIMSA915C-N-PRO](#) [ADP-R202-00B](#) [PEPPER WIRELESS C1 USB](#) [S2-1050J-Z0K4J](#) [S2-10732-Z1T61](#) [S2-107XB-Z2356-Z2352](#) [S2-10672-Z1L85](#) [S2-10686-Z1L1D](#) [S2-10688-Z1L1T](#) [S2-106BA-Z1P20](#) [S2-1060C-Z1F0A](#) [S2-106R4-Z1Q6F-Z1Q6Q](#) [S2-106R4-Z1Q6J-Z1Q6Q](#) [S2-106R4-Z1Q67-Z1Q6Q](#) [S2-106RB-Z1Q6V-Z1Q6Q](#) [S2-107DR-Z1Y5B](#) [SU60-2230C-PU](#) [RC-TFSK3-868](#)