

# Leaded MLCC for General Purpose Data Sheet


## Feature

- Small size and large capacitance
- Low ESR characteristics for high frequency
- Meet LF (Lead Free) and HF (Halogen Free)
- Epoxy resin coating

## Applications

- General electronic equipment


## Part Number Code



## Specifications


|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reference Standard                          | GB/T 5966                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Operating Temperature Range                 | -55~125℃                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Capacitance(C) and Dissipation Factor(tg δ) | Class 1:<br>$C \leq 1000\text{pF}$ , $1\text{MHz} \pm 10\%$ , $1.0\text{V}$<br>$C > 1000\text{pF}$ , $1\text{KHz} \pm 10\%$ , $1.0\text{V}$<br>$CR \geq 50\text{PF}$ , $DF \leq 0.15\%$<br>$CR < 50\text{PF}$ , $DF \leq 0.15\% \left[ \left( \frac{150}{CR} \right) + 7 \right] \times 10^{-4}$<br>Class 2:<br>$1\text{KHz} \pm 10\%$ , $1.0\text{V(B)}/0.5\text{V(Y)}$<br>B: $DF \leq 3.5\%$<br>Y: $DF \leq 7.5\%$ ( $CR \leq 0.1\mu\text{F}$ )<br>$DF \leq 10.0\%$ ( $1\mu\text{F} > CR > 0.1\mu\text{F}$ )<br>$DF \leq 15\%$ ( $CR \geq 1\mu\text{F}$ ) |
| Rated Voltage                               | 25V、50V、100V、250V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Withstand Voltage                           | Class1 300% Withstand Voltage<br>Class2 250% Withstand Voltage<br>The charge/discharge current is less than 50mA                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Insulation Resistance                       | Rated Voltage, $60 \pm 5\text{sec}$<br>Class1: $C \leq 10\text{nF}$ , $IR \geq 10000\text{M}\Omega$<br>$C > 10\text{nF}$ , $IR \geq 100\text{M}\Omega \cdot \mu\text{F}$<br>Class2: $C \leq 25\text{nF}$ , $IR \geq 4000\text{M}\Omega$<br>$C > 25\text{nF}$ , $IR \geq 100\text{M}\Omega \cdot \mu\text{F}$                                                                                                                                                                                                                                                |
| Temperature Characteristic                  | COG(NP0)、X7R、Y5V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## Dimension、Voltage and Capacitance



| Dimension | Dimensions (Unit: mm) |           |      |     |     |              | Rated voltage      | Available Capacitance Range   |                               |                           |
|-----------|-----------------------|-----------|------|-----|-----|--------------|--------------------|-------------------------------|-------------------------------|---------------------------|
|           | F                     | H         | L    | W   | T   | Φd           |                    | N                             | B                             | Y                         |
|           | ±0.5                  | ±1        | max  | max | max | ±0.05        |                    | COG(NPO)                      | X7R                           | Y5V                       |
| 0805      | 2.54                  | 10        | 4.2  | 3.8 | 3.8 | 0.45         | 25V<br>50V<br>100V | 0R5-272<br>0R5-222<br>05R-102 | 101-105<br>101-105<br>101-104 | 102-125<br>102-105<br>--- |
|           | 5.08                  | 5.0/      |      |     |     |              |                    |                               |                               |                           |
|           | 5.08                  | 10.0<br>5 |      |     |     |              |                    |                               |                               |                           |
| 1206      | 3.50<br>5.08          | 10        | 5.5  | 4.5 | 3.8 | 0.45<br>0.50 | 25V                | 0R5-562                       | 101-225                       | 102-125                   |
|           |                       |           |      |     |     |              | 50V                | 0R5-472                       | 101-105                       | 102-105                   |
|           |                       |           |      |     |     |              | 100V               | 0R5-332                       | 101-154                       | ---                       |
| 1210/1209 | 3.50<br>5.08          | 10        | 5.5  | 5.5 | 3.8 | 0.45<br>0.50 | 25V                | 100-103                       | 471-105                       | 472-155                   |
|           |                       |           |      |     |     |              | 50V                | 100-103                       | 471-105                       | 472-205                   |
|           |                       |           |      |     |     |              | 100V               | 5R0-103                       | 101-105                       | ---                       |
| 1812      | 4.57                  | 10        | 8.5  | 6.5 | 3.8 | 0.45<br>0.50 | 25V                | 100-153                       | 471-335                       | 103-335                   |
|           |                       |           |      |     |     |              | 50V                | 100-103                       | 471-225                       | 103-225                   |
|           |                       |           |      |     |     |              | 100V               | 5R0-103                       | 101-105                       | ---                       |
| 2225      | 5.50                  | 10        | 10.5 | 9.5 | 4.2 | 0.45<br>0.50 | 25V                | 100-473                       | 102-475                       | 103-475                   |
|           |                       |           |      |     |     |              | 50V                | 100-273                       | 102-335                       | 103-335                   |
|           |                       |           |      |     |     |              | 100V               | 5R0-273                       | 101-105                       | ---                       |

## Taping And Dimensions (mm)



Note: P1=3.85mm for F=5.08mm; P1=5.1mm for F=2.54mm

| Code | P         | P0        | P1        | P2        | $\Phi d$  | $\Delta h$ | W         | W0        | W1        | W2        | H     | H0        | I    | $\Phi D0$ | t   |
|------|-----------|-----------|-----------|-----------|-----------|------------|-----------|-----------|-----------|-----------|-------|-----------|------|-----------|-----|
| Dim  | 12.7      | 12.7      | 3.85      | 6.35      | 0.5       | 0          | 18.5      | 8         | 9         | 1.5       | 32.25 | 15-20     | 1.42 | 4.0       | 0.7 |
|      |           |           | 5.1       |           |           |            |           | 10        |           |           |       |           |      |           |     |
| TOL  | $\pm 1.0$ | $\pm 0.2$ | $\pm 0.7$ | $\pm 1.3$ | $\pm 0.1$ | $\pm 1.0$  | $\pm 1.0$ | $\pm 1.0$ | $\pm 0.5$ | $\pm 1.5$ | Max   | $\pm 0.5$ | Max  | $\pm 0.2$ | Max |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for [Ceramic Disc Capacitors](#) category:***

***Click to view products by [Songtian](#) manufacturer:***

Other Similar products are found below :

[009377XM](#) [5AS560JCFCA](#) [5AU100JCECA](#) [5AU470JCJCA](#) [DEF2CLH020CA3B](#) [HSE102MAQBF0KR](#) [432202101621](#) [432202282431](#)  
[DEF2CLH030CJ3B](#) [W1X223MCVCF0KR](#) [564RC0GBA302EJ470K](#) [5AS270JCDCA](#) [5AS330JCDCA](#) [5AU330JCGCA](#)  
[DE1E3KX222MJ4BN01F](#) [440LT68AP-R](#) [JN222MQ47FAAAAKPLP](#) [H8000090-245](#) [H8000090-225RY](#) [H8000090-309RY](#) [H8000090-](#)  
[291RY](#) [F471K39S3NR63K7R](#) [DEF2CLH040CN3A](#) [DEF2CLH080DA3B](#) [564R3DF0T22](#) [CC2150KY5P1KVB5LS-LF](#)  
[CC2180KY5P1KVB5LS-LF](#) [CC2470KY5P1KVB5LS-LF](#) [CC2820KY5P1KVB5LS-LF](#) [0838-040-X7R0-220K](#) [JN102MQ35FAAAAKPLP](#)  
[0841-040-X5U0-103M](#) [CCH-6K8-5/1000V](#) [140-50N2-101J-TB-RC](#) [ECK-DGL102ME](#) [562R5GAD47RR](#) [S103K75Y5PN8BT0R](#)  
[615R100GAD10](#) [615R150GAD10](#) [NCD100K1KVSLF](#) [NCD682M1KVZ5UF](#) [CCK-100N](#) [CCK-100P](#) [CCK-22N](#) [CCK-2N2](#) [CCK-47N](#) [CCK-](#)  
[47P](#) [CCK-4N7](#) [CCK-4P7](#) [CK45-B3FD681KYNNA](#)