



# 产品参数表 Product Specification

# B02-F

Wi-Fi 智能LED灯丝灯/Wi-Fi Smart LED Filament Bulb



B02-F-A60(青光/Cyan)



B02-F-ST64(琥珀/Amber)

#### 基本信息 Basic Information

产品系列 LBS照明系列 **Product series** LBS Smart Lighting

产品类型 LED灯丝灯 **LED Filament Bulb** Type 工作电压 220-240V AC 50Hz Voltage

光通量 B02-F-A60: 806Lm / B02-F-ST64: 700Lm **Luminous Flux** 

色温 B02-F-A60: 2200K-6500K / B02-F-ST64: 1800K-5000K CCT

颜色 冷暖双色 color Warm & Cold

额定功率 7W **Power Rating** 

接口类型 E27 Lamp base

显色指数 ≥Ra80 CRI

发光角度 360° Beam angle

寿命 15000h Life Expectancy

MCU SV6166F 产品认证

## 外观信息 Appearance

Certification

灯芯数量 LED quantity

尺寸规格 B02-F-A60: 60x104mm / B02-F-ST64: 64x138mm Dimension

4

CE/ROHS

产品净重 B02-F-A60: 35g / B02-F-ST64: 50g Weight

外壳材质 玻璃灯罩+铝材

Glass lampshade + aluminium Casing material

## 功能特性 Features

Operating systems

**Encryption type** 

适用场所

产品特点 远程控制、智能定时/延时、语音控制、分享功能、智能场景控制、同步状态、 无级调光、情景模式、添加摄像头、群组功能

Remote control, single/countdown timing, voice control, share control,

**Functions** smart scene, sync status, stepless dimming, scene mode, camera feature, group control

支持平台 Android & iOS

## 无线标准 Wireless standard

Wi-Fi IEEE 802.11 b/g/n 2.4GHz(2400M - 2483.5M)

室内使用

天线 内置铜导天线 Antenna Built-in copper antenna

安全机制

WPA/WPA2 Security mode 加密类型 WEP/TKIP/AES

## 使用环境 Working Enviroment

Applicable place Indoor

工作温度 -10°C ~ 40°C

Working temperature 5%-95% RH, 无冷凝 工作湿度

5%-95% RH, non-condensing Working humidity

2000米以下 工作海拔 Working height Less than 2000m

Shenzhen Sonoff Technologies Co., Ltd.

安装信息 Installation

设备安装 顺时针旋转拧紧 Installation method Clockwise to screw

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Sonoff manufacturer:

Other Similar products are found below:

61FGPN8DAC120 CV500SLK21 70177-1011 F03-03 HAS C F03-31 81550401 FT1A-C12RA-W H2CAC24A H2CRSAC110B R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 AFP0RT32CT DRT2ID08C DTB4896VRE DTB9696LVE E53-AZ01 E53E01 E53E8C E5C4Q40J999FAC120 E5CWLQ1TCAC100240 E5GNQ03PFLKACDC24 B300LKL21 NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV-CN001 OAS-160-N C40PEDRA K31S6 K33-L1B K3MA-F 100-240VAC K3TX-AD31A 89750101 L595020 SRM1-C02 SRS2-1 G32X-V2K 26546803 26546805 PWRA440A CPM1AETL03CH CV500SLK11 3G2A5BI081 3G2A5IA122 3G2A5LK010E 3G2A5OA223 3G2A5OD211 3G2A5PS223E