



## 产品参数表 Product Specification

# TX US

Wi-Fi智能墙壁触摸开关(美规)/Wi-Fi Smart Wall Switch US Type



T0、T2 (1C/2C/3C)



T3 (1C/2C/3C)

#### 基本信息 Basic Information

产品系列 TX墙壁触摸开关系列 Product series Smart Wall Switches

产品类型 开关模块

Type Smart switch module 工作电压 Voltage 100-240V AC 50/60Hz

输出电流 Current output 2A/gang

最大功率 480W/gang Max. power

LED灯负载 150W/110V/gang 20

LED load 150W/110V/gang、300W/220V/gang

支持433MHz遥控功能 **仅限**T2/T3 Support 433MHz RF control T2/T3 only

通道 Gang 1-gang / 2-gang / 3-gang

MCU ESP8285

产品认证 CE/FCC/ROHS Certification

#### 外观信息 Appearance

产品颜色白色(T0、T2)/黑色(T3)ColorWhite(T0、T2)/Black(T3)

尺寸规格 120x74x38mm Dimension

产品净重 147g-165g Weight

外壳材质 PC+钢化玻璃面板

Casing material PC+tempered glass panel

### 功能特性 Features

支持平台

Encryption type

工作温度

产品特点 远程控制、智能定时/延时、语音控制、分享功能、智能场景控制、

433MHz遥控控制、添加摄像头、触摸开关、局域网功能 Remote control, single/countdown timing, voice control, share control,

Functions smart scene, 433MHz RF control, camera feature, touch control,

LAN control

Operating systems Android & iOS

## 无线标准 Wireless standard

Wi-Fi IEEE 802.11 b/g/n 2.4GHz(2400M - 2483.5M)

天线 内置板载天线 Antenna PCB board with antenna

安全机制 WPA/WPA2

Security mode
加密类型
WEP/TKIP/AES

# 使用环境 Working Enviroment

适用场所 室内使用 Applicable place Indoor

Working temperature −10°C ~ 40°C

工作湿度 5%-95% RH, 无冷凝 5%-95% RH, non-condensing

工作海拔 2000米以下 Working height Less than 2000m

# 安装信息 Installation

设备安装 嵌入(120型)美规暗盒上

Installation method Embedded (120 type) US mounting box

固定模式 通过螺钉固定 Installation type Screws installation

接线方式 零火 Wiring way N and L

Wiring way N and 接线线径范围

接线线性視菌 Ф 0.5-1.5mm(24-14AWG) Wire diameter

2020.11.16

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Sonoff manufacturer:

Other Similar products are found below:

61FGPN8DAC120 CV500SLK21 70177-1011 F03-03 HAS C F03-31 81550401 FT1A-C12RA-W H2CAC24A H2CRSAC110B R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 AFP0RT32CT DRT2ID08C DTB4896VRE DTB9696LVE E53-AZ01 E53E01 E53E8C E5C4Q40J999FAC120 E5CWLQ1TCAC100240 E5GNQ03PFLKACDC24 B300LKL21 NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV-CN001 OAS-160-N C40PEDRA K31S6 K33-L1B K3MA-F 100-240VAC K3TX-AD31A 89750101 L595020 SRM1-C02 SRS2-1 G32X-V2K 26546803 26546805 PWRA440A CPM1AETL03CH CV500SLK11 3G2A5BI081 3G2A5IA122 3G2A5LK010E 3G2A5OA223 3G2A5OD211 3G2A5PS223E