

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

Features:

- RMCF – standard power ratings
- RMCP – high power ratings
- Nickel barrier terminations standard
- Power derating from 100% at 70°C to zero at +155°C
- AEC-Q200 compliant (except 01005 and 0201 sizes)
- RoHS compliant and halogen free
- REACH compliant
- For ultra-high power, see [RMCP-UP Series – Thick Film Ultra High Power Chip Resistor](#)



Electrical Specifications - RMCF

Type/Code	Power Rating (W) @ 70°C	Max. Working Voltage (V) ⁽¹⁾	Max. Overload Voltage (V)	Max. Jumper Current (A)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance ⁽²⁾	
						1%	5%
RMCF01005	0.03	15	30	0.5	± 300	10 - 97.6	
					± 200	100 - 1M	
RMCF0201	0.05	25	50	0.5	± 400	1 - 9.76	
					± 200	10 - 10M	
RMCF0402	0.063	50	100	1	± 200	1 - 9.76	
					± 100	10 - 1M	
					± 200	1.02M - 10M	1.1M - 20M
RMCF0603	0.1	75	150	1	± 500	0.1 - 0.499	
					± 400	0.5 - 0.976	
					± 200	1 - 9.76	1 - 20M
					± 100	10 - 1M	-
					± 200	1.02M - 10M	-
RMCF0805	0.125	150	300	2	± 200	0.1 - 9.76	0.1 - 20M
					± 100	10 - 1M	-
					± 200	1.02M - 10M	-
RMCF1206	0.25	200	400	2	± 200	0.1 - 9.76	0.1 - 20M
					± 100	10 - 1M	-
					± 200	1.02M - 10M	-
RMCF1210	0.5	200	400	3	± 200	0.1 - 0.976	
					± 400	1 - 9.76	
					± 100	10 - 10M	
RMCF2010	0.75	200	400	3	± 200	0.1 - 0.976	
					± 400	1 - 9.76	
					± 200	-	10 - 10M
					± 100	10 - 10M	-
RMCF2512	1	200	400	3	± 200	0.1 - 0.976	
					± 400	1 - 9.76	
					± 200	-	10 - 10M
					± 100	10 - 10M	-

Notes: (1) Lesser of $\sqrt{P \cdot R}$ or maximum working voltage

(2) Contact Stackpole for higher or lower values

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

Electrical Specifications - RMCP

Type/Code	Power Rating (W) @ 70°C	Max. Working Voltage (V) ⁽¹⁾	Max. Overload Voltage (V)	Max. Jumper Current (A)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance ⁽²⁾
						1%, 5%
RMCP0201	0.063	25	50	1	-200 / +400	1 - 9.76
					± 200	10 - 10M
RMCP0402	0.125	50	100	1.5	± 200	1 - 9.76
					± 100	10 - 10M
RMCP0603	0.25	75	150	2	± 200	1 - 9.76
					± 100	10 - 10M
RMCP0805	0.33	150	300	2.5	± 200	1 - 9.76
					± 100	10 - 10M
RMCP1206	0.5	200	400	3.5	± 400	1 - 9.76
					± 100	10 - 10M
RMCP1210	0.66	200	400	5	± 400	1 - 9.76
					± 100	10 - 10M
RMCP2010	1	200	400	6	± 200	1 - 9.76
					± 100	10 - 10M
RMCP2512	2	250	500	7	± 200	1 - 9.76
					± 100	10 - 10M

Notes: (1) Lesser of $\sqrt{P \cdot R}$ or maximum working voltage

(2) Contact Stackpole for higher or lower values


The resistance value range for RMCP jumper is max. 0.02Ω

Electrical Specifications - Jumper

Type/Code	Jumper Rated Current (A)	Max Overload Current (A)*	Jumper Resistance Value (Ω)
RMCF01005	0.5	1	0.05 max.
RMCF0201	0.5	1	
RMCF0402	1	3	
RMCF0603	1	5	
RMCF0805	2	10	
RMCF1206	2	10	
RMCF1210	3	12	
RMCF2010	3	12	
RMCF2512	3	15	

* < 1 second and 1 time

Mechanical Specifications



Type/Code	Average Unit Weight (mg)	L Body Length	W Body Width	H Body Height	a Top Termination	b Bottom Termination	Unit
RMCF01005	0.07	0.016 ± 0.001 0.40 ± 0.02	0.008 ± 0.001 0.20 ± 0.02	0.005 ± 0.001 0.13 ± 0.02	0.004 ± 0.001 0.10 ± 0.03	0.004 ± 0.001 0.10 ± 0.03	inches mm
RMCF0201 RMCP0201	0.16	0.024 ± 0.001 0.60 ± 0.03	0.012 ± 0.001 0.30 ± 0.03	0.009 ± 0.002 0.23 ± 0.05	0.006 ± 0.002 0.15 ± 0.05	0.006 ± 0.002 0.15 ± 0.05	inches mm
RMCF0402 RMCP0402	0.57 0.62	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.002 0.50 ± 0.05	0.012 ± 0.004 0.30 ± 0.10	0.006 ± 0.004 0.15 ± 0.10	0.010 ± 0.006 0.25 ± 0.15	inches mm
RMCF0603 RMCP0603	1.88 2.04	0.061 ± 0.006 1.55 ± 0.15	0.031 ± 0.006 0.80 ± 0.15	0.018 ± 0.006 0.45 ± 0.15	0.012 ± 0.008 0.30 ± 0.20	0.012 ± 0.008 0.30 ± 0.20	inches mm
RMCF0805 RMCP0805	5.00 4.37	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.004 1.25 ± 0.10	0.020 ± 0.006 0.50 ± 0.15	0.014 ± 0.010 0.35 ± 0.25	0.014 ± 0.010 0.35 ± 0.25	inches mm

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

Mechanical Specifications (cont.)

Type/Code	Average Unit Weight (mg)	L Body Length	W Body Width	H Body Height	a Top Termination	b Bottom Termination	Unit
RMCF1206	8.86	0.126 ± 0.010	0.063 ± 0.006	0.022 ± 0.006	0.020 ± 0.012	0.020 ± 0.012	inches
RMCP1206	8.95	3.20 ± 0.25	1.60 ± 0.15	0.55 ± 0.15	0.50 ± 0.30	0.50 ± 0.30	mm
RMCF1210	15.55	0.126 ± 0.010	0.098 ± 0.010	0.022 ± 0.006	0.020 ± 0.012	0.020 ± 0.012	inches
RMCP1210	15.96	3.20 ± 0.25	2.50 ± 0.25	0.55 ± 0.15	0.50 ± 0.30	0.50 ± 0.30	mm
RMCF2010	23.56	0.197 ± 0.008	0.098 ± 0.008	0.022 ± 0.006	0.024 ± 0.012	0.024 ± 0.014	inches
RMCP2010	24.24	5.00 ± 0.20	2.50 ± 0.20	0.55 ± 0.15	0.60 ± 0.30	0.60 ± 0.35	mm
RMCF2512	40.02	0.248 ± 0.008	0.126 ± 0.010	0.022 ± 0.008	0.024 ± 0.012	0.024 ± 0.014	inches
RMCP2512	39.45	6.30 ± 0.20	3.20 ± 0.25	0.55 ± 0.20	0.60 ± 0.30	0.60 ± 0.35	mm


Performance Characteristics

Test	Test Specifications	Test Conditions (JIS-C 5202)
Short Time Overload	± (2% + 0.1Ω)	2.5 X rated voltage for 5 seconds
	Jumper: Max 0.05Ω after test	0201 = 1A 0402 / 0603 = 2.5A 0805 / 1206 / 1210 / 2010 / 2512 = 5A
Dielectric Withstanding Voltage	No flashover or breakdown	100 VAC, 1 minute
Resistance to Soldering Heat	± 1%	260°C ± 5°C, for 10 seconds ± 0.5 seconds (Solder Bath)
Solderability	95% coverage, minimum	235°C ± 5°C, for 2 seconds ± 0.5 seconds (Colophonium flux)
Temperature Cycle	± (1% + 0.05Ω) Jumper (< 0.05Ω)	-65°C: 30 minutes 25°C: 2 to 3 minutes 155°C: 30 minutes 25°C: 2 to 3 minutes (5 Cycles)
Load Life (Endurance)	1% and below: ± (1% + 0.05Ω) 2% and 5%: ± (3% + 0.1Ω) Value < 1Ω: ± (3% + 0.1Ω) Jumper: Max 0.1Ω after test.	70°C ± 2°C, RCWV or max. working voltage whichever is less for 1000 hours with 1.5 hours "ON" and 0.5 hour "OFF"
Voltage Coefficient	± 100 (ppm/V)	1/10 rated voltage for 3 seconds max. then rated voltage for 3 seconds max.
Robustness of Termination	± (1% + 0.05Ω)	Bend of 2 mm for 5 ± 1 seconds
Resistance to Solvent	1%: ± (0.5% + 0.05Ω) 5%: ± (0.5% + 0.05Ω) Jumper: Max. 0.05Ω after test	The tested resistor should be immersed into isopropyl alcohol of 20°C ~ 25°C for 60 seconds. Then the resistor is left in the room for 48 hours.
Damp Heat with Load	1%: ± (1% + 0.05Ω) 5%: ± (2% + 0.05Ω) Values < 1Ω: ± (3% + 0.1Ω) Jumper: Max. 0.1Ω after test	40°C ± 2°C, 90%~95% R.H. RCWV or max. working voltage whichever is less for 1000 hours with 1.5 hours "ON" and 0.5 hours "OFF"

Operating temperature range is -55°C to +155°C for all sizes except for 01005 size

Operating temperature range for 01005 is -55°C to +125°C

Power Derating Curve:



Repetitive Pulse Information

(This information is for reference only and is not guaranteed performance.)


If repetitive pulses are applied to resistors, pulse wave form must be less than “Pulse limiting voltage”, “Pulse limiting current” or “Pulse limiting wattage” calculated by the formula below.

$$V_p = K\sqrt{P \times R \times T/t}$$

$$I_p = K\sqrt{P/R \times T/t}$$

$$P_p = K^2 \times P \times T/t$$

Where: V_p : Pulse limiting voltage (V)
 I_p : Pulse limiting current (A)
 P_p : Pulse limiting wattage (W)
 P : Power rating (W)
 R : Nominal resistance (ohm)
 T : Repetitive period (sec)
 t : Pulse duration (sec)
 K : Coefficient by resistors type (refer to below matrix)
[V_r : Rated Voltage (V), I_r : Rated Current (A)]



Note 1: If $T > 10 \rightarrow T = 10$ (sec), $T/t > 1000 \rightarrow T/t = 1000$

Note 2: If $T > 10$ and $T/t > 1000$, “Pulse Limiting power (Single pulse) is applied

Note 3: If $V_p < V_r$ ($I_p < I_r$ or $P_p < P$), V_r (I_r , P) is V_p (I_p , P_p)

Note 4: Pulse limiting voltage (current, wattage) is applied at less than rated ambient temperature. If ambient temperature is more than the rated temperature (70°C), please decrease power rating according to “Power Derating Curve”

Note 5: Please assure sufficient margin for use period and conditions for “Pulse limiting voltage”


Note 6: If the pulse waveform is not square wave, please judge after transform the waveform into square wave according to the “Waveform Transformation to Square Wave”.

RMCF Coefficient (K) Matrix


Ohmic Value	K
$R < 10\Omega$	0.50
$10\Omega \leq R < 100\Omega$	0.45
$100\Omega \leq R < 1K\Omega$	0.35
$1K\Omega \leq R < 10K\Omega$	0.25
$10K\Omega \leq R$	0.20

Waveform Transformation to Square Wave


1. Discharge curve wave with time constant " t " → Square wave




2. Damping oscillation wave with time constant of envelope " t " → Square wave




3. Half-wave rectification wave → Square wave



4. Triangular wave → Square wave



5. Special wave → Square wave




RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

Recommended Pad Layout



Type/Code	A	B	C	Unit
RMCF01005	0.008 0.20	0.020 0.50	0.008 0.20	inches mm
RMCF0201	0.012	0.039	0.016	inches
RMCP0201	0.30	1.00	0.40	mm
RMCF0402	0.020	0.059	0.024	inches
RMCP0402	0.50	1.50	0.60	mm
RMCF0603	0.031	0.083	0.035	inches
RMCP0603	0.80	2.10	0.90	mm
RMCF0805	0.047	0.118	0.051	inches
RMCP0805	1.20	3.00	1.30	mm
RMCF1206	0.087	0.165	0.063	inches
RMCP1206	2.20	4.20	1.60	mm
RMCF1210	0.087	0.165	0.110	inches
RMCP1210	2.20	4.20	2.80	mm
RMCF2010	0.138	0.240	0.110	inches
RMCP2010	3.50	6.10	2.80	mm
RMCF2512	0.193	0.315	0.138	inches
RMCP2512	4.90	8.00	3.50	mm

Recommended Solder Profile

This information is intended as a reference for solder profiles for Stackpole resistive components. These profiles should be compatible with most soldering processes. These are only recommendations. Actual numbers will depend on board density, geometry, packages used, etc., especially those cells labeled with “**”.

100% Matte Tin / RoHS Compliant Terminations

Soldering iron recommended temperatures: 330°C to 350°C with minimum duration.
Maximum number of reflow cycles is 3.

Wave Soldering

Description	Maximum	Recommended	Minimum
Preheat Time	80 seconds	70 seconds	60 seconds
Temperature Diff.	140°C	120°C	100°C
Solder Temp.	260°C	250°C	240°C
Dwell Time at Max	10 seconds	5 seconds	*
Ramp DN (°C/sec)	N/A	N/A	N/A

Temperature Diff. = Difference between final preheat stage and soldering stage.

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor


Stackpole Electronics, Inc.

Resistive Product Solutions

Convection IR Reflow


Description	Maximum	Recommended	Minimum
Ramp Up (°C/sec)	3°C/sec	2°C/sec	*
Dwell Time > 217°C	150 seconds	90 seconds	60 seconds
Solder Temp.	260°C	245°C	*
Dwell Time at Max.	30 seconds	15 seconds	10 seconds
Ramp DN (°C/sec)	6°C/sec	3°C/sec	*

Recommended Lead Free Resistor Reflow Profile



Packaging (EIA Standard RS-481)

Packaging Specifications



Reel Type	Wa	M	A	B	C	D	Unit
7" reel for 8 mm tape	0.354 ± 0.020	7.008 ± 0.079	0.079 ± 0.020	0.531 ± 0.020	0.827 ± 0.020	2.362 ± 0.039	inches
	9.00 ± 0.50	178.00 ± 2.00				60.00 ± 1.00	mm
10" reel for 8 mm tape	0.394 ± 0.020	10.000 ± 0.079	2.00 ± 0.50	13.50 ± 0.50	21.00 ± 0.50	3.937 ± 0.039	inches
	10.00 ± 0.50	254.00 ± 2.00				100.00 ± 1.00	mm


RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.


Resistive Product Solutions

Taping Specifications - 01005, 0201, 0402



Type/Code	7" Reel Quantity	Typical Full Reel Weight (g)	Tape Width	A	B	W	E	F	Unit
RMCF01005	10000	127.3 ± 12.0	0.315 8.00	0.018 ± 0.001 0.45 ± 0.02	0.010 ± 0.001 0.25 ± 0.02	0.315 ± 0.008 8.00 ± 0.20	0.069 ± 0.004 1.75 ± 0.10	0.138 ± 0.002 3.50 ± 0.05	inches mm
RMCF0201 RMCP0201		97.2 ± 9.0		0.028 ± 0.006 0.70 ± 0.15	0.016 ± 0.006 0.40 ± 0.15				inches mm
RMCF0402 RMCP0402		94.5 ± 9.0		0.047 ± 0.006 1.20 ± 0.15	0.028 ± 0.006 0.70 ± 0.15				inches mm
Type/Code	T1	T2	P	P0	P1	Unit			
RMCF01005	0.012 ± 0.001 0.31 ± 0.03	0.007 ± 0.001 0.17 ± 0.03	0.079 ± 0.004 2.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	inches mm			
RMCF0201 RMCP0201	0.015 ± 0.006 0.38 ± 0.15	0.011 ± 0.001 0.28 ± 0.02				inches mm			
RMCF0402 RMCP0402	0.016 ± 0.008 0.40 ± 0.20	0.016 ± 0.002 0.40 ± 0.05				inches mm			

Taping Specifications - 0603, 0805, 1206, 1210



Type/Code	7" Reel Quantity ⁽¹⁾	Typical Full Reel Weight (g)	Tape Width	A	B	W	E	Unit
RMCF0603 RMCP0603	5000	118.3 ± 11.0	0.315 8.00	0.071 ± 0.008 1.80 ± 0.20	0.041 ± 0.008 1.05 ± 0.20	0.315 ± 0.008 8.00 ± 0.20	0.069 ± 0.004 1.75 ± 0.10	inches
RMCF0805 RMCP0805	5000	139.2 ± 13.0		0.093 ± 0.010 2.35 ± 0.25	0.063 ± 0.010 1.60 ± 0.25			mm
RMCF1206 RMCP1206	5000	151.4 ± 15.0		0.140 ± 0.010 3.55 ± 0.25	0.077 ± 0.010 1.95 ± 0.25			inches
RMCF1210 RMCP1210	4000	175.7 ± 17.0		0.138 ± 0.008 3.50 ± 0.20	0.110 ± 0.010 2.80 ± 0.25			mm

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor


Stackpole Electronics, Inc.

Resistive Product Solutions

Taping Specifications - 0603, 0805, 1206, 1210 (cont.)

Type/Code	F	T1	T2	P	P0	P1	Unit
RMCF0603	0.138 ± 0.002 3.50 ± 0.05	0.024 ± 0.008	0.024 ± 0.004	0.157 ± 0.004 4.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	inches
RMCP0603		0.60 ± 0.20	0.60 ± 0.10				mm
RMCF0805		0.030 ± 0.008	0.030 ± 0.004				inches
RMCP0805		0.75 ± 0.20	0.75 ± 0.10				mm
RMCF1206		0.030 ± 0.008	0.030 ± 0.004				inches
RMCP1206		0.75 ± 0.20	0.75 ± 0.10				mm
RMCF1210	0.030 ± 0.008	0.030 ± 0.008	0.030 ± 0.004	0.030 ± 0.008	0.030 ± 0.004	0.030 ± 0.004	inches
RMCP1210		0.75 ± 0.20	0.75 ± 0.10				mm

Taping Specifications - 2010, 2512



Type/Code	7" Reel Quantity	Typical Full Reel Weight (g)	Tape Width	A	B	W	E	F	Unit
RMCF2010	4000	183.1 ± 18.0	0.472	0.217 ± 0.012	0.110 ± 0.008	0.472 ± 0.008	0.069 ± 0.004	0.217 ± 0.002	inches
RMCP2010				5.50 ± 0.30	2.80 ± 0.20				mm
RMCF2512		255.3 ± 25.0	12.00	0.264 ± 0.008	0.134 ± 0.008				inches
RMCP2512				6.70 ± 0.20	3.40 ± 0.20				mm
Type/Code	T1		T2	P	P0	P1		Unit	
RMCF2010	0.041 ± 0.008 1.05 ± 0.20	0.009 ± 0.006 0.23 ± 0.15	0.157 ± 0.004 4.00 ± 0.10	0.157 ± 0.004 4.00 ± 0.10	0.079 ± 0.002 2.00 ± 0.05	inches			
RMCP2010						mm			
RMCF2512						inches			
RMCP2512	mm								

Note: Plastic carrier tape used for 2010 and 2512 sizes.


RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

Single Pulse Power



The data provided are for reference only. They are typical performance for this product but are not guaranteed. The actual pulse handling of each individual resistor may vary depending on a variety of factors including resistance tolerance and resistance value. Stackpole Electronics, Inc. assumes no liability for the use of this information. Customers should validate the performance of these products in their applications. Contact Stackpole marketing to discuss specific pulse application requirements.

Temperature Measurement of Resistor Surface

Description: The resistor surface generated temperature variation after applied rated voltage.


Products and power:

Size	0201	0402	0603	0805	1206	1210	2010	2512
R-V	15K	40.2K	57.6K	180K	182K	100K	100K	75K
Rated Power (W)	1/20	1/16	1/10	1/8	1/4	1/2	3/4	1
Max Rated Voltage (V)	25	50	75	150	200	200	200	200

Test method: Measure component surface temperature directly after the temperature stabilizes.

Test result: As per table below:

Hot Spot Temperature - RMCF



Size	0201	0402	0603	0805	1206	1210	2010	2512
Surface Temp. (°C)	36	37	46.2	50.4	70.6	110.6	141	150.4

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

The thermal resistance of the RMCP will be similar to the RMCF. For example, the RMCF2512 and the RMCP2512 will have similar surface temperatures at 1W; the RMCP is designed to withstand higher temperatures associated with high power levels.

Part Marking Specifications



1% Marking

The nominal resistance is marked on the surface of the overcoating with the use of 4 digit markings.
0201 and 0402 are not marked.



5% Marking

The nominal resistance is marked on the surface of the overcoating with the use of 3 digit markings.
0201 and 0402 are not marked.

For shared E24/E96 values, 1% tolerance product may be marked with three digit marking instead of the standard four-digit marking for all other E96 values. All E24 values available in 1% tolerance are also marked with three-digit marking.

Marking Instructions for 0603 1% Chip Resistors (per EIA-J)

A two-digit number is assigned to each standard R-Value (E96) as shown in the chart below. This is followed by one alpha character which is used as a multiplier. Each letter represents a specific multiplier as follows:

Z = 0.01	A = 10	D = 10000
Y = 0.1	B = 100	E = 100000
X = 1	C = 1000	F = 1000000

EXAMPLE:

Chip Marking	Explanation	Value
01B	01 means 10.0 and B = 100	10.0 x 100 = 1K ohm
25C	25 means 17.8 and C = 1,000	17.8 x 1,000 = 17.8K ohm
93D	93 means 90.9 and D = 10,000	90.9 x 10,000 = 909K ohm

E96

#	R-Value	#	R-Value	#	R-Value	#	R-Value	#	R-Value	#	R-Value
01	10.0	17	14.7	33	21.5	49	31.6	65	46.4	81	68.1
02	10.2	18	15.0	34	22.1	50	32.4	66	47.5	82	69.8
03	10.5	19	15.4	35	22.6	51	33.2	67	48.7	83	71.5
04	10.7	20	15.8	36	23.2	52	34.0	68	49.9	84	73.2
05	11.0	21	16.2	37	23.7	53	34.8	69	51.1	85	75.0
06	11.3	22	16.5	38	24.3	54	35.7	70	52.3	86	76.8
07	11.5	23	16.9	39	24.9	55	36.5	71	53.6	87	78.7
08	11.8	24	17.4	40	25.5	56	37.4	72	54.9	88	80.6
09	12.1	25	17.8	41	26.1	57	38.3	73	56.2	89	82.5
10	12.4	26	18.2	42	26.7	58	39.2	74	57.6	90	84.5
11	12.7	27	18.7	43	27.4	59	40.2	75	59.0	91	86.6
12	13.0	28	19.1	44	28.0	60	41.2	76	60.4	92	88.7
13	13.3	29	19.6	45	28.7	61	42.2	77	61.9	93	90.9
14	13.7	30	20.0	46	29.4	62	43.2	78	63.4	94	93.1
15	14.0	31	20.5	47	30.1	63	44.2	79	64.9	95	95.3
16	14.3	32	21.0	48	30.9	64	45.3	80	66.5	96	97.6

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union's directive regarding "Restrictions on Hazardous Substances" (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status						
Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
RMCF	General Purpose Thick Film Surface Mount Chip Resistor	SMD	YES ⁽¹⁾	100% Matte Sn over Ni	Jan-04 (Japan) Jan-05 (Taiwan, China)	04/01 05/01
RMCP	General Purpose High Power Thick Film Chip Resistor	SMD	YES ⁽¹⁾	100% Matte Sn over Ni	Always	Always

Note (1): RoHS Compliant by means of exemption 7c-l.

"Conflict Metals" Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the "conflict region" of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to "REACH"

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, "The Registration, Evaluation, Authorization and Restriction of Chemicals", otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy

It is the policy of Stackpole Electronics, Inc. (SEI) to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

RMCF / RMCP Series

General Purpose Thick Film Standard Power
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

How to Order - RMCF

R M C F 0 6 0 3 J T 4 K 7 0

Product Series		Size		Tolerance			Packaging				Resistance Value			
Code	Description	Size	W	Code	Tol	Value	Code	Description	Size	Quantity	Four characters with the multiplier used as the decimal holder.			
RMCF	Thick Film Chip	01005	0.03	F	1%	E96, E24	T	7" Reel - Paper Tape	01005	10000	0.1 ohm = R100			
		0201	0.05	J	5%	E24			0201, 0402	10000	4.70 ohm = 4R70			
		0402	0.063	Z	Jumper				0603, 0805, 1206	5000	10.0 Kohm = 10K0			
		0603	0.1						1210	4000	1 Mohm = 1M00			
		0805	0.125					7" Reel - Plastic Tape	2010, 2512	4000	Zero ohm jumper = 0R00			
		1206	0.25											
		1210	0.5				G	10" Reel - Paper Tape						
		2010	0.75											
		2512	1						0603, 0805, 1206	10000				

How to Order - RMCP

R M C P 0 6 0 3 J T 4 K 7 0

Product Series		Size		Tolerance			Packaging				Resistance Value	
Code	Description	Size	W	Code	Tol	Value	Code	Description	Size	Quantity	Four characters with the multiplier used as the decimal holder.	
RMCP	High Power	0201	0.063	F	1%	E96, E24	T	7" Reel Paper Tape	0201, 0402	10000		
		0402	0.125	J	5%	E24			0603, 0805	5000		
		0603	0.25	Z	Jumper				1206, 1210	5000		
		0805	0.33			2010, 2512			4000			
		1206	0.5				G	10" Reel Paper Tape	0603, 0805	10000		
		1210	0.66						1206			
		2010	1									
		2512	2									

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Thick Film Resistors - SMD](#) ***category:***

Click to view products by [Stackpole](#) ***manufacturer:***

Other Similar products are found below :

[M55342K08B46E4SWL](#) [M55342K08B62J0SUL](#) [M55342K08B6J20SWB](#) [MCR01MZPF1202](#) [MCR01MZPF1800](#) [MCR01MZPF6201](#)
[MCR01MZPJ121](#) [MCR01MZPJ751](#) [MCR03EZPFX2004](#) [MCR10EZPF1102](#) [RC1005F2052CS](#) [RC1005F471CS](#) [RC1005J122CS](#)
[RC1005J180CS](#) [RC1005J181CS](#) [RC1608F333CS](#) [RC1608J121CS](#) [RC2012F2493CS](#) [RC2012J105CS](#) [RC2012J470CS](#) [RC2012J561CS](#)
[RC2012J8R2CS](#) [RC3216F272CS](#) [RCP0603W100RGED](#) [RCWP1100100KFKS3](#) [RCWP110037R4FKED](#) [RCWP110043R2FKS3](#)
[RCWP72251K47FKWB](#) [RMCF0201FT49R9](#) [RMCF0603FT300K](#) [RMCF0805FT221K](#) [RMCF1210JT20R0](#) [RMCF1210JT68K0](#)
[RMCF1210ZT0R00](#) [RMCF2512FT1R00](#) [RMCF2512JT20R0](#) [RMCF2512JT7K50](#) [RMCF2512JT910R](#) [NRC04F1000TRF](#) [NRC04F1004TRF](#)
[NRC04F10R0TRF](#) [NRC04F1132TRF](#) [NRC04F2001TRF](#) [NRC04F2002TRF](#) [NRC04F2203TRF](#) [NRC04F3011TRF](#) [NRC04F33R0TRF](#)
[NRC04F51R1TRF](#) [NRC04J103TRF](#) [NRC04J204TRF](#)