

USB-C Multiport Adapter w/Attached USB-C to USB-A Dongle, Dual HDMI (4K30Hz/1080p60Hz), 3x USB-A 5Gbps, Mini Travel Dock, Laptop Docking Station, 1.3ft/40cm Cable

Product ID: 167B-USBC-MULTIPORT



This USB Type-C & USB Type-A Multiport Adapter turns almost any laptop or desktop into a high-productivity workstation that supports dual external HDMI displays and features a 3-port USB hub. The Mini Dock has a built-in 1.3ft (40cm) USB-C host cable and includes a tethered USB-C to USB-A adapter, so it can support both USB-C and USB-A host computers.

Enhance productivity with two HDMI output ports for connecting external monitors. The HDMI output ports support resolutions up to 4K 30Hz (Video Output 1, HDMI 1.4), and 1080p 60Hz (Video Output 2, HDMI 1.2). Dual external monitors increase productivity - enabling users to have different applications, documents, or windows open on each monitor.

The Multiport Adapter is compatible with Windows, macOS, and Chrome OS. With its tethered USB-C to USB-A dongle that ensures it ensures seamless USB compatibility with any host running a supported OS. The Multiport Adapter supports dual-extended displays on Apple M1/M2/M3 MacBooks, which are not capable of driving more than one external display natively.

The USB-C & USB-A Multiport Adapter features three downstream USB-A ports. For fast and reliable data transfers the built-in USB hub supports SuperSpeed USB 3.2 Gen 1 (5Gbps) and is backward compatible with legacy USB 2.0 and USB 1.1 (HID) devices.

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that is compatible with a wide variety of IT connectivity accessories. The software suite includes:

Advanced Windows Layout Utility: Setup and save custom windows layouts.

USB Event Monitoring Utility: Track and log connected USB devices.

For more information and to download the StarTech.com Connectivity Tools application, please visit:
www.startech.com/connectivity-tools

Certifications, Reports and Compatibility



Applications

- Home office IT deployment, ideal for traveling between the home and office
- Run multiple applications on extended HDMI displays

Features

- **INCREASED PRODUCTIVITY:** Multiport Adapter adds dual HDMI displays to almost any laptop with a built-in USB-C host cable & attached USB-C to USB-A dongle; Supports resolutions up to 4K 30Hz (HDMI 1.4, Video Output 1) & 1080p 60Hz (HDMI 1.2, Video Output 2)
- **APPLE M-SERIES DUAL DISPLAY COMPATIBLE:** Works with macOS, Windows, ChromeOS and Ubuntu, enabling extended dual displays on USB & Thunderbolt laptops incl. Apple M-Series MacBooks which are not capable of driving more than 1 external display natively
- **HIGH-PERFORMANCE:** 3-Port USB Type-A (5Gbps) Hub for fast/reliable data transfer; Works with legacy USB 2.0/1.1; Portable bus-powered adapter; Silicon Motion's Content Adaptive Technology uses processing algorithms to reduce latency for smoother graphics
- **EXTRA-LONG CABLE:** Extended port reach with attached 1.3ft (40cm) host cable for easy setup that prevents adapter from dangling on the host connector; Ideal cable length to reduce port strain on 2-in-1 convertible laptops, or host laptops on riser stands
- **OUR ADVANTAGE:** Hybrid Mini docking station incl. Connectivity Tools app w/USB Event Monitoring to log/timestamp USB port usage for admins to identify potentially malicious devices & Windows Layout Utility restores app locations when re-connecting displays

General

UPC	065030901260
Warranty	3 Years

Special Notes / Requirements

Special Notes	USB 3.2 Gen 1 (5Gbps) is also known as USB 3.1 Gen 1 (5Gbps) and USB 3.0 (5Gbps)
	When installed on Linux, this adapter supports up to two 1080p 60Hz displays
System and Cable Requirements	Manual driver installation is required for macOS

Power

Power Source	Bus Powered
Power Delivery	No PD Pass-Through

Physical & Environmental

Color	Space Gray
Material	Aluminum
Cable Length	15.7 in [400 mm]
Product Length	4.7 in [120.5 mm]
Product Width	2.2 in [56.6 mm]
Product Height	0.6 in [16.5 mm]
Weight of Product	4.0 oz [114.0 g]
Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	-10C to 60C (14F to 140F)
Humidity	10% to 90% RH

Performance

Maximum Data Transfer Rate	5Gbps
Type and Rate	USB 5Gbps
UASP Support	Yes
MTBF	30,000 Hours
Maximum Digital Resolutions	Video Output 1: 4K 30Hz

Video Output 2: 1080p 60Hz

Hardware

Fast-Charge Port(s)	No
4K Support	Yes
Displays Supported	2
Interface	USB 3.2 Gen 1 (5Gbps)
Bus Type	USB-C
	USB-A
Number of Displays	2
Industry Standards	HDMI 1.4
	HDMI 1.2
	USB 3.2 Gen 1 (5Gbps)
Chipset ID	SMI - SM768G0
	ITE - IT66121FN
	VIA - VL817C0
	Terminus - FE1.1S

Packaging & In-the-Box

Included in Package	1 - Multiport Adapter
	1 - Quick-Start Guide
Package Width	7.2 in [184 mm]
Package Depth	5.2 in [131 mm]
Package Height	1.3 in [32 mm]
Shipping (Package) Weight	6.2 oz [176 g]

Connector(s)

Host Connector 1 (Quantity)	1
-----------------------------	---

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) ***category:***

Click to view products by [Startech](#) ***manufacturer:***

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)