


M.2 to U.3 Adapter for M.2 NVMe SSDs, PCIe M.2 Drive to 2.5inch U.3 (SFF-TA-1001) Host Adapter/Converter, TAA Compliant - 2.5" Drive Form Factor

Product ID: 1M25-U3-M2-ADAPTER



Convert and connect a PCIe M.2 NVMe/AHCI SSD to a 2.5inch form factor to install in a U.3 drive bay or backplane.

Change the form factor of a 2242, 2260, or 2280 M.2 NVMe drive while maintaining PCIe Gen 4 read and write speeds. This adapter has been designed with no chipset to maintain performance when adapting an M.2 drive to a 2.5-inch form factor.

The M.2 to U.3 Host Adapter is compatible with all operating systems, including Windows, macOS, and Linux. No additional drivers or software for installation and operation. The adapter includes M.2 drive and U.3 adapter mounting hardware.

The M.2 to U.3 Host Adapter is backward compatible with earlier versions of M.2 PCIe NVMe drives. It is not compatible with SATA or SAS host controllers, M.2 SATA SSDs, or U.2 host interfaces.

Certifications, Reports and Compatibility



Applications

- Connect an M.2 NVMe SSD to a computer or server through an available U.3 (SFF-TA-1001) connection to increase data storage capacity

- Enhance productivity for data-intensive applications, making it ideal for developers and content creators

Features

- **COMPATIBILITY:** This drive adapter is compatible with U.3 (SFF-TA-1001) host interfaces and PCIe M.2 NVMe/AHCI SSD drives only and does not support SATA/SAS/U.2 host controllers or SATA-based M.2 SSDs; M.2 to U.3 Adapter is TAA Compliant
- **FULL PERFORMANCE:** Change the form factor of a 2242, 2260, or 2280 M.2 NVMe drive while preserving the read and write speeds; No chipset design ensures no loss in performance when adapting to 2.5inch
- **HASSLE-FREE SETUP:** M.2 to U.3 Host Adapter works with all operating systems including Windows, macOS, and Linux; M2 to U.3 Adapter requires no additional drivers or software; Includes drive and adapter mounting screws for an efficient installation
- **VERSATILE M.2 NVME SUPPORT:** Open frame design enables support for M.2 drives with larger heatsinks, and allows for better airflow; Supports PCIe 4.0 and lower drives; SFF-TA-1001 is not compatible with SATA/SAS/U.2 host controllers or SATA-based M.2 SSDs
- **OUR ADVANTAGE:** IT professionals' choice for over 30 years; This M2 to U.3 converter is backed for two years, including free 24/5 North America based multi-lingual technical assistance

General

UPC	065030900744
Warranty	2 Years

Special Notes / Requirements

Special Notes	NVMe SSDs may require additional drivers, provided by the manufacturer, or may be natively provided by the operating system (Windows 8 and later - Mac OS 10.10.3 and later). Earlier OS versions do not have native NVMe support.
---------------	--

Power

Output Voltage	3.3V DC
Output Current	5A

Physical & Environmental

Color	Red
Product Length	3.9 in [100.0 mm]
Product Width	2.8 in [70.0 mm]
Product Height	0.3 in [7.0 mm]

Weight of Product	1.3 oz [37.0 g]
Operating Temperature	0C to 50C (32F to 122F)
Storage Temperature	-40C to 85C (-40F to 185F)
Humidity	15% - 90% RH

Performance

S.M.A.R.T. Support	Yes
RAID	No
Insertion Rating	60 Cycles
MTBF	12,368,734 Hours

Hardware

Fans Included? Yes/No	No
Interface	U.3 (PCIe, NVMe, SFF-TA-1001)
Bus Type	PCI Express
Number of Drives	1
Compatible Drive Types	M.2 (PCIe, NVMe, M-Key, NGFF)
Supported Drive Height(s)	2242
	2260
	2280

Packaging & In-the-Box

Included in Package	1 - M.2 to U.3 Adapter
	1 - Quick-Start Guide
Package Width	6.9 in [175 mm]
Package Depth	5.6 in [142 mm]
Package Height	1.3 in [33 mm]
Shipping (Package) Weight	4.7 oz [132 g]

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) ***category:***

Click to view products by [Startech](#) ***manufacturer:***

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)