

USB C Multiport Adapter - Portable USB-C Mini Dock 4K HDMI Video - Gigabit Ethernet, USB 3.0 Hub (1x USB-A 1x USB-C) - USB Type-C Multiport Adapter - Thunderbolt 3 Compatible - TAA

Product ID: DKT30CHD



This USB-C Multiport Adapter with HDMI combines the capability of three single-function adapters, a USB-C video adapter, USB-C to USB 3.0 adapter, and Gigabit Ethernet adapter, into a portable docking station for your laptop. You can connect a 4K HDMI display and two USB 3.0 devices (1x USB-A, 1x USB-C), and get high-speed network access, all through a single cable.

The USB Type-C adapter is compatible with Thunderbolt 3 ports.

With HDMI output, this USB-C multiport adapter makes it easy to expand your virtual workspace onto an external 4K HDMI monitor. The adapter supports resolutions up to 4096 x 2160p (24Hz) or 3840 x 2160p (30Hz), as well as audio.

The USB-C multiport adapter ensures a reliable wired network connection with a Gigabit Ethernet port, which is ideal for areas with limited Wi-Fi access such as in classrooms, office buildings and hotels.

With two USB 3.0 ports (1x USB-A, 1x USB-C) you get access to traditional USB Type-A devices, as well as newer USB-C devices you add in the future.

With its compact design and bus-powered performance, the portable multiport adapter is easy to take with you anywhere you take your laptop. The adapter features a pre-attached USB-C cable, so you have one less cable to carry when you're on the move.

- Maximum compatibility - StarTech.com has a docking station to fit every operating system, laptop brand, and connectivity need

Get more done faster - More ports and more displays maximize end user connectivity and productivity

Quick installation - eliminate deployment headaches that waste time and frustrate end users

IT Grade quality - trusted by IT pros around the world for our rigorous in-house product testing, robust compliance, and lifetime multilingual technical support

The DKT30CHD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: Your USB-C equipped host laptop must support video (DP Alt Mode) to work with this adapter. The adapter does not support USB Power Delivery.

Certifications, Reports and Compatibility



Applications

- Ideal for mobile use
- Integrate into small workspaces in offices and home offices

Features

- **DOCKING STATION WITH ESSENTIAL PORTS:** 4-in-1 USB C multiport adapter with 4K 30Hz HDMI video output, Gigabit Ethernet port, USB 3.0 Hub 5Gbps (1x USB-A and 1x USB-C ports); USB bus-powered
- **EXTRA LONG CABLE:** Mini dock has an attached 13 in (34cm) cable to provide extended reach to reduce connector strain on 2-in-1 devices like Surface Pro 7, iPad Pro, HP Elite or laptops on riser stands
- **DESIGNED FOR PORTABILITY:** USB-C port expander w/ ultra compact square design for presentations in meeting rooms connected to a TV/display/monitor, working from home or on the go
- **WIDE DEVICE COMPATIBILITY:** USB-C and Thunderbolt 3 laptops, ultrabooks, USB-C Chromebook, tablets and phones for brands such as HP, Dell, Lenovo, MacBooks, iPad Pro, Surface, Samsung and Pixelbook
- **WIDE OS COMPATIBILITY & EASY SETUP:** Universal USB Type-C multiport adapter features automatic driver installation & supports major operating systems like Windows, macOS, Chrome OS, iPadOS and Android

General

UPC	065030868266
Package Quantity	1

Warranty 3 Years

Special Notes / Requirements

Special Notes	Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your laptop USB-C port supports DP alt mode. A 4K-capable display is required to achieve 4K x 2K resolution (4K is also known as 4K x 2K). USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps. The USB Type-C connector (female) is data only.
System and Cable Requirements	Host laptop with an available USB-C port (to ensure full functionality, the laptop's USB-C port must support DP alt mode).

Power

Power Source	USB-Powered
Power Delivery	No PD Pass-Through
Output Voltage	5 DC

Physical & Environmental

Color	Black
Material	Plastic
Cable Length	13.4 in [340 mm]
Product Length	2.6 in [65 mm]
Product Width	2.4 in [62 mm]
Product Height	0.6 in [15 mm]
Weight of Product	1.8 oz [52 g]
Operating Temperature	0C to 60C (32F to 140F)
Storage Temperature	-20C to 60C (-4F to 140F)
Humidity	5~90% RH (Non-condensing)

Performance

Maximum Data Transfer Rate	5 Gbps (USB 3.0) <br / >2 Gbps (Ethernet; Full-Duplex)
Type and Rate	USB 3.0 (5Gbps)
UASP Support	Yes
Compatible Networks	10/100/1000 Mbps
Auto MDIX	Yes
Full Duplex Support	Yes
Maximum Digital Resolutions	4096 x 2160p @ 24Hz or 3840 x 2160p (HDMI) @ 30Hz

Hardware

Fast-Charge Port(s)	No
4K Support	Yes
Displays Supported	1
Bus Type	USB-C
Number of Displays	1
Chipset ID	Genesys Logic - GL3523 Realtek - RTL8153 Parade - PS176

Packaging & In-the-Box

Included in Package	1 - USB-C multiport adapter 1 - quick-start guide
Package Width	8.3 in [212 mm]
Package Depth	5.7 in [145 mm]
Package Height	1.7 in [42 mm]
Shipping (Package) Weight	5.9 oz [168 g]

Connector(s)

Connector 1 (Quantity)	1
------------------------	---

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) ***category:***

Click to view products by [Startech](#) ***manufacturer:***

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)