

USB C Multiport Adapter - USB-C Travel Dock to 4K HDMI, 3x USB 3.0 Hub, SD/SDHC, GbE, 100W PD 3.0 Pass-Through - Portable USB-C Mini Docking Station USB Type-C/Thunderbolt 3

Product ID: DKT30CSDHPD3



This USB-C multiport adapter with HDMI turns your MacBook Pro, Dell XPS, or other USB-C laptop into a workstation, anywhere you go. The USB Type-C multiport adapter provides 4K HDMI video output, a USB Type-C port (data/power), two USB 3.0 Type-A ports, a Gigabit Ethernet port and an SD card reader slot, all through one connection to your laptop's USB-C or Thunderbolt 3 port. Plus, it offers advanced charging through USB Power Delivery 3.0.

The portable docking station connects your laptop to a 4K HDMI monitor (4096 x 2160p) to create a powerful workstation. It can also connect to an ultrawide monitor.

The USB-C to USB 3.0 hub gives you one USB-C port and two USB-A ports to connect your latest and legacy USB devices.

Access your multimedia content with ease. The multiport adapter provides direct access to your SD, SDHC and SDXC memory cards or microSD cards (with adapter, sold separately).

With support for USB PD 3.0 (up to 100W), the USB Type-C multiport adapter lets you power and charge your laptop, and power your peripherals when connected to a USB-C power adapter. PD 3.0 features Fast Role Swap to prevent USB data disruption when you switch power sources (USB-C power adapter to bus power).

The Gigabit Ethernet port ensures reliable wired network access.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.

Certifications, Reports and Compatibility



Applications

- Ideal for meetings and making presentations in the boardroom
- Transfer photos, videos or other files from your SD cards to your USB-C laptop, tablet or other device
- Use an HDMI port-equipped television in a hotel room as an external display
- Power the adapter and your laptop through USB-C, using your laptop's power adapter
- Ideal for small workspaces in offices, home offices as well as office hoteling

Features

- **USB-C MULTIPOINT ADAPTER:** Portable USB C travel docking station with 4K 30Hz HDMI video output; aluminum space gray design complements Macbook Air, MacBook Pro, Dell XPS, HP EliteBook laptops
- **6-IN-1 USB-C HUB:** This USB C multiport adapter features 4K HDMI (UHD), 2x USB-A 3.0 (5Gbps) and 1x USB-C (Data or Power Delivery 3.0 Pass Through), SD / SDHC / SDXC card reader slot & Gigabit Ethernet
- **100W PD 3.0 PASS THROUGH:** Use a USB-C power adapter to charge laptop (up to 88W) & power the dock (12W); Prevents USB device drop out when the power is added/removed on PD 3.0 laptops like MacBook Pro
- **WIDE DEVICE COMPATIBILITY:** USB-C mini dock works w/ Thunderbolt 3 (TB3) laptops/ultrabooks; USB-C laptops, ultrabooks, chromebooks, tablets & phones for brands like MacBook, HP, Dell, Lenovo, Surface
- **WIDE OS COMPATIBILITY & EASY SETUP:** This USB Type-C Multiport adapter has automatic driver installation & supports Windows, macOS, Chrome OS and Android; ideal for business travel and work from home

General

UPC	065030880022
Package Quantity	1
Warranty	3 Years

Special Notes / Requirements

Special Notes

Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 or higher and DP alt mode.

The adapter can connect to a host laptop's USB-C port that doesn't support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.

A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)

USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.

Your laptop might have specific charging requirements. For example, if your laptop requires exactly 60W of power and an adapter consumes some of the 60W, your laptop might not recognize that it is getting enough power. For more information about Power Delivery, refer to the manufacturer of your hardware.

System and Cable Requirements

A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode)

Optional: USB-C power adapter (for example, your laptop's USB-C based power adapter)

Power

Power Source	USB-Powered
Power Delivery	100W
Output Voltage	5 DC

Physical & Environmental

Color	Space Gray
Material	Aluminum
Cable Length	6.0 in [152.4 mm]
Product Length	10.6 in [270.0 mm]
Product Width	1.8 in [45.0 mm]
Product Height	0.6 in [15.0 mm]

Weight of Product	3.0 oz [85.0 g]
Operating Temperature	0C to 45C (32F to 113F)
Storage Temperature	-10C to 85C (14F to 185F)
Humidity	5~90% RH (Non-condensing)

Performance

Maximum Data Transfer Rate	5 Gbps (USB 3.0) <br / >2 Gbps (Ethernet; Full-Duplex)
Type and Rate	USB 3.0 (5Gbps)
UASP Support	Yes
Compatible Networks	10/100/1000 Mbps
Auto MDIX	Yes
Full Duplex Support	Yes
Memory Media Type	Secure Digital Card
	SDHC (Secure Digital High Capacity)
	SDXC (Secure Digital eXtended Capacity)
	microSD (Micro Secure Digital) (adapter required)
	microSDHC (Micro Secure Digital High Capacity) (adapter required)
	microSDXC (Micro Secure Digital eXtended Capacity) (adapter required)
Maximum Digital Resolutions	4096 x 2160p @ 24Hz or 3840 x 2160p (HDMI) @ 30Hz
	UltraWide - 3440 x 1440p @ 60 Hz or 2560x1080 at 60Hz
	Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p.

Hardware

Fast-Charge Port(s)	No
4K Support	Yes

Displays Supported	1
Bus Type	USB-C
Number of Displays	1
Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1
Chipset ID	VIA/VLI - VL163 VIA Labs - VL163 VIA/VLI - VL817S Genesys Logic - GL3224 Parade - PS178 Realtek - RTL8153B

Packaging & In-the-Box

Included in Package	1 - multiport adapter 1 - quick-start guide
Package Width	4.8 in [122 mm]
Package Depth	6.4 in [163 mm]
Package Height	1.4 in [35 mm]
Shipping (Package) Weight	5.4 oz [152 g]

Connector(s)

Connector 1 (Quantity)	1
Connector 1	USB-C (5Gbps, 4.5W)
Connector 2 (Quantity)	1
Connector 2	HDMI
Connector 3 (Quantity)	1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) ***category:***

Click to view products by [Startech](#) ***manufacturer:***

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)