

## 15 ft Cat5e Blue Snagless Shielded RJ45 STP Cat 5e Patch Cable - 15ft Patch Cord

**Product ID:** S45PATCH15BL



Ensure reliable, interference-free network performance with this Cat5e Shielded F UTP Snagless Patch Cable, built to support consistent connectivity in demanding IT environments. Full-length shielding and protected RJ45 connectors help reduce EMI, RFI, and crosstalk, while the snagless boot and molded strain relief safeguard against damage during installs and routine use. Constructed with 100% copper conductors and gold-plated connectors, this cable delivers dependable signal integrity and long-term durability you can trust.

### Certifications, Reports and Compatibility



### Applications

- Designed for Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems and other applications requiring high-speed cables
- Works with 1000 BASE-T, 100 BASE-T, 10 BASE-T, Token Ring, ATM & ISDN networks
- Suited for industrial applications

### Features

- **HIGH PERFORMANCE CAT5E ETHERNET CABLE:** 100% copper for consistent & error-free 1 gigabit connection. Individually tested to comply with ANSI/TIA-568.2-D Category 5e requirements; UL Listed
- **PROTECT YOUR NETWORK:** Shielded RJ45 connectors minimize Near-End Crosstalk (NEXT) & protect against

noise & electromagnetic (EMI/RFI) interference; Compatible w/ multi-speed 10Base-T/100Base-TX/1000Base-T networks

- **QUALITY CONSTRUCTION:** 50-micron gold-plated contacts for clear signal & to stop rust/corrosion. Snagless connector enables easy installation & flexible disconnection of patch cord in wiring conduits
- **POE SUPPORT:** 24 AWG stranded copper conductors & UL Listed wiring (E151955) support up to 100W for PoE devices like VOIP phone & security systems. IEEE 802.3bt & DTE power compliant to prevent cable overheating
- **SOPORTE DE PoE:** Conductores de cobre 24 AWG y cableado con certificacin UL (E151955) admiten hasta 100W en dispositivos PoE – Conforme a IEEE 802.3bt y alimentacin DTE para evitar sobrecalentamiento del cable
- **SOPORTE DE PoE:** Conductores de cobre 24 AWG y cableado con certificacin UL (E151955) admiten hasta 100W en dispositivos PoE – Conforme a IEEE 802.3bt y alimentacin DTE para evitar sobrecalentamiento del cable
- **THE IT PRO'S CHOICE:** Designed for reliability in edge and on-prem deployments, our network cables are lab-tested and field-proven for seamless integration and maximum uptime; Backed by free lifetime 24/5 multi-lingual technical assistance
- **LA ELECCIN DEL PROFESIONAL DE INFORMTICA:** Cables fiables para despliegues perimetrales y locales, probados en laboratorio y en campo para integracin fluida y mxima disponibilidad – Asistencia tcnica multilinge gratuita de por vida 24/5
- **LA ELECCIN DEL PROFESIONAL DE TI:** Cables confiables para despliegues perimetrales y locales, probados en laboratorio y en campo para integracin fluida y mxima disponibilidad – Asistencia tcnica multilinge gratuita de por vida 24/5

---

#### Hardware

|                       |                             |
|-----------------------|-----------------------------|
| Warranty              | Lifetime                    |
| Number of Conductors  | 4-Pair STP                  |
| Cable Jacket Material | PVC - Polyvinyl Chloride    |
| Fire Rating           | CMG Rated (General Purpose) |

---

#### Connector(s)

|             |           |
|-------------|-----------|
| Connector A | 1 - RJ-45 |
| Connector B | 1 - RJ-45 |

---

#### Environmental

|                       |                           |
|-----------------------|---------------------------|
| Operating Temperature | 0C to 50C (32F to 122F)   |
| Storage Temperature   | -20C to 70C (-4F to 158F) |
| Humidity              | 0-95% RH                  |

---

#### Physical

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for*** [Ethernet Cables / Networking Cables](#) ***category:***

***Click to view products by*** [Startech](#) ***manufacturer:***

Other Similar products are found below :

[73-7795-1](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1-1997459-2](#) [1-1997459-3](#) [ASP-144414-04](#) [E16A06002M030](#) [18169-0524](#) [1969343-6](#)  
[C5UMB3FBG](#) [21949-1](#) [360031](#) [AX100351](#) [09459711142](#) [73-7793-1](#) [WHU18-1836-060](#) [1-3636-620-5214](#) [STS](#) [09470303023](#) [09459711118](#)  
[1404682](#) [C5SMB14FBG](#) [CA21116001](#) [WK-100](#) [UTPCH22VLY](#) [UTPSP50BLY](#) [C6F1106003](#) [UTPSP16MRDY](#) [UTPSP16MGRY](#)  
[UTP28CH30MBL](#) [AX105520](#) [CAPFCU-B25](#) [CB8MMBK-B100](#) [DK-1511-002/B](#) [STP6X1BU](#) [904873-000](#) [17-103134](#) [1110401155](#)  
[09459711186](#) [EL6614](#) [MRC191ZN79H1](#) [SSFPP-P03M0-2](#) [1426514](#) [1413684](#) [1426515](#) [1414043](#) [1413685](#) [7000-44511-6590150](#) [7000-](#)  
[44511-7940300](#) [7000-44561-7940150](#)