

4 Port High Resolution VGA Video Splitter - 350 MHz - TAA

Product ID: ST124PRO



The ST124PRO 4 Port High Resolution VGA Video Splitter - 350 MHz splits a VGA video source signal to 4 monitors or projectors simultaneously - a professional grade solution that is perfect for presentations, classrooms, tradeshow, or in-store displays, where the highest quality video on several monitors is needed.

This High Resolution VGA Splitter supports monitors with up to 350MHz of video bandwidth and display resolutions up to 2048x1536 @80Hz. For added versatility, the VGA splitter features an integrated booster circuit that allows the video signal to be extended up to 210 feet (65 meters), enabling you to situate your displays in the most convenient location based on your application.

This product is TAA compliant and backed by a Startech.com 2-year warranty with free lifetime technical support., Male to Female VGA extension cable required (MXT101HQ)

Certifications, Reports and Compatibility



Applications

- Create engaging multimedia presentations for demonstration in lecture halls and classrooms
- Display travel schedules and alerts in airports, bus terminals and train stations etc.
- Create eye-catching displays in trade-shows and auditoriums
- Use for in-store product merchandising in retail environments to give your advertisements greater visibility

- Get your message across multiple displays for trade-shows or information booths/kiosks
- Quick and easy solution to split a video signal in an auditorium or house of worship

Features

- Allows 1 VGA video source to simultaneously display on 4 different monitors
- Supports resolutions up to 2048x1536 @ 80Hz
- High video bandwidth (350 MHz)
- Daisy chainable for almost unlimited expansion
- Maximum VGA cable length of 210ft (65m)

General

UPC	065030783101
Package Quantity	1
Warranty	2 Years

Power

Power Source	AC Adapter Included
Input Voltage	100 - 240 AC
Input Current	0.3 A
Output Voltage	5 DC
Output Current	1
Plug Type	N
Power Consumption	5

Physical & Environmental

Color	Black
Material	Steel
Product Length	7.2 in [182.0 mm]
Product Width	3.1 in [80.0 mm]

Product Height	0.8 in [21.0 mm]
Weight of Product	13.8 oz [392.0 g]
Operating Temperature	0 to 40 C
Storage Temperature	5 to 40 C
Humidity	0~80% RH non-condensing

Performance

Maximum Cable Length	2520.7 in [64025 mm]
Bandwidth	350MHz
General Specifications	Male to Female VGA extension cable required (MXT101HQ)
MTBF	1,065,824 Hours
Maximum Analog Resolutions	2048x1536 @ 80Hz

Hardware

Number of Ports	4
Regulatory Approvals	FCC Part 15 Class A, CE Mark
Industry Standards	DDC compatible - all other monitors must be able to support the highest video resolution of the DDC-type monitor connected to Video Out 1

Packaging & In-the-Box

Included in Package	1 - 4 Port High Res. Video Splitter
	4 - Rubber Feet
	1 - Power Adapter
	1 - Instruction Manual
Package Width	9.6 in [243 mm]
Package Depth	7.3 in [186 mm]
Package Height	3.7 in [95 mm]
Shipping (Package) Weight	24.7 oz [700 g]

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) ***category:***

Click to view products by [Startech](#) ***manufacturer:***

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)