

4-Port USB 2.0 Hub, USB Bus Powered, Small Travel Mini USB Hub, USB 2.0 Splitter, Portable Multi-Port USB Hub, 480Mbps, Overcurrent Protection (OCP)

Product ID: ST4200MINI2-USB-HUB



Connect up to four USB 2.0 devices to a laptop/PC via a single available USB 2.0 or 3.0 port.

With its compact and lightweight design, this 4-port USB hub is designed for mobility. It features a compact, USB-powered design that makes it perfect for travel. The hub also features small-footprint housing, which means it takes up less desk space. It easily fits into a laptop bag when traveling, allowing you to expand your connection options almost anywhere you need to. It's perfect for connecting common USB devices such as a mouse, keyboard, or flash drive.

This versatile hub features a built-in 6in (15cm) USB cable and is bus-powered, so it draws its power directly from the computer's USB port, reducing clutter and simplifying setup by eliminating the need for an external power adapter.

With all four USB 2.0 ports on one side, this hub makes it easier to access ports to connect or disconnect devices.

The USB Hub is OS independent, supporting all operating systems (Windows, macOS, ChromeOS, and Linux), and installs automatically when connected to a computer.

Certifications, Reports and Compatibility



Applications

- Carry the hub with you while you're traveling, and connect your USB devices wherever you go
- Deploy at home, in the office, or in hot-desk environments to provide USB hub access for multiple devices
- Make hard-to-reach USB ports more accessible
- Connect larger USB plugs to your computer

Features

- **4-PORT USB HUB:** Bus-powered USB-A to USB 2.0 Hub connects up to four USB 2.0 devices to a laptop/PC via a single free USB 2.0 or 3.0 port; Supports USB 2.0 (480Mbps) transfer speeds, and is backward compatible with USB 1.1
- **BUS POWERED USB HUB:** Offers plug-and-play installation and supports hot-swapping and hot-plugging; Overcurrent Protection (OCP) protects connected peripherals from overdrawing power; Provides up to 500mA per port
- **ORGANIZED & PORTABLE:** Compact and lightweight design with 6in (15cm) built-in USB-A cable makes it ideal for both travelling and desktop use; All ports are located on one side for easy access when connecting or disconnecting devices
- **NO DRIVERS OR SOFTWARE:** Works on all operating systems including Windows, macOS, Linux, and ChromeOS; Compatible with USB Type-A host devices such as Lenovo X1 Carbon, Dell XPS, and Microsoft Surface
- **APPLICATIONS:** Works on computers and notebooks for USB devices such as a mouse, keyboard, or flash drive; Make hard-to-reach USB ports more accessible; Ideal for use in home/office/hot-desk environments to provide USB hub access for multiple devices

Hardware

Warranty	2 Years
USB-C Device Port(s)	No
USB-C Host Connection	No
Fast-Charge Port(s)	No
Ports	4
Cable Jacket Material	TPE - Thermoplastic Elastomers
Interface	USB 2.0
Bus Type	USB 2.0
Industry Standards	USB 2.0

	Chipset ID	GL850S
Performance		
	Maximum Data Transfer Rate	480 Mbps
	Type and Rate	USB 2.0 (480Mbps)
	UASP Support	No
	MTBF	147132 hours
Connector(s)		
	Connector Type(s)	4 - USB 2.0 Type-A (4 pin, 480Mbps)
		1 - USB 2.0 Type-A (4 pin, 480Mbps)
Software		
	OS Compatibility	OS Independent; No additional drivers or software required
Special Notes / Requirements		
	System and Cable Requirements	Available USB Type-A port - USB 2.0 (480Gbps)
Power		
	Power Source	Bus Powered
Environmental		
	Operating Temperature	0C to 45C (32F to 113F)
	Storage Temperature	-10C to 70C (14F to 158F)
	Humidity	10~85% RH (Non-condensing)
Physical Characteristics		
	Color	Black
	Material	ABS
	Cable Length	6.0 in [152.4 mm]
	Product Length	3.1 in [8.0 cm]
	Product Width	1.6 in [4.0 cm]

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [Startech](#) manufacturer:

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)