

Portable 4 Port SuperSpeed Mini USB 3.0 Hub - 5Gbps - White - TAA

Product ID: ST4300MINU3W



The ST4300MINU3W Portable 4 Port SuperSpeed Mini USB 3.2 Gen 1 Hub (White) lets you expand your USB connectivity by turning a single USB 3.2 Gen 1 port into four external USB 3.2 Gen 1 ports. The integrated cable design makes this mini USB hub the perfect accessory for your Mac / PC notebook or Ultrabook computer.

The 4 Port USB 3.2 Gen 1 hub supports USB 3.2 Gen 1 data bandwidth (5 Gbps - up to 10x more than USB 2.0) and is backward compatible with USB 2.0 and 1.1 devices, ensuring flawless performance from all of your USB peripherals/devices, regardless of their age.

Ideal for home and business users who require portability, the external USB 3.2 Gen 1 hub is USB-powered and features a rugged, compact design with a built-in cable so no additional cables are needed to connect the hub to your system.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Mac or PC notebook / Ultrabook users with limited USB 3.2 Gen 1 ports and multiple USB 3.2 Gen 1 devices

- Make hard to access USB ports more accessible, by being able to position the hub anywhere the cable will reach
- Separate tightly packed USB ports, to better accommodate larger USB plugs or prevent overcrowding

Features

- Four USB type-A ports that can be accessed simultaneously
- SuperSpeed USB 3.2 Gen 1 compliant, with data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.0/1.1 specifications and devices
- Compact and portable design with built-in cable
- Plug-and-Play and hot-swap compatible

Hardware

Warranty	2 Years
USB-C Device Port(s)	No
USB-C Host Connection	No
Fast-Charge Port(s)	No
Ports	4
Interface	USB 3.2 Gen 1 (5Gbps)
Bus Type	USB 3.2 Gen 1 (5Gbps)
Chipset ID	Realtek - RTS5411

Performance

Maximum Data Transfer Rate	5 Gbps (USB 3.2 Gen 1)
Type and Rate	USB 3.2 Gen 1 - 5 Gbit/s

Connector(s)

External Ports	4 - USB Type-A (9 pin, 5 Gbps)
	1 - USB Type-A (9 pin, 5 Gbps)

Software

OS Compatibility	OS Independent; No additional drivers or software required
------------------	--

Special Notes / Requirements

System and Cable Requirements	Available USB Port
-------------------------------	--------------------

Indicators

LED Indicators	1 - Power
----------------	-----------

Power

Power Source	USB-Powered
Input Voltage	5V DC
Output Voltage	5 DC

Environmental

Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	-20C to 60C (-4F to 140F)
Humidity	0~80% RH

Physical Characteristics

Color	White
Form Factor	Compact
Material	Plastic
Cable Length	5.7 in [145 mm]
Product Length	3.1 in [80 mm]
Product Width	1.4 in [3.6 cm]
Product Height	0.6 in [1.4 cm]
Weight of Product	1.3 oz [38 g]

Packaging Information

Package Quantity	1
Package Length	5.2 in [13.3 cm]
Package Width	6.5 in [16.4 cm]

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) ***category:***

Click to view products by [Startech](#) ***manufacturer:***

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)