

2 Port Professional USB KVM Switch Kit with Cables - TAA

Product ID: SV231USB



The SV231USB 2 Port Professional USB KVM Switch Kit with Cables offers simple control of two Mac or PC computers from a single monitor/display and USB peripheral set (keyboard, mouse).

The 2 Port KVM switch includes 2 USB KVM cables, providing a complete out-of-the-box KVM solution saving you time and money. An integrated 3 port USB hub allows you to share connected USB peripherals between connected computers as though they were connected directly. A compact form factor design and rear-port connections to master and slave computers minimizes disruption to your workspace.

A cross-platform solution, this OS independent KVM switch supports high resolution applications up to 1920x1440, and provides a smooth operating experience when controlling mixed (Windows/Mac/Linux) environments.

Certifications, Reports and Compatibility



Applications

- Dual system control for a single workstations increasing user productivity in the office
- Provide centralized control for multiple high-res Digital Signage server control
- Great for manufacturing line computer control, simplifying access to multiple systems

- Perfect for PC test/burn-in computer control saving the desk space required for two monitors, keyboards and mice

Features

- Control 2 computers from one USB keyboard/mouse/monitor
- Share 3 different USB peripherals using the integrated hub
- High 1920x1440 resolution capability
- Front panel push buttons for easy computer selection
- OS independent - No software or drivers required

General

UPC	065030789196
Package Quantity	1
Warranty	3 Years

Special Notes / Requirements

Special Notes	This KVM supports the use of VGA cables up to 100ft in length - active extension required for USB to achieve that distance
---------------	--

Power

Power Source	AC Adapter Included
Input Voltage	100 - 240 AC
Input Current	0.4A
Output Voltage	5 DC
Output Current	2
Center Tip Polarity	Positive
Plug Type	N
Power Consumption	10

Physical & Environmental

Color	Black
Material	Steel

Cable Length	72.0 in [1828.8 mm]
Product Length	4.9 in [124.0 mm]
Product Width	2.8 in [70.0 mm]
Product Height	1.6 in [40.0 mm]
Weight of Product	14.9 oz [421.0 g]
Operating Temperature	0C ~ 40C (32F ~ 104F)
Storage Temperature	-20C ~ 60C (-4F ~ 140F)
Humidity	0 - 80%

Performance

Maximum Cable Length	180.0 in [4572 mm]
IP Control	No
Hot-Key Selection	No
Port Selection Support	Push Button
On-Screen Display	No
Auto Scan	3, 8, 15 & 30 seconds
Maximum Number of Users	1
MTBF	111,000 Hours
DVI Support	No
Maximum Analog Resolutions	1920 x 1440

Hardware

CAC Support	No
U Height	1U
Audio	No
Number of KVM Ports	2
Supported Platforms	USB

PC Video Type	VGA
Number of Monitors Supported	1
Rack-Mountable	No
Cables Included	Yes
Cascadable	No

Packaging & In-the-Box

Included in Package	1 - 2 Port USB KVM Switch
	2 - 2 IN 1 USB/VGA Cables
	1 - Power Adapter
	1 - Manual
Package Width	7.4 in [187 mm]
Package Depth	9.4 in [238 mm]
Package Height	3.8 in [97 mm]
Shipping (Package) Weight	40.6 oz [1150 g]

Connector(s)

Host Connector 1 (Quantity)	2
Host Connector 1	VGA
Host Connector 2 (Quantity)	2
Host Connector 2	USB-B (480Mbps, 2.5W)
Connector 1 (Quantity)	1
Connector 1	VGA
Connector 2 (Quantity)	3
Connector 2	USB-A (480Mbps, 2.5W)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) *category:*

Click to view products by [Startech](#) *manufacturer:*

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)