

Dual-Monitor Thunderbolt Mini Dock, 4K 60Hz HDMI, Driverless Hub for Windows & Mac, Gigabit Ethernet, 1 x USB 5Gbps & 1x USB 2.0, 11in (28cm) Cable

Product ID: TB3DKM2HDL



This certified Thunderbolt 3 docking station is a compact mini dock, delivering essential connections for productivity. The bus-powered dock connects dual 4K HDMI displays, Gigabit Ethernet, and one USB-A port and for flexible set up, the attached Thunderbolt cable has an extended length of (11 in./ 28 cm).

Great for editing 4K video or other Ultra HD tasks, this portable Thunderbolt to HDMI dock supports 40 Gbps of throughput and 4K resolution at 60Hz on dual HDMI monitors, through a single Thunderbolt port. Run resource-demanding applications on two independent displays without draining system resources.

Connect your laptop to:

- 2x 4K HDMI displays (up to 4096 x 2160p @ 60Hz)

At just 2.4" x 4.9" (6.1 cm x 12.4 cm), this dock takes up minimal room on your desk and in your laptop case. The dock's 28 cm (11 inches) attached cable provides extended reach to reduce port/connector strain on MacBooks and laptops on riser stands, or if needed, offers the flexibility to position dock further away from the laptop on your desk.

- 1x USB 5Gbps Type-A port
- 1x Gigabit Ethernet port (with PXE Boot and Wake-on-LAN support)

As many high powered, later generation laptops optimally require more than 100W of power to stay charged, some users prefer to use their laptop's power adapter vs. using their docking stations to keep laptops charged.

This bus-powered TB mini dock is ideally suited for those users, providing full Thunderbolt docking station performance and functionality, while their workstation laptops are separately charged."

Certifications, Reports and Compatibility



Applications

Features

- **HIGH-PERFORMANCE THUNDERBOLT 3 CERTIFIED DOCK:** Driverless setup for plug-and-play installation; Thunderbolt (40 Gbps); Dual 4K 60Hz HDMI outputs; 1x USB 5Gbps port; Gigabit Ethernet port with PXE boot and WoL
- **FOR HIGH-POWERED LAPTOPS:** Dual 4K 60Hz video output with direct GPU performance and no software or compression; Ideal for high-performance laptops that need a direct power adapter connection, but require Thunderbolt 3 dock performance & functionality
- **COMPATIBILITY:** This docking station is compatible with Windows, macOS, and Ubuntu; Supports Thunderbolt or USB4 laptops; Dual Display on M1, M2, M3 Max/Pro, M4 Pro/Max MacBooks, and single display on base M-series MacBooks and iPad Pro M1 & later
- **EXTRA-LONG CABLE:** Attached 11in (28cm) cable provides long reach for easy setup and prevents adapter from dangling on the host connector; Ideal cable length to reduce port strain on 2-in-1 convertible laptops, or host laptops on riser stands
- **THE IT PRO'S CHOICE:** Our docking stations are rigorously tested in our Innovation Lab to ensure enterprise-grade reliability and cross-platform compatibility; Built to support large-scale deployments, Windows 11 upgrades, and the shift to AI-enabled PCs

General

UPC	065030888042
Package Quantity	1
Warranty	3 Years

Special Notes / Requirements

Special Notes	MacBook Air and MacBook Pro systems using the new Apple M1 chip support only a single external display over the Thunderbolt
---------------	---

3 ports, even when connected to a Thunderbolt 3 docking station with more than one video output. This single monitor limitation does not affect Intel-based Macs with Thunderbolt 3.

Power

Power Source	Bus Powered
Power Delivery	No PD
Input Voltage	5V DC
Output Voltage	5 DC

Physical & Environmental

Color	Black & Silver
Material	Aluminum and Plastic
Cable Length	11.0 in [280 mm]
Product Length	4.9 in [124.0 mm]
Product Width	2.7 in [69.0 mm]
Product Height	1.1 in [27.0 mm]
Weight of Product	5.2 oz [147.8 g]
Operating Temperature	5C to 40C
Storage Temperature	-20C to 70C
Humidity	0% to 95% (non-condensing) at 25C

Performance

Maximum Cable Length	11.0 in [280 mm]
Compatible Networks	10/100/1000 Mbps
PXE	Yes
Wake-On-LAN (WOL)	Yes
Maximum Digital Resolutions	4K 60Hz

Hardware

Fast-Charge Port(s)	No
---------------------	----

4K Support	Yes
Displays Supported	2
Audio	No
Interface	Thunderbolt 3
Bus Type	Thunderbolt 3
Number of Displays	2
Industry Standards	1Gb connectivity to any 1000Base-T device (IEEE802.3ab Compliant)
	100Mb connectivity to any 100Base-TX device (IEEE802.3u Compliant)
	10Mb connectivity to any 10Base-T device (IEEE802.3i Compliant)
Chipset ID	Intel JHL6540 (Alpine Ridge)
	Texas Instruments TPS65983A
	Parade PS176
	ASMedia ASM1042A
	Intel WGI210
Form Factor	Compact

Packaging & In-the-Box

Included in Package	1 - Docking Station
	1 - User Manual
Package Width	8.3 in [211 mm]
Package Depth	5.8 in [148 mm]
Package Height	1.6 in [40 mm]
Shipping (Package) Weight	9.4 oz [266 g]

Connector(s)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [Startech](#) manufacturer:

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)