

Composite and S-Video to VGA Video Scan Converter - TAA

Product ID: VID2VGATV2



The VID2VGATV2 Composite and S-Video to VGA Video Scan Converter (with Scaler) provides a simple way to convert Composite or S-Video signals to VGA (or Component RCA) output, for use with computer monitors, projectors or HDTV sets.

Equipped with an On-Screen Display (OSD) menu and dip switches for simple configuration and selection of your video output settings, this compact video scaler installs quickly and easily for a true plug-and-play experience. An integrated scaler circuit dynamically converts the S-Video or Composite video input signal, giving you multiple output resolutions to choose from, to ensure compatibility with your display or projector.

Plus, the Component/S-Video-VGA Converter includes a VGA to Component (RCA) breakout cable, which enables you to connect to TV sets that are not equipped with a VGA port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Perfect for displaying video from DVD players, VCRs or legacy Game Consoles on VGA projectors and HDTV sets
- Display camcorder output on televisions or monitors equipped with VGA input
- Monitor security cameras with S-Video or composite signaling using VGA monitors or televisions

- Adapt VHS video in the classroom to newer televisions
- Convert legacy Medical Imaging equipment for display on computer monitors
- Use in boardrooms for adapting legacy video equipment to work with new projectors

Features

- Convert and scale Composite/S-Video input to VGA/Component output
- Accepts NTSC and PAL input
- On-Screen Display for simple output setting selection
- VGA to Component (YPbPr) RCA Adapter included
- 50 Hz to 60 Hz frame rate conversion

General

UPC	065030844345
Package Quantity	1
Warranty	2 Years

Power

Power Source	AC Adapter Included
Output Voltage	5 DC
Output Current	1
Power Consumption	2.5

Physical & Environmental

Color	Black
Material	Plastic
Product Length	4.4 in [112 mm]
Product Width	2.5 in [64 mm]
Product Height	1.0 in [26 mm]
Weight of Product	3.0 oz [86 g]

Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	0C to 60C (32F to 140F)
Humidity	0~60% RH

Performance

Supported Resolutions	PC: 1600x1200, 1280x1024, 1024x768 HDTV: 480p (50/60Hz), 576p (50Hz), 720p (50/60Hz), 1080p (50/60Hz)
-----------------------	--

Hardware

Active or Passive Adapter	Active
AV Input	S-Video Composite
AV Output	VGA Component
Audio	No
LED Indicators	1 - Composite (Yellow) / S-Video (Red) input indicator

Packaging & In-the-Box

Included in Package	1 - Video Converter/Scaler 1 - VGA to Component (RCA) breakout cable 1 - Universal Power Adapter 1 - Instruction Manual
Package Width	8.3 in [210 mm]
Package Depth	4.6 in [117 mm]
Package Height	2.4 in [62 mm]
Shipping (Package) Weight	15.7 oz [444 g]

Connector(s)

Connector 1 (Quantity)	1
------------------------	---

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [Startech](#) manufacturer:

Other Similar products are found below :

[9441560000](#) [73-546-001](#) [ADAM-4541-C](#) [USB-CARD-READER](#) [USB-RS485](#) [USB-SATA](#) [TD501D232H](#) [RSM232D](#) [TD502D232H](#) [RS232](#)
[TO RS485](#) [TD302D232H](#) [TD501D232H](#) [RSM232](#) [RSM232D](#) [TD301D232H](#) [TD302D232H](#) [TD502D232H](#) [SAVAK-58](#) [SAVKABELCL-24](#)
[20270](#) [20294](#) [30255](#) [50260](#) [20295](#) [20277](#) [50261](#) [EUR0001H](#) [ZHB2301G](#) [30346](#) [KS-308A](#) [KS-302A](#) [KS-304A](#) [KS-1041UA](#) [KS-1021UA](#)
[CEHBB](#) [66255](#) [50985](#) [4000-68512-0940003](#) [GPS50M](#) [2200002208](#) [4000-68112-1220000](#) [44110](#) [4000-68000-1300000](#) [4000-68512-4040001](#)
[446139](#) [60004-006](#) [2200002207](#) [1020882](#) [1021056](#) [1021058](#)