


XZGL-410



Item number 66.9327-*

Stackable, Ø 4 mm, with spring-loaded MULTILAM, for self-assembly of test leads. With retractable sleeve to prevent accidental touching. As a result of the protective collar, the clearances and creepage distances allow test leads equipped with this plug also to be safely connected to older

test instruments not yet fitted with safety sockets up to 600 V, CAT II in accordance with the standards. Screw connection.

| Technical data | |
|--------------------------------------|--|
| Diameter of plug system | 4 mm |
| Rated Values | 600 V, CAT II, 19 A |
| Surface treatment electrical contact | Ni |
| Base material electrical contact | CuZn |
| Standard color(s) * | 20 21 22 23 24 25 26 27 28 |
| Outer diameter | 3.9 mm |
| Test accessory acc. to | IEC EN 61010-031 |
| Remarks | Outer diameter: PVC/TPE: 2,1 mm; SIL: 2,3 mm; Other colors available on request. |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [STAUBLI](#) manufacturer:

Other Similar products are found below :

[R644543000](#) [R948161000](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [1905509](#) [1905527](#) [211-101](#) [RS100GBL](#)
[RS250GBL](#) [251-102](#) [923743-28-I](#) [30-443G](#) [1909861](#) [1916466](#) [1918007](#) [1919515](#) [1929125](#) [1933440](#) [1938303](#) [1944375](#) [204-103](#) [2435108](#)
[2803-102](#) [30-442G](#) [R644543002](#) [R644543004](#) [R644543020](#) [R644543021](#) [R948160000](#) [3502-103](#) [430-102](#) [105-1106-001](#) [108](#) [108-1000-106](#)
[105-0306-001](#) [R948141029](#) [R644543024](#) [HSEB 3125 L AU/BL](#) [325-105](#) [923690-20-R](#) [923739-14-I](#) [5124](#) [PP250GBL](#) [PP250GY](#) [2541996](#)
[930109100](#)