

Multilayer Chip Ceramic Inductor – ASDCL1005 -A01 Series



Operating Temp : -55°C ~+125°C

FEATURES

- ◆ Monolithic structure for high reliability
- ◆ High self-resonant frequency
- ◆ Excellent solderability and high heat resistance
- ◆ AEC-Q200D verified

APPLICATIONS

- ◆ Infotainment system
- ◆ Passive keyless entry
- ◆ Tire pressure monitoring system

PRODUCT IDENTIFICATION

1	2	3	4	5	6	7	8	9	10
A	SDCL	1005	C	XXX	□	T	D	F	A01

1	Feature Code
A	Automotive Electronics

2	Type
SDCL	Chip Ceramic Inductor

3	External Dimensions (L×W) (mm)
1005 [0402]	1.0×0.5

4	Characteristics Code
Q	Characteristics Code

5	Nominal Inductance
Example	Nominal Value
3N9	3.9nH
10N	10nH
R12	120nH

6	Inductance Tolerance
B	±0.1nH
C	±0.2nH
S	±0.3nH
H	±3%
J	±5%


7	Packing
T	Tape & Reel

8	Internal Code
D	Internal Code

9	HFS Products
F	HFS Products

10	Design Code
A01	Internal Code

SHAPE AND DIMENSIONS



Unit: mm [inch]

Type	L	W	T	a
ASDCL1005 [0402]	1.0±0.05 [0.39±0.06]	0.5±0.05 [0.20±0.06]	0.5±0.05 [0.20±0.06]	0.25±0.1 [0.10±0.04]

SPECIFICATIONS ASDCL1005-A01 TYPE

Part Number	L	Q	L, Q Test Freq	Q (Typ.) Freq. (MHz)			S.R.F	DC Resistance	Rated Current	Thickness
				100	800	1000				
Units	nH	(Min.)	MHz	/			MHz	Ω	mA	(mm) [inch]
Symbol	L	Q	/	/			S.R.F	DCR	Ir	T
ASDCL1005C0N6 □ TDFA01	0.6	4	100	6	35	41	10000	0.10	800	0.5±0.05 [.020±.002]
ASDCL1005C1N0 □ TDFA01	1.0	8	100	11	34	36	10000	0.10	400	
ASDCL1005C1N1 □ TDFA01	1.1	8	100	11	34	36	10000	0.10	400	
ASDCL1005C1N2 □ TDFA01	1.2	8	100	11	34	36	10000	0.10	400	
ASDCL1005C1N3 □ TDFA01	1.3	8	100	11	34	36	10000	0.10	400	
ASDCL1005C1N5 □ TDFA01	1.5	8	100	11	34	36	6000	0.10	300	
ASDCL1005C1N6 □ TDFA01	1.6	8	100	11	32	35	6000	0.10	300	
ASDCL1005C1N8 □ TDFA01	1.8	8	100	11	30	34	6000	0.10	300	
ASDCL1005C2N0 □ TDFA01	2.0	8	100	10	29	33	6000	0.20	300	
ASDCL1005C2N2 □ TDFA01	2.2	8	100	10	29	33	6000	0.20	300	
ASDCL1005C2N4 □ TDFA01	2.4	8	100	10	29	32	6000	0.20	300	
ASDCL1005C2N7 □ TDFA01	2.7	8	100	10	29	32	6000	0.20	300	
ASDCL1005C3N0 □ TDFA01	3.0	8	100	10	29	32	6000	0.20	300	
ASDCL1005C3N3 □ TDFA01	3.3	8	100	10	29	32	6000	0.20	300	
ASDCL1005C3N6 □ TDFA01	3.6	8	100	10	28	31	4000	0.20	300	
ASDCL1005C3N9 □ TDFA01	3.9	8	100	10	28	31	4000	0.20	300	
ASDCL1005C4N3 □ TDFA01	4.3	8	100	10	28	31	4000	0.20	300	
ASDCL1005C4N7 □ TDFA01	4.7	8	100	10	28	31	4000	0.20	300	
ASDCL1005C5N1 □ TDFA01	5.1	8	100	10	28	30	4000	0.30	300	
ASDCL1005C5N6 □ TDFA01	5.6	8	100	10	28	30	4000	0.30	300	
ASDCL1005C6N2 □ TDFA01	6.2	8	100	10	27	30	3900	0.30	300	
ASDCL1005C6N8 □ TDFA01	6.8	8	100	10	27	30	3900	0.30	300	
ASDCL1005C7N5 □ TDFA01	7.5	8	100	10	27	30	3700	0.40	300	
ASDCL1005C8N2 □ TDFA01	8.2	8	100	10	27	30	3600	0.40	300	
ASDCL1005C9N1 □ TDFA01	9.1	8	100	10	27	30	3400	0.40	300	
ASDCL1005C10N □ TDFA01	10	8	100	10	27	30	3200	0.40	300	
ASDCL1005C12N □ TDFA01	12	8	100	10	26	29	2700	0.50	300	
ASDCL1005C15N □ TDFA01	15	8	100	10	26	28	2300	0.50	300	
ASDCL1005C18N □ TDFA01	18	8	100	10	25	27	2100	0.60	300	
ASDCL1005C20N □ TDFA01	20	8	100	10	25	26	2000	0.60	300	
ASDCL1005C22N □ TDFA01	22	8	100	10	25	25	1900	0.60	300	
ASDCL1005C27N □ TDFA01	27	8	100	10	25	23	1600	0.70	300	
ASDCL1005C33N □ TDFA01	33	8	100	10	22	22	1300	0.80	200	
ASDCL1005C39N □ TDFA01	39	8	100	10	22	19	1200	1.00	200	
ASDCL1005C43N □ TDFA01	43	8	100	10	21	16	1100	1.10	200	
ASDCL1005C47N □ TDFA01	47	8	100	10	21	16	1000	1.10	200	
ASDCL1005C56N □ TDFA01	56	8	100	10	18	13	750	1.20	200	
ASDCL1005C68N □ TDFA01	68	8	100	10	18	9	750	1.40	180	
ASDCL1005C82N □ TDFA01	82	8	100	10	13	-	750	2.40	150	
ASDCL1005CR10 □ TDFA01	100	8	100	10	12	-	700	2.60	150	
ASDCL1005CR12 □ TDFA01	120	8	100	10	-	-	600	2.80	150	
ASDCL1005CR15 □ TDFA01	150	8	100	10	-	-	550	3.20	100	
ASDCL1005CR18 □ TDFA01	180	8	100	10	-	-	500	3.70	100	


※ □ : Please specify the inductance tolerance. For L≤6.2nH, choose B=±0.1nH, C=±0.2nH or S=±0.3nH; For L>6.2nH, choose H=±3%, J=±5% or K=±10%.

(1) Operating and storage temperature range (individual chip without packing): -55°C ~ +125°C ,


(2) Storage temperature range (packaging conditions): -10°C ~ +40°C and RH 70% (Max.)

TYPICAL ELECTRICAL CHARACTERISTICS

Inductance vs. Frequency Characteristics ASDCL1005-A01 TYPE



Q vs. Frequency Characteristics ASDCL1005-A01 TYPE



EMC Components

Coils/Inductors

Pulse Transformers

NTC Thermistors

RF Components

Winding Transformers

Current Sense Transformers

LLC Transformers

PFC Inductors

Resonant Inductors

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [Sunlord](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [70F224AI](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#)
[PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#)
[HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-4R7M](#) [RCP1317NP-391L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-](#)
[RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#)
[1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#) [1812LS-824XJ](#) [NIN-FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-](#)
[HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#) [NIN-HDR82JTRF](#) [NIN-HK2N7STRF](#) [NIN-PA150KTR370F](#) [NIN-PB100KTR550F](#)