

# Multilayer Chip Ceramic Inductor - SDCL0603Q-02-B Series

Operating Temp. : -55℃~+125℃



## FEATURES

- Monolithic structure for high reliability
- High self-resonant frequency
- Excellent solderability and high heat resistance
- High Q factor

## APPLICATIONS

- RF circuit in telecommunication and other equipments

## PRODUCT IDENTIFICATION

①

②

③

④

⑤

⑥

⑦

⑧

①

②

③

④

⑤

⑥

⑦

⑧

Type

SDCL

Chip Ceramic Inductor

(L×W) (mm)

External Dimensions (L×W) (mm)

0603 [0201]

0.6×0.3

Characteristics Code

Q

Packing

T

Tape & Reel

Serial Code

02

Internal Code

B01/B02/B03

Nominal Inductance

Example

Nominal Value

3N9

3.9nH

10N

10nH

※R=, N=nH

Inductance Tolerance

B

C

S

G

H

J

±0.1nH

±0.2nH


±0.3nH

±2%

±3%

±5%

## SHAPE AND DIMENSIONS



| Unit: mm [inch]          |                          |                          |                          |                          |
|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| Type                     | L                        | W                        | T                        | a                        |
| SDCL0603Q-02-B<br>[0201] | 0.6±0.03<br>[.024±.0012] | 0.3±0.03<br>[.012±.0012] | 0.3±0.03<br>[.012±.0012] | 0.12±0.05<br>[.005±.002] |

# SPECIFICATIONS

## SDCL0603Q-02B01 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | Ω                  | mA                 |
| Symbol              | L          | Q                   | Freq                | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q0N6□T02B01 | 0.6        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 10000                        | 0.06               | 600                |
| SDCL0603Q0N7□T02B01 | 0.7        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 10000                        | 0.06               | 550                |
| SDCL0603Q0N8□T02B01 | 0.8        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 10000                        | 0.07               | 550                |
| SDCL0603Q0N9□T02B01 | 0.9        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 10000                        | 0.07               | 550                |
| SDCL0603Q1N0□T02B01 | 1.0        | 13                  | 500                 | 24                      | 32  | 54  | 57  | 65  | 10000                        | 0.08               | 520                |
| SDCL0603Q1N1□T02B01 | 1.1        | 13                  | 500                 | 19                      | 26  | 45  | 47  | 55  | 10000                        | 0.11               | 440                |
| SDCL0603Q1N2□T02B01 | 1.2        | 13                  | 500                 | 19                      | 25  | 43  | 44  | 52  | 10000                        | 0.12               | 420                |
| SDCL0603Q1N3□T02B01 | 1.3        | 13                  | 500                 | 19                      | 25  | 40  | 42  | 47  | 10000                        | 0.12               | 420                |
| SDCL0603Q1N4□T02B01 | 1.4        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 47  | 10000                        | 0.11               | 440                |
| SDCL0603Q1N5□T02B01 | 1.5        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.12               | 420                |
| SDCL0603Q1N6□T02B01 | 1.6        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.13               | 410                |
| SDCL0603Q1N7□T02B01 | 1.7        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.15               | 380                |
| SDCL0603Q1N8□T02B01 | 1.8        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.15               | 380                |
| SDCL0603Q1N9□T02B01 | 1.9        | 13                  | 500                 | 18                      | 24  | 38  | 40  | 45  | 10000                        | 0.18               | 350                |
| SDCL0603Q2N0□T02B01 | 2.0        | 13                  | 500                 | 17                      | 24  | 38  | 39  | 44  | 10000                        | 0.23               | 300                |
| SDCL0603Q2N1□T02B01 | 2.1        | 13                  | 500                 | 17                      | 24  | 37  | 39  | 44  | 10000                        | 0.24               | 300                |
| SDCL0603Q2N2□T02B01 | 2.2        | 13                  | 500                 | 17                      | 24  | 38  | 40  | 43  | 10000                        | 0.25               | 290                |
| SDCL0603Q2N3□T02B01 | 2.3        | 13                  | 500                 | 17                      | 24  | 37  | 39  | 43  | 10000                        | 0.20               | 330                |
| SDCL0603Q2N4□T02B01 | 2.4        | 13                  | 500                 | 17                      | 23  | 36  | 38  | 42  | 10000                        | 0.22               | 310                |
| SDCL0603Q2N5□T02B01 | 2.5        | 13                  | 500                 | 17                      | 23  | 35  | 36  | 40  | 9600                         | 0.20               | 330                |
| SDCL0603Q2N6□T02B01 | 2.6        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9400                         | 0.20               | 330                |
| SDCL0603Q2N7□T02B01 | 2.7        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9200                         | 0.22               | 310                |
| SDCL0603Q2N8□T02B01 | 2.8        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8900                         | 0.24               | 300                |
| SDCL0603Q2N9□T02B01 | 2.9        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8800                         | 0.26               | 280                |
| SDCL0603Q3N0□T02B01 | 3.0        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8600                         | 0.26               | 280                |
| SDCL0603Q3N1□T02B01 | 3.1        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8500                         | 0.28               | 270                |
| SDCL0603Q3N2□T02B01 | 3.2        | 13                  | 500                 | 17                      | 22  | 33  | 35  | 39  | 8200                         | 0.28               | 270                |
| SDCL0603Q3N3□T02B01 | 3.3        | 13                  | 500                 | 18                      | 23  | 34  | 36  | 40  | 8100                         | 0.30               | 270                |
| SDCL0603Q3N4□T02B01 | 3.4        | 13                  | 500                 | 17                      | 23  | 33  | 35  | 39  | 8000                         | 0.30               | 270                |
| SDCL0603Q3N5□T02B01 | 3.5        | 13                  | 500                 | 17                      | 23  | 33  | 35  | 39  | 7900                         | 0.34               | 250                |
| SDCL0603Q3N6□T02B01 | 3.6        | 13                  | 500                 | 16                      | 23  | 33  | 35  | 39  | 7700                         | 0.38               | 240                |
| SDCL0603Q3N7□T02B01 | 3.7        | 13                  | 500                 | 16                      | 23  | 33  | 35  | 38  | 7600                         | 0.40               | 230                |
| SDCL0603Q3N8□T02B01 | 3.8        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7500                         | 0.42               | 230                |
| SDCL0603Q3N9□T02B01 | 3.9        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7400                         | 0.42               | 230                |
| SDCL0603Q4N3□T02B01 | 4.3        | 13                  | 500                 | 16                      | 21  | 32  | 34  | 37  | 6800                         | 0.44               | 220                |
| SDCL0603Q4N7□T02B01 | 4.7        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 6200                         | 0.45               | 220                |
| SDCL0603Q5N1□T02B01 | 5.1        | 13                  | 500                 | 17                      | 22  | 34  | 36  | 38  | 5900                         | 0.46               | 210                |
| SDCL0603Q5N6□T02B01 | 5.6        | 13                  | 500                 | 16                      | 21  | 33  | 34  | 37  | 5500                         | 0.46               | 210                |
| SDCL0603Q6N2□T02B01 | 6.2        | 13                  | 500                 | 18                      | 23  | 34  | 35  | 37  | 5100                         | 0.48               | 210                |
| SDCL0603Q6N8□T02B01 | 6.8        | 13                  | 500                 | 17                      | 22  | 32  | 33  | 35  | 5500                         | 0.50               | 200                |
| SDCL0603Q7N5□T02B01 | 7.5        | 13                  | 500                 | 16                      | 21  | 31  | 33  | 34  | 4700                         | 0.50               | 200                |
| SDCL0603Q8N2□T02B01 | 8.2        | 13                  | 500                 | 16                      | 21  | 31  | 32  | 34  | 4300                         | 0.56               | 190                |
| SDCL0603Q9N1□T02B01 | 9.1        | 13                  | 500                 | 16                      | 20  | 30  | 31  | 32  | 4100                         | 0.72               | 170                |
| SDCL0603Q10N□T02B01 | 10         | 13                  | 500                 | 16                      | 20  | 28  | 29  | 31  | 3800                         | 0.80               | 160                |
| SDCL0603Q12N□T02B01 | 12         | 13                  | 500                 | 16                      | 20  | 27  | 28  | 28  | 3400                         | 0.80               | 160                |
| SDCL0603Q15N□T02B01 | 15         | 13                  | 500                 | 15                      | 19  | 24  | 24  | 23  | 2600                         | 0.85               | 160                |

## SPECIFICATIONS

### SDCL0603Q-02B01 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | Ω                  | mA                 |
| Symbol              | L          | Q                   | Freq.               | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q18N□T02B01 | 18         | 13                  | 500                 | 15                      | 19  | 23  | 24  | 22  | 2300                         | 1.00               | 140                |
| SDCL0603Q22N□T02B01 | 22         | 13                  | 500                 | 15                      | 19  | 22  | 23  | 20  | 1900                         | 1.20               | 130                |
| SDCL0603Q27N□T02B01 | 27         | 13                  | 500                 | 15                      | 19  | 15  | 13  | 8   | 1800                         | 1.60               | 120                |
| SDCL0603Q33N□T02B01 | 33         | 11                  | 300                 | 14                      | 15  | 8   | 5   | -   | 1800                         | 2.20               | 110                |
| SDCL0603Q39N□T02B01 | 39         | 11                  | 300                 | 14                      | 15  | 6   | -   | -   | 1600                         | 2.30               | 100                |
| SDCL0603Q47N□T02B01 | 47         | 11                  | 300                 | 14                      | 15  | -   | -   | -   | 1500                         | 2.60               | 100                |
| SDCL0603Q56N□T02B01 | 56         | 11                  | 300                 | 13                      | 13  | -   | -   | -   | 1400                         | 2.80               | 80                 |
| SDCL0603Q68N□T02B01 | 68         | 11                  | 300                 | 13                      | 11  | -   | -   | -   | 1200                         | 3.20               | 80                 |
| SDCL0603Q82N□T02B01 | 82         | 10                  | 300                 | 12                      | 10  | -   | -   | -   | 1100                         | 3.80               | 70                 |
| SDCL0603QR10□T02B01 | 100        | 10                  | 300                 | 12                      | 10  | -   | -   | -   | 1000                         | 4.00               | 60                 |
| SDCL0603QR12□T02B01 | 120        | 9                   | 300                 | 12                      | 8   | -   | -   | -   | 1000                         | 5.00               | 50                 |

### SDCL0603Q-02B02 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | Ω                  | mA                 |
| Symbol              | L          | Q                   | Freq.               | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q0N1□T02B02 | 0.1        | 13                  | 500                 | 20                      | 39  | 77  | 100 | 119 | 10000                        | 0.07               | 900                |
| SDCL0603Q0N2□T02B02 | 0.2        | 13                  | 500                 | 29                      | 41  | 77  | 85  | 94  | 10000                        | 0.08               | 900                |
| SDCL0603Q0N3□T02B02 | 0.3        | 13                  | 500                 | 19                      | 25  | 41  | 45  | 50  | 10000                        | 0.08               | 900                |
| SDCL0603Q0N4□T02B02 | 0.4        | 13                  | 500                 | 14                      | 18  | 30  | 31  | 35  | 10000                        | 0.08               | 900                |
| SDCL0603Q0N5□T02B02 | 0.5        | 13                  | 500                 | 15                      | 20  | 31  | 34  | 36  | 10000                        | 0.08               | 900                |
| SDCL0603Q0N6□T02B02 | 0.6        | 13                  | 500                 | 24                      | 32  | 54  | 57  | 65  | 10000                        | 0.08               | 850                |
| SDCL0603Q0N7□T02B02 | 0.7        | 13                  | 500                 | 19                      | 26  | 45  | 47  | 55  | 10000                        | 0.11               | 750                |
| SDCL0603Q0N8□T02B02 | 0.8        | 13                  | 500                 | 19                      | 25  | 43  | 44  | 52  | 10000                        | 0.12               | 700                |
| SDCL0603Q0N9□T02B02 | 0.9        | 13                  | 500                 | 19                      | 25  | 40  | 42  | 47  | 10000                        | 0.12               | 700                |
| SDCL0603Q1N0□T02B02 | 1.0        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 47  | 10000                        | 0.11               | 600                |
| SDCL0603Q1N1□T02B02 | 1.1        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.12               | 600                |
| SDCL0603Q1N2□T02B02 | 1.2        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.13               | 600                |
| SDCL0603Q1N3□T02B02 | 1.3        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.15               | 600                |
| SDCL0603Q1N4□T02B02 | 1.4        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 10000                        | 0.15               | 600                |
| SDCL0603Q1N5□T02B02 | 1.5        | 13                  | 500                 | 18                      | 24  | 38  | 40  | 45  | 10000                        | 0.15               | 600                |
| SDCL0603Q1N6□T02B02 | 1.6        | 13                  | 500                 | 17                      | 24  | 38  | 39  | 44  | 10000                        | 0.15               | 600                |
| SDCL0603Q1N7□T02B02 | 1.7        | 13                  | 500                 | 17                      | 24  | 37  | 39  | 44  | 10000                        | 0.15               | 500                |
| SDCL0603Q1N8□T02B02 | 1.8        | 13                  | 500                 | 17                      | 24  | 38  | 40  | 43  | 10000                        | 0.18               | 500                |
| SDCL0603Q1N9□T02B02 | 1.9        | 13                  | 500                 | 17                      | 24  | 37  | 39  | 43  | 10000                        | 0.20               | 450                |
| SDCL0603Q2N0□T02B02 | 2.0        | 13                  | 500                 | 17                      | 23  | 36  | 38  | 42  | 10000                        | 0.20               | 450                |
| SDCL0603Q2N1□T02B02 | 2.1        | 13                  | 500                 | 17                      | 23  | 35  | 36  | 40  | 9600                         | 0.20               | 450                |
| SDCL0603Q2N2□T02B02 | 2.2        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9400                         | 0.20               | 450                |
| SDCL0603Q2N3□T02B02 | 2.3        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9200                         | 0.22               | 450                |
| SDCL0603Q2N4□T02B02 | 2.4        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8900                         | 0.22               | 450                |
| SDCL0603Q2N5□T02B02 | 2.5        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8800                         | 0.25               | 450                |
| SDCL0603Q2N6□T02B02 | 2.6        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8600                         | 0.25               | 450                |
| SDCL0603Q2N7□T02B02 | 2.7        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8500                         | 0.25               | 450                |
| SDCL0603Q2N8□T02B02 | 2.8        | 13                  | 500                 | 17                      | 22  | 33  | 35  | 39  | 8200                         | 0.25               | 450                |
| SDCL0603Q2N9□T02B02 | 2.9        | 13                  | 500                 | 18                      | 23  | 34  | 36  | 40  | 8100                         | 0.25               | 450                |
| SDCL0603Q3N0□T02B02 | 3.0        | 13                  | 500                 | 17                      | 23  | 33  | 35  | 39  | 8000                         | 0.25               | 450                |

**Sunlord**

Specifications subject to change without notice. Please check our website for latest information. Revised 2018/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

## SPECIFICATIONS

### SDCL0603Q-02B02 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | Ω                  | mA                 |
| Symbol              | L          | Q                   | Freq.               | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q3N1□T02B02 | 3.1        | 13                  | 500                 | 17                      | 23  | 33  | 35  | 39  | 7900                         | 0.32               | 400                |
| SDCL0603Q3N2□T02B02 | 3.2        | 13                  | 500                 | 16                      | 23  | 33  | 35  | 39  | 7700                         | 0.32               | 400                |
| SDCL0603Q3N3□T02B02 | 3.3        | 13                  | 500                 | 16                      | 23  | 33  | 35  | 38  | 7600                         | 0.32               | 400                |
| SDCL0603Q3N4□T02B02 | 3.4        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7500                         | 0.34               | 350                |
| SDCL0603Q3N5□T02B02 | 3.5        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7400                         | 0.34               | 350                |
| SDCL0603Q3N6□T02B02 | 3.6        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7400                         | 0.34               | 350                |
| SDCL0603Q3N7□T02B02 | 3.7        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7400                         | 0.34               | 350                |
| SDCL0603Q3N8□T02B02 | 3.8        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7400                         | 0.34               | 350                |
| SDCL0603Q3N9□T02B02 | 3.9        | 13                  | 500                 | 16                      | 21  | 32  | 34  | 37  | 6800                         | 0.34               | 350                |
| SDCL0603Q4N3□T02B02 | 4.3        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 6400                         | 0.45               | 300                |
| SDCL0603Q4N7□T02B02 | 4.7        | 13                  | 500                 | 17                      | 22  | 34  | 36  | 38  | 6400                         | 0.46               | 250                |
| SDCL0603Q5N1□T02B02 | 5.1        | 13                  | 500                 | 16                      | 21  | 33  | 34  | 37  | 6200                         | 0.46               | 250                |
| SDCL0603Q5N6□T02B02 | 5.6        | 13                  | 500                 | 18                      | 23  | 34  | 35  | 37  | 6000                         | 0.48               | 250                |
| SDCL0603Q6N2□T02B02 | 6.2        | 13                  | 500                 | 17                      | 22  | 32  | 33  | 35  | 6000                         | 0.50               | 200                |
| SDCL0603Q6N8□T02B02 | 6.8        | 13                  | 500                 | 16                      | 21  | 31  | 33  | 34  | 5400                         | 0.50               | 200                |
| SDCL0603Q7N5□T02B02 | 7.5        | 13                  | 500                 | 16                      | 21  | 31  | 32  | 34  | 4800                         | 0.56               | 200                |
| SDCL0603Q8N2□T02B02 | 8.2        | 13                  | 500                 | 16                      | 20  | 30  | 31  | 32  | 4800                         | 0.72               | 200                |
| SDCL0603Q9N1□T02B02 | 9.1        | 13                  | 500                 | 16                      | 20  | 28  | 29  | 31  | 4500                         | 0.80               | 200                |
| SDCL0603Q10N□T02B02 | 10         | 11                  | 500                 | 16                      | 19  | 24  | 24  | 22  | 4500                         | 1.20               | 190                |
| SDCL0603Q12N□T02B02 | 12         | 11                  | 500                 | 16                      | 18  | 22  | 22  | 17  | 3700                         | 1.42               | 180                |
| SDCL0603Q15N□T02B02 | 15         | 11                  | 500                 | 15                      | 17  | 20  | 18  | 13  | 3100                         | 1.58               | 170                |
| SDCL0603Q18N□T02B02 | 18         | 11                  | 500                 | 15                      | 18  | 15  | 13  | 8   | 2800                         | 1.71               | 160                |
| SDCL0603Q22N□T02B02 | 22         | 11                  | 500                 | 15                      | 17  | 14  | 12  | 7   | 2600                         | 1.92               | 140                |
| SDCL0603Q24N□T02B02 | 24         | 13                  | 500                 | 15                      | 19  | 15  | 13  | 8   | 1800                         | 2                  | 120                |
| SDCL0603Q27N□T02B02 | 27         | 13                  | 500                 | 15                      | 19  | 15  | 13  | 8   | 1800                         | 2.1                | 120                |
| SDCL0603Q30N□T02B02 | 30         | 11                  | 300                 | 14                      | 15  | 8   | 5   | -   | 1800                         | 2.2                | 110                |
| SDCL0603Q33N□T02B02 | 33         | 11                  | 300                 | 14                      | 15  | 8   | 5   | -   | 1800                         | 2.2                | 110                |
| SDCL0603Q36N□T02B02 | 36         | 11                  | 300                 | 14                      | 15  | 6   | -   | -   | 1600                         | 2.3                | 100                |
| SDCL0603Q39N□T02B02 | 39         | 11                  | 300                 | 14                      | 15  | 6   | -   | -   | 1500                         | 2.3                | 100                |
| SDCL0603Q43N□T02B02 | 43         | 11                  | 300                 | 14                      | 15  | -   | -   | -   | 1500                         | 2.6                | 100                |
| SDCL0603Q47N□T02B02 | 47         | 11                  | 300                 | 13                      | 15  | -   | -   | -   | 1500                         | 2.6                | 100                |
| SDCL0603Q51N□T02B02 | 51         | 11                  | 300                 | 13                      | 13  | -   | -   | -   | 1400                         | 2.8                | 80                 |
| SDCL0603Q56N□T02B02 | 56         | 11                  | 300                 | 13                      | 13  | -   | -   | -   | 1400                         | 2.8                | 80                 |
| SDCL0603Q68N□T02B02 | 68         | 11                  | 300                 | 13                      | 11  | -   | -   | -   | 1200                         | 3.2                | 80                 |
| SDCL0603Q82N□T02B02 | 82         | 10                  | 300                 | 12                      | 10  | -   | -   | -   | 1100                         | 3.8                | 80                 |
| SDCL0603QR10□T02B02 | 100        | 10                  | 300                 | 12                      | 10  | -   | -   | -   | 1000                         | 4                  | 80                 |
| SDCL0603QR12□T02B02 | 120        | 6                   | 300                 | 12                      | 10  | -   | -   | -   | 800                          | 5                  | 80                 |

### SDCL0603Q-02B03 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | Ω                  | mA                 |
| Symbol              | L          | Q                   | Freq.               | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q0N6□T02B03 | 0.6        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 20000                        | 0.06               | 850                |
| SDCL0603Q0N7□T02B03 | 0.7        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 20000                        | 0.06               | 800                |

**Sunlord**

Specifications subject to change without notice. Please check our website for latest information. Revised 2018/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

# SPECIFICATIONS

## SDCL0603Q-02B03 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | Ω                  | mA                 |
| Symbol              | L          | Q                   | Freq.               | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q0N8□T02B03 | 0.8        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 18000                        | 0.07               | 800                |
| SDCL0603Q0N9□T02B03 | 0.9        | 13                  | 500                 | >24                     | >32 | >54 | >57 | >65 | 18000                        | 0.07               | 750                |
| SDCL0603Q1N0□T02B03 | 1.0        | 13                  | 500                 | 24                      | 32  | 54  | 57  | 65  | 17000                        | 0.08               | 750                |
| SDCL0603Q1N1□T02B03 | 1.1        | 13                  | 500                 | 19                      | 26  | 45  | 47  | 55  | 17000                        | 0.10               | 750                |
| SDCL0603Q1N2□T02B03 | 1.2        | 13                  | 500                 | 19                      | 25  | 43  | 44  | 52  | 17000                        | 0.10               | 750                |
| SDCL0603Q1N3□T02B03 | 1.3        | 13                  | 500                 | 19                      | 25  | 40  | 42  | 47  | 17000                        | 0.12               | 600                |
| SDCL0603Q1N4□T02B03 | 1.4        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 47  | 16000                        | 0.12               | 600                |
| SDCL0603Q1N5□T02B03 | 1.5        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 15000                        | 0.12               | 600                |
| SDCL0603Q1N6□T02B03 | 1.6        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 15000                        | 0.13               | 600                |
| SDCL0603Q1N7□T02B03 | 1.7        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 15000                        | 0.15               | 600                |
| SDCL0603Q1N8□T02B03 | 1.8        | 13                  | 500                 | 19                      | 24  | 39  | 41  | 46  | 15000                        | 0.15               | 600                |
| SDCL0603Q1N9□T02B03 | 1.9        | 13                  | 500                 | 18                      | 24  | 38  | 40  | 45  | 12500                        | 0.15               | 600                |
| SDCL0603Q2N0□T02B03 | 2.0        | 13                  | 500                 | 17                      | 24  | 38  | 39  | 44  | 12500                        | 0.15               | 600                |
| SDCL0603Q2N1□T02B03 | 2.1        | 13                  | 500                 | 17                      | 24  | 37  | 39  | 44  | 11000                        | 0.15               | 600                |
| SDCL0603Q2N2□T02B03 | 2.2        | 13                  | 500                 | 17                      | 24  | 38  | 40  | 43  | 11000                        | 0.15               | 600                |
| SDCL0603Q2N3□T02B03 | 2.3        | 13                  | 500                 | 17                      | 24  | 37  | 39  | 43  | 10000                        | 0.20               | 500                |
| SDCL0603Q2N4□T02B03 | 2.4        | 13                  | 500                 | 17                      | 23  | 36  | 38  | 42  | 10000                        | 0.20               | 500                |
| SDCL0603Q2N5□T02B03 | 2.5        | 13                  | 500                 | 17                      | 23  | 35  | 36  | 40  | 10000                        | 0.20               | 500                |
| SDCL0603Q2N6□T02B03 | 2.6        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 10000                        | 0.20               | 500                |
| SDCL0603Q2N7□T02B03 | 2.7        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 10000                        | 0.20               | 500                |
| SDCL0603Q2N8□T02B03 | 2.8        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9500                         | 0.20               | 500                |
| SDCL0603Q2N9□T02B03 | 2.9        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9500                         | 0.20               | 500                |
| SDCL0603Q3N0□T02B03 | 3.0        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 9500                         | 0.25               | 450                |
| SDCL0603Q3N1□T02B03 | 3.1        | 13                  | 500                 | 17                      | 22  | 34  | 35  | 39  | 8500                         | 0.25               | 450                |
| SDCL0603Q3N2□T02B03 | 3.2        | 13                  | 500                 | 17                      | 22  | 33  | 35  | 39  | 8200                         | 0.25               | 450                |
| SDCL0603Q3N3□T02B03 | 3.3        | 13                  | 500                 | 18                      | 23  | 34  | 36  | 40  | 8100                         | 0.25               | 450                |
| SDCL0603Q3N4□T02B03 | 3.4        | 13                  | 500                 | 17                      | 23  | 33  | 35  | 39  | 8000                         | 0.25               | 450                |
| SDCL0603Q3N5□T02B03 | 3.5        | 13                  | 500                 | 17                      | 23  | 33  | 35  | 39  | 7900                         | 0.25               | 450                |
| SDCL0603Q3N6□T02B03 | 3.6        | 13                  | 500                 | 16                      | 23  | 33  | 35  | 39  | 7700                         | 0.30               | 400                |
| SDCL0603Q3N7□T02B03 | 3.7        | 13                  | 500                 | 16                      | 23  | 33  | 35  | 38  | 7600                         | 0.30               | 400                |
| SDCL0603Q3N8□T02B03 | 3.8        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7500                         | 0.30               | 400                |
| SDCL0603Q3N9□T02B03 | 3.9        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 7400                         | 0.30               | 400                |
| SDCL0603Q4N3□T02B03 | 4.3        | 13                  | 500                 | 16                      | 21  | 32  | 34  | 37  | 6800                         | 0.40               | 350                |
| SDCL0603Q4N7□T02B03 | 4.7        | 13                  | 500                 | 16                      | 22  | 33  | 35  | 38  | 6200                         | 0.40               | 350                |
| SDCL0603Q5N1□T02B03 | 5.1        | 13                  | 500                 | 17                      | 22  | 34  | 36  | 38  | 5900                         | 0.40               | 350                |
| SDCL0603Q5N6□T02B03 | 5.6        | 13                  | 500                 | 16                      | 21  | 33  | 34  | 37  | 5500                         | 0.40               | 350                |
| SDCL0603Q6N2□T02B03 | 6.2        | 13                  | 500                 | 18                      | 23  | 34  | 35  | 37  | 5100                         | 0.48               | 300                |
| SDCL0603Q6N8□T02B03 | 6.8        | 13                  | 500                 | 17                      | 22  | 32  | 33  | 35  | 5500                         | 0.50               | 300                |
| SDCL0603Q7N5□T02B03 | 7.5        | 13                  | 500                 | 16                      | 21  | 31  | 33  | 34  | 4700                         | 0.50               | 300                |
| SDCL0603Q8N2□T02B03 | 8.2        | 13                  | 500                 | 16                      | 21  | 31  | 32  | 34  | 4300                         | 0.56               | 250                |
| SDCL0603Q9N1□T02B03 | 9.1        | 13                  | 500                 | 16                      | 20  | 30  | 31  | 32  | 4100                         | 0.70               | 250                |
| SDCL0603Q10N□T02B03 | 10         | 13                  | 500                 | 16                      | 20  | 28  | 29  | 31  | 3800                         | 0.70               | 250                |
| SDCL0603Q12N□T02B03 | 12         | 13                  | 500                 | 16                      | 20  | 27  | 28  | 28  | 3400                         | 0.70               | 250                |
| SDCL0603Q15N□T02B03 | 15         | 13                  | 500                 | 15                      | 19  | 24  | 24  | 23  | 2600                         | 0.70               | 250                |
| SDCL0603Q18N□T02B03 | 18         | 13                  | 500                 | 15                      | 19  | 23  | 24  | 22  | 2300                         | 0.80               | 200                |
| SDCL0603Q22N□T02B03 | 22         | 13                  | 500                 | 15                      | 19  | 22  | 23  | 20  | 2200                         | 1.20               | 150                |
| SDCL0603Q27N□T02B03 | 27         | 13                  | 500                 | 15                      | 19  | 15  | 13  | 8   | 2000                         | 1.60               | 140                |
| SDCL0603Q33N□T02B03 | 33         | 11                  | 300                 | 14                      | 15  | 8   | 5   | -   | 2000                         | 2.20               | 120                |

**Sunlord**

Specifications subject to change without notice. Please check our website for latest information. Revised 2018/04/15

Sunlord Industrial Park, Dafuyuan Industrial Zone, Guanlan, Shenzhen, China 518110 Tel: 0086-755-29832660 Fax: 0086-755-82269029 E-Mail: sunlord@sunlordinc.com

## SPECIFICATIONS

### SDCL0603Q-02B03 Series

| Part Number         | Inductance | Min. Quality Factor | L, Q Test Freq. L/Q | Typical Q @ Freq. (GHz) |     |     |     |     | Min. Self-resonant Frequency | Max. DC Resistance | Max. Rated Current |
|---------------------|------------|---------------------|---------------------|-------------------------|-----|-----|-----|-----|------------------------------|--------------------|--------------------|
|                     |            |                     |                     | 0.5                     | 0.8 | 1.8 | 2.0 | 2.4 |                              |                    |                    |
| Units               | nH         | -                   | MHz                 | -                       |     |     |     |     | MHz                          | $\Omega$           | mA                 |
| Symbol              | L          | Q                   | Freq.               | Q                       |     |     |     |     | S.R.F                        | DCR                | I <sub>r</sub>     |
| SDCL0603Q39N□T02B03 | 39         | 11                  | 300                 | 14                      | 15  | 6   | -   | -   | 1600                         | 2.30               | 120                |
| SDCL0603Q47N□T02B03 | 47         | 11                  | 300                 | 14                      | 15  | -   | -   | -   | 1500                         | 2.60               | 100                |
| SDCL0603Q56N□T02B03 | 56         | 11                  | 300                 | 13                      | 13  | -   | -   | -   | 1400                         | 2.80               | 100                |
| SDCL0603Q68N□T02B03 | 68         | 11                  | 300                 | 13                      | 11  | -   | -   | -   | 1200                         | 3.20               | 100                |
| SDCL0603Q82N□T02B03 | 82         | 10                  | 300                 | 12                      | 10  | -   | -   | -   | 1100                         | 3.80               | 100                |
| SDCL0603QR10□T02B03 | 100        | 10                  | 300                 | 12                      | 10  | -   | -   | -   | 1000                         | 4.00               | 80                 |
| SDCL0603QR12□T02B03 | 120        | 9                   | 300                 | 12                      | 8   | -   | -   | -   | 1000                         | 5.00               | 80                 |

※□: Please specify the inductance tolerance. For  $L \leq 4.2\text{nH}$ , choose  $B = \pm 0.1\text{nH}$ ,  $C = \pm 0.2\text{nH}$  or  $S = \pm 0.3\text{nH}$ ; For  $4.2\text{nH} < L < 5.6\text{nH}$ , choose,  $H = \pm 3\%$ ,  $J = \pm 5\%$ . or  $S = \pm 0.3\text{nH}$ ; For  $L \geq 5.6\text{nH}$ , choose,  $H = \pm 3\%$ ,  $J = \pm 5\%$

※: Please refer to "Measurement Notice For RF Inductors".

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [Sunlord](#) manufacturer:*

Other Similar products are found below :

[CR32NP-100KC](#) [CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#)