## everbit™

# swissbit®

**Product Fact Sheet** 

**Industrial** microSD / SDHC / SDXC **Memory Card** 

S-46u Series UHS-I Interface, pSLC

Extended and Industrial Temperature Grade

Date: Revision: March 29, 2019





# Product Fact Sheet S-46u Series



### **Product Summary**

- Capacities: 2 GBytes, 4 GBytes, 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes
- Form Factor: Standard microSD memory Card form factor: 15.0mm x 11.0mm x 0.7mm (1.0mm)
- Compliance: Fully compliant with SD Memory Card specification 2.0 and
  - 3.0 and MICRO SD Memory Card Addendum 4.00
  - SD/SDHC/SDXC default/high speed mode and UHS supported
  - Up to speed class 10 and U3 according SD3.0 specification
  - o FAT16, FAT32 or exFAT preformatted
- Performance: High performance 3.0 specification
  - SD Default speed, SD High speed, SD UHS-I
  - Read Performance: Sequential Read up to 46 MBytes/s, Random Read IOPS up to 1,433
  - o Write Performance: Sequential Write up to 41 MBytes/s, Random Write IOPS up to 1,249
- Operating Temperature Range\*:
  - o Extended: -25 to 85 °C
  - o Industrial: -40 to 85 °C
- Storage Temperature Range:
  - o Extended: -25 to 100 °C
  - o Industrial: -40 to 100 °C
- Operating Voltage: 2.7 ... 3.6V normal operating voltage (Low-power CMOS technology)
- Data Retention: 10 years @ Life Begin / 1 Year @ Life End
- Humidity: 85% RH @85°C 1000h
- Electromagnetic Compatibility Test: Radiated Emission; Radiated Immunity; Electrostatic Discharge

#### **Product Features**

- Optimized FW algorithms especially for high read access and long data retention applications
  - Patented power-off reliability technology, Wear Leveling technology
  - o Write Endurance technology, Read Disturb Management
  - Data Care Management, Near miss ECC technology
  - Diagnostic features with Life Time Monitoring tool support
- High reliability
  - S-46u cards with pseudo SLC (pSLC) feature higher write performance and endurance than MLC based cards (S-45u)
  - The product is optimized for long life cycle and provides excellent data retention in high temperature mission profiles.
  - Number of card insertions/removals up to 20,000
  - SIP (System In Package) process for extreme dust, water and ESD proof
  - Selected AEC-Q100 qualification
- Manufactured in a TS 16949 certified factory
- Controlled BOM & PCN process
- Customized options like CID registers, CPRM keys, firmware incl. settings and marking by projects
- In-Field Firmware Update
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

#### Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addressees the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

<sup>\*</sup> High Temperature storage without operation reduces the data retention, in operation the data will be refreshed, if data error issues were detected

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Memory Cards category:

Click to view products by Swissbit manufacturer:

Other Similar products are found below:

SQF-ISDS1-8G-21C USDCOEM-32GB LMEX1L128GG2 LMEX1L256GG2 LMEX1L016GG2 LMEX1L032GG2 LMEX1L064GG2
SDSDQAF4-032G-I SDSDQAF4-256G-I AP-CF016GKBNS-ETNRG CFLSH-016SDG MS-C6-8G HMC-EF283 SDCFXPS-032G-X46
SDCFXSB-128G-G46 SDSDQB-032G-B35 SDSDQM-032G-B35A SDU4GDMGRB SDU4GDPGRB 5788667-1-CUT-TAPE RPSMLE32DA1 SDC4GDPGRB 2729389 VTDCFBPI004G SDSDAF3-016G-XI 2403484 VTDS41PI008G SDSDAF3-016G-I
VSFCS2CC060G SDSDAF3-032G-XI SDSDAD-016G SDSDAF3-008G-XI SDSDAF3-008G-I SDSDQAB-016G-J VTDCFBPI008G
M1A0-0160R12 M1A0-0320R12 M1A4-0320R12 M1AA-0160R12 M1AA-0320R12 M1AA-0640R12 M1AA-1280R12 SDCFXPS-256GX46 SDSDXPK-128G-GN4IN SDSDXXG-032G-GN4IN SDSDXXY-064G-GN4IN SDSDXXY-128G-GN4IN SDSDXXY-512G-GN4IN
SDSQXA1-128G-GN6MA SDSQXA1-256G-GN6MA