

200mA, 100V Switching Diode

FEATURES

- Designed for mounting on small surface
- Low Capacitance
- Low forward voltage drop
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21


APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- Lighting application
- On-board DC/DC converter

MECHANICAL DATA

- Case: SOT-23
- Molding compound meets UL 94 V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Weight: 8.00mg (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	200	mA
V_{RRM}	100	V
I_{FSM}	2	A
V_F at $I_F = 10\text{mA}$	0.82	V
$T_{J\text{ MAX}}$	150	°C
Package	SOT-23	



SOT-23

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Marking code on the device	MMBD4148	5D	
	MMBD4148CA	A1	
	MMBD4148CC	A4	
	MMBD4148SE	A7	
Repetitive peak reverse voltage	V_{RRM}	100	V
Forward current	I_F	200	mA
Repetitive peak forward surge current	I_{FRM}	700	mA
Non-repetitive peak forward surge current	$t = 1\mu\text{s}$	2	A
	$t = 1\text{s}$	1	A
Junction temperature range	T_J	-55 to +150	°C
Storage temperature range	T_{STG}	-55 to +150	°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-ambient thermal resistance	$R_{\Theta JA}$	357	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ C$ unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	MIN	MAX	UNIT
Forward voltage per diode ⁽¹⁾	$I_F = 10\text{mA}$, $T_J = 25^\circ C$	V_F	-	0.82	V
Reverse current per diode ⁽²⁾	$V_R = 20V$, $T_J = 25^\circ C$	I_R	-	25	nA
	$V_R = 75V$, $T_J = 25^\circ C$		-	5	μA
	$V_R = 20V$, $T_A = 150^\circ C$		-	50	μA
Reverse breakdown voltage per diode	$I_R = 5\mu\text{A}$, $T_J = 25^\circ C$	V_{BR}	75	-	V
	$I_R = 100\mu\text{A}$, $T_J = 25^\circ C$		100	-	V
Junction capacitance per diode	$f = 1\text{MHz}$, $V_R = 0V$	C_J	-	4	pF
Reverse recovery time per diode	$I_F = 10\text{mA}$, $I_R = 1\text{mA}$, $R_L = 100\Omega$, $V_R = 6V$	t_{rr}	-	4	ns

Notes:

1. Pulse test with PW = 0.3ms
2. Pulse test with PW = 30ms

ORDERING INFORMATION

ORDERING CODE ⁽¹⁾	PACKAGE	PACKING
MMBD414x RFG	SOT-23	3,000 / 7" Tape & Reel
MMBD414x R5G	SOT-23	10,000 / 13" Tape & Reel

Notes:

1. "x" defines part no. from "8" to "8SE"

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Power Derating Curve




Fig.2 Forward Characteristics




Fig.3 Typical Reverse Characteristics






Fig.4 Typical Capacitance vs. Reverse Voltage




PACKAGE OUTLINE DIMENSIONS

SOT-23


DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	0.89	1.12	0.035	0.044
b	0.30	0.50	0.012	0.020
c	0.08	0.20	0.003	0.008
D	2.80	3.04	0.110	0.120
E	2.10	2.64	0.083	0.104
E1	1.20	1.40	0.047	0.055
e	1.90 BSC		0.075 BSC	
L1	0.54 REF.		0.021 REF.	

SUGGESTED PAD LAYOUT







Symbol	Unit (mm)	Unit (inch)
A	1.00	0.039
B	0.85	0.033
C	2.10	0.083
D	3.10	0.122
E	0.98	0.039

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

PIN CONFIGURATION



Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Taiwan Semiconductor manufacturer:

Other Similar products are found below :

[TS19378CS RLG](#) [BC548C B1G](#) [MBS6](#) [SF14](#) [SS26 R4](#) [GBPC2506W](#) [P4SMA200A R3G](#) [P4SMA36CA R3G](#) [SS15](#) [P6SMB62CA R5G](#)
[SMCJ40CA R7G](#) [P4SMA36A R3G](#) [SS34V7G](#) [SMAJ58CA R3G](#) [SK56C R7G](#) [SMAJ24A R3G](#) [S2D R5G](#) [TSS83L45 MWG](#) [SS16 R3G](#)
[SMA6J11AHR3G](#) [S8JC R7G](#) [S3MBHR5G](#) [RS1J R3G](#) [MUR820 C0](#) [MUR120S R5G](#) [MBS6 RCG](#) [ES3G R7G](#) [ES2BA R3G](#) [SMCJ28A V7G](#)
[SMBJ15CA](#) [SMBJ40CA](#) [SMCJ17CA](#) [SMBJ6V5CA](#) [BZT52C15-G RHG](#) [ABS10 REG](#) [GBPC2510W T0](#) [RS1GL RVG](#) [SMCJ43A](#)
[SMCJ70A V7G](#) [MMBT2222A RFG](#) [SS26LWHRVG](#) [SS16LWHRVG](#) [ES1DLW RVG](#) [TSP10U100S S1G](#) [BYG20J R3G](#) [BYG20G R3G](#)
[BZT52C3V3S RRG](#) [1.5SMC82A V7G](#) [S1G M2G](#) [1.5KE180A R0G](#)