
Spec Sheet

Ceramic RF Devices (Band Pass Type)for 5G

TSB1N18D4G70LV0KWT



Features

- Item Summary

 Band Pass Type, 1.6x0.8x0.65mm

 for 5G
- Lifecycle Stage
 - Mass Production (Preferred)
- Standard packaging quantity (minimum)

Taping Papered 5000

■ Products characteristics table

System	5G	
Passband Frequency1 (f1)	4400 to 5000 MHz	
Insertion Loss2 (max)(in f1)	1.6 dB at 4400 to 5000MHz (-40 to +85 ℃)	
VSWR1 (max)(in f1)	2 at 4400 to 5000MHz	
Attenuation1 (min)(f1)	35 dB 500 to 3300MHz	
Attenuation2 (min)(f1)	20 dB 6450 to 7700MHz	
Input Impedance / Output Impedance	50 Ω / 50 Ω	
Operating Temp. Range	-40 to +85 ℃	
RoHS Compliance (10 subst.)	Yes	
REACH Compliance (247 subst.)	Yes	
Halogen Free	Yes	
Soldering	Reflow	

■ External Dimensions

Dimension L	1.6 ±0.10 mm
Dimension W	0.8 ±0.10 mm
Dimension T	Max 0.65 mm

2025.03.04

Please read this notice before using the TAIYO YUDEN products.

Approval of Product Specifications

Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available. When using our products, please be sure to approve our product specifications or make a written agreement on the product specification with TAIYO YUDEN in advance. Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in individual product specification sheets.

Pre-Evaluation in the Actual Equipment and Conditions

Please conduct validation and verification of our products in actual conditions of mounting and operating environment before using our products.

Limited Application

1. Equipment Intended for Use

Our products are intended for general-purpose and standard use in general electronic equipment for consumer (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and other equipment specified in the product catalog or the individual product specification sheets, or the equipment approved separately by TAIYO YUDEN.

TAIYO YUDEN has the product series intended for use in the following equipment. Therefore, when using our products for these equipment, please check available applications specified in the product catalog or the individual product specification sheets and use the corresponding products.

	Product Series		
Application	Equipment *1	Category (Part Number Code *2)	Quality Grade *3
Automotive Electronic Equipment (POWERTRAIN, SAFETY) Automotive Electronic Equipment (BODY & CHASSIS, INFOTAINMENT)	А	1	
	Automotive Electronic Equipment (BODY & CHASSIS, INFOTAINMENT)	С	2
Industrial	Telecommunications Infrastructure and Industrial Equipment	В	2
Medical	Medical Devices classified as GHTF Class C (Japan Class III)	M	2
iviedicai	Medical Devices classified as GHTF Classes A or B (Japan Classes I or II)	L	3
Consumer -	General Electronic Equipment	S	3
	Only for Mobile Devices *4	E	4

^{*}Notes: 1.Based on the general specifications required for electronic components for such equipment, which are recognized by TAIYO YUDEN, the use of each product series for the equipment is recommended. Please be sure to contact TAIYO YUDEN before using our products for equipment other than those covered by the product series.

- 2.On each of our part number, the 2nd code from the left is a code indicating the "Category" as shown in the above table. For details, please check the explanatory materials regarding the part numbering system of each of our products.
- 3. Each product series is assigned a "Quality Grade" from 1 to 4 in order of higher quality. Please do not incorporate a product into any equipment with a higher Quality Grade than the Quality Grade of such product without the prior written consent of TAIYO YUDEN.
- 4.The applications covered by this product series are limited to mobile devices (smartphone, tablet PC, smartwatch, handheld game console, etc.) among general electronic equipment for consumer. The design, specifications and operating environment, etc. differ from those of the product series for "General Electronic Equipment" (Category: S), so please check the individual product specification sheets for details. The product series for "General Electronic Equipment" (Category: S) can also be used for mobile devices.

2. Equipment Requiring Inquiry

Please be sure to contact TAIYO YUDEN for further information before using our products for the following equipment (excluding intended equipment as specified in the product catalog or the individual product specification sheets) which may cause loss of human life, bodily injury, serious property damage and/or serious public impact due to a failure or defect of the products and/or malfunction attributed thereto.

- (1) Aviation equipment
- (2) Aerospace equipment (artificial satellite, rocket, etc.)
- (3) Undersea equipment (submarine repeating equipment, etc.)
- (4) Power generation control equipment (nuclear power, hydroelectric power, thermal power plant control system, etc.)
- (5) Transportation equipment (train control system, and ship control system, etc.)
- (6) Traffic signal equipment
- (7) Disaster prevention equipment, crime prevention equipment
- (8) Combustion control equipment, explosion control equipment
- (9) Military equipment (excluding lethal weapons, weapons of mass destruction and conventional weapons)
- (10) Any other equipment requiring high levels of quality and/or reliability equal to the equipment listed above

3. Equipment Prohibited for Use

Please do not incorporate our products into (i) the following equipment requiring extremely high levels of safety and/or reliability, and/or (ii) the following equipment that may hinder the maintenance of international peace and security.

- (1) Medical devices classified as GHTF Class D (Japan Class IV), implantable medical devices *
- (2) lethal weapons, weapons of mass destruction, conventional weapons
- (3) Any other equipment requiring extremely high levels of safety and/or reliability equal to the equipment listed in (1) above
- *Notes: Implantable medical devices contain not only internal unit which is implanted in a body, but also external unit which is connected to the internal unit.

4. Limitation of Liability

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of our products for any equipment that is not intended for use by TAIYO YUDEN, or any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

Safety Design

When using our products for high safety and/or reliability-required equipment or circuits, please fully perform safety and/or reliability evaluation. In addition, please install (i) systems equipped with a protection circuit and a protection device and/or (ii) systems equipped with a redundant circuit or other system to prevent an unsafe status in the event of a single fault for a failsafe design to ensure safety.

Intellectual Property Rights

Information contained in this spec sheet is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.

Limited Warranty

Please note that the scope of warranty for our products is limited to the delivered our products themselves conforming to the product specifications specified in the individual product specification sheets, and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a failure or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement, provided, however, that our products shall be used for general-purpose and standard use in the equipment specified in the product catalog or the individual product specification sheets.

■ TAIYO YUDEN's Official Sales Channel

The contents of this spec sheet are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this spec sheet are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.

Caution for Export

Some of our products may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Signal Conditioning category:

Click to view products by Taiyo Yuden manufacturer:

Other Similar products are found below:

PD0409J5050S2HF AFS14A35-1591.50-T3 AFS20A20-1227.60-T3 JP510S LFB322G45SN1A504 SF2159E FM-104-PIN CER0813B MAPDCC0005 3A325 BD0810N50100AHF DC0710J5005AHF DC2327J5005AHF X3C19F1-20S XC3500P-20S CDBLB455KCAX39-B0 PD0922J5050D2HF 600S150FTRB 1E1305-3 1F1304-3S BD1222J50200AHF BD1722J50100AHF 2450DP39K5400E BD0810J50150AHF BD1722J50200AHF DS-329-PIN TP-104-PIN TP-101-PIN HH-128-PIN T-1000-N JP506S XC0900P-10S 11305-10 5962-9091202MXA 3A412S X3C06A4-03S DSS-333-PIN PD2425J5050S2HF B39242B4360P810 B39781B8005P810 B39881B8013P810 B39791B8039P810 B39771B8035P810 B39741B8012P810 B39212B8033P810 B39162B8636P810 SF2225E SF2275E SF2395E SF2188D