



TAOGLAS®



Datasheet

Part No:
MA341.W.LB.001

Description

2in1 White Magnetic Mount GNSS and 4G/LTE Antenna

Features:

Compact Design with Magnetic Mounting
1* LTE Antenna covering 600-6000MHz
1* GNSS Antenna
Dims: 58mm * 58mm * 65mm
Cable: 2m of RG174
Connector: SMA(M)
RoHS & Reach Compliant

1.	Introduction	3
2.	Specification	4
3.	Mechanical Drawing	7
4.	Packaging	8
5.	Antenna Characteristics	9
6.	LNA Characteristics	15
7.	Radiation Patterns	18
<hr/>		
	Changelog	35

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Ireland & USA
ISO 9001:2015
Certified



Taiwan
ISO 9001:2015
Certified



1. Introduction



The Taoglas MA341 magnetic mount antenna is a high performance 2-in-1 combination antenna with GNSS and 5G/4G. The robust, compact housing is just at only 65mm tall and 58mm in diameter, it is an ideal for external antenna for assets requiring GNSS, Cellular and Wi-Fi connectivity.

The GPS/GLONASS/Galileo antenna has stable gain and radiation patterns on all bands. The 5G/4G antenna, covers all worldwide LTE bands, includes many sub 6GHz, 5G FR1 bands and includes fallback to 3G/2G bands where required.

The IP67 rated enclosure is made from a durable, UV resistant ASA material that makes it resistant to vandalism or impact. An integrated rubber O-ring under the enclosure prevents water ingress under the antenna. It is mounted from the inside of the user device enclosure and the small thread allows for installation in situations where space is minimal.


Typical applications include:

- Smart Metering and Remote Monitoring
- Digital Signage
- Transportation and Telematics

Cable type and length, and connectors are fully customizable, and the MA341 can also be customized for other configurations. It is also available in black (MA341.A.LBI.001). Contact your regional Taoglas customer support team for more information.

2. Specification

GNSS Frequency Bands					
GPS	L1 1575.42 MHz	L2 1227.6 MHz	L5 1176.45 MHz		
	■	□	□		
GLONASS	G1 1602 MHz	G2 1248 MHz	G3 1207 MHz		
	■	□	□		
Galileo	E1 1575.24 MHz	E5a 1176.45 MHz	E5b 1201.5 MHz	E6 1278.75 MHz	
	■	□	□	□	
BeiDou	B1C 1575.42 MHz	B1I 1561 MHz	B2a 1176.45 MHz	B2b 1207.14 MHz	B3 1268.52 MHz
	■	■	□	□	□
L-Band	L-Band 1542 MHz				
	□				
QZSS (Regional)	L1 1575.42 MHz	L2C 1227.6 MHz	L5 1176.45 MHz	L6 1278.75e6	
	■	□	□	□	
IRNSS (Regional)	L5 1176.45 MHz				
	□				
SBAS	L1/E1/B1 1575.42 MHz	L5/B2a/E5a 1176.45 MHz	G1 1602 MHz	G2 1248 MHz	G3 1207 MHz
	■	□	■	□	□



GNSS Bands and Constellations

GNSS Electrical			
Frequency (MHz)	1561	1575.42	1603
VSWR (max.)	3:1	3:1	3:1
Passive Antenna Efficiency (%)	28.22	36.12	45.39
Passive Antenna Gain (dBi)	-3.73	-1.2	-1.2
Polarization	RHCP		
Impedance	50 Ω		




LNA and Filter Electrical Properties			
Frequency (MHz)	1561	1575.42	1603
Gain (dB)	31.7	31.2	29.8
Noise (dB)	2.29	2.15	2.5
Voltage Range	1.8-5.5V		
Current Consumption	9 ± 3		
Out-off-band rejection (dB)	> 70 @700-960MHz , > 60 @ 1710-6000MHz		

LTE Electrical								
Band	Frequency (MHz)	Efficiency (%)	Average Gain (dB)	Peak Gain (dBi)	Impedance	Polarization	Radiation Pattern	Max. input power
5G NR/4G Band 71	617-698	28.1	-5.51	-0.78	50 Ω	Linear	Omni	2W
4G/3G Band 12,13,14,17,28,29	698-824	44.7	-3.50	0.99				
4G/3G/NB-IoT/Cat M Band 5,8,18,19,20,26,27	824-960	46.7	-3.31	0.99				
5G NR/4G Band 21,32,74,75,76	1427-1518	33.2	-4.79	2.87				
4G/3G Band 1,2,3,4,9,23,25,35,39,66	1710-2200	65.3	-1.85	5.93				
4G/3G Band 7,30,38,40,41	2300-2690	69.0	-1.61	5.64				
5G NR/4G Band 22,42,48,77,78,79	3300-5000	55.7	-2.54	6.84				
LTE5200/Wi-Fi5800	5150-5925	57.3	-2.42	6.00				


Mechanical	
Dimensions	58 x 58 x 65mm
Material	ASA
Connector	SMA(M)
Cable	2m of RG174

Environmental	
Temperature Range (Use & Storage)	-40 - +85°C
RoHS & REACH Compliant	Yes


3. Mechanical Drawing



DETAIL AG
SCALE 1 : 1



DETAIL B
SCALE 2 : 1




Accessory

	Name	Material	Finish	Qty
1	Top housing	ASA	White	1
2	Bottom housing	ASA	Black	1
3	Grommet	Silicone Rubber	Black	1
4	Magnet pack/N48	NdFeB	Ni Plated	1
5	Matte Silver Label	PET	Matte Silver	1
6	RG174 Coaxial Cable	PVC	Black	2
7	Heat Shrink Tube(GNS5)	PE	Blue Tube/White Text	1
8	Heat Shrink Tube(4G/5G-1)	PE	Red Tube/White Text	1
9	SMA(M)ST Plug for RG-316/RG-174	Brass	Au Plated	2
10	CE,WEEE and UKCA mark logo Label	PEPA	White	1
11	Double Sided Adhesive	3M VHB 5952	Black foam/Red liner	1
12	Grommet plug_RG174	ASA	Black	1

4. Packaging

1 PCS / PE Bag
Weight: 161g



60 PCS / Carton
Dimensions: 430 x 380 x 280mm
Weight: 10.76Kg




5. Antenna Characteristics

5.1 Test Setup

AUT




Vector Network Analyzer




VNA Set-up on 30x30cm Ground Plane


5.2 GNSS - Return Loss




5.3 GNSS - VSWR




5.4 GNSS - Efficiency




5.5 GNSS - Average Gain




5.6 GNSS - Peak Gain (Gtotal)




5.7 LTE - Return Loss




5.8 LTE - VSWR




5.9 LTE - Efficiency



5.10 LTE - Average Gain




5.11 LTE - Peak Gain




6. LNA Characteristics


6.1 Block Diagram




6.2 Gain




6.3 Noise Figure




6.4 Wide Band Gain



6.5 Out Of Band Rejection





6.6 Group Delay





7. Radiation Patterns

7.1 Test Setup





Chamber Set-up on 30x30cm Ground Plane



7.2 GNSS Patterns at 1576 MHz





7.3 GNSS Patterns at 1562 MHz





7.4 GNSS Patterns at 1602 MHz





7.5 LTE1 Patterns at 650 MHz





7.6 LTE1 Patterns at 750 MHz





7.7 LTE1 Patterns at 890 MHz





7.8 LTE1 Patterns at 1470 MHz





7.9 LTE1 Patterns at 1805 MHz





7.10 LTE1 Patterns at 1920 MHz





7.11 LTE1 Patterns at 1990 MHz





7.12 LTE1 Patterns at 2360 MHz





7.13 LTE1 Patterns at 2595 MHz





7.14 LTE1 Patterns at 3550 MHz



7.15 LTE1 Patterns at 4600 MHz



7.16 LTE1 Patterns at 5530 MHz



Changelog for the datasheet

SPE-24-8-222 – MA341.W.LB.001

Revision: A (Original First Release)	
Date:	2024-09-09
Notes:	Initial Release
Author:	Cesar Sousa

Previous Revisions



TAOGLAS[®]
www.taoglas.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Taoglas](#) manufacturer:

Other Similar products are found below :

[930-033-R](#) [108-00014-50](#) [66089-2406](#) [A09-F8NF-M](#) [A09-F5NF-M](#) [RGFRA1903041A1T](#) [W1049B090](#) [WTL2449CQ1-FRSMM](#) [CPL9C](#)
[0600-00060](#) [PAL90209H-FNF](#) [GD53-25](#) [S9025PLSMF](#) [GPSCPMM00](#) [ANTDOM-05-01-WPM](#) [ANT-WP868SMA-Y](#) [CBNC58](#) [ABFT](#)
[LP800NMOW](#) [NMOQ88C](#) [NMOQB](#) [NMOQC](#) [ANT-GSMGPSPUKS](#) [60210](#) [60140](#) [ANT-8WPIG-UFL](#) [ANT-GPSPUKS](#) [A21H0](#) [29000863](#)
[29000848](#) [955179003](#) [RFANT2012090A0T](#) [RGFRA3216110A5T](#) [22100003](#) [DL-T022-2.4G](#) [DL-T023-4G](#) [T1-915M](#) [DL-T021-2.4GW](#) [DL-](#)
[T021-2.4G](#) [KH-IPEX-1.13](#) [BWGNXCX16-6B1Y2L120](#) [BWGNXCX15-15B1Y4L120](#) [DL-T023-4GW](#) [DL-J020-433M](#) [J008-GSM](#)
[3N0401LG-021](#) [KHA\(RG1.13\)-TX90B-IPEX](#) [KH-GPS181804-WY](#) [KHA\(RG1.13\)-TX80B-IPEX](#) [TX5800-JZ-5](#)