



TAOGLAS®



Datasheet

Part No:
PC301.A.001

Description

FR4 PCB Combination Antenna (105x20mm) for Cellular and GNSS with 150mm Black and White 1.37 Cable and I-PEX MHFI

Features:

FR4 Combination Antenna
1 * GNSS covering L1, B1I, G1 and L-Band
1 * Cellular covering 600MHz – 8000MHz
Cable: 150mm of 1.37 Coaxial
Connector: I-PEX MHFI
Dims: 105 x 20 x 1.1 mm
RoHS & Reach Compliant

1.	Introduction	3
2.	Specification	4
3.	Mechanical Drawing	8
4.	Packaging	9
5.	Antenna Characteristics	10
6.	Radiation Patterns	17
	Changelog	31

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.



1. Introduction



The **PC301** FR4 PCB Combination Antenna is a high-performance, rigid PCB antenna designed to cover Cellular (600 MHz–8000 MHz) and GNSS (L1, B1I, G1, and L-Band) frequencies.

With its compact construction (105 x 20 x 1.1mm), the PC301 provides excellent efficiency, ground-plane independence, and quick integration into compact wireless devices- ideal for applications requiring robust global connectivity across multiple wireless standards.

By integrating Cellular and GNSS capabilities into a single compact antenna, it delivers a space-saving and cost-efficient solution. This allows designers to incorporate advanced wireless communication and easy positioning into their products without needing multiple antennas.

Typical Applications:


- Asset tracking
- Telematics
- E-Mobility
- Smart agriculture
- Connected healthcare devices
- Wearables and other IoT solutions

Installation is quick and simple with a “peel-and-stick” 3M adhesive backing, enabling secure mounting on non-metal surfaces such as plastic or glass. With peak gains ranging from 1 to 5 dBi across Cellular and GNSS bands, the PC301 allows designers to cover multiple frequency ranges with a single antenna — reducing cost, complexity, and time-to-market.

The antenna is supplied with a pre-assembled cable and connector for plug-and-play integration, both of which can be customized to meet specific project requirements. Different cable colours are available to simplify identification and streamline the assembly process during production, ensuring efficient installation and minimizing connection errors. For further optimization to customer-specific device environments, and for support in integrating and testing antenna performance within your device, please contact your regional Taoglas Customer Support Team.

2. Specification

GNSS Frequency Bands					
GPS	L1 1575.42 MHz	L2 1227.6 MHz	L5 1176.45 MHz		
	■	□	□		
GLONASS	G1 1602 MHz	G2 1248 MHz	G3 1207 MHz		
	■	□	❖		
Galileo	E1 1575.24 MHz	E5a 1176.45 MHz	E5b 1201.5 MHz	E6 1278.75 MHz	
	■	□	□	□	
BeiDou	B1C 1575.42 MHz	B1I 1561 MHz	B2a 1176.45 MHz	B2b 1207.14 MHz	B3 1268.52 MHz
	■	■	□	□	□
L-Band	L-Band 1542 MHz				
	■				
QZSS (Regional)	L1 1575.42 MHz	L2C 1227.6 MHz	L5 1176.45 MHz	L6 1278.75e6	
	■	□	□	□	
IRNSS (Regional)	L5 1176.45 MHz				
	□				
SBAS	L1/E1/B1 1575.42 MHz	L5/B2a/E5a 1176.45 MHz	G1 1602 MHz	G2 1248 MHz	G3 1207 MHz
	■	□	■	□	□



GNSS Bands and Constellations

GNSS Electrical				
Frequency (MHz)	1542	1561	1575.42	1602
VSWR (max.)	1.5:1	1.5:1	1.5:1	2:1
Efficiency (%)	60.6	64.1	63.1	58.8
Average Gain (dB)	-2.0	-1.9	-1.9	-2.3
Peak Gain (dBi)	3.6	4.0	4.2	4.1
Polarization	Linear			
Impedance	50 Ω			


Cellular Electrical								
Band	Frequency (MHz)	Efficiency (%)	Average Gain (dB)	Peak Gain (dBi)	Impedance	Polarization	Radiation Pattern	Max. input power
5G NR/4G Band 71	617-698	55.8	-2.53	1.39	50 Ω	Linear	Omni directional	5W
4G/3G Band 12,13,14,17,28,29	698-806	69.7	-1.57	2.73				
4G/3G/NB-IoT/Cat M Band 5,8,18,19,20,26,27	824-960	61.2	-2.13	3.70				
5G NR/4G Band 21,32,74,75,76	1427-1518	39.2	-4.07	1.54				
4G/3G Band 1,2,3,4,9,23,25,35,39,66	1710-2200	72.7	-1.39	3.45				
4G/3G Band 7,30,38,40,41	2300-2690	69.4	-1.59	4.47				
5G NR/4G Band 22,42,48,77,78,79	3300-5000	39.8	-4.00	4.60				
LTE5200/Wi-Fi5800	5150-5925	29.4	-5.32	3.56				
Wi-Fi - 6GHz	5925-7125	51.8	-2.85	5.09				

5G/4G Bands			
Band Number	5G NR / FR1 / LTE / LTE-Advanced / WCDMA / HSPA / HSPA+ / TD-SCDMA / NTN		
	Uplink	Downlink	Covered
B1	1920 to 1980	2110 to 2170	✓
B2	1850 to 1910	1930 to 1990	✓
B3	1710 to 1785	1805 to 1880	✓
B4	1710 to 1755	2110 to 2155	✓
B5	824 to 849	869 to 894	✓
B7	2500 to 2570	2620 to 2690	✓
B8	880 to 915	925 to 960	✓
B9*	1749.9 to 1784.9	1844.9 to 1879.9	✓
B11	1427.9 to 1447.9	1475.9 to 1495.9	✓
B12	699 to 716	729 to 746	✓
B13	777 to 787	746 to 756	✓
B14	788 to 798	758 to 768	✓
B17	704 to 716	734 to 746	✓
B18	815 to 830	860 to 875	✓
B19	830 to 845	875 to 890	✓
B20	832 to 862	791 to 821	✓
B21	1447.9 to 1462.9	1495.9 to 1510.9	✓
B22*	3410 to 3490	3510 to 3590	✓
B23 / n23	2000 to 2020	2180 to 2200	✓
B24 / n255	1626.5 to 1660.5	1525 to 1559	✓
B25	1850 to 1915	1930 to 1995	✓
B26	814 to 849	859 to 894	✓
B27*	807 to 824	852 to 869	✓
B28	703 to 748	758 to 803	✓
B29		717 to 728	✓
B30	2305 to 2315	2350 to 2360	✓
B31	452.5 to 457.5	462.5 to 467.5	✗
B32		1452 to 1496	✓
B34		2010 to 2025	✓
B35		1850 to 1910	✓
B36		1930 to 1990	✓
B37		1910 to 1930	✓
B38		2570 to 2620	✓
B39		1880 to 1920	✓
B40		2300 to 2400	✓
B41		2496 to 2690	✓
B42		3400 to 3600	✓
B43		3600 to 3800	✓
B45		1447 to 1467	✓
B46		5150 to 5925	✓
B47		5855 to 5925	✓
B48		3550 to 3700	✓
B49		3550 to 3700	✓
B50		1432 to 1517	✓
B51		1427 to 1432	✓
B52		3300 to 3400	✓
B53		2483.5 to 2495	✓
B65	1920 to 2010	2110 to 2200	✓
B66	1710 to 1780	2110 to 2200	✓
B68	698 to 728	753 to 783	✓
B69		2570 to 2620	✓
B70	1695 to 1710	1995 to 2020	✓
B71	663 to 698	617 to 652	✓
B72	451 to 456	461 to 466	✗
B73	450 to 455	460 to 465	✗
B74	1427 to 1470	1475 to 1518	✓
B75		1432 to 1517	✓
B76		1427 to 1432	✓
B77		3300 to 4200	✓
B78		3300 to 3800	✓
B79		4400 to 5000	✓
B85	698 to 716	728 to 746	✓
B87	410 to 415	420 to 425	✗
B88	412 to 417	422 to 427	✗
n256	1980 to 2010	2170 to 2200	✓

Mechanical	
Dimensions	105mm x 20mm x 1.1 mm
Weight	5.3g
Mount	Adhesive, 3M 9448 HK
Material	FR4 (NP-140)
Connector	I-PEX MHFI
Cable	GNSS: 150 mm of 1.37 (White) Cellular: 150 mm of 1.37 Coaxial (Black)

Environmental	
Operation Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Relative Humidity	Non-condensing 65°C 95% RH

3. Mechanical Drawing



ITEM NO.	DESCRIPTION	MATERIAL	FINISH	QTY.
1	PCB_PCB.000305_Single Layer_L20_W105_H0.8mm_NP-140_35um	NP-140	BLACK	1
2	PC301.A Adhesive Tape	3M-9448HK	WHITE PAPER LINER	1
3	4FXAD00157AA400110-IPEX IPEX I (U.FL Compatible)_Au Plated for 1.37 Micro Coax(Black) 157mm, TIN/STRIP/OPEN(1.5/1.5/4mm),No Winding	COAX	BLACK	1
4	4FXBJ00150AA400110-IPEX IPEX I (U.FL Compatible)_Au Plated for 1.37 Micro Coax(white) 150mm, TIN/STRIP/OPEN(1.5/1.5/4mm),No Winding	COAX	WHITE	1



4. Packaging



- ☑ 50 PCS / PE bag
- ☑ PE bag(mm): 230x330 (Ref)
- ☑ Weight (Kg): 0.54 ±3%
- ☑ SPQ Label




- ☑ 2000 PCS / Carton
- ☑ Carton(mm): 360x310x160
- ☑ Weight (Kg): 11.34 ±3%
- ☑ Carton Label

5. Antenna Characteristics

5.1 Test Setup




Vector Network Analyzer




VNA Test Setup on 2mm ABS


5.2 GNSS - Return Loss




5.3 GNSS - VSWR




5.4 GNSS - Efficiency




5.5 GNSS - Average Gain




5.6 GNSS - Peak Gain




5.7 Cellular - Return Loss




5.8 Cellular - VSWR




5.9 Cellular - Efficiency




5.10 Cellular - Average Gain



5.11 Cellular - Peak Gain





5.12 Isolation





6. Radiation Patterns

6.1 Test Setup




Chamber Test Setup on 2mm ABS


6.2 GNSS Patterns at 1525 MHz




6.3 GNSS Patterns at 1561 MHz




XZ Plane




YZ Plane




XY Plane




6.4 GNSS Patterns at 1575 MHz




XZ Plane




YZ Plane




XY Plane




6.5 GNSS Patterns at 1602 MHz




XZ Plane





YZ Plane




XY Plane




6.6 Cellular Patterns at 652 MHz




6.7 Cellular Patterns at 751 MHz




XZ Plane




YZ Plane




XY Plane




6.8 Cellular Patterns at 890 MHz




XZ Plane




YZ Plane




XY Plane




6.9 Cellular Patterns at 1475 MHz




XZ Plane




YZ Plane




XY Plane




6.10 Cellular Patterns at 1930 MHz




XZ Plane




YZ Plane




XY Plane




6.11 Cellular Patterns at 2496 MHz




XZ Plane




YZ Plane




XY Plane




6.12 Cellular Patterns at 4200 MHz




XZ Plane




YZ Plane




XY Plane




6.13 Cellular Patterns at 5550 MHz




XZ Plane




YZ Plane




XY Plane




6.14 Cellular Patterns at 6525 MHz




XZ Plane



YZ Plane



XY Plane



Changelog for the datasheet

SPE-25-8-273 - PC301.A.001

Revision: A (Original First Release)	
Date:	2025-10-07
Notes:	Initial Release
Author:	Gary West

Previous Revisions

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Taoglas](#) manufacturer:

Other Similar products are found below :

[930-033-R](#) [A09-F8NF-M](#) [108-00016-050](#) [W1049B090](#) [WTL2449CQ1-FRSMM](#) [0600-00060](#) [GD53-25](#) [S9025PLSMF](#) [GPSCPMM00](#) [ANT-WP868SMA-Y](#) [CBNC58](#) [MD10-004](#) [ABFT](#) [LP800NMOW](#) [NMOQ88C](#) [NMOQB](#) [NMOQC](#) [ANT-GSMGPSPUKS](#) [60210](#) [60140](#) [ANT-8WPIG-UFL](#) [ANT-GPSPUKS](#) [A21H0](#) [29000863](#) [EXD450TN](#) [2.4GHz 2dBi-1.13-L=50mm](#) [3E0702BK-005](#) [22100003](#) [DL-T022-2.4G](#) [DL-T023-4G](#) [T1-915M](#) [DL-T021-2.4GW](#) [DL-T021-2.4G](#) [KH-IPEX-1.13](#) [BWGNSCNX16-6B1Y2L120](#) [BWGNSCNX15-15B1Y4L120](#) [DL-T023-4GW](#) [3N0401LG-021](#) [KHA\(RG1.13\)-TX90B-IPEX](#) [KHA\(RG1.13\)-TX80B-IPEX](#) [KH-137-TX90B-IPEX4](#) [KH-113-TX100B-IPEX4](#) [KH-113-TX60B-IPEX4](#) [KH-081-TX300-IPEX](#) [3K0001BK00-001](#) [3K0001BK00-002](#) [3N0401LG-038](#) [3N0401BK-049](#) [PRO-OB-440](#) [DL-F8-5G](#)