

## Features

- Operate from 2.0V to 6.0V
- Same electrical characteristics as 74HC Series
- $|IOH| = IOL = 2mA$  (min)
- SOT23-5 Package Available


## General Description

ELM7S86 are CMOS 2-input EXOR gate ICs. They realize a high speed operation similar to LS TTL with a lower power consumption by CMOS features. An inner circuit structure of 3-stages logic gates obtains a wider noise immunity and a constant output.

## Ordering Information

ORDER NUMBER	PACKAGE DESCRIPTION	PACKAGE OPTION	Marking
NC7S86M5X	SOT23-5	Tape and Reel,3000	7S86F
NC7S86P5X	SOT353	Tape and Reel,3000	S86Z

## Pin Configuration



## Function Table

INPUT(B)	INPUT(A)	OUTPUT(X)
L	L	L
H	L	H
L	H	H
H	H	L

Note:H: HIGH voltage level;L: LOW voltage level.

## Absolute Maximum Ratings

PARAMETER	SYMBOL	CONDITIONS	RATINGS	UNIT
Supply Voltage	Vcc		-0.5 ~ +7	V
Input Voltage	VIN		-0.5 ~ VCC+0.5	V
Output Voltage	VOUT	Output in the Power-off state	-0.5 ~ VCC+0.5	V
		Output in the High or Low state	-0.5 ~ VCC+0.5	V
VCC / GND Current	ICC,IGND		±25	mA
Continuous Output Current	IOUT	VOUT=0~Vcc	±25	mA
Input Clamp Current	IIK	VIN<0	±20	mA
Output Clamp Current	IOK	VOUT<0	±20	mA
Storage Temperature Range	TSTG		-65 ~ +150	°C
Power Dissipation	PD	SOT-23-5	200	mW

## Recommended Operating Conditions


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	Vcc	Operating	2	--	6.0	V
Input Voltage	VIN		0	--	VCC	V
Output Voltage	VOUT		0	--	VCC	V
High-input,Down-time	Tr,tf	VCC=2.0V	0	--	1000	ns
		VCC=4.5V	0	--	500	ns
		VCC=6.0V	0	--	400	ns
High-Output,Down-time	tTLH	Refer to following test circuit CL=15pF,tr=tf=6ns,VCC=5V	--	7	10	ns
	tTHL		--	7	10	ns
Propagation,Down-time	tPLH		--	9	20	ns
	tPHL		--	9	20	ns
Operating Temperature	TOP		-40	--	+85	°C

**Electrical Characteristics** (TA =25°C, unless otherwise specified)

PARAMETER	SYM BOLt PLH	TEST Conditions	TA=25°C			TA=-40°C~+125°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
High-Level Input Voltage	VIH	Vcc=2.0V	1.5	--	--	1.5	--	--	V
		Vcc=4.5V	3.15	--	--	3.15	--	--	V
		Vcc=6.0V	4.2	--	--	4.2	--	--	V
Low-Level Input Voltage	VIL	Vcc=2.0V	--	--	0.5	--	--	0.5	V
		Vcc=4.5V	--	--	1.35	--	--	1.35	V
		Vcc=6.0V	--	--	1.8	--	--	1.8	V
High-Level Output Voltage	VOH	Vcc=2.0V, IOH=-20µA	1.9	2.0	--	1.9	--	--	V
		Vcc=4.5V, IOH=-20µA	4.4	4.5	--	4.4	--	--	V
		Vcc=6.0V, IOH=-20µA	5.9	6.0	--	5.9	--	--	V
		Vcc=4.5V, IOH=-2mA	4.18	4.31	--	4.13	--	--	V
		Vcc=6.0V, IOH=-2.6mA	5.68	5.80	--	5.63	--	--	V
Low-Level Output Voltage	VOL	Vcc=2.0V, IOH=20µA	--	0.0	0.1	--	--	0.1	V
		Vcc=4.5V, IOH=20µA	--	0.0	0.1	--	--	0.1	V
		Vcc=6.0V, IOH=20µA	--	0.0	0.1	--	--	0.1	V
		Vcc=4.5V, IOH=2mA	--	0.17	0.26	--	--	0.33	V
		Vcc=6.0V, IOH=2.6mA	--	0.18	0.26	--	--	0.33	V
Input Current	IIN	VCC=6V, VIN=VCC or GND	--	±0.1	±0.1	--	±0.1	±1.0	uA
Static Current	Icc	VCC=6V, VIN=VCC or GND	--	--	1.0	--	--	10	uA
High-Output, Down-time (CL=50PF, tr=tf=6ns) Refer to test circuit	tTLH	Vcc=2.0V, Refer to test circuit	--	50	125	--	--	155	ns
		Vcc=4.5V, Refer to test circuit	--	14	25	--	--	31	ns
		Vcc=6.0V, Refer to test circuit	--	12	21	--	--	26	ns
	tTHL	Vcc=2.0V, Refer to test circuit	--	50	125	--	--	155	ns
		Vcc=4.5V, Refer to test circuit	--	14	25	--	--	31	ns
		Vcc=6.0V, Refer to test circuit	--	12	21	--	--	26	ns
Propagation, Down-time (CL=50PF, tr=tf=6ns)	tPLH	Vcc=2.0V, Refer to test circuit	--	60	135	--	--	170	ns
		Vcc=4.5V, Refer to test circuit	--	16	27	--	--	34	ns
		Vcc=6.0V, Refer to test circuit	--	10	22	--	--	28	ns
	tPHL	Vcc=2.0V, Refer to test circuit	--	60	135	--	--	170	ns
		Vcc=4.5V, Refer to test circuit	--	16	27	--	--	34	ns
		Vcc=6.0V, Refer to test circuit	--	10	22	--	--	28	ns
Input Capacitance	CIN		--	5	10	--	--	10	pF
Equivalent Inner Capacity	CPD		--	10	--	--	--	--	pF


## TEST CIRCUIT AND WAVEFORMS

### TEST CIRCUIT






\* Output should be opened when measuring current consumption.

### MEASURED WAVE PATTERN




### Package information

SOT23-5 (Unit: mm)




### Mounting Pad Layout (Unit: mm)




### Package information

SOT353 (Unit: mm)



### Mounting Pad Layout (unit: mm)



# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Logic Gates category:***

***Click to view products by TECH PUBLIC manufacturer:***

Other Similar products are found below :

[74HC85N](#) [NL17SG32DFT2G](#) [CD4068BE](#) [NL17SG86DFT2G](#) [NLX1G11AMUTCG](#) [NLX1G97MUTCG](#) [74LS38](#) [74LVC1G08Z-7](#)  
[CD4025BE](#) [NLV17SZ00DFT2G](#) [NLV17SZ126DFT2G](#) [NLV27WZ17DFT2G](#) [NLV74HC02ADR2G](#) [74HC32S14-13](#) [74LS133](#)  
[74LVC1G32Z-7](#) [74LVC1G86Z-7](#) [NLV74HC14ADR2G](#) [NLV74HC20ADR2G](#) [NLVVHC1G09DFT1G](#) [NLX2G86MUTCG](#)  
[74LVC2G32RA3-7](#) [74LVC2G00HD4-7](#) [NL17SG02P5T5G](#) [74LVC2G86HK3-7](#) [NLVVHC1G14DFT2G](#) [NLX1G99DMUTWG](#)  
[NLVVHC1G00DFT2G](#) [NLV7SZ57DFT2G](#) [NLV74VHC04DTR2G](#) [NLV27WZ00USG](#) [NLU1G86CMUTCG](#) [NLU1G08CMUTCG](#)  
[NL17SZ32P5T5G](#) [NL17SZ00P5T5G](#) [NL17SH02P5T5G](#) [74AUP2G00RA3-7](#) [NLVVHC1GT00DFT2G](#) [NLV74HC02ADTR2G](#)  
[NLX1G332CMUTCG](#) [NLVHCT132ADTR2G](#) [NL17SG86P5T5G](#) [NL17SZ05P5T5G](#) [NLV74VHC00DTR2G](#) [NLVVHC1G02DFT1G](#)  
[NLV74HC86ADR2G](#) [74LVC2G32HK3-7](#) [74LVC2G86RA3-7](#) [NL17SZ38DBVT1G](#) [NLV18SZ00DFT2G](#)