

REVISIONS

- NOTES:
1. MATERIAL:
 - 1.1 HOUSING: HALOGEN FREE PLASTIC,UL94V-0.
 - 1.2 CONTACT: COPPER ALLOY
 - 2.FINISH:
 - TYPE A: CONTACT: 50U" MIN. NICKEL UNDER PLATING OVERALL
100U" MIN. MATTE TIN PLATING ON CONTACT AREA AND SOLDER AREA.
 - TYPE B: CONTACT: 50U" MIN. NICKEL UNDER PLATING OVERALL
GOLD FLASH PLATING ON CONTACT AREA AND SOLDER AREA.
 3. REFLOW SOLDER CAPABLE TO 260°C, PER PRODUCTION SPEC.



RECOMMENDED PCB LAYOUT FOR *-2380320-*

TOLERANCE ± 0.05




SEC. A-A


REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

POS. NO	DIM A	DIM B	DIM C	DIM D
2	2.30	4.60	7.50	16.00
3	3.80	6.10		
4	5.30	7.60		



- NOTES:
1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE:±0.20mm
 2. CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
 3. ALL DIMENSIONS MEET EIA-481-C REQUIREMENTS.
 4. MATERIAL: BLACK ANTI-STATIC POLYSTYRENE.
 5. THICKNESS: 0.40±0.05 mm.
 6. PACKING LENGHT PER 13” REEL : 12.4 METERS.
 7. COMPONENT LOAD PER 13” REEL : 950 PCS.
 8. PRODUCTS PLACEMENT MUST BE IN THE SAME DIRECTION.



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Jone Ji 23SEP2020	 TE Connectivity Ltd.		
DIMENSIONS: mm		CHK Wenke He			
		APVD Wenke He	NAME 1.5P WTB VERTICAL TYPE WITH LATCH		
		PRODUCT SPEC			
MATERIAL SEE NOTE		FINISH	SIZE A3		
			CAGE CODE 00779		
			DRAWING NO C-2380320		
			RESTRICTED TO		
			SCALE N/A		
			SHEET 2 of 5		
			REV A		
			CUSTOMER DRAWING		

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

D

D

C

C

B


B

A

A

POS. NO	DIM A	DIM B	DIM C	DIM D
5	6. 80	9. 10	11. 5	24
6	8. 30	10. 60		
7	9. 80	12. 10		
8	11. 30	13. 60		
9	12. 80	15. 10		

- NOTES:
- 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE:±0.20mm
 - CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
 - ALL DIMENSIONS MEET EIA-481-C REQUIREMENTS.
 - MATERIAL: BLACK ANTI-STATIC POLYSTYRENE.
 - THICKNESS: 0.40±0.05 mm.
 - PACKING LENGHT PER 13” REEL : 12.4 METERS.
 - COMPONENT LOAD PER 13” REEL : 950 PCS.
 - PRODUCTS PLACEMENT MUST BE IN THE SAME DIRECTION.



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Jone Ji 23SEP2020	TE Connectivity Ltd.		
DIMENSIONS: mm		CHK Wenke He			
		APVD Wenke He	NAME 1.5P WTB VERTICAL TYPE WITH LATCH		
		PRODUCT SPEC —	—		
MATERIAL SEE NOTE		APPLICATION SPEC —	SIZE A3	CAGE CODE 00779	DRAWING NO C-2380320
		WEIGHT —	RESTRICTED TO —		—
		CUSTOMER DRAWING	SCALE N/A	SHEET 3 of 5	REV A

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

POS. NO	DIM A	DIM B	DIM C	DIM D	DIM S
10	14.3	16.6	14.2	32	28.4
11	15.8	18.1			
12	17.3	19.6			
13	18.8	21.1	20.2	44	40.4
14	20.3	22.6			
15	21.8	24.1			
16	23.3	25.6			
17	24.8	27.1			
18	26.3	28.6			
19	27.8	30.1			
20	29.3	31.6			

- NOTES:
- 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE:±0.20mm
 - CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
 - ALL DIMENSIONS MEET EIA-481-C REQUIREMENTS.
 - MATERIAL: BLACK ANTI-STATIC POLYSTYRENE.
 - THICKNESS: 0.40±0.05 mm.
 - PACKING LENGHT PER 13" REEL : 12.4 METERS.
 - COMPONENT LOAD PER 13" REEL : 950 PCS.
 - PRODUCTS PLACEMENT MUST BE IN THE SAME DIRECTION.

D

C

B







A


D

C


B

A




THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Jone Ji	23SEP2020		TE Connectivity Ltd.			
		CHK Wenke He	—					
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC± 0.5 1 PLC± 0.35 2 PLC± 0.25 3 PLC± 0.15 4 PLC± — ANGLES± 2°	APVD Wenke He	—		NAME 1.5P WTB VERTICAL TYPE WITH LATCH —			
		PRODUCT SPEC —	—					
		APPLICATION SPEC —	—					
MATERIAL SEE NOTE		FINISH —	WEIGHT	SIZE A3		CAGE CODE 00779	DRAWING NO C=2380320	RESTRICTED TO —
CUSTOMER DRAWING			SCALE N/A		SHEET 4 of 5	REV A		

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	—	SEE SHEET 1	—	—	—




POS.NO.	PARTS PER PRIMARY CARTON	PARTS PER REEL	TOTAL REELS PER PRIMARY CARTON
2	15200(PCS)	950(PCS)	16
3	15200(PCS)	950(PCS)	16
4	15200(PCS)	950(PCS)	16
5	10450(PCS)	950(PCS)	11
6	10450(PCS)	950(PCS)	11
7	10450(PCS)	950(PCS)	11
8	10450(PCS)	950(PCS)	11
9	10450(PCS)	950(PCS)	11
10	8550(PCS)	950(PCS)	9
11	8550(PCS)	950(PCS)	9
12	8550(PCS)	950(PCS)	9
13	6650(PCS)	950(PCS)	7
14	6650(PCS)	950(PCS)	7
15	6650(PCS)	950(PCS)	7



NOTE:

1. STAPLES SHOULD ONLY BE USED TO SET UP CARTON
ALL CARTONS CLOSURES MUST BE DONE WITH TAPE.
2. FILL PACKAGING REEL WITH THE QUANTITIES AS INDICATED
IN THE CHART.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Jones Jj		23SEP2020		 TE Connectivity Ltd.									
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK Wenke He		NAME									
		0 PLC ± 0.5		APVD Wenke He		1.5P WTb VERTICAL TYPE WITH LATCH —									
		1 PLC ± 0.35		PRODUCT SPEC —											
		2 PLC ± 0.25		APPLICATION SPEC —		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO			
		3 PLC ± 0.15				A3		00779		C-2380320		—			
		4 PLC ± —													
MATERIAL SEE NOTE		FINISH —		WEIGHT —											
		ANGLES ± 2°													
CUSTOMER DRAWING										SCALE N/A		SHEET 5 of 5		REV A	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) *category:*

Click to view products by [TE Connectivity](#) *manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)