

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

G

14

R3

REVISED PER ECO-11-004587

07APR11

RK

HMR

11.10 MAX  
[.437] WASHER R.

5.00±0.08[.197±.003] DIA  
(FOR #10 STUD)

10.95  
[.431]

DIMPLED SURFACE

BODY

1

SLEEVE

"B" MAX

"A" MAX

AMP  
WIRE RANGE

8 AWG  
STRANDED

FILE  
E13288

8 AWG  
STRANDED

LR7189  
Certified

8 AWG  
STRANDED

1

STAMP AMP 8\* LOCATE APPROX AS SHOWN

2

TONGUE MATERIAL THK 1.02±0.08[.040±.003]

3

SEE TABLE FOR WIRE INSULATION DIA MAX

4

TAPE ITEMS ARE ON 30.48[1.200] CENTERS

|                           |                  |                  |     |              |         |
|---------------------------|------------------|------------------|-----|--------------|---------|
| 9.91<br>[.390]            | 33.99<br>[1.338] | 39.52<br>[1.556] | 100 | LOOSE PC     | 52263-5 |
| 8.38<br>[.330]            | 34.49<br>[1.358] | 40.03<br>[1.576] | 500 | ON TAPE      | 52263-4 |
| 9.14<br>[.360]            | 33.99<br>[1.338] | 39.52<br>[1.556] |     |              | 52263-3 |
| 8.38<br>[.330]            | 34.49<br>[1.358] | 40.03<br>[1.576] |     |              | 52263-2 |
| 9.14<br>[.360]            | 33.99<br>[1.338] | 39.52<br>[1.556] | 100 | LOOSE PC     | 52263-1 |
|                           |                  |                  |     |              | 52263   |
| WIRE<br>INSULATION<br>DIA | "B"              | "A"              | QTY | PACKAGE TYPE | PART NO |

AMP INCORPORATED  
CUSTOMER SERVICE SYSTEMS

MAX RECOMMENDED OPERATING  
TEMPERATURE:  
105° C

FOR ADDITIONAL  
PRODUCT INFORMATION OR  
COPIES OF DRAWINGS  
AND TECHNICAL DOCUMENTS

PRODUCT INFORMATION CENTER  
1-800-522-6752

FOR APPLICATION  
TOOLING INFORMATION

TOOLING ASSISTANCE CENTER  
1-800-722-1111

FOR ORDER ENTRY

1-800-526-5142

VOLTAGE RATING:  
600 V MAX

CIRCULAR MIL AREA:  
6.64-10.54mm²[13,100-20,800]  
STRANDED

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
mm [INCHES]

0 PLC

1 PLC

2 PLC

3 PLC

4 PLC

ANGLES

± -

± -

± 0.20[.008]

± -

± -

± -

MATERIAL

COPPER PER ASTM B-152  
PVC, COLOR: RED

FINISH

TIN PLATE  
PER ASTM-B545

DWN  
S.S. GOULDEN

CHK  
R. HERSEY

APVD  
B. BARE

PRODUCT SPEC  
NOT AVAILABLE

APPLICATION SPEC  
114-2161

WEIGHT  
-

9-29-93

9-29-93

9-29-93

STE

TE Connectivity

NAME  
TERMINAL, RING TONGUE,  
PLASTI-GRIP,  
WIRE SIZE: 8 AWG

SIZE  
A3

CAGE CODE  
00779

DRAWING NO  
C-52263

RESTRICTED TO  
-

CUSTOMER DRAWING

SCALE  
4:1

SHEET  
1 OF 1

REV  
R3

1470-19 (3/11)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for [Terminals](#) category:***

***Click to view products by [TE Connectivity](#) manufacturer:***

Other Similar products are found below :

[00-054007-01074-6](#) [00-054007-70206-1](#) [00-054007-70210-8](#) [00-054007-70217-7](#) [00-054007-70226-9](#) [00-054007-70228-3](#) [00-054007-70248-1](#) [00-054007-70256-6](#) [00-054007-70301-3](#) [00-054007-70316-7](#) [00-054007-49560-4](#) [00-054007-70209-2](#) [00-054007-70225-2](#) [00-054007-70227-6](#) [00-054007-70231-3](#) [00-054007-70241-2](#) [00-054007-70242-9](#) [00-054007-70244-3](#) [00-054007-70246-7](#) [00-054007-70263-4](#) [00-054007-70288-7](#) [00-054007-70290-0](#) [00-054007-70300-6](#) [00-054007-70304-4](#) [01-2065-1-0216](#) [01-2900-1-04412](#) [00581P0075](#) [600TS-10](#) [60205-1](#) [604200-1](#) [605601-1](#) [60598-1-CUT-TAPE](#) [61314-6-C](#) [61810-3](#) [61-S](#) [61-SN](#) [626-0194](#) [62-NBM-A](#) [62-SN](#) [62-SP](#) [63-S](#) [640179-1](#) [M55155/059I03](#) [M55155/079C01](#) [M55155/099H02](#) [M55155/109H01](#) [M55155/109H02](#) [M55155/12XH05](#) [M55155/16XH02](#) [M55155/29-5S](#)