

Agastat

TE Part # 5-1423159-4

TE Internal #: 7012SFX

[View on TE.com >](#)

Relays, Contactors &amp; Switches &gt; Relays &gt; Time Delay Relays

Type of Control: **Knob**Input Voltage: **250 VDC**Contact Current Rating: **10A@240VAC A**Mode of Operation: **On-Delay**Delay Time: **1 – 10 minutes**

## Features

### Product Type Features

|                          |                          |
|--------------------------|--------------------------|
| Product Type             | Relay                    |
| Relay Type               | Time Delay               |
| Product Category         | Electromechanical Relays |
| Magnetic Blow-Out Device | Without                  |

### Configuration Features

|                        |         |
|------------------------|---------|
| Multiple Timing Ranges | Without |
|------------------------|---------|

### Electrical Characteristics

|                  |         |
|------------------|---------|
| Actuating System | DC      |
| Input Voltage    | 250 VDC |

### Contact Features

|                        |                       |
|------------------------|-----------------------|
| Contact Arrangement    | 2 Form C, DPDT, 2 C/O |
| Type of Control        | Knob                  |
| Contact Current Rating | 10A@240VAC A          |
| Delay Time             | 1 – 10 minutes        |

### Termination Features

|                  |                 |
|------------------|-----------------|
| Termination Type | Screw Terminals |
|------------------|-----------------|

### Mechanical Attachment

|               |             |
|---------------|-------------|
| Mounting Type | Panel Mount |
|---------------|-------------|

### Dimensions

|                                      |  |
|--------------------------------------|--|
| Dimensions (L x W x H) (Approximate) | 114.8 x 65.3 x 71.9 mm[4.523 x 2.572 x 2.832 in] |
|--------------------------------------|--|

### Usage Conditions

|                             |             |
|-----------------------------|-------------|
| Operating Temperature Range | -30 – 75 °C |
|-----------------------------|-------------|

### Operation/Application

|                   |  |
|-------------------|--|
| Option            | Hardware and Adjustment for Horizontal Operation |
| Mode of Operation | On-Delay   |

### Other

|                     |      |
|---------------------|------|
| Repeatability (Max) | ±10% |
|---------------------|------|

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|   |  |
|---|--|
| EU RoHS Directive 2011/65/EU                  | Not Compliant  |
| EU ELV Directive 2000/53/EC                   | Not Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2019 (197)<br>Candidate List Declared Against: JAN 2019 (197) |
| Halogen Content                               | Not Yet Reviewed for halogen content   |
| Solder Process Capability                     | Not applicable for solder process capability   |

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## Compatible Parts



TE Part # 2-1423157-4  
7012AK=RLY,STD,ON,2P,  
120VAC,30


## Customers Also Bought



TE Part #55799-1  
TERMINAL,SOLISTRAND  
12-10 8



TE Part #1423155-6  
GPDN=RLY,GEN,PURP,  
125VDC



TE Part #55782-1  
TERMINAL,SOLISTRAND  
12-10 8



TE Part #8-1393101-9  
KRP-11DG-48=KA/KB/KC  
/KR



TE Part #1710731-6  
35kILD-KS9C-w/T-556.5



TE Part #1710737-5  
69kILD-KR9C-w/T-556.5



TE Part #543005-000  
S03-10-R-100HN



TE Part #4-1423159-1  
7012PKLLX=RLY,STD,ON,  
2P,125VDC



TE Part #7-1423164-3  
7022SCM=RLY,STD,OFF,  
2P,250VDC



TE Part #6-1423164-1  
7022PCX=RLY,STD,OFF,  
2P,125VDC

## Documents

### Product Drawings

7012SFX=RLY,STD,ON,2P,250VDC,

English

### Datasheets & Catalog Pages

5-1773450-5\_sec12\_7000

English

7012SFX=RLY,STD,ON,2P,250VDC,

TE Part # 5-1423159-4  
TE Internal #: 7012SFX



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Time Delay & Timing Relays](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[5NO30](#) [614-11B-0A2](#) [614-11B-0A3](#) [614-11B-0A4](#) [614-11B-0A6](#) [614-11B-0A8](#) [614-11C-0A1](#) [614-11C-0A2](#) [614-11C-0A5](#) [614-11Q-0A3](#) [614-11Q-0A6](#) [614-11T-0A3](#) [614-11T-0A6](#) [614-11T-0A7](#) [614-12B-4A1](#) [614-12C-400](#) [614-12Q-400](#) [614-12T-600](#) [614-22T-4A1](#) [614-43B-400](#) [614-43C-100](#) [614-43F-200](#) [614-43Q-0A2](#) [614-43Q-100](#) [614-43Q-600](#) [614-43T-0A9](#) [614-43T-600](#) [614-43U-400](#) [614-43U-4A1](#) [614-43U-6A2](#) [615-21T-200](#) [655-11T-100](#) [655-11U-500](#) [655-12T-300](#) [655-22T-400](#) [655-22T-600](#) [CUA-41-30001](#) [CUA-41-30030](#) [CUA-41-70180](#) [CUA-41-71038](#) [CUA-42-30005](#) [CUA-42-30010](#) [CUA-42-30120](#) [CUA-42-70120](#) [CUA-99-72502](#) [CUC-41-30030](#) [CUF-42-30010](#) [CUH-41-31006](#) [7012AFX](#) [7012GD](#)