

DWTC

Flexible, Dual Wall, Moisture-Proof, Heat-Shrinkable Polyolefin Tubing

Product Facts

- Excellent mechanical strength
- Abrasion resistance
- Excellent optical clarity
- Environmental sealing
- Shrink ratio 4:1
- RoHS compliant



Applications

DWTC is a flexible, heat-shrinkable, dual wall tubing with an integrally bonded meltable adhesive inner liner designed to offer moisture proof encapsulation to a wide variety of substrates. In particular, it adheres well to PVC. Available in clear, DWTC offers excellent clarity for protection of substrates that may need to be inspected during service.

The tough outer jacket gives excellent mechanical strength with a high resistance to splitting. The high-shrink-ratio means that only four sizes are needed to give protection to a full range of irregular shapes with widely varying dimensions.

Installation

Minimum shrink temperature: 60°C [140°F]

Minimum full recovery temperature: 100°C [212°F]

Operating Temperature Range

-55°C to 75°C
[-67°F to 167°F]

Specifications/Approvals

Series	Raychem
DWTC	RK-6204

Available in:	Americas	Europe	Asia Pacific
		■	■

DWTC (Continued)

Product Dimensions

Size	Inside Diameter		Recovered Wall Thickness*	
	Minimum Expanded as Supplied	Maximum Recovered After Heating	Nominal Total Wall After Heating	Nominal Adhesive Wall After Heating
4/1	4.0 [0.158]	1.0 [0.039]	0.8 [0.032]	0.3 [0.012]
8/2	8.0 [0.315]	2.0 [0.079]	0.9 [0.035]	0.3 [0.012]
12/3	12.0 [0.472]	3.0 [0.118]	1.2 [0.047]	0.4 [0.016]
16/4	16.0 [0.630]	4.0 [0.158]	1.5 [0.059]	0.5 [0.020]

*Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard	Clear (-X)
Size selection	Always order the largest size that will shrink snugly over the component to be covered.	
Standard packaging	On spools, in 1.2-meter [4-foot] lengths.	
Ordering description	Specify product name, size and color (for example DWTC-4/1-X-STK).	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[7-1103638-1](#) [1775485-2](#) [1-1393565-8](#) [796136-1](#) [539664-2](#) [5-1814821-1](#) [1-967621-5](#) [504021-1](#) [W57-XA8A4A10-5](#) [172131-1](#) [892583-000](#)
[000859-000](#) [5-690482-4](#) [5745928-2](#) [5745967-2](#) [CRB-48-70060](#) [5767006-7](#) [58061-1](#) [58062-1](#) [58063-2](#) [58079-3](#) [58246-2](#) [583785-000](#)
[58380-2](#) [58436-2](#) [58510-1](#) [58516-1](#) [585435-000](#) [5864-5002-10](#) [586863-000](#) [59170](#) [592165-000](#) [59773-1](#) [004845-000](#) [5J0-1000LG-SIL](#)
[5JO-1000CD-SIL](#) [5R4-SS-PAL](#) [600850-1](#) [0104-201-2402](#) [0113-201-2029](#) [601156-000](#) [603995-2](#) [604200-1](#) [609-1030](#) [609-1441](#) [60AYP6C](#)
[60DCB6](#) [61243C500](#) [6131-207-1158P](#) [6131-207-2358P](#)