


5G COMBO MOBILE SMA ANTENNA



Technical data

Mounting type	M6 Screw or Adhesive
Enclosure material	PC/PC+ABS
UV resistant	✓
Cable length	3000 mm
Weight	400 g
Operating temperature	-40 °C ~ +80 °C
Operating humidity	≤ 90 %
Ingress protection rating	IP67
RoHS compliant	✓

5G mobile MIMO antenna

Frequency range	600 ~ 960, 1427 ~ 2700, 3300 ~ 4200, 4400 ~ 5000 MHz
Polarisation	Linear
Radiation pattern type	Omni-directional
Gain	≤ 4 dBi
V.S.W.R	≤ 2.5
Impedance	50 Ω


Connector type and count 4 x SMA Male

Cable type 4 x LMR100


Radiation patterns

Mobile - 1 Antenna

ELEVATION




AZIMUTH




Mobile - 2 Antenna

ELEVATION




AZIMUTH




Radiation patterns

Mobile - 3 Antenna

ELEVATION




AZIMUTH




Mobile - 4 Antenna


ELEVATION



AZIMUTH



Spatial measurements



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antennas](#) category:

Click to view products by [Teltonika](#) manufacturer:

Other Similar products are found below :

[930-033-R](#) [A09-F8NF-M](#) [108-00016-050](#) [W1049B090](#) [WTL2449CQ1-FRSMM](#) [0600-00060](#) [GD53-25](#) [S9025PLSMF](#) [GPSCPMM00](#) [ANT-WP868SMA-Y](#) [CBNC58](#) [MD10-004](#) [ABFT](#) [LP800NMOW](#) [NMOQ88C](#) [NMOQB](#) [NMOQC](#) [ANT-GSMGPSPUKS](#) [60210](#) [60140](#) [ANT-8WPIG-UFL](#) [ANT-GPSPUKS](#) [A21H0](#) [29000863](#) [EXD450TN](#) [2.4GHz 2dBi-1.13-L=50mm](#) [3E0702BK-005](#) [22100003](#) [DL-T022-2.4G](#) [DL-T023-4G](#) [T1-915M](#) [DL-T021-2.4GW](#) [DL-T021-2.4G](#) [KH-IPEX-1.13](#) [BWGNSCNX16-6B1Y2L120](#) [BWGNSCNX15-15B1Y4L120](#) [DL-T023-4GW](#) [3N0401LG-021](#) [KHA\(RG1.13\)-TX90B-IPEX](#) [KHA\(RG1.13\)-TX80B-IPEX](#) [KH-137-TX90B-IPEX4](#) [KH-113-TX100B-IPEX4](#) [KH-113-TX60B-IPEX4](#) [KH-081-TX300-IPEX](#) [3K0001BK00-001](#) [3K0001BK00-002](#) [3N0401LG-038](#) [3N0401BK-049](#) [PRO-OB-440](#) [DL-F8-5G](#)