

Cat6a 10G Certified Snagless Shielded STP Ethernet Cable (RJ45 M/M), PoE, Blue, 10 ft. (3.05 m)

MODEL NUMBER: N262-010-BL











Highlights

- 10-ft. (3.05 m) Augmented Cat6 (CAT6a) Shielded (STP)
 Snagless Patch Cable, Blue
- 10Gbps Over Copper
- Each cable Fluke® Tested and Verified

Package Includes

• 10-ft. (3.05 m) Cat6a BluePatch Cable

Description

Tripp Lite's N262-010-BL 10-ft. (3.05 m) Blue Augmented Cat6 (Cat6a) Shielded (STP) Snagless patch cable allows 10Gbps data transmission over 4-pair copper. Each Cat6a cable is individually tested and certified on Fluke® test equipment. Snag-free strain relief boot provides the most secure and accurate connections.

Features

- 10-ft. (3.05 m) Blue Cat6a Shielded (STP) Snagless Patch Cable 10Gbps
- 100% FLUKE® tested and certified
- ETL/UL Verified
- Supports IEEE 802.3af and is DTE power compliant
- Backward compatible with all previous 10BaseT generations
- RJ45 plug improves NEXT performance to 650Mhz
- 26AWG, 4-Pair, Stranded PVC cable
- Compatible with T568A and T568B wiring
- Easy disconnect snagless hood
- PoE rated to four times the standard

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332188304 |



| Technology | Cat6a | |
|---------------------------------|----------------------|--|
| PHYSICAL | | |
| Color | Blue | |
| Cable Shielding | STP | |
| Cable Jacket Material | PVC | |
| Cable Jacket Rating | FT4 | |
| Number of Conductors | 4 Pair | |
| Conductor Material | Stranded Copper | |
| Conductor Gauge | 26 AWG | |
| Cable Length (ft.) | 10 | |
| Cable Length (m) | 3 | |
| Cable Length (in.) | 120 | |
| Cable Length (cm) | 304.8 | |
| Shipping Dimensions (hwd / cm) | 22.86 x 17.78 x 1.27 | |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 | |
| Shipping Weight (kg) | 0.15 | |
| Shipping Weight (lbs.) | 0.32 | |
| COMMUNICATIONS | | |
| Bandwidth per TIA Standard | 500 MHz | |
| Maximum Bandwidth as Tested | 600 MHz | |
| Maximum Data Rate | 10Gbps | |
| Network Speed | 10Gbps | |
| IEEE Standards Supported | 802.3at | |
| CONNECTIONS | | |
| Side A - Connector 1 | RJ45 (MALE) | |
| Side B - Connector 1 | RJ45 (MALE) | |
| Connector Type | Molded | |
| Wiring Configuration | EIA/TIA 568B | |
| SPECIAL FEATURES | | |
| IP68 Rated | No | |
| Snagless Connector | Yes | |
| Antibacterial | No | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| STANDARDS & COMPLIANCE | | |
|--|---------------------------|--|
| Certifications | RoHS Compliant | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tripp Lite manufacturer:

Other Similar products are found below:

79-653 N001-015-YW N204-005-BL-UP N001-010-RD U152-003-M M100-006-WH 79-519 79-537 PR40 PV-400FC 152-0199 152-1380

152-2404 P022-015 ISOBAR6 RT-2 3040 SU1500RTXL2U PV1000HF B042-004 INTERNET-OFFICE-280 3251 UL7408-6 ULHC4-15

DG115-SR P006-015 CK-8455-L2 SMART-1400-RM BC PERS300 PS3612 BCPRO600 RS-0615-F RS-0615-R SUINT1000RTXL2U

3310 B078-101-USB-8 SUINT1000LCD2U DCPU1 DWT3270X DWM1742S DDR1327SDD TLM615NC20 TLP806TELTAA PS3612
20HW PDUMV30HV2 OMNIVS800 SMART1500RM2UN SU3000RTXLCD2U P005010 SR14UBDP