

eSATA, SATA-II External Signal Shielded Cable (7Pin/7Pin), 18-in. (45.72 cm)

MODEL NUMBER: P950-18I



Highlights

- Connect your high-speed eSATA device to a eSATA controller
- Support data transfer rates of up to 6Gbps
- Cable is double-shielded to protect against EMI/RFI

System Requirements

- eSATA Device
- eSATA Controller

Features

- Connect your high-speed eSATA device to an eSATA controller
- Support data transfer rates of up to 6Gbps
- 18" Cable is double-shielded to protect against EMI/RFI
- RoHS Compliant

Specifications

OVERVIEW	
UPC Code	037332130952
Technology	SATA/eSATA
PHYSICAL	
Color	Blue
Cable Length (ft.)	1.5
Cable Length (m)	0.5
Cable Length (in.)	18
Cable Length (cm)	45.72
Shipping Dimensions (hwd / cm)	0.64 x 15.24 x 15.24
Shipping Dimensions (hwd / in.)	0.25 x 6.00 x 6.00
Shipping Weight (kg)	0.05



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Shipping Weight (lbs.)	0.10
CONNECTIONS	
Side A - Connector 1	7 PIN ESATA (MALE)
Side B - Connector 1	7 PIN ESATA (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Computer Cables](#) category:

Click to view products by [Tripp Lite](#) manufacturer:

Other Similar products are found below :

[68809-0004](#) [8F36-AAA105-1.00](#) [IB63](#) [IB68](#) [CBK-11-290K-00](#) [ACL-10568-5](#) [419-2083-202](#) [427522400-3](#) [IB76](#) [CB-3PSATA-RS](#)
[426091300-3](#) [48000023](#) [10114976-P015002LF](#) [88761-6101](#) [NT631C-CN321-EU](#) [1700009397](#) [MIKROE-2092](#) [PCL-10488-2E](#) [1700009405](#)
[PS/2 Cable](#) [NT31C-CN323-EU](#) [FWAX-PK1-51](#) [68801-1905](#) [SATA Power to B4P cable](#) [68801-0630](#) [68801-3612](#) [68801-3618](#) [205058-1002](#)
[PS2NK](#) [820153-R12](#) [FCB-3235-UAS](#) [821016](#) [SATA cable](#) [96021-0000-00-0](#) [RS-CBL-OC-2MSAS](#) [0685610020](#) [0745063002](#) [0745460813](#)
[0745461605](#) [0745470304](#) [0887505318](#) [0887511310](#) [0DT60002](#) [C-PS2WG/5](#) [C-PS2WW/2](#) [C-PS2WW/3](#) [73220861](#) [CV0002](#) [CV0005](#)
[CV0006](#)