


# 24-Outlet Vertical Power Strip, 120V, 15A, 5-15P, 15 ft. (4.57 m) Cord, 72 in.

MODEL NUMBER: PS7224











#### **Highlights**

- 24 outlets
- Convenient and safe covered, on/off switch
- 15-amp circuit breaker
- 15-ft. (4.57 m) cord
- 72" length

#### **Package Includes**

- PS7224
- · Mounting hardware
- Instruction manual

### Description

Tripp Lite's PS7224 power strip offers 15 amp, 120V multi-outlet AC power distribution in a convenient 72 inch mountable housing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications. Includes 24 NEMA 5-15R output receptacles with 2.795 inch center-to-center spacing, 15-ft. (4.57 m) AC line cord and lighted power switch with locking transparent cover to prevent accidental shutoff. Sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 24 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: 72 in. corded, mountable power strip

#### **Features**

- Sturdy all-metal 72 inch corded strip format with 2.795 inch center-to-center outlet spacing
- Included mounting hardware
- Includes 24 NEMA 5-15R output receptacles
- Lighted power switch with locking transparent cover prevents accidental shutoff
- 15 amp electrical capacity with circuit breaker
- 120VAC, 50/60Hz electrical compatibility

## **Specifications**

OVERVIEW	
UPC Code	037332011480



INPUT	INDIT		
Nominal Input Voltage(s) Supported	120V AC		
Recommended Electrical Service	15A 120V		
Input Cord Gauge Type	14 gauge; SJT		
Voltage Compatibility (VAC)	120		
Input Plug Type	NEMA 5-15P		
Input Cord Length (ft.)	15		
Input Cord Length (m)	4.57		
Integrated Cord Clip	No		
OUTPUT			
Frequency Compatibility	50 / 60 Hz		
Output (Watts)	1800		
Output Receptacles	(24) 5-15R		
Circuit Breaker (amps)	15		
Transformer Accommodation	(12) Yes		
Right-Angle Outlets	No		
Outlet Spacing	2.795 in.		
USER INTERFACE, ALERTS & CONTROLS			
Switches	Lighted 2 position switch controls power to all outlets		
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off		
PHYSICAL			
Color	Silver		
Antimicrobial Coating	No		
Power Cord Color	Black		
Form Factors Supported	Supports horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications		
Housing Color	Silver		
Included Mounting Accessories	Includes mounting clips		
Integrated Keyhole Mounting Slots	No		
Material of Construction	Aluminum		
Outlets Measurement (Center to Center)	72mm		
Receptacle Color	Black		
Shipping Dimensions (hwd / cm)	7.62 x 5.08 x 193.04		



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Shipping Dimensions (hwd / in.)	3.00 x 2.00 x 76.00	
Shipping Weight (kg)	2.72	
Shipping Weight (lbs.)	6.00	
Unit Dimensions (hwd / cm)	183 x 3.8 x 3.8	
Unit Dimensions (hwd / in.)	72 x 1.5 x 1.5	
Unit Weight (kg)	2.49	
Unit Weight (lbs.)	5.5	
STANDARDS & COMPLIANCE		
Canada	cUL	
UL1363 (Power Tap)	UL1363	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Outlet Strips category:

Click to view products by Tripp Lite manufacturer:

Other Similar products are found below:

G20IG606 1301430288 1301430321 1447B163 UL602CB-6 UL7408-6 ULHC4-15 V20IG606 UL2063BD TSB 4748.03 4309 UL720815 3083 3050F 3090 1301350158 1301350173 3085-10 DAPI-USEU 1583H8B1BKV 1589H77D1JV 1589H77G1JV 1589H8D1BKRRV
1589H8G1BKRRV DTEL2 TLP712B STRIKER TLM825SA UL620-15 3SP 1301370166 130143-0153 1301370216 602 6SP 1584B10
1589H48G1 1589T6D1 1301350185 1301350186 1301350187 1301350197 1301350233 1301350234 1301350201 1301350207
1301350209 1301350211 1301350213