


Dual N-Channel 30-V (D-S) MOSFET with Schottky Diode

| PRODUCT SUMMARY | | | | |
|-----------------|---------------------|----------------------------------|---------------------------------|-----------------------|
| | V _{DS} (V) | R _{DS(on)} (Ω) | I _D (A) ^a | Q _g (Typ.) |
| Channel-1 | 30 | 0.018 at V _{GS} = 10 V | 10 | 6.6 |
| | | 0.023 at V _{GS} = 4.5 V | 8.5 | |
| Channel-2 | | 0.018 at V _{GS} = 10 V | 10.5 | 8.9 |
| | | 0.022 at V _{GS} = 4.5 V | 9.3 | |

| SCHOTTKY PRODUCT SUMMARY | | |
|--------------------------|--|--------------------|
| V _{DS} (V) | V _{SD} (V) Diode Forward Voltage | I _F (A) |
| 30 | 0.50 V at 1.0 A | 2.0 |



Ordering Information: Si4916DY-T1-E3 (Lead (Pb)-free)
Si4916DY-T1-GE3 (Lead (Pb)-free and Halogen-free)

FEATURES


- Halogen-free According to IEC 61249-2-21 Available
- LITTLE FOOT[®] Plus Integrated Schottky
- 100 % R_g Tested

APPLICATIONS

- DC/DC Converters
- Notebook



RoHS
COMPLIANT
HALOGEN
FREE
Available



| ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted | | | | | |
|---|-----------------------------------|------------------------|------------------------|------------------------|-----|
| Parameter | Symbol | Channel-1 | Channel-2 | Unit | |
| Drain-Source Voltage | V _{DS} | 30 | | V | |
| Gate-Source Voltage | V _{GS} | 20 | | | |
| Continuous Drain Current (T _J = 150 °C) ^{a, b} | I _D | T _C = 25 °C | 10 | 10.5 | A |
| | | T _C = 70 °C | 8 | 8.3 | |
| | | T _A = 25 °C | 7.5 ^{a, b, c} | 7.8 ^{a, b, c} | |
| | | T _A = 70 °C | 6 ^{a, b, c} | 6.3 ^{a, b, c} | |
| Pulsed Drain Current (10 μs Pulse Width) | I _{DM} | 40 | 40 | A | |
| Continuous Source-Drain Diode Current | I _S | T _C = 25 °C | 3 | | 3.2 |
| | | T _A = 25 °C | 1.7 ^{a, b, c} | 1.8 ^{a, b, c} | |
| PulseD Source-Drain Current | I _{SM} | 40 | 40 | mJ | |
| Single-Pulse Avalanche Current | I _{AS} | 15 | | | |
| Single-Pulse Avalanche Energy | E _{AS} | 11.2 | | | |
| Maximum Power Dissipation ^{a, b} | P _D | T _C = 25 °C | 3.3 | 3.5 | W |
| | | T _C = 70 °C | 2.1 | 2.2 | |
| | | T _A = 25 °C | 1.9 ^{a, b, c} | 2.0 ^{a, b, c} | |
| | | T _A = 70 °C | 1.2 ^{a, b, c} | 1.3 ^{a, b, c} | |
| Operating Junction and Storage Temperature Range | T _J , T _{stg} | - 55 to 150 | | °C | |

Notes:

a. Based on T_C = 25 °C.

b. Surface Mounted on 1" x 1" FR4 board.

c. t = 10 s.

THERMAL RESISTANCE RATINGS

| Parameter | | Symbol | Channel-1 | | Channel-2 | | Unit |
|--|---------------|------------|-----------|------|-----------|------|------|
| | | | Typ. | Max. | Typ. | Max. | |
| Maximum Junction-to-Ambient ^a | $t \leq 10$ s | R_{thJA} | 54 | 65 | 47 | 60 | °C/W |
| Maximum Junction-to-Foot (Drain) | Steady State | R_{thJF} | 32 | 38 | 30 | 35 | |

Notes:

a. Surface Mounted on 1" x 1" FR4 board.

b. Maximum under Steady State conditions is 112 °C/W for Channel 1 and 107 °C/W for Channel 2.

MOSFET SPECIFICATIONS $T_J = 25$ °C, unless otherwise noted

| Parameter | Symbol | Test Conditions | Min. | Typ. ^a | Max. | Unit | |
|---|-------------------------|---|--------------------------|-------------------|------------|------------|----------|
| Static | | | | | | | |
| Drain-Source Breakdown Voltage | V_{DS} | $V_{GS} = 0$ V, $I_D = 250$ μ A | Ch-1 30 Ch-2 30 | | | V | |
| V_{DS} Temperature Coefficient | $\Delta V_{DS}/T_J$ | $I_D = 250$ μ A | Ch-1 Ch-2 | 24 25 | | mV/°C | |
| $V_{GS(th)}$ Temperature Coefficient | $\Delta V_{GS(th)}/T_J$ | | Ch-1 Ch-2 | -6 -6 | | | V |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS} = V_{GS}$, $I_D = 250$ μ A | Ch-1 Ch-2 | 1.5 1.5 | 3.0 2.7 | | |
| Gate-Body Leakage | I_{GSS} | $V_{DS} = 0$ V, $V_{GS} = 20$ V | Ch-1 Ch-2 | | 100 100 | nA | |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS} = 30$ V, $V_{GS} = 0$ V | Ch-1 Ch-2 | | 1 100 | μ A | |
| | | $V_{DS} = 30$ V, $V_{GS} = 0$ V, $T_J = 85$ °C | Ch-1 Ch-2 | | 15 2000 | | |
| On-State Drain Current ^b | $I_{D(on)}$ | $V_{DS} = 5$ V, $V_{GS} = 10$ V | Ch-1 Ch-2 | 20 20 | | A | |
| Drain-Source On-State Resistance ^b | $R_{DS(on)}$ | $V_{GS} = 10$ V, $I_D = 10$ A | Ch-1 | | 0.0145 | 0.018 | Ω |
| | | $V_{GS} = 10$ V, $I_D = 10.5$ A | Ch-2 | | 0.015 | 0.018 | |
| | | $V_{GS} = 4.5$ V, $I_D = 8.5$ A | Ch-1 | | 0.019 | 0.023 | |
| | | $V_{GS} = 4.5$ V, $I_D = 9.3$ A | Ch-2 | | 0.018 | 0.022 | |
| Forward Transconductance ^b | g_{fs} | $V_{DS} = 15$ V, $I_D = 10$ A | Ch-1 | | 30 | S | |
| | | $V_{DS} = 15$ V, $I_D = 10.5$ A | Ch-2 | | 35 | | |
| Diode Forward Voltage ^b | V_{SD} | $I_S = 1.7$ A, $V_{GS} = 0$ V | Ch-1 | | 0.75 | 1.1 | V |
| | | $I_S = 1$ A, $V_{GS} = 0$ V | Ch-2 | | 0.47 | 0.5 | |
| Dynamic^a | | | | | | | |
| Total Gate Charge | Q_g | Channel-1 $V_{DS} = 15$ V, $V_{GS} = 4.5$ V, $I_D = 10$ A | Ch-1 Ch-2 | | 6.6 8.9 | 10 14 | nC |
| Gate-Source Charge | Q_{gs} | | Ch-1 Ch-2 | | 2.9 3.4 | | |
| Gate-Drain Charge | Q_{gd} | Channel-2 $V_{DS} = 15$ V, $V_{GS} = 4.5$ V, $I_D = -10.5$ A | Ch-1 Ch-2 | | 2.3 2.4 | | |
| | | | Ch-1 Ch-2 | | 0.5 0.5 | 1.9 2.3 | |
| Gate Resistance | R_g | | Ch-1 Ch-2 | | | | Ω |



| MOSFET SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted | | | | | | |
|--|--------------|--|------|-------------------|------|------|
| Parameter | Symbol | Test Conditions | Min. | Typ. ^a | Max. | Unit |
| Dynamic^a | | | | | | |
| Turn-On Delay Time | $t_{d(on)}$ | Channel-1 $V_{DD} = 15\text{ V}$, $R_L = 15\ \Omega$ $I_D \cong 1\text{ A}$, $V_{GEN} = 10\text{ V}$, $R_g = 6\ \Omega$ | Ch-1 | 8 | 15 | ns |
| | | | Ch-2 | 9 | 15 | |
| Rise Time | t_r | | Ch-1 | 11 | 18 | |
| | | | Ch-2 | 13 | 20 | |
| Turn-Off Delay Time | $t_{d(off)}$ | Channel-2 $V_{DD} = 15\text{ V}$, $R_L = 15\ \Omega$ $I_D \cong 1\text{ A}$, $V_{GEN} = 10\text{ V}$, $R_g = 6\ \Omega$ | Ch-1 | 21 | 32 | |
| | | | Ch-2 | 27 | 40 | |
| Fall Time | t_f | | Ch-1 | 6 | 10 | |
| | | | Ch-2 | 9 | 15 | |
| Source-Drain Reverse Recovery Time | t_{rr} | $I_F = 1.3\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$ $I_F = 2.2\text{ A}$, $dI/dt = 100\ \mu\text{A}/\mu\text{s}$ | Ch-1 | 28 | 40 | |
| | | | Ch-2 | 24 | 35 | |
| Body Diode Reverse Recovery Charge | Q_{rr} | $I_F = 1.3\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$ $I_F = 2.2\text{ A}$, $dI/dt = 100\ \mu\text{A}/\mu\text{s}$ | Ch-1 | 17 | | nC |
| | | | Ch-2 | 12 | | |
| Reverse Recovery Fall Time | t_a | $I_F = 1.3\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$ $I_F = 2.2\text{ A}$, $dI/dt = 100\ \mu\text{A}/\mu\text{s}$ | Ch-1 | 12 | | ns |
| | | | Ch-2 | 11 | | |
| Reverse Recovery Rise Time | t_b | $I_F = 1.3\text{ A}$, $dI/dt = 100\text{ A}/\mu\text{s}$ $I_F = 2.2\text{ A}$, $dI/dt = 100\ \mu\text{A}/\mu\text{s}$ | Ch-1 | 16 | | |
| | | | Ch-2 | 13 | | |


Notes:

- a. Guaranteed by design, not subject to production testing.
- b. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$.


| SCHOTTKY SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted | | | | | | |
|--|----------|--|------|-------|-------|------|
| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
| Forward Voltage Drop | V_F | $I_F = 1.0\text{ A}$ | | 0.47 | 0.50 | V |
| | | $I_F = 1.0\text{ A}$, $T_J = 125\text{ }^\circ\text{C}$ | | 0.36 | 0.42 | |
| Maximum Reverse Leakage Current | I_{rm} | $V_R = 30\text{ V}$ | | 0.004 | 0.100 | mA |
| | | $V_R = 30\text{ V}$, $T_J = 100\text{ }^\circ\text{C}$ | | 0.7 | 10 | |
| | | $V_R = -30\text{ V}$, $T_J = 125\text{ }^\circ\text{C}$ | | 3.0 | 20 | |
| Junction Capacitance | C_T | $V_R = 10\text{ V}$ | | 50 | | pF |

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance








Gate Charge





On-Resistance vs. Junction Temperature







CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted








CHANNEL-1 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



CHANNEL-2 TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?74331.


SOIC (NARROW): 8-LEAD

JEDEC Part Number: MS-012



| DIM | MILLIMETERS | | INCHES | |
|--------------------------------|-------------|------|-----------|-------|
| | Min | Max | Min | Max |
| A | 1.35 | 1.75 | 0.053 | 0.069 |
| A ₁ | 0.10 | 0.20 | 0.004 | 0.008 |
| B | 0.35 | 0.51 | 0.014 | 0.020 |
| C | 0.19 | 0.25 | 0.0075 | 0.010 |
| D | 4.80 | 5.00 | 0.189 | 0.196 |
| E | 3.80 | 4.00 | 0.150 | 0.157 |
| e | 1.27 BSC | | 0.050 BSC | |
| H | 5.80 | 6.20 | 0.228 | 0.244 |
| h | 0.25 | 0.50 | 0.010 | 0.020 |
| L | 0.50 | 0.93 | 0.020 | 0.037 |
| q | 0° | 8° | 0° | 8° |
| S | 0.44 | 0.64 | 0.018 | 0.026 |
| ECN: C-06527-Rev. I, 11-Sep-06 | | | | |
| DWG: 5498 | | | | |

RECOMMENDED MINIMUM PADS FOR SO-8



Recommended Minimum Pads
Dimensions in Inches/(mm)

[Return to Index](#)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Vishay](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#) [IRF100S201](#) [JANTX2N5237](#)
[2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#) [2SK1691-DL-E](#) [2SK2545\(Q,T\)](#)
[405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#) [424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#)
[614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#) [IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-](#)
[M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#) [NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#)
[JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#) [2SK2614\(TE16L1,Q\)](#) [2N7002KW-FAI](#) [APT1201R6BVFRG](#)