



CNX 714FV Series 0.551" (14mm) Ruggedized LED FlexVolt™ Panel Mount Indicator



Ruggedized CNX 714FV all-in-one indicator with FlexVolt™ and moisture seal for outdoor applications


Applications

- control cabinets
- instrument panels
- disinfection and sterilization environments
- transportation dashboards
- switch stations
- safety applications
- outdoor signage
- aircraft and military
- industrial machinery
- vending and gaming machines

Key features

- designed for extreme harsh and outdoor environments
- new FlexVolt™ technology allows this indicator to be used with any voltage from 5V to 28V DC
- fast pitch threads for easy assembly, requires 1 turn
- direct sunlight visibility
- wide viewing angle
- resistant to shock and vibration
- custom LEDs and lens colors available
- moisture sealed, IP67/NEMA 6P rated

Product dimensions



Product specifications

Materials	
body	polycarbonate, UL 94-V2
retaining nut	Valox, black UL 94-V0
wire	24 AWG 1007/1569
lens	polycarbonate, UL 94-V2
moisture seal	EPDM
retainer width	1" (25.4mm)

Ordering data

CNX 714FV 14mm indicator ordering code (example) **CNX 714 C XXX FV W**

Body Type	
X	material
C	colored*

*Lens body color to match LED color

LED Color	
XXX	color
200	red
400	soft yellow
401	yellow
500	green
600	blue
900	white

Termination Style	
W	wire leads

Product specifications (cont)

LED output		
LED color	typ intensity (mcd)	I (mA)
red	1300-1900	20
soft yellow	80-200	20
yellow	450-1120	30
green	700-1400	20
blue	280-710	30
white	1300-1700	20

Installation specification	
mounting hole	0.551" (14.0mm)
panel thickness	Up to .250" (6.3mm)
spacing	minimum 1.05" center to center

Operating parameters	
operating temperature	-40°F (-40°C) to 176°F (80°C)

Compliance & approvals



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Panel Mount Indicators](#) category:

Click to view products by [Visual Communications Company](#) manufacturer:

Other Similar products are found below :

[607-3232-140F](#) [821-0331-503](#) [FL2870C8R](#) [FL2950WL7B](#) [FL2950WL8G](#) [FL589WL8R](#) [FL67C8R](#) [H8630FBBA3](#) [NL177WL2A](#)
[NL177WL3G](#) [NL276C2A](#) [NL2950BWL3G](#) [NL589WL2R](#) [NL67C2C](#) [NL67C3R](#) [C480AABG3](#) [PB22BM41K](#) [PB22SIM40Y](#)
[PB22SKRS31KC](#) [L32R-R2-2311](#) [L3353-MWRG](#) [L39UR-R24-2111](#) [L58D-G2-W](#) [L58D-Y2-W](#) [L59D-R12-W](#) [L59UD-R12-W](#) [L625DG](#)
[L625DR](#) [LE177WL39007](#) [LE2821H5G](#) [LH1048BSWL3702](#) [LH1048BWL3702](#) [LH382A](#) [LH677G](#) [LHM628A](#) [FL276WL7R](#)
[FL2950BWL7R](#) [FL2950WL7R](#) [FL2950WL8R](#) [FL2950WL8R-12](#) [FL2951WL8G](#) [FL2951WL8R](#) [FL589C7R](#) [FL67WL8G](#) [MPC5BCW18.0](#)
[556-1605-808F](#) [556-1705-809F](#) [556-3008-839F](#) [558-0201-818F](#) [559-0001-813F](#)