


Male Headers with Solder and Press-In Pins, MCS-MIDI

Pin Spacing: 3.5 mm, 3.81 mm

MCS MINI




- Male headers may be mounted horizontally or vertically via straight or angled solder pins
- 1 x 1 mm pin cross section (MCS MINI) allows a nominal current of 10 A
- Double-deck male headers save space on the PCB, providing a large number of “wire-to-board” connections
- 100% protected against mismatching
- Coding pins available

Technical data:	Press-in technology:						Double-deck version:		
Pin Spacing	3.5/3.81 mm 0.138 in.			3.5/3.81 mm 0.138 in.			3.5/3.81 mm 0.138 in.		
Ratings per	IEC/EN 60664-1			IEC/EN 60664-1			IEC/EN 60664-1		
Overvoltage category	III	III	II	III	III	II	III	III	II
Pollution degree	3	2	2	3	2	2	3	2	2
Rated voltage	160 V	160 V	320 V	160 V	160 V	320 V	160 V	160 V	320 V
Rated surge voltage	2.5 kV	2.5 kV	2.5 kV	2.5 kV	2.5 kV	2.5 kV	2.5 kV	2.5 kV	2.5 kV
Nominal current	10 A	10 A	10 A	8 A	8 A	8 A	10 A	10 A	10 A
Approvals per	UL/CSA			UL/CSA			UL/CSA		
Use group UL 1059	B	C	D	B	C	D	B	C	D
Rated voltage	300 V	–	300 V	300 V	–	300 V	300 V	–	300 V
Nominal current UL	10 A	–	10 A	10 A	–	10 A	10 A	–	10 A
Nominal current CSA	10 A	–	10 A	10 A	–	10 A	10 A	–	10 A

Solder and press-in pin data:	
Solder pin: length/width	4.5 mm / 1 x 1 mm (straight)
Solder pin: length/width	3.8 mm / 1 x 1 mm (angled)
Solder pin: length/width	3.6 mm / 1 x 1 mm (double-deck male headers)
Solder pin: drilled hole diameter	1.4 ^{+0.1} mm
Press-in pin: length/width	2.9 mm / 0.6 x 1.2 mm
Press-in pin: drilled hole diameter	1,15 ^{±0.025}
Press-in pin: metal-plated hole	1.0 Ø ^{+0.09} _{-0.08} mm (HAL Sn)
Press-in pin: metal-plated hole	1.0 Ø ^{+0.09} _{-0.08} mm (Chem. Sn)
For other pin lengths, please contact factory.	

Material data:	
Material group	I
Insulating material	Polyamide 66 (PA 66)
Flammability class per UL 94	V0
Lower/Upper limit temperature	-60 °C / +100 °C / Press-in pin: -40 °C / +85 °C
Contact material	Electrolytic copper (E _{cu}) / Copper alloy for press-in technology
Contact plating	tin-plated
MCS connectors are also available upon request with gold-plated or partially gold-plated contact surfaces.	
Depending on the version requested, “item no. suffix . . . /010-000” is added to the “basic item no.”	



MCS MINI accessory:	Page:
Coding keys	273

The *MULTI CONNECTION SYSTEM* (MCS) is designed without breaking capacity for compliance with DIN EN 61984. When used as intended, these connectors shall not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [wago](#) manufacturer:

Other Similar products are found below :

[750-460](#) [231-118/026-000](#) [231-303/026-000](#) [231-620/019-000](#) [257-403](#) [280-438](#) [280-831](#) [284-624](#) [210-111](#) [231-303/037-000](#) [231-446/001-000_NR](#) [232-216/026-000](#) [234-510](#) [264-726](#) [280-339](#) [0283-0671](#) [830-800/000-305](#) [750-512](#) [750-455](#) [51251782](#) [286-312](#) [713-1428/107-000](#) [731-138/048-000](#) [750-459](#) [750-517](#) [793-3505](#) [826-172](#) [859-304](#) [280-335](#) [231-535/001-000](#) [2604-1106](#) [2604-1504](#) [2606-1103/020-000](#) [2624-1103](#) [2626-3103/020-000](#) [821-104](#) [713-1107](#) [852-1411](#) [2106-1307](#) [2116-5307](#) [832-1205](#) [832-3604](#) [2009-110](#) [281-512/281-501](#) [286-336](#) [750-421](#) [750-838](#) [753-559](#) [750-1505](#) [787-732](#)