Wera

Be a Tool Rebel

The Catalogue



Content

Screwdrivers



Kraftform Stainless Steel	20
Kraftform Plus - Series 900	26
Kraftform Plus - Series 300	32
Kraftform Series Comfort	52
Wooden Handle Series	58
Flagdriver Series	61
Screwdriving Accessories	62
Kraftform Micro Series	64
400 T-Handle Series	74
ESD Tools	80

VDE Tools



Kraftform Stainless VDE	88
Kraftform 100 VDE	92
Kraftform Kompakt VDE	106
Kraftform Comfort VDE	120
The Zyklop VDE Ratchet and accessories	124

Ratchets



1/4" Zyklop Speed	144
1/4" Zyklop Metal Push	152
1/4" Zyklop Metal Switch	154
1/4" Zyklop Accessories	156
3/8" Zyklop Speed	172
3/8" Zyklop Metal Push	176
3/8" Zyklop Metal Switch	178
3/8" Zyklop Accessories	180
1/2" Zyklop Speed	190
1/2" Zyklop Hybrid	194
1/2" Zyklop Metal Push	198
1/2" Zyklop Metal Switch	200
1/2" Zyklop Accessories	202
1/2" Koloss	210
Zyklop Mini 1 & 2	214

Joker Combination Ratchet Wrenches



Joker Ratcheting Combination Wrenches	228
Joker Switch Ratcheting Combination Wrenches	230

L-Keys



L-Keys for Hexagon Socket Screws	238
L-Keys for TORX® Screws	250
Offset Screwdrivers	257

Kraftform Kompakt



Kraftform Kompakt 10, 12	262
Kraftform Kompakt 20, 22, 25, 26, 28	264
Kraftform Kompakt 40, 41	268
Kraftform Kompakt 50	269
Kraftform Kompakt 60, 62	270
Kraftform Kompakt 70, 71	276
Kraftform Kompakt 100	278
Kraftform Kompakt User-Specific Sets	280
Bitholding Screwdrivers And Adaptors	284
Kraftform Kompakt Vario With Ratchet Function	288
Kraftform Kompakt Vario Without Ratchet Function	292

Wera 2go



Wera 2go 1 Tool Carrier	300
Wera 2go 2 Tool Container	300
Wera 2go 3 Tool Box	300
Wera 2go 4 Tool Quiver	300
Wera 2go 5 Tool Carrier	301
Wera 2go 6 Shoulder Strap	301
Hook and Loop Fastener Strips	303

Bits



Bits For Phillips Screws 316
Bits For Pozidriv Screws 338
Bits For Plusminus Screws – Slotted/Phillips 350
Bits For Plusminus Screws – Slotted/Pozidriv 351
Bits For TORX® Screws 352
Bits For TORX® BO Screws 366
Bits For TORX PLUS® Screws 368
Bits For TORX PLUS® IPR Screws 372
Bits For ASSY® Screws 375
Bits For Slotted Screws Guide Sleeves 376
Bits For Hexagon Socket Screws 380
Bits For Hexagon Socket BO Screws 387
Bits For Square Socket Screws 388
Bits For TORQ-SET® Screws 392
Bits For TRI-WING® Screws 395
Bits For Multi-Point Screws 396
Bits For Hi-TORQUE Screws 397
Bits For Microstix® Screws 398
Bits For Spanner Screws 400
Nutsetters 401
Internal Thread Insertion Tool 403

Holder and Adaptors



Impaktor Bit Holders 410
Rapidaptor Bit Holders 414
BiTorsion Bit Holders With Quick-Release Chuck 418
Universal Bit Holders With Quick-Release Chuck 419
Universal Bit Holders With Retaining Ring 421
Universal Bit Holders With Stainless Steal Sleeve 422
Universal Bit Holders With Copper Beryllium Sleeve 424
Bit Holders With adjustable Depth-Control Stop 425
Adaptors 426

Bit Sets



Bit-Checks Impaktor 434
Bit-Checks Stainless 438
Bit-Checks / Bit-Safes BiTorsion 440
Bit-Checks Diamond 444
Bit-Checks / Bit-Safes Universal 448
Bit-Checks Wood 458
Bit-Checks Metal 460
Bit Sets For Special Applications 461

Torque Tools



Series 7400 Adjustable 470
Series 7400 Pre-Set 478
Series Torque-indicators 484
Series Click-Torque 490
Series Insert Tools 502

Impact Driver and Soft-faced Hammers



Impact Driver 90 Nm 510
Soft Faced Hammers 512

TechLex

Technical Compendium 516
Code No. Index 526
Article No. Index 540
Alphabetical Index 551

Tool Findex

Tool / Tip type	Stainless	Series 900	Series 300	Series Comfort	Wooden Series	Micro Series	400 T-Handle Series	VDE	ESD	Ratchets	L-Keys	Kraftform Kompakt	Impact Drivers	Joker
Phillips	22, 24, 25	28, 30	36, 45, 46, 48, 49, 50	54, 56	60	66, 70, 71, 72		90, 91, 95, 96, 102	80, 81	144ff	257	264ff		
Pozidriv	22, 24, 25	29, 30, 31	36, 45, 46, 48, 49, 50	54, 56	60	66, 70		90, 91, 95, 96, 102, 103	80	144ff	257	264ff		
PlusMinus Phillips								97						
PlusMinus Pozidriv								98, 102						
TORX® TORX® BO	23	29, 31	38, 39, 40, 45, 50, 51	55		66, 67, 73	76	99, 102, 103	80	144ff	250-256	264ff		
TORX® ZA														
TORX PLUS®			40											
TORX PLUS® IPR						68, 72			80					
ASSY®														
Slotted	22, 24, 25	28, 30, 31, 45, 46	34, 35, 45, 48, 49, 50	54, 56	60	66, 70, 71, 72		45, 46, 90, 91, 94, 102	80, 81		257	264ff		
Hexagon Socket			38			68, 72	76			148ff	238-249	270		
Hexagon Socket BO														
Square Socket	23		41, 46, 51					100				266, 271, 272		
TORQ - SET®			40									273, 276		
TRI - WING®			42									273, 276		
Multi-Point														
HTN														
Microstix®						68			82					
Spanner												273, 276		
External Hex			42, 43, 51			69, 73	77	100, 126, 127	82	144ff				228-232

Your guide to getting the best tools for the job.

 ¼"	 5/16"	 ¼"	 7/16"	 4 mm	 M4	 M5	 M6	 NF2A	 4 mm	 5 mm	 ¼"	 5/16"	Tool / Tip type
316-325	332	326-331		335	333	333	334	334	335	336	332	336	Phillips
338-343	348	344-348			348	349	349						Pozidriv
		350											PlusMinus Phillips
		350											PlusMinus Pozidriv
352-357, 366	361	358-360, 367		364	362	362	363	363	364	365			TORX® TORX® BO
													TORX® ZA
				370					370	370			TORX PLUS®
372		369, 373		373					373				TORX PLUS® IPR
375													ASSY®
376-377	379	378											Slotted
380-381	385	382-384		386									Hexagon Socket
387		387											Hexagon Socket BO
388-389	390-391												Square Socket
392	394	393	394										TORQ - SET®
395	395	395											TRI - WING®
396		396											Multi-Point
397													HTN
				398					398				Microstix®
400		400											Spanner
		401,402							402				External Hex


were
BE A
TOOL
REBEL

What we believe in ...

We believe in challenging the standard
We believe in thinking in a rebellious way
We believe in Rock´n´Roll
We love to be Tool Rebels

The way we challenge the standard is …
by making the experience for our users …
easier, safer and full of joy.

We simply create great tools for rebels.

Be a Tool Rebel



Wera Tools

Passionate staff and a considerable degree of vertical manufacturing integration ensure an unmatched level of tool know-how.




Logistics Center Wera Werkzeuge GmbH, Wuppertal











Production plant, Wera Werk Bystřice









Great Tools for Rebels

Kraftform Micro
Precision engineering made easy.



BiTorsion
Bits and holder live longer.







Zyklop Mini
Whenever space is tight.



Kraftform Kompakt
Big content, small size.

Kraftform
Ergonomics you can grasp.

The Chiseldriver
More than just screwdriving.

Zyklop Speed
A really fast mover.



Joker
With an amazing holding function.

Koloss
Ratchet and hammer.


Lasertip
No more slips when screwdriving.

Great Tools for Rebels

Bit-Check
Everything at a glance. Always to hand.



Tools in textile boxes
Small size and low weight for simpler mobility.





Rapidaptor
More rapid bit change.

Kraftform Kompakt 20
Getting a handle on things.



Diamond-coated Bits
Bits with “bite”.



Impaktor Bits
For extreme situations.



Hex-Plus

Allows hexagon socket screws
a longer service life.



Tools with holding function

Secure holding of screws.









"Take it easy" Tool finder

Rapid access to the tool thanks
to colour coding.

Stainless tools

Attractive and hard.

Great Tools for Rebels



Zyklop VDE

The Zyklop ratchet now in an insulated version.



Wera Belts

Storage of sockets completely revolutionised.



Click-Torque wrenches

The new generation of Wera torque wrenches.



Wera 2go

The space-saving wonder for mobile applications.

We love design

Wera has received several awards for the design of its products and packaging. Including: Red Dot Award, iF Gold Award, German Design Award and German Brand Award Gold.







”Our DNA“

We love Rock'n'Roll




2
20
7,0
1
20
2
4,0
Wera
BE A TOOL REBEL

Screwdrivers

	Kraftform Stainless Steel	20
	Kraftform Plus - Series 900	26
	Kraftform Plus - Series 300	32
	Kraftform Series Comfort	52
	Wooden Handle Series	58
	Flagdriver Series	61
	Screwdriving Accessories	62
	Kraftform Micro Series	64
	400 T-Handle Series	74
	ESD Tools	80

Kraftform Stainless Screwdrivers

Why are stainless elements so often affected by rust?
One reason: screwdriving jobs are often carried out with a tool made of conventional steel which can result in extraneous rust forming. This is annoying. We were confident that this could be prevented by using tools likewise out of stainless steel and meeting the required standard of industrial hardness.

A tool series out of stainless steel. The forming of extraneous rust is prevented and a special vacuum ice-hardening process ensures the required degree of hardness.



Solution to the rust problem: screw stainless steel together with stainless steel! Wera stainless steel tools are manufactured out of stainless steel so unsightly rust can be avoided.



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.





A precisely-focused laser creates a sharp-edged surface structure. This laser treatment results in an edge hardness of up to 1000 HV 0.3. Wera Lasertip "bites" itself into the screw head and prevents any slips out of the recess. It is available for screwdrivers for slotted, Phillips and Pozidriv screws.



Wera Lasertip reduces the contact pressure required and enhances force transfer – meaning less screwdriving effort is required. Screwdriving becomes safer and easier.




The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.






The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking” to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.



The hexagonal non-roll feature prevents any rolling away at the workplace.

Series Kraftform Screwdrivers Stainless Steel

3335 Screwdriver for slotted screws, stainless



Application: Slotted screws

Blade: Round

Design: Stainless steel for minimising rust, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm	mm		
05**032001**001 [1]	0,5	3,0	3,0	80	81	1/8"	3 1/8"
05**032002**001	0,6	3,5	3,5	100	81	9/64"	4"
05**032003**001	0,8	4,0	4,0	100	98	5/32"	4"
05**032004**001	1,0	5,5	5,5	125	98	7/32"	5"

[1] without Lasertip

3334 Screwdriver for slotted screws, stainless



Application: Slotted screws

Blade: Round

Design: Lasertip, stainless steel for minimising rust,

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm	mm		
05**032005**001	1,2	6,5	6,0	150	105	1/4"	6"
05**032006**001	1,2	8,0	7,0	175	112	5/16"	7"
05**032007**001	1,6	10,0	9,0	200	112	3/8"	8"

3350 PH Screwdriver for Phillips screws, stainless



Application: Phillips screws

Blade: Round

Design: Stainless steel for minimising rust, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

		mm	mm	mm	
05**032020**001 [1]	PH 0	60	81	3,0	2 3/8"
05**032021**001	PH 1	80	98	4,5	3 1/8"
05**032022**001	PH 2	100	105	6,0	4"
05**032023**001	PH 3	150	112	8,0	6"

[1] without Lasertip

3355 PZ Screwdriver for Pozidriv screws, stainless



Application: Suitable for Pozidriv screws

Blade: Round

Design: Stainless steel for minimising rust, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (black = Pozidriv) and size stamp.

		mm	mm	mm	
05**032030**001 [1]	PZ 0	60	81	3,0	2 3/8"
05**032031**001	PZ 1	80	98	4,5	3 1/8"
05**032032**001	PZ 2	100	105	6,0	4"
05**032033**001	PZ 3	150	112	8,0	6"

[1] without Lasertip

3367 Screwdriver for TORX® screws, stainless



Application: TORX® socket screws

Blade: Round

Design: Stainless steel for minimising rust

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (green = TORX®) and size stamp.

		mm	mm	mm	
05**032050**001	TX 8	60	81	3,5	2 3/8"
05**032051**001	TX 9	60	81	4,0	2 3/8"
05**032052**001	TX 10	80	81	4,0	3 1/8"
05**032053**001	TX 15	80	98	4,0	3 1/8"
05**032054**001	TX 20	100	98	4,5	4"
05**032055**001	TX 25	100	105	5,0	4"
05**032056**001	TX 27	115	105	5,5	4 9/16"
05**032057**001	TX 30	115	105	6,0	4 9/16"
05**032058**001	TX 40	130	112	7,0	5 3/16"

3368 Screwdriver for square socket screws, stainless



Application: Square socket screws

Blade: Round


Design: Stainless steel for minimising rust

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**032070**002	# 1	80	98	4,5	3 1/8"
05**032071**002	# 2	100	105	6,0	4"

Tip

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

How to prevent the screwdriver from slipping out of the screw head?



It happens time and time again that the tip slips out of the screw head when screwdriving, sometimes damaging valuable surfaces or even causing injury. The tips of the Wera Lasertip screwdrivers are microscopically roughened by means of a laser. This rough surface literally “bites” itself firmly into the screw head. Slipping out becomes a thing of the past.

Vacuum ice-hardened



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

Series Kraftform Screwdrivers Stainless Steel

3334/6 Screwdriver set, stainless and rack



Application: Slotted and Phillips screws

Content: 6-piece set with “Take it easy” tool finder: colour coding according to profile and size stamp and rack in display carton

05**032060**001		
	3350 PH	1 x PH 1x80; 1 x PH 2x100
	3335	1 x 0,5x3,0x80 [1]; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	3334	1 x 1,2x6,5x150

[1] without Lasertip

3334/3355/6 Screwdriver set, stainless and rack



Application: Slotted and Pozidriv screws

Content: 6-piece set with “Take it easy” tool finder: colour coding according to profile and size stamp and rack in display carton

05**032061**001		
	3355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	3335	1 x 0,5x3,0x80 [1]; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	3334	1 x 1,2x6,5x150

[1] without Lasertip

3334/3350/3355/6 Screwdriver set, stainless and rack



Application: Slotted, Phillips and Pozidriv screws


Content: 6-piece set with “Take it easy” tool finder: colour coding according to profile and size stamp and rack in display carton

05**032063**001		
	3350 PH	1 x PH 1x80; 1 x PH 2x100
	3355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	3335	1 x 0,5x3,0x80 [1]
	3334	1 x 1,2x6,5x150

[1] without Lasertip

Tip

Screwdrivers “Take it easy”




“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

Kraftform



The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.

Non-roll feature



The hexagonal non-roll feature prevents any rolling away at the workplace.

Series 900 – the Chiseldriver

Screwdrivers are often misused as chisels. This can be dangerous.

The chiseldriver is the solution when not only screwdriving is required. For fastening, chiselling and loosening seized screws.

Wera chiseldriver: the screwdriver whenever the going gets tough!



An integrated impact cap lengthens the service life and reduces the danger of splintering. Nevertheless, always wear protective goggles.



Greater torque can be transferred by fitting an open-jaw or ring spanner over the integrated hex bolster.



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking“ to the handle. The softer “anti-slip“ zones provide increased grip, enabling the low-loss transfer of high forces.





A hexagon blade made out of high-quality bit material extends right through the handle – thereby ensuring full transfer of force, even when struck with a hammer. The ductile tempered material prevents the blade from splintering or breaking.



The outstanding design of the Kraftform handle that fits perfectly into the hand. Prevents hand injuries such as blisters and calluses. Wera Kraftform: a synonym for “graspable“ ergonomics!



The hexagonal non-roll feature prevents any annoying rolling away at the workplace.



Kraftform Plus – Series 900

The chiseldriver for fastening and chiselling

932 A Screwdriver for slotted screws



Application: Slotted screws

Blade: Hexagonal throughout with impact cap, hexagonal bolster from 0.8 x 4.5

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component, sizes 2.0 x 12.0, 2.5 x 14.0: Kraftform with non-roll feature, single-component

	mm	mm	mm	mm	mm	mm		
05**018260**001 [1]	0,6	3,5	4		80	81	9/64"	3 1/8"
05**018262**001	0,8	4,5	5	8	90	98	0,178"	3 1/2"
05**018264**001	1,0	5,5	6	10	100	105	7/32"	4"
05**018266**001	1,2	7,0	6	10	125	105	9/32"	5"
05**018268**001	1,6	9,0	8	13	150	112	11/32"	6"
05**018270**001	1,6	10,0	8	13	175	112	3/8"	7"
05**018272**001	2,0	12,0	10	16	200	117	1/2"	8"
05**018274**001	2,5	14,0	10	16	250	117	9/16"	10"

[1] No throughout blade, no impact cap and no hexagon bolster

932 A SB Screwdriver for slotted screws

		4013288
05**100085**001	1 x 1.0x5.5x100	181596
05**100086**001	1 x 1.2x7.0x125	181602
05**100087**001	1 x 1.6x9.0x150	181619



917 SPHS Screwdriver for Phillips screws



Application: Phillips screws

Blade: Hexagonal throughout, impact cap with integrated square socket for insertion of 1/4" blades for higher torque

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	mm	
05**017040**001	PH 1	5	8	90	98	3 35/64"
05**017041**001	PH 2	6	10	113	105	4 29/64"

932 AS Screwdriver for slotted screws



Application: Slotted screws

Blade: Hexagonal throughout, impact cap with integrated square socket for insertion of 1/4" blades for higher torque, hexagonal bolster

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

	mm	mm	mm	mm	mm	mm		
05**018300**001	0,8	4,5	5	8	100	98	0,178"	4 3/64"
05**018301**001	1,0	5,5	6	10	113	105	7/32"	4 1/16"
05**018302**001	1,2	7,0	6	10	138	105	9/32"	5 7/16"

917 SPH Screwdriver for Phillips screws



Application: Phillips screws

Blade: Hexagonal throughout with impact cap, hexagonal bolster for sizes 1 - 4

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component, size 4/200: Kraftform with non-roll feature, single-component

		mm	mm	mm	mm	
05**017005**001	PH 1	5	8	80	98	3 1/8"
05**017010**001	PH 2	6	10	100	105	4"
05**017015**001	PH 3	8	13	150	112	6"
05**017020**001	PH 4	10	16	200	117	8"

917 SPH SB Screwdriver for Phillips screws

		4013288
05**100075**001	1 x PH 1x80	181565
05**100076**001	1 x PH 2x100	181572
05**100077**001	1 x PH 3x150	181589



918 SPZ Screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Hexagonal throughout with impact cap, hexagonal bolster for sizes 1 - 4

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component, size 4/200: Kraftform with non-roll feature, single-component

		mm	mm	mm	mm	
05**017050**001	PZ 1	5	8	80	98	3 1/8"
05**017052**001	PZ 2	6	10	100	105	4"
05**017054**001	PZ 3	8	13	150	112	6"
05**017056**001	PZ 4	10	16	200	117	8"

918 SPZ SB Screwdriver for Pozidriv screws

		4013288
05**100080**001	1 x PZ 1x80	181633
05**100081**001	1 x PZ 2x100	181640
05**100082**001	1 x PZ 3x150	181657



977 Screwdriver for TORX® screws



Application: TORX® socket screws

Blade: Hexagonal throughout with impact cap, hexagonal bolster

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	mm	
05**024400**001	TX 15	5	8	80	98	3 1/8"
05**024401**001	TX 20	5	8	90	98	3 1/2"
05**024402**001	TX 25	6	10	100	105	4"
05**024403**001	TX 27	6	10	125	105	5"
05**024404**001	TX 30	8	13	150	112	6"
05**024405**001	TX 40	8	13	150	112	6"

Tip

KRAFTFORM ERGONOMICS

Why is the Kraftform Plus handle made from several components?



Wera makes its Kraftform handles from several materials with different properties. The core is made from a hardwearing plastic that holds the blade securely even when subjected to great forces. The yellow soft zones of the external mantle consist of a softer material with more friction resistance for high torque transfer. The black areas with a harder surface prevent the hand from sticking to the handle enabling you to adjust your grip more quickly.

BLACK POINT


Wera Black Point tip



The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.

SQUARE SOCKET CAP

Impact cap with integrated square socket



Even higher torque can be transferred by connecting the square drive version to a T-handle or Zyklop ratchet.

Kraftform Plus – Series 900

The chiseldriver for fastening and chiselling

Big Pack 900 Screwdriver set Kraftform Wera: Chiseldriver and rack



Application: Slotted, Phillips, Pozidriv and TORX® socket screws

Content: 13-piece set

05**133285**001		
	917 SPH	1 x PH 1x80; 1 x PH 2x100; 1 x PH 3x150
	918 SPZ	1 x PZ 1x80; 1 x PZ 2x100; 1 x PZ 3x150
	932 A	1 x 0,6x3,5x80 [1]; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125; 1 x 1,6x9,0x150
	977 TORX®	1 x TX 20x90; 1 x TX 25x100
	Rack	2 x 190,0x50,0

[1] No throughout blade, no impact cap and no hexagon bolster

932 S/6 Screwdriver set Kraftform Wera: Chiseldriver and rack



Application: Slotted and Phillips screws, impact cap with integrated square socket for insertion of $^{1}/_{4}$" blades for higher torque

Content: 6-piece set and rack in display carton

05**018283**001		
	917 SPHS	1 x PH 1x90; 1 x PH 2x113
	932 A	1 x 0,6x3,5x80 [1]
	932 AS	1 x 0,8x4,5x100; 1 x 1,0x5,5x103; 1 x 1,2x7,0x138

[1] No throughout blade, no impact cap and no hexagon bolster

932/6 Screwdriver set Kraftform Wera: Chiseldriver and rack



Application: Slotted and Phillips screws

Content: 6-piece set and rack in display carton

05**018282**001		
	917 SPH	1 x PH 1x80; 1 x PH 2x100
	932 A	1 x 0,6x3,5x80 [1]; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125

[1] No throughout blade, no impact cap and no hexagon bolster

932/918/6 Screwdriver set Kraftform Wera: Chiseldriver and rack



Application: Slotted and Pozidriv screws
Content: 6-piece set and rack in display carton

05**018287**001		
	918 SPZ	1 x PZ 1x80; 1 x PZ 2x100
	932 A	1 x 0,6x3,5x80 [1]; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125

[1] No throughout blade, no impact cap and no hexagon bolster

977/6 TORX® Screwdriver set Kraftform Wera: Chiseldriver and rack



Application: TORX®
Content: 6-piece set and rack in display carton

05**024410**001		
	977 TORX®	1 x TX 15x80; 1 x TX 20x90; 1 x TX 25x100; 1 x TX 27x125; 1 x TX 30x150; 1 x TX 40x150



Kraftform Screwdrivers Series 300

Kraftform Plus screwdrivers – ergonomics you can grasp. They relieve the entire hand-arm system even when used intensively.

Along with other technical and product advantages such as the Lasertip for a secure fit in the screw head, Kraftform screwdrivers are the ideal choice whenever manual screwdriving jobs are concerned.





The basic idea for the prototype of the Kraftform handle – that the hand should dictate the design – has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After a long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.





The large contact area – with particularly high friction to the soft zones – results in high torque transfer without any bruising from the edges.

The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking” to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.






A precisely-focused laser creates a sharp-edged surface structure. This laser treatment results in an edge hardness of up to 1000 HV 0.3. Wera Lasertip “bites” itself into the screw head and prevents any slips out of the recess. It is available for screwdrivers for slotted, Phillips and Pozidriv screws.






Wera Lasertip reduces the contact pressure required and enhances force transfer – meaning less screwdriving effort is required. Screwdriving becomes safer and easier.



"Take it easy" tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.



The hexagonal non-roll feature prevents any rolling away at the workplace.

Kraftform Plus – Series 300

The answer to almost every screw.

335 Screwdriver for slotted screws



Application: Slotted screws

Blade: Round

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm	∅ mm		
05**008006**001 [1]	0,4	2,0	60	70	2,5	5/64"	2 3/8"
05**110000**001 [1]	0,4	2,5	60	70	2,5	3/32"	2 3/8"
05**008007**001 [1]	0,4	2,5	75	70	2,5	3/32"	3"
05**008008**001 [1]	0,5	3,0	150	81	4,0	1/8"	6"
05**008009**001 [1]	0,5	3,0	200	81	4,0	1/8"	8"
05**110001**001 [1]	0,5	3,0	80	81	3,0	1/8"	3 1/8"
05**008015**001	0,6	3,5	100	81	3,5	9/64"	4"
05**110002**001	0,6	3,5	125	81	3,5	9/64"	5"
05**110003**001	0,6	3,5	200	81	3,5	9/64"	8"
05**110004**001	0,8	4,0	100	98	4,0	5/32"	4"
05**110005**001	0,8	4,0	150	98	4,0	5/32"	6"
05**110006**001	0,8	4,0	200	98	4,0	5/32"	8"
05**008027**001 [1]	0,8	4,0	300	98	4,0	5/32"	12"
05**110007**001	1,0	5,5	125	98	5,5	7/32"	5"
05**008055**001	1,0	5,5	150	98	5,5	7/32"	6"
05**110008**001	1,0	5,5	200	98	5,5	7/32"	8"
05**008060**001 [1]	1,0	5,5	300	98	5,5	7/32"	12"
05**008061**001	1,2	6,0	100	105	6,0	5/16"	4"

[1] without Lasertip

335 SB Slotted screwdriver

		4013288
05**100042**001	1 x 0.6x3.5x100	181275
05**100043**001	1 x 0.8x4.0x100	181251
05**100044**001	1 x 1.0x5.5x125	181244



334 SK Screwdriver for slotted screws



Application: Slotted screws

Blade: Hexagonal with bolster from 0.8 x 4.5

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm	mm	mm		
05**007670**001	0,6	3,5	4	-	75	81	9/64"	3"
05**007671**001	0,8	4,0	4	-	90	81	5/32"	3 1/2"
05**007672**001	0,8	4,5	5	8	90	98	0,178"	3 1/2"
05**007673**001	1,0	5,5	6	10	100	98	7/32"	4"
05**007674**001	1,2	6,5	6	10	125	105	1/4"	5"
05**007675**001	1,2	7,0	6	10	125	105	9/32"	5"
05**007676**001	1,6	9,0	8	13	150	112	11/32"	6"
05**007677**001	1,6	10,0	8	13	175	112	3/8"	7"

334 Screwdriver for slotted screws



Application: Slotted screws

Blade: Round

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component, sizes 2.0 x 12.0, 2.5 x 14.0: Kraftform with non-roll feature, single-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm	∅ mm		
05**007610**001	0,8	5,0	100	98	5,0	3/16"	4"
05**007620**001	1,0	6,0	125	105	6,0	1/4"	5"
05**340330**001	1,0	6,0	150	105	6,0	1/4"	6"
05**110010**001	1,2	6,5	150	105	6,0	1/4"	6"
05**007635**001	1,2	7,0	150	105	7,0	9/32"	6"
05**007621**001	1,2	6,5	200	105	7,0	9/32"	8"
05**110011**001	1,2	8,0	175	112	7,0	5/16"	7"
05**007640**001	1,6	8,0	175	112	7,0	5/16"	7"
05**110104**001	1,6	10,0	200	112	9,0	3/8"	8"
05**110105**001 [1]	2,0	12,0	250	117	10,0	1/2"	10"

[1] without Lasertip

334 SB Screwdriver for slotted screws

		4013288
05**100030**001	1 x 1.2x6.5x150	181411
05**100031**001	1 x 1.2x8.0x175	181220



378 B Screwdriver for slotted screws



Application: Slotted screws

Blade: Square as bolster

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component, sizes 2.0 x 12.0 x 250, 2.5 x 14.0 x 225; Kraftform with non-roll feature, single-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm	mm		
05**110050**001	0,8	4,0	4	75	98	5/32"	3"
05**110051**001	1,0	5,5	5	100	98	7/32"	4"
05**110052**001	1,2	6,5	6	125	105	1/4"	5"
05**110053**001	1,6	8,0	8	150	112	5/16"	6"
05**007355**001	1,6	10,0	8	60	112	3/8"	2 3/8"
05**110054**001	1,6	10,0	8	175	112	3/8"	7"
05**110150**001	1,6	10,0	8	200	112	3/8"	8"
05**110055**001	2,0	12,0	10	200	112	1/2"	8"
05**110151**001	2,0	12,0	10	250	112	1/2"	10"

Tip

LASERTIP

How to prevent the screwdriver from slipping out of the screw head?



It happens time and time again that the tip slips out of the screw head when screwdriving, sometimes damaging valuable surfaces or even causing injury. The tips of the Wera Lasertip screwdrivers are microscopically roughened by means of a laser. This rough surface literally “bites” itself firmly into the screw head. Slipping out becomes a thing of the past.

KRAFTFORM ERGONOMICS


Why is the Kraftform Plus handle made out of several components?



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely, even under high strain. A softer material is used for the coloured soft zones, which has a high frictional resistance and allows the transfer of high forces – thus requiring less screwdriving effort. The black sections with their hard surfaces prevent any “sticking” of the hand to the handle, making rapid repositioning of the hand possible.

BLACK POINT

Wera Black Point tip



The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.

Kraftform Plus – Series 300

The answer to almost every screw.

350 SK PH Screwdriver for Phillips screws



Application: Phillips screws

Blade: Hexagonal, sizes 1 - 3 with bolster

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

	⊕	⬡ mm	mm	mm	mm	
05**008750**001 [1]	PH 0	4		60	81	2 3/8"
05**008751**001	PH 1	5	8	80	98	3 1/8"
05**008752**001	PH 2	6	10	100	105	4"
05**008753**001	PH 3	8	13	150	112	6"

[1] without Lasertip

350 PH Screwdriver for Phillips screws



Application: Phillips screws

Blade: Round

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

	⊕	mm	mm	∅ mm	
05**008705**001 [1]	PH 0	60	81	3,0	2 3/8"
05**008706**001 [1]	PH 0	100	81	3,0	4"
05**008710**001	PH 1	80	98	4,5	3 1/8"
05**008712**001	PH 1	200	98	4,5	8"
05**008715**001 [1]	PH 1	300	98	4,5	12"
05**008720**001	PH 2	100	105	6,0	4"
05**008723**001	PH 2	150	105	6,0	6"
05**008725**001	PH 2	200	105	6,0	8"
05**008730**001 [1]	PH 2	300	105	6,0	12"
05**008735**001	PH 3	150	112	8,0	6"
05**008740**001 [1]	PH 4	200	112	10,0	8"

[1] without Lasertip

350 PH SB Screwdriver for Phillips screws

		4013288
05**100050**001	⊕ 1 x PH 0x60 [1]	181329
05**100051**001	⊕ 1 x PH 1x80	181336
05**100052**001	⊕ 1 x PH 2x100	181343

[1] without Lasertip



355 SK PZ Screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Hexagonal, sizes 1 - 3 with bolster

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (black = Pozidriv) and size stamp.

		mm	mm	mm	mm	
05**009340**001 [1]	PZ 0	4		60	81	2 3/8"
05**009341**001	PZ 1	5	8	80	98	3 1/8"
05**009342**001	PZ 2	6	10	100	105	4"
05**009343**001	PZ 3	8	13	150	112	6"

[1] without Lasertip

355 PZ Screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Round

Design: Chrome-plated, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (black = Pozidriv) and size stamp.

		mm	mm	mm	
05**009305**001 [1]	PZ 0	60	81	3,0	2 3/8"
05**009310**001	PZ 1	80	98	4,5	3 1/8"
05**009312**001	PZ 1	200	98	4,5	8"
05**009313**001 [1]	PZ 1	300	98	4,5	12"
05**009315**001	PZ 2	100	105	6,0	4"
05**009317**001	PZ 2	200	105	6,0	8"
05**347743**001	PZ 2	250	105	6,0	10"
05**009319**001 [1]	PZ 2	300	105	6,0	12"
05**009320**001	PZ 3	150	112	8,0	6"
05**009325**001 [1]	PZ 4	200	112	10,0	8"

[1] without Lasertip

355 PZ SB Screwdriver for Pozidriv screws

		4013288
05**100055**001	1 x PZ 0x60 [1]	181282
05**100056**001	1 x PZ 1x80	181299
05**100057**001	1 x PZ 2x100	181305



Kraftform Plus – Series 300

The answer to almost every screw.

354 Screwdriver for hexagon socket screws



Application: Hexagon socket screws

Blade: Round

Design: Hex-Plus, chrome-plated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (blue = hexagon) and size stamp.

	mm	mm	mm	mm	
05**023105**001	2,0	75	70	3,0	3"
05**023107**001	2,5	75	81	3,0	3"
05**023110**001	3,0	75	81	4,0	3"
05**023115**001	4,0	75	98	5,0	3"
05**023120**001	5,0	80	105	6,0	3 1/8"
05**023125**001	6,0	80	105	7,0	3 1/8"
05**023130**001	8,0	100	112	10,0	4"

352 Ball end screwdriver for hexagon socket screws



Application: Hexagon socket screws


Blade: Hexagonal

Design: Ball end hexagon, chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component, sizes W/F 12.0, W/F 1/2": Kraftform with non-roll feature, single-component. “Take it easy” tool finder: colour coding according to profile (blue = hexagon) and size stamp.

	mm		mm	mm	
05**022795**001	1,5		60	70	2 3/8"
05**022800**001	2,0		100	70	4"
05**138070**001	2,5		100	81	4"
05**022805**001	3,0		100	81	4"
05**022810**001	4,0		100	98	4"
05**022815**001	5,0		100	105	4"
05**022820**001	6,0		125	105	5"
05**022825**001	8,0		150	112	6"
05**022830**001	10,0		150	112	6"
05**022835**001	12,0		150	117	6"
05**022905**001		5/32"	100	98	4"
05**022910**001		3/16"	100	105	4"
05**022915**001		7/32"	100	105	4"
05**022920**001		1/4"	125	105	5"
05**022925**001		5/16"	150	112	6"
05**022930**001		3/8"	150	112	6"
05**022935**001		1/2"	150	117	6"

367 TORX® HF Screwdriver with holding function for TORX® screws



Application: TORX® socket screws

Blade: Round

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, chrome-plated

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**028048**001	TX 8	60	81	3,5	2 3/8"
05**028049**001	TX 9	60	81	4,0	2 3/8"
05**028050**001	TX 10	80	81	4,0	3 1/8"
05**028051**001	TX 15	80	98	4,0	3 1/8"
05**028052**001	TX 20	100	98	4,5	4"
05**028070**001	TX 20	300	98	4,5	12"
05**028053**001	TX 25	100	105	5,0	4"
05**028071**001	TX 25	300	105	6,0	12"
05**028054**001	TX 27	115	105	5,5	4 9/16"
05**028072**001	TX 27	300	105	6,0	12"
05**028055**001	TX 30	115	105	6,0	4 9/16"
05**028073**001	TX 30	300	105	6,0	12"
05**028056**001	TX 40	130	112	7,0	5 3/16"

367 Screwdriver for TORX® screws



Application: TORX® socket screws

Blade: Round

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (green = TORX®) and size stamp.

		mm	mm	mm	
05**028000**001	TX 5	60	70	3,5	2 3/8"
05**028001**001	TX 6	60	70	3,5	2 3/8"
05**028002**001	TX 7	60	70	3,5	2 3/8"
05**028003**001	TX 8	60	81	3,5	2 3/8"
05**028004**001	TX 9	60	81	4,0	2 3/8"
05**028005**001	TX 10	80	81	4,0	3 1/8"
05**028008**001	TX 15	80	98	4,0	3 1/8"
05**028010**001	TX 20	100	98	4,5	4"
05**028012**001	TX 25	100	105	5,0	4"
05**028013**001	TX 27	115	105	5,5	4 9/16"
05**028015**001	TX 30	115	105	6,0	4 9/16"
05**028020**001	TX 40	130	112	7,0	5 1/8"
05**028025**001	TX 45	130	112	8,0	5 1/8"

367 SB Screwdriver for TORX® screws

		4013288
05**100060**001	1 x TX 10x80	181350
05**100061**001	1 x TX 15x80	181367
05**100062**001	1 x TX 20x100	181374
05**100063**001	1 x TX 25x100	181381
05**100064**001	1 x TX 30x115	181398



Tip

BALL END

TORX® and hexagon ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, “around-the-corner” screwdriving jobs. This ball tip geometry – often found on L-keys – is now available on a number of Wera bits.

HOLDING FUNCTION

What is the purpose of the HF profile?



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

HEX-PLUS

How to prevent rounded screw heads?



Hexagon socket screws are a problem, because the contact surfaces that transfer the force of the tool to the screw are very narrow. The consequence: the head of the screw can be damaged, usually rounding out the recess. Hex-Plus tools have larger contact surfaces to prevent this, driving from the flats of the recess, rather than the corners. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Kraftform Plus – Series 300

The answer to almost every screw.

367 K Ball end screwdriver for TORX® screws



Application: TORX® socket screws

Blade: Round

Design: Ball end, chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**027950**001	TX 15	80	98	4,0	3 1/8"
05**027952**001	TX 20	100	98	4,5	4"
05**027954**001	TX 25	100	105	5,0	4"
05**027956**001	TX 27	115	105	5,5	4 9/16"
05**027958**001	TX 30	115	105	6,0	4 9/16"

367 TORX® BO Screwdriver for tamper-proof TORX® screws



Application: TORX® screws with safety pin

(BO = with bore hole)

Blade: Round

Design: Bore hole in TORX® section, chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**138257**001	TX 7	60	70	3,5	2 3/8"
05**138258**001	TX 8	60	81	3,5	2 3/8"
05**138259**001	TX 9	60	81	4,0	2 3/8"
05**138260**001	TX 10	80	81	4,0	3 1/8"
05**138268**001	TX 10	300	81	4,0	12"
05**138261**001	TX 15	80	98	4,0	3 1/8"
05**138269**001	TX 15	300	98	4,0	12"
05**138262**001	TX 20	100	98	4,5	4"
05**138270**001	TX 20	300	98	4,5	12"
05**138263**001	TX 25	100	105	5,0	4"
05**138264**001	TX 27	115	105	5,5	4 9/16"
05**138265**001	TX 30	115	105	6,0	4 9/16"
05**138266**001	TX 40	130	112	7,0	5 3/16"

367 TORX PLUS® Screwdriver for TORX PLUS® screws



Application: TORX PLUS® socket screws

Blade: Round

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**028029**001	5 IP	60	70	3,5	2 3/8"
05**028030**001	6 IP	60	70	3,5	2 3/8"
05**028031**001	7 IP	60	70	3,5	2 3/8"
05**028032**001	8 IP	60	70	3,5	2 3/8"
05**028033**001	9 IP	60	81	4,0	2 3/8"
05**028034**001	10 IP	80	81	4,0	3 1/8"
05**028035**001	15 IP	80	98	4,0	3 1/8"
05**028036**001	20 IP	100	98	4,5	4"
05**028037**001	25 IP	100	105	5,0	4"
05**028038**001	30 IP	115	105	6,0	4 9/16"

371 TORQ-SET® Mplus screwdriver for TORQ-SET® screws



Application: TORQ-SET® screws

Blade: Round

Design: Mplus for higher breaking torque and longer service life, chrome-plated

Handle: Kraftform with non-roll feature, multi-component

	mm		mm	mm	mm	
05**028130**001	6		80	98	4,5	3 1/8"
05**028132**001	8		100	105	6,0	4"
05**028134**001	10		100	105	6,0	4"
05**028136**001		1/4"	125	112	8,0	5"

368 Screwdriver for square socket head screws



Application: Square socket screws

Blade: Round

Design: Chrome-plated, Black Point except for sizes 01+02

Handle: Kraftform with non-roll feature, multi-component, # 2/300, # 01/25, # 02/25: single-component

		mm	mm	mm	
05**117680**001	# 00	60	81	3,5	2 3/8"
05**117681**001	# 0	60	81	4,0	2 3/8"
05**117682**001	# 1	80	98	4,5	3 1/8"
05**117683**001	# 1	200	98	4,5	8"
05**117684**001	# 2	100	105	6,0	4"
05**117685**001	# 2	200	105	6,0	8"
05**117691**001	# 2	300	105	6,0	12"
05**117686**001	# 3	150	112	8,0	6"
05**117687**001	# 4	200	112	8,0	8"
05**117688**001	# 01	25	54	4,5	1"
05**117689**001	# 02	25	54	6,0	1"


368 SB Screwdriver for square socket head screws

		4013288
05**100070**001	1 x # 1x80	181404
05**100071**001	1 x # 2x100	181428
05**100072**001	1 x # 3x150	181435



Tip

How can I prevent frequent breakages of TORQ-SET® tools?



Wera developed the Mplus profile with stronger flanks compared with tools with a conventional TORQ-SET® profile. This results in approximately 70 % extra torsional strength and greatly extends the service life of Wera Mplus tools.

TORX PLUS®



Compared with the “normal” TORX® profile, the elliptical instead of circular profile enlarges the 6 flanks that transfer torque between the tool and the screw. This means that the force applied when screwdriving is spread across a larger surface area. Higher torque is transferred and, in addition, the service life of the screw and tool are lengthened. The so-called centre-lock screws on cutting tools represent a typical use of this type of screw profile. The thermal influences on such holders for carbide insert tips often “bake” the retaining screws so firmly that it is important to have a profile that considerably enhances the loosening torque capability of the screws. For this reason a torque-stable screw profile is necessary to avoid any possible damage to the screw and to exclude the possibility of an otherwise costly machine downtime.

TORX® with borehole (BO)



TORX® tools with a borehole prevent the unauthorised unfastening of safety screws. The screws contain a pin that protrudes into the drive profile so that “normal” TORX® tools cannot be used. This pin fits into the borehole of TORX® BO tools allowing safety screws to be unfastened.

Kraftform Plus – Series 300

The answer to almost every screw.

375 TRI-WING® screwdriver for TRI-WING® screws



Application: TRI-WING® screws

Blade: Round

Design: Chrome-plated, Black Point

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**028116**001	0	80	81	3,5	3 1/8"
05**028118**001	1	80	81	3,5	3 1/8"
05**028120**001	2	80	98	4,5	3 1/8"
05**028122**001	3	80	98	4,5	3 1/8"
05**028124**001	4	100	98	6,0	4"
05**028126**001	5	100	98	6,0	4"

391 Hose clamp screwdriver



Application: Hexagon headed bolts, screws and nuts

Blade: Round, flexible

Design: Nutdriver for hexagon head bolts

Handle: Kraftform with non-roll feature, multi-component

	mm	mm	mm	
05**028148**001	6	167	98	6 9/16"
05**028150**001	7	167	98	6 9/16"
05**028152**001	8	167	98	6 9/16"

395 Nutdriver



Application: Hexagon headed bolts, screws and nuts

Blade: Round

Design: Chrome-plated, nutdriver for hexagon head bolts

Handle: Kraftform with non-roll feature, multi-component

	mm	mm	mm	mm	
05**028205**001	3,0	125	98	5,0	5"
05**028210**001	3,5	125	98	6,1	5"
05**028215**001	4,0	125	98	6,9	5"
05**028220**001	4,5	125	98	7,1	5"
05**028225**001	5,0	125	98	8,1	5"
05**028230**001	5,5	125	98	8,1	5"
05**029405**001	6,0	125	98	9,1	5"
05**029410**001	7,0	125	105	11,0	5"
05**029415**001	8,0	125	105	12,1	5"
05**029420**001	9,0	125	105	13,1	5"
05**029425**001	10,0	125	112	14,1	5"
05**029430**001	11,0	125	112	16,0	5"
05**029435**001	12,0	125	112	17,1	5"
05**029440**001	13,0	125	112	18,1	5"
05**029445**001	14,0	125	112	19,1	5"
05**029450**001	15,0	125	112	21,0	5"

395 HO Nutdriver



Application: Hexagon headed bolts, screws and nuts

Blade: Round

Design: Chrome-plated, hollow shaft for protruding threaded rods


Handle: Kraftform with non-roll feature, multi-component

TIP: The hollow shaft enables seized screws or those on long threads to be tightened and loosened

	mm		mm	mm	mm	
05**029460**001	5,0		90	98	7,2	3 35/64"
05**029461**001	5,5		90	98	7,2	3 35/64"
05**029462**001	6,0		90	98	7,2	3 35/64"
05**029463**001	7,0		90	105	7,2	3 35/64"
05**029464**001	8,0		90	105	9,3	3 35/64"
05**029465**001	10,0		90	112	9,3	3 35/64"
05**029466**001	13,0		90	112	11,0	3 35/64"
05**029501**001		3/16"	90	98	7,2	3 35/64"
05**029502**001		1/4"	90	98	7,2	3 35/64"
05**029503**001		5/16"	90	105	9,3	3 35/64"
05**029504**001		11/32"	90	105	9,3	3 35/64"
05**029505**001		3/8"	90	112	9,3	3 35/64"
05**029506**001		7/16"	90	112	11,0	3 35/64"
05**029507**001		1/2"	90	112	11,0	3 35/64"

Tip

What is the purpose of a screwdriver with hollow shaft?



A screwdriver with a hollow shaft is needed whenever there are screwdriving jobs involving threaded rods i.e. the threaded rod through the nut can slip into the hollow shaft of the screwdriver.

Flexible shaft



Screwdriving can also be achieved “around the corner” with the screwdriver 391. The flexible shaft allows unfavourably-positioned screw fastenings to be reached. The ideal tool for difficult-to-access screwdriving applications e.g. in the engine compartment of a car.

The TRI-WING® screwdriving system



The TRI-WING® screwdriving system is mainly found in aviation and household technology (here e.g. on live components). The asymmetric arrangement of the three profile flanks prevents the use of anything other than the original tools. The high-precision Wera profile design ensures a secure fit of the tool in the head of the screw. The blades are manufactured out of bit material. The Wera know-how with regard to the hardening technology ensures a long service life of the tool.

Kraftform Plus – Series 300

The answer to almost every screw.

336 Stubby/Carburettor screwdriver



Application: Slotted screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform with non-roll feature, single-component

	mm	mm	mm	mm	∅ mm		
05**110068**001	0,6	3,5	25	54	3,5	9/64"	1"
05**110069**001	0,8	4,0	25	54	4,0	5/32"	1"
05**110070**001	1,0	5,5	25	54	5,5	7/32"	1"
05**110075**001	1,2	6,5	25	54	6,5	1/4"	1"
05**110078**001	1,2	8,0	25	54	8,0	5/16"	1"

Stubby/Carburettor screwdriver



Application: Phillips screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform, with non-roll feature, single-component

		mm	mm	∅ mm	
05**008775**001	PH 01	25	54	4,5	1"
05**008780**001	PH 02	25	54	6,0	1"
05**008782**001	PH 03	25	54	8,0	1"

Stubby/Carburettor screwdriver




Application: Suitable for Pozidriv screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform with non-roll feature, single-component

		mm	mm	∅ mm	
05**009330**001	PZ 01	25	54	4,5	1"
05**009335**001	PZ 02	25	54	6,0	1"
05**009337**001	PZ 03	25	54	8,0	1"

Kraftform Big Pack 300





Kraftform Plus – Series 300. With Lasertip blade, voltage tester and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, cross, Phillips-Recess, Pozidriv and TORX® screws

Content: 14-piece set in display carton

05**105630**001		
	350 PH	1 x PH 1x80; 1 x PH 2x100; 1 x PH 3x150
	355 PZ	1 x PZ 1x80; 1 x PZ 2x100; 1 x PZ 3x150
	367 TORX®	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115
	334	1 x 1,2x6,5x150
	335	1 x 0,6x3,5x100; 1 x 0,8x4,0x100
	Rack	2 x 190,0x50,0

Kraftform XXL





12-piece screwdriver set for all-round applications. “Take it easy” tool finder: colour coding according to profile and size stamp.

05**051010**001		
	350 PH	1 x PH 1x80; 1 x PH 2x100
	355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	932 A	1 x 1,0x5,5x100; 1 x 1,2x7,0x125
	334	1 x 1,2x6,5x150
	335	1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100
	247	1 x 0,5x3,0x70
	Rack	2 x 190,0x50,0


[1] without Lasertip

[*] Product not available in the USA and Canada.

Tip



Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.



The Chiseldriver



An integrated impact cap lengthens the service life and reduces the danger of splintering. Nevertheless, always wear protective goggles.

Kraftform Plus – Series 300

The answer to almost every screw.

Kraftform XXL 2





12-piece screwdriver set for all-round applications. “Take it easy” tool finder: colour coding according to profile and size stamp.

05**051011**001		
	350 PH	1 x PH 2x100
	355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	932 A	1 x 1,0x5,5x100; 1 x 1,2x7,0x125
	335	1 x 0,8x4,0x100
	367 TORX®	1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100
	247	1 x 0,5x3,0x70
	Rack	2 x 190,0x50,0

[1] without Lasertip
[**] Product not available in the USA and Canada.

Kraftform XXL 3





11-piece screwdriver set for all-round applications. “Take it easy” tool finder: colour coding according to profile and size stamp.

05**347106**001		
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100
	350 PH	1 x PH 1x80; 1 x PH 2x100
	932 A	1 x 1,0x5,5x100; 1 x 1,2x7,0x125
	335	1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	334	1 x 1,2x6,5x150
	368	1 x # 1x80; 1 x # 2x100
	Rack	2 x 190,0x50,0

[1] without Lasertip

Kraftform 2go 300





11 Kraftform screwdrivers, Series 300 for cross recess screws Phillips and Pozidriv, TORX® and slotted screws. “Take it easy” tool finder: colour coding according to profile and size stamp.

1 dimensionally stable and robust Tool Quiver, equipped with handle for the storage and transport of tools; high resistance against cuts and stabs; comes with hook and loop fastener zone for docking with the Wera 2go system and includes 1 variably adjustable hook and loop fastener partition for a division into as many as 5 sections.

05**004313**001		
	Wera 2go 4	1 x 165,0x165,0x105
	350 PH	1 x PH 1x80; 1 x PH 2x100
	355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	367 TORX®	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115
	334 SK	1 x 0,8x4,5x90; 1 x 1,2x7,0x125
	Hook and Loop Fastener Strip 120	1 x 50,0x120,0


Wera

Kraftform Plus – Series 300

The answer to almost every screw.

334 SK/6 Rack screwdriver set Kraftform Plus Lasertip and rack





Lasertip hexagon blades and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Phillips screws

Content: 6-piece set and rack in display carton

05**007680**001		
✪	**350 SK PH**	1 x PH 1x80; 1 x PH 2x100
⊖	**334 SK**	1 x 0,6x3,5x75; 1 x 0,8x4,0x90; 1 x 1,0x5,5x100; 1 x 1,2x6,5x125

334/355 SK/6 Screwdriver set Kraftform Plus Lasertip and rack





Lasertip hexagonal blades and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Pozidriv screws

Content: 6-piece set and rack in display carton

05**007681**001		
✪	**355 SK PZ**	1 x PZ 1x80; 1 x PZ 2x100
⊖	**334 SK**	1 x 0,6x3,5x75; 1 x 0,8x4,0x90; 1 x 1,0x5,5x100; 1 x 1,2x6,5x125

334/6 Rack screwdriver set Kraftform Plus Lasertip and rack





Lasertip round blades and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Phillips screws

Content: 6-piece set and rack in display carton

05**105650**001		
✪	**350 PH**	1 x PH 1x80; 1 x PH 2x100
⊖	**334**	1 x 1,2x6,5x150
⊖	**335**	1 x 0,5x3,0x80 [1]; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

[1] without Lasertip

334/355/6 Rack screwdriver set Kraftform Plus Lasertip and rack





Lasertip round blades and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Pozidriv screws

Content: 6-piece set and rack in display carton

05**105656**001		
✪	**355 PZ**	1 x PZ 1x80; 1 x PZ 2x100
⊖	**334**	1 x 1,2x6,5x150
⊖	**335**	1 x 0,5x3,0x80 [1]; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

[1] without Lasertip

335/350/355/6 Screwdriver set Kraftform Plus Lasertip and rack



Lasertip blades and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips and Pozidriv screws

Content: 6-piece set and rack in display carton

05**105622**001		
	350 PH	1 x PH 1x80; 1 x PH 2x100
	355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	335	1 x 0,8x4,0x100; 1 x 1,0x5,5x125

335/350/355/3 Screwdriver set Kraftform Plus with holding function and 300 mm-long blades



“Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips and Pozidriv screws


Content: 3-piece set

05**347735**002		
	350 PH	1 x PH 2x300 [1]
	355 PZ	1 x PZ 2x300 [1]
	335	1 x 1,0x5,5x300 [1]

[1] without Lasertip

Tip

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

How to prevent the screwdriver from slipping out of the screw head?



It happens time and time again that the tip slips out of the screw head when screwdriving, sometimes damaging valuable surfaces or even causing injury. The tips of the Wera Lasertip screwdrivers are microscopically roughened by means of a laser. This rough surface literally “bites” itself firmly into the screw head. Slipping out becomes a thing of the past.

Why is the Kraftform Plus handle made out of several components?



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely, even under high strain. A softer material is used for the coloured soft zones, which has a high frictional resistance and allows the transfer of high forces – thus requiring less screwdriving effort. The black sections with their hard surfaces prevent any “sticking” of the hand to the handle, making rapid repositioning of the hand possible.

Kraftform Plus – Series 300

The answer to almost every screw.

335/350/355/4 Screwdriver set Kraftform Plus Lasertip with holding function and 200 mm-long blades



Lasertip blades. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips and Pozidriv screws

Content: 4-piece set

053**47736**002		
	350 PH	1 x PH 2x200
	355 PZ	1 x PZ 1x200; 1 x PZ 2x200
	335	1 x 1,0x5,5x200

335/350/367/7 Rack screwdriver set Kraftform Plus Lasertip and rack



Lasertip round blades and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, cross, Phillips-Recess, Pozidriv and TORX® screws

Content: 7-piece set and rack in display carton

053**20540**001		
	350 PH	1 x PH 2x100
	355 PZ	1 x PZ 1x80; 1 x PZ 2x100
	335	1 x 0,8x4,0x100
	367 TORX®	1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100

367/7 TORX® HF Kraftform Plus screwdriver set with holding function and rack



Application: TORX®

Content: 7-piece set and rack in display carton

052**23161**001	
	367 TORX® HF 1 x TX 8x60; 1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 27x115; 1 x TX 30x115

367/6 TORX® HF Kraftform Plus screwdriver set with holding function and rack




Application: TORX®

Content: 6-piece set and rack in display carton

050**28059**001	
	367 TORX® HF 1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115; 1 x TX 40x130

367/4 TORX® HF Kraftform Plus screwdriver set with holding function and 300 mm-long blades



Application: TORX® with holding function, extra long (300 mm) blade

Content: 4-piece set

050**28074**001	
	367 TORX® HF 1 x TX 20x300; 1 x TX 25x300; 1 x TX 27x300; 1 x TX 30x300

367/6 Screwdriver set Kraftform Plus TORX® and rack



Application: TORX®

Content: 6-piece set with “Take it easy” tool finder: colour coding according to profile and size stamp and rack in display carton.

05**028062**001		
	367 TORX®	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115; 1 x TX 40x130

334/368/6 Screwdriver set and rack



Application: Slotted, Phillips and square-head screws

Content: 6-piece set with “Take it easy” tool finder: colour coding according to profile and size stamp and rack in display carton

05**347778**001		
	350 PH	1 x PH 1x80; 1 x PH 2x100
	334	1 x 1,2x6,5x150
	335	1 x 0,8x4,0x100
	368	1 x # 1x80; 1 x # 2x100

367/6 TORX® BO Kraftform Plus screwdriver set and rack



Application: TORX® screws with safety pin (BO = with bore hole)

Content: 6-piece set and rack in display carton

05**138250**001	
	367 TORX® BO 1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115; 1 x TX 40x130

395 HO/7 SM Nutdriver set



Application: Hexagon headed bolts, screws and nuts

Content: 7-piece set in display carton

TIP: The hollow shaft enables seized screws or those on long threads to be tightened and loosened

05**029510**001		
	395 HO	1 x 5,0x90; 1 x 5,5x90; 1 x 6,0x90; 1 x 7,0x90; 1 x 8,0x90; 1 x 10,0x90; 1 x 13,0x90

Kraftform Comfort Screwdrivers

The ergonomic introduction to convenient screwdriving.

Handle with Kraftform geometry and blade made from power bit material with Black Point tip for precise fit.

For all kinds of application.







The multi-component Kraftform handle for quick and low-exertion working.



The screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case, or at the workplace.



The hexagonal non-roll feature prevents any annoying rolling away.





The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.




The bit material used for manufacturing is subjected to a specific Wera hardening process, and this ensures longer product service life.

Kraftform Comfort

Convenient, safe, good!

1335 Screwdriver for slotted screws



Application: Slotted screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Comfort with non-roll feature, multi-component

	mm	mm	mm	mm	mm		
05**031400**001	0,4	2,0	60	81	2,5	5/64"	2 3/8"
05**031401**001	0,4	2,5	75	81	2,5	3/32"	3"
05**031402**001	0,5	3,0	80	81	3,0	1/8"	3 1/8"
05**031403**001	0,5	3,0	150	81	3,0	1/8"	6"
05**031405**001	0,6	3,5	100	81	3,5	9/64"	4"
05**031406**001	0,6	3,5	125	81	3,5	9/64"	5"
05**031408**001	0,8	4,0	100	98	4,0	5/32"	4"
05**031409**001	0,8	4,0	150	98	4,0	5/32"	6"
05**031411**001	0,8	4,0	300	98	4,0	5/32"	12"
05**031412**001	1,0	5,5	125	98	5,5	7/32"	5"
05**031413**001	1,0	5,5	150	98	5,5	7/32"	6"
05**031416**001	1,2	6,0	100	105	6,0	15/64"	4"

1334 Screwdriver for slotted screws



Application: Slotted screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Comfort with non-roll feature, multi-component

	mm	mm	mm	mm		
05**031420**001	0,8	5,0	100	98	3/16"	4"
05**031421**001	1,0	6,0	125	105	15/64"	5"
05**031422**001	1,2	6,5	150	105	1/4"	6"
05**031424**001	1,2	7,0	150	105	9/32"	6"
05**031425**001	1,2	8,0	175	112	5/16"	7"
05**031426**001	1,6	8,0	175	112	5/16"	7"
05**031427**001	1,6	10,0	200	112	3/8"	8"

1350 PH Screwdriver for Phillips screws



Application: Phillips screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Comfort with non-roll feature, multi-component

		mm	mm	mm	
05**031440**001	PH 0	60	81	3,0	2 3/8"
05**031441**001	PH 1	80	98	4,5	3 1/8"
05**031442**001	PH 1	200	98	4,5	8"
05**031444**001	PH 2	100	105	6,0	4"
05**031445**001	PH 2	200	105	6,0	8"
05**031447**001	PH 3	150	112	8,0	6"


1355 PZ Screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Comfort with non-roll feature, multi-component

		mm	mm	mm	
05**031460**001	PZ 0	60	81	3,0	2 3/8"
05**031461**001	PZ 1	80	98	4,5	3 1/8"
05**031463**001	PZ 2	100	105	6,0	4"
05**031466**001	PZ 3	150	112	8,0	6"

1367 TORX® screwdriver for TORX® screws




Application: TORX® socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Comfort with non-roll feature, multi-component

		mm	mm	mm	
05**031500**001	TX 5	60	81	3,5	2 3/8"
05**031501**001	TX 6	60	81	3,5	2 3/8"
05**031502**001	TX 7	60	81	3,5	2 3/8"
05**031503**001	TX 8	60	81	3,5	2 3/8"
05**031504**001	TX 9	60	81	4,0	2 3/8"
05**031505**001	TX 10	80	81	4,0	3 1/8"
05**031506**001	TX 15	80	98	4,0	3 1/8"
05**031507**001	TX 20	100	98	4,5	4"
05**031508**001	TX 25	100	105	5,0	4"
05**031509**001	TX 27	115	105	5,5	4 9/16"
05**031510**001	TX 30	115	105	6,0	4 9/16"
05**031511**001	TX 40	130	112	7,0	5 3/16"
05**031512**001	TX 45	130	112	8,0	5 1/8"

Tip

BLACK POINT

The Wera Black Point tip



The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.

The screw symbol



The screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case, or at the workplace.

Kraftform Comfort

Convenient, safe, good!

1334/6 Screwdriver set Kraftform Comfort



Application: Slotted and Phillips screws
Content: 6-piece set in display carton

05**031551**001		
⊕	**1350 PH**	1 x PH 1x80; 1 x PH 2x100
⊖	**1335**	1 x 0,5x3,0x80; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
⊖	**1334**	1 x 1,2x6,5x150

1335/1350/1355/6 Screwdriver set Kraftform Comfort



Application: Slotted, Phillips and Pozidriv screws
Content: 6-piece set in display carton

05**031553**001		
⊕	**1350 PH**	1 x PH 1x80; 1 x PH 2x100
✪	**1355 PZ**	1 x PZ 1x80; 1 x PZ 2x100
⊖	**1335**	1 x 0,8x4,0x100; 1 x 1,0x5,5x125

1334/1355/6 Screwdriver set Kraftform Comfort



Application: Slotted and Pozidriv screws
Content: 6-piece set in display carton

05**031552**001		
✪	**1355 PZ**	1 x PZ 1x80; 1 x PZ 2x100
⊖	**1335**	1 x 0,5x3,0x80; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
⊖	**1334**	1 x 1,2x6,5x150

1367/6 TORX® Screwdriver set Kraftform Comfort



Application: TORX® screws
Content: 6-piece set in display carton

05**031554**001		
✪	**1367 TORX®**	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x100; 1 x TX 25x100; 1 x TX 30x115; 1 x TX 40x130



Wera
Kraftform
Wera
Kraftform

Screwdrivers with wooden handles

The traditional screwdriver with very specific product benefits.



Higher torque can be transferred by fitting an open-jaw or ring spanner over the hex bolster that is welded to the blade.





The Wera Black Point tip and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.

A double leather cap combined with the blade that extends right through the handle provide additional safety and reduce the danger of a splintering of the handle when struck with a hammer.



With pound-thru blade out of high quality bit material. As a result, loss-free transfer of power, even in the case of hammer blows. The material prevents any splintering or breakage of the blade.





Wooden Handle Series

Traditionally good quality!

930 A Screwdriver for slotted screws



Application: Slotted screws
Blade: Round, hexagon bolster
Design: Chrome-plated, Black Point
Handle: Beech wood with leather cap

	mm	mm	mm	mm	mm		
05**018005**001	0,6	3,5	8	90	102	9/64"	3 1/2"
05**018010**001	0,8	4,5	8	90	102	0,178"	3 1/2"
05**018015**001	1,0	5,5	8	100	102	7/32"	4"
05**018020**001	1,2	7,0	10	125	111	9/32"	5"
05**018025**001	1,6	9,0	13	175	126	11/32"	7"
05**018030**001	1,6	10,0	13	175	126	3/8"	7"
05**018035**001	2,0	12,0	13	200	126	1/2"	8"
05**018040**001	2,5	14,0	16	250	140	9/16"	10"

935 SPH Screwdriver for Phillips screws



Application: Phillips screws
Blade: Round, hexagon bolster
Design: Chrome-plated, Black Point
Handle: Beech wood with leather cap

		mm	mm	mm	
05**018350**001	PH 1	8	90	102	3 1/2"
05**018352**001	PH 2	10	100	111	4"
05**018354**001	PH 3	13	175	126	7"
05**018355**001	PH 4	16	200	140	8"

955 SPZ Screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws
Blade: Round, hexagon bolster
Design: Chrome-plated, Black Point
Handle: Beech wood with leather cap

		mm	mm	mm	
05**023305**001	PZ 1	8	90	102	3 1/2"
05**023307**001	PZ 2	10	100	111	4"
05**023309**001	PZ 3	13	175	126	7"

930/935/6 Screwdriver set



Application: Slotted and Phillips screws
Content: 6-piece set in display carton

05**018251**001		
	935 SPH	1 x PH 1x90; 1 x PH 2x100
	930 A	1 x 0,6x3,5x90; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125

930/955/6 Screwdriver set



Application: Slotted and Pozidriv screws
Content: 6-piece set in display carton

05**137810**001		
	955 SPZ	1 x PZ 1x90; 1 x PZ 2x100
	930 A	1 x 0,6x3,5x90; 1 x 0,8x4,5x90; 1 x 1,0x5,5x100; 1 x 1,2x7,0x125

Flagdriver Series

The right tool for every application

1267 A TORX® flagdriver for TORX® screws



Application: TORX® socket screws
Blade: Round
Design: BlackLaser surface
Handle: Multi-component

		mm	mm	mm	
05**026350**001	TX 6	33	62,0	3,0	1 19/64"
05**026351**001	TX 7	33	62,0	3,0	1 19/64"
05**026352**001	TX 8	40	69,0	3,0	1 37/64"
05**026353**001	TX 9	40	69,0	3,0	1 37/64"
05**026354**001	TX 10	40	69,0	3,0	1 37/64"

1267 B TORX® combination flagdriver for TORX® and hexagon socket screws



Application: TORX® and hexagon socket screws
Blade: Hexagon
Design: TORX® and hexagon, BlackLaser surface
Handle: Multi-component

		mm	mm	mm	
05**026372**001	TX 15	3,5	47	86,0	1 27/32"
05**026373**001	TX 15	4	47	86,0	1 27/32"
05**026374**001	TX 20	4	47	86,0	1 27/32"

1267 A TORX PLUS® flagdriver for TORX PLUS® screws



Application: TORX PLUS® socket screws
Blade: Round
Design: BlackLaser surface
Handle: Multi-component

		mm	mm	mm	
05**026360**001	6 IP	33	62,0	3,0	1 19/64"
05**026361**001	7 IP	33	62,0	3,0	1 19/64"
05**026363**001	9 IP	40	69,0	3,0	1 37/64"

1267 B TORX PLUS® combination flagdriver for TORX PLUS® and hexagon socket screws



Application: TORX PLUS® and hexagon socket screws
Blade: Hexagon
Design: TORX PLUS® and hexagon, BlackLaser surface
Handle: Multi-component

		mm	mm	mm	
05**026382**001	15 IP	3,5	47	86,0	1 27/32"

Accessories

Indispensable aids for screwdriving jobs

Wera Star Magnetizer/Demagnetizer




Application: Simply run the tool down the positive side of the Wera magnetiser/demagnetiser and the tool immediately becomes magnetised and is able to hold the screw securely on the blade. To demagnetise the tool, simply run it down one of the four negative sides.

05**073403**001	
	Wera Star 1 x 48,0



Magnetising



Demagnetising

1427 Awl



Handle: single-component
Blade: Extends through handle

	mm	mm	
05**027405**001	105	92	4 3/16"

1428 Reamer



Handle: single-component
Blade: Extends through handle

	mm	mm	
05**027455**001	107	92	4 9/32"

Rack for Kraftform Micro screwdrivers



	mm	mm
05**134002**001	190,0	80

Rack for Kraftform screwdrivers



	mm	mm
05**134001**001	190,0	50,0

1440/1442 Screw gripper set



Application: Attachment with holding function for screws, holds all screw profiles and sizes securely on the tool, suitable for round and hexagon blades with a diameter from 4.5 mm to 6.0 mm and 6.0 mm to 8.5 mm

Design: Elastomer

05**073680**001		
	1440	1 x 4,5 - 6,0x41,0
	1442	1 x 6,0-8,5x41,0

1441 Screw gripper attachment for screwdriver blades, long bits and L-keys, with holding function for screws



Application: Attachment with holding function for screws, holds all screw profiles and sizes securely on the tool, suitable for round and hexagon blades with a diameter from 4.5 mm to 6.0 mm

Design: Elastomer

	∅ mm	mm
05**073681**001	4,5-6,0	41,0

And this is how the gripper works:



Push the screw gripper onto the tip of the screwdriver until the end of the blade protrudes from the rubber blade holder.




Attach the screw to the tip of the blade and secure it in the screw gripper.



Pull the screw gripper towards the screwdriver handle until the two arms of the gripper sit against the head of the screw and are spread slightly apart. The Wera screw gripper releases the screw automatically after it has been fastened.



The two gripper arms spread further apart as they are pushed against the surface and automatically snap back when the head of the screw is countersunk.



When fastening screws in blind holes the screw gripper is pushed back, making it possible to reach even deep-seated screws.



The screw gripper attachment can also be used with L-keys and long bits!

Kraftform Micro

Screwdriving jobs in electrical and precision engineering applications are often tedious and time-consuming.

We learned from users what is important for them: working speeds, torque, precision – and we then focused particularly on these issues.



The fast-turning zone just below the rotating cap allows rapid twisting.




The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.





The Wera Black Point tip, as well as a refined hardening process, ensure long service life and enhanced corrosion protection.



Multi-component screwdriver handle for ergonomic working.



Indispensable for many users, including electronics technicians, opticians, precision engineers, jewellers, EDP hardware fitters and model-makers.



Series Kraftform Micro

The refined screwdriver for electronics technicians

2035 Screwdriver for slotted screws for electronic applications



Application: Slotted screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm	mm	mm	mm	mm		
05**117990**001	0,16	0,8	40	97	2,0	1/32"	1 9/16"
05**117991**001	0,18	1,0	40	97	2,0	0,04"	1 9/16"
05**117992**001	0,20	1,2	40	97	2,0	0,05"	1 9/16"
05**118002**001	0,23	1,5	40	97	2,0	1/16"	1 9/16"
05**118003**001	0,23	1,5	60	97	2,0	1/16"	2 3/8"
05**118000**001	0,25	1,2	40	97	2,0	0,05"	1 9/16"
05**117993**001	0,30	1,8	40	97	2,0	0,07"	1 9/16"
05**118004**001	0,30	1,8	60	97	2,0	0,07"	2 3/8"
05**117997**001	0,35	2,5	40	97	2,0	0,07"	1 9/16"
05**118017**001	0,30	2,0	50	97	2,0	0,07"	2"
05**118005**001	0,40	2,0	40	97	2,5	5/64"	1 9/16"
05**118006**001	0,40	2,0	60	97	2,5	5/64"	2 3/8"
05**118007**001	0,40	2,0	100	97	2,5	5/64"	4"
05**117994**001	0,40	2,5	50	97	2,5	3/32"	2"
05**118008**001	0,40	2,5	80	97	2,5	3/32"	3 1/8"
05**117995**001	0,50	3,0	50	97	3,0	1/8"	2"
05**118010**001	0,50	3,0	80	97	3,0	1/8"	3 1/8"
05**118012**001	0,60	3,5	80	97	4,0	9/64"	3 1/8"
05**118014**001	0,80	4,0	80	97	4,0	5/32"	3 1/8"

2055 PZ Screwdriver for Pozidriv screws for electronic applications



Application: Suitable for Pozidriv screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**118030**001	PZ 0	60	97	3,0	2 3/8"
05**118032**001	PZ 1	80	97	4,0	3 1/16"

2050 PH Screwdriver for Phillips screws for electronic applications



Application: Phillips screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**345290**001 [1) 3)]	PH 000	40	97	1,5/2.5	1 9/16"
05**118019**001 [1) 3)]	PH 00	40	97	1,8/2,5	1 9/16"
05**118020**001 [1)]	PH 00	60	97	2,5	2 3/8"
05**118026**001 [2)]	PH 0	40	97	3,0	1 9/16"
05**118022**001 [2)]	PH 0	60	97	3,0	2 3/8"
05**118023**001	PH 1	60	97	4,0	2 3/8"
05**118024**001	PH 1	80	97	4,0	3 1/8"

[1)] Optimised for Asian PH screws
[2)] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)
[3)] On the output side, the blade is turned to a nominal length of 10 mm.

2067 TORX® HF screwdriver with holding function for electronic applications



Application: TORX® socket screws
Blade: Round
Design: Holding function for TORX® screws made according to Acument Global Technologies Inc. specifications, chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**118180**001	TX 4	40	97	2,5	1 9/16"
05**118181**001	TX 5	40	97	3,0	1 9/16"
05**118182**001	TX 6	40	97	3,0	1 9/16"
05**118183**001	TX 7	60	97	3,0	2 3/8"
05**118184**001	TX 8	60	97	3,0	2 3/8"
05**118185**001	TX 9	60	97	4,0	2 3/8"
05**118186**001	TX 10	60	97	4,0	2 3/8"

2067 TORX® screwdriver for TORX® screws for electronic applications



Application: TORX® socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**118035**001	TX 1	40	97	2,0	1 9/16"
05**118036**001	TX 2	40	97	2,0	1 9/16"
05**118037**001	TX 3	40	97	2,0	1 9/16"
05**118039**001	TX 4	40	97	2,5	1 9/16"
05**118040**001	TX 5	40	97	3,0	1 9/16"
05**118042**001	TX 6	40	97	3,0	1 9/16"

2067 TORX® BO screwdriver for tamper-proof TORX® screws for electronic applications



Application: TORX® socket screws with safety pin (BO = with bore hole)
Blade: Round
Design: Bore hole in TORX® section, chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**118044**001	TX 7	60	97	3,0	1 9/16"
05**118046**001	TX 8	60	97	3,0	2 3/8"
05**118048**001	TX 9	60	97	4,0	2 3/8"
05**118050**001	TX 10	60	97	4,0	2 3/8"
05**118052**001	TX 15	60	97	4,0	2 3/8"
05**118054**001	TX 20	60	97	4,0	2 3/8"

Tip




How can I hold my TORX® screw securely on the screwdriver?



The electronic TORX® screwdriver with holding function (HF) literally presses the screw onto the screwdriver. The conical driving flanks that taper toward the tip of the tool, the optimised flank base and the ideal engage depth hold the screw securely on the blade.

How to perform precision screwdriving jobs quickly whilst still applying the required degree of force?



The Kraftform Micro, with its three zones and their specific arrangement, satisfies these requirements perfectly. The free-turning cap that provides support for the hand works with these advantages, enabling quick and easy precision work.

Series Kraftform Micro

The refined screwdriver for electronics technicians

2067 IPR TORX PLUS® screwdriver for electronic applications



Application: TORX PLUS® IPR socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030160**001	1 IPR	44	97	2,0	1 47/64"

2054 Screwdriver for hexagon socket screws for electronic applications



Application: Hexagon socket screws
Blade: Round
Design: Hex-Plus, chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm		mm	mm	mm	
05**118060**001	0,7		40	97	3,0	1 9/16"
05**118062**001	0,9		40	97	3,0	1 9/16"
05**118064**001	1,3		40	97	3,0	1 9/16"
05**118066**001	1,5		60	97	3,0	2 3/8"
05**118068**001	2		60	97	3,0	2 3/8"
05**118070**001	2,5		60	97	4,0	2 3/8"
05**118072**001	3,0		60	97	4,0	2 3/8"
05**345284**001	-	0,028"	40	97	3,0	1 9/16"
05**345285**001	-	0,035"	40	97	3,0	1 9/16"
05**118074**001	-	0,05"	40	97	3,0	1 9/16"
05**118076**001	-	1/16"	60	97	3,0	2 3/8"
05**118078**001	-	5/64"	60	97	3,0	2 3/8"
05**118080**001	-	3/32"	60	97	4,0	2 3/8"
05**118082**001	-	7/64"	60	97	4,0	2 3/8"
05**118075**001	-	1/8"	60	97	4,0	2 3/8"

2052 Ball end hexagon screwdriver for electronic applications



Application: Hexagon socket screws
Blade: Round
Design: Hexagon ball end, chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm		mm	mm	mm	
05**118089**001	1,3		60	97	3,0	2 3/8"
05**118090**001	1,5		60	97	3,0	2 3/8"
05**118092**001	2,0		60	97	3,0	2 3/8"
05**118094**001	2,5		60	97	4,0	2 3/8"
05**118096**001	3,0		60	97	4,0	2 3/8"
05**118098**001	-	1/16"	60	97	3,0	2 3/8"
05**118100**001	-	5/64"	60	97	3,0	2 3/8"
05**118102**001	-	3/32"	60	97	3,0	2 3/8"
05**118106**001	-	7/64"	60	97	4,0	2 3/8"
05**118103**001	-	1/8"	60	97	4,0	2 3/8"

2072 Kraftform Micro screwdriver for Microstix® screws



Application: Microstix® socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**118145**001	m	40	97	2,5	1 9/16"

2069 Nutdriver for electronic applications



Application: Hexagon headed bolts, screws and nuts
Blade: Round
Design: Chrome-plated
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm		mm	mm	mm	
05**118108**001	1,5		60	97	5,7	2 3/8"
05**118109**001	1,8		60	97	5,7	2 3/8"
05**118110**001	2,0		60	97	5,7	2 3/8"
05**118112**001	2,5		60	97	5,7	2 3/8"
05**118114**001	3,0		60	97	5,7	2 3/8"
05**118116**001	3,2		60	97	5,7	2 3/8"
05**118118**001	3,5		60	97	5,7	2 3/8"
05**118120**001	4,0		60	97	5,7	2 3/8"
05**118122**001	4,5		60	97	6,4	2 3/8"
05**118124**001	5,0		60	97	7,0	2 3/8"
05**118126**001	5,5		60	97	7,8	2 3/8"
05**345281**001	6,0		60	97	8,5	2 3/8"
05**118128**001	-	3/32"	60	97	5,7	2 3/8"
05**118130**001	-	7/64"	60	97	5,7	2 3/8"
05**118132**001	-	1/8"	60	97	5,7	2 3/8"
05**118134**001	-	9/64"	60	97	5,7	2 3/8"
05**118136**001	-	5/32"	60	97	5,7	2 3/8"
05**118135**001	-	3/16"	60	97	6,6	2 3/8"
05**118137**001	-	7/32"	60	97	7,8	2 3/8"
05**345282**001	-	1/4"	60	97	9,0	2 3/8"

1429 Chip lifter



Application: Lifting tightly-fitting parts from circuit boards after desoldering
Blade: Round
Design: Chrome-plated
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm	mm	mm	mm
05**027456**001	1,0	3,5	50	97

Tip

How to hold any screw securely on the screwdriver?



With the Wera magnetiser/demagnetiser: simply run the tool down the positive side of the Wera magnetiser/demagnetiser and the tool immediately becomes magnetised and is able to hold the screw securely on the blade.



To demagnetise the tool, simply run it down one of the four negative sides. See page 62.

BALL END

Hexagon ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, “around-the-corner” screwdriving jobs.

Series Kraftform Micro

The refined screwdriver for electronics technicians

1013 Kraftform Micro bitholding screwdriver



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck for rapid bit change

Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm	mm	
05**051276**001	23	97	1"

Kraftform Micro 12 Universal 1 Screwdriver set for electronic applications



Application: Slotted and Phillips screws, TORX® socket screws, and Hexagon socket screws

Content: 12-piece set, in a belt pouch

05**073675**001		
	2050 PH Micro	1 x PH 00x60 [1]; 1 x PH 0x60 [2]
	2067 TORX® HF	1 x TX 5x40; 1 x TX 6x40
	2035 Micro	1 x 0,23x1,5x40; 1 x 0,30x1,8x60; 1 x 0,40x2,0x60; 1 x 0,40x2,5x80; 1 x 0,50x3,0x80
	2054 Micro	1 x 0,9x40; 1 x 1,5x60; 1 x 2x60

[1] Optimised for Asian PH screws

[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

Kraftform Micro 12 Electronics 1 Screwdriver set for electronic applications



Application: Slotted, Phillips, TORX® BO, TORX PLUS® IPR, Microstix® screws and hexagon headed bolts, screws and nuts. 1 remover.

Content: 12-piece set, in a belt pouch

05**073677**001		
	2050 PH Micro	1 x PH 000x40 [1]; 1 x PH 00x40 [1]; 1 x PH 0x40 [2]
	2067 TORX® BO Micro	1 x TX 8x60; 1 x TX 10x60
	2067 IPR Micro	1 x 1 IPR x 44
	2035 Micro	1 x 0,23x1,5x40; 1 x 0,35x2,5x40
	2069 Micro	1 x 2,5x60; 1 x 3,0x60
	2072	1 x mx40
	1429	1 x 1,0x3,5x50

[1] Optimised for Asian PH screws

[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

Kraftform Kompakt Micro 11 Electronics 1



11-piece set
Pouch with 44 mm bits
1 Kraftform Micro bitholding screwdriver 1013

05**073676**001		
	1013 Kraftform Micro	1 x 97
	851/9 C	1 x PH 000x44 [1]; 1 x PH 00x44 [1]; 1 x PH 0x44 [2]
	867/9 C TORX®	1 x TX 8x44
	867/9 C TORX PLUS®	1 x 3 IPx44
	867/9 IPR TORX® PLUS	1 x 1 IPRx44
	800/9 C	1 x 0,35x2,5x44
	872/9	1 x mx44
	869/9	1 x 2,5x44,0; 1 x 3,0x44,0

[1] Optimised for Asian PH screws
[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

Kraftform Kompakt Micro 11 Universal 1



11-piece set
Pouch with 44 mm bits
1 Kraftform Micro bitholding screwdriver 1013

05**135938**001		
	1013 Kraftform Micro	1 x 97
	851/9 C	1 x PH 00x44 [1]; 1 x PH 0x44 [2]; 1 x PH 1x44 [1]
	840/9 C	1 x 1,5x44; 1 x 2,0x44
	800/9 C	1 x 0,23x1,5x44; 1 x 0,40x2,0x44; 1 x 0,50x3,0x44
	867/9 C TORX®	1 x TX 5x44; 1 x TX 6x44

[1] Optimised for Asian PH screws
[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

2035/6 A Screwdriver set and rack for electronic applications



Application: Slotted and Phillips screws
Content: 6-piece set and rack in display carton

05**118150**001		
	2050 PH Micro	1 x PH 00x60 [1]; 1 x PH 0x60 [2]
	2035 Micro	1 x 0,30x1,8x60; 1 x 0,40x2,0x60; 1 x 0,40x2,5x80; 1 x 0,50x3,0x80

[1] Optimised for Asian PH screws
[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

Series Kraftform Micro

The refined screwdriver for electronics technicians

2035/6 B Screwdriver set and rack for electronic applications



Application: Slotted and Phillips screws

Content: 6-piece set and rack in display carton

05**118152**001		
	2050 PH Micro	1 x PH 0x60 [1]; 1 x PH 1x80
	2035 Micro	1 x 0,40x2,5x80; 1 x 0,50x3,0x80; 1 x 0,60x3,5x80; 1 x 0,80x4,0x80

[1] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

2052/6 Hexagon screwdriver set and rack for electronic applications



Application: Ball end for hexagon socket screws

Content: 6-piece set and rack in display carton

05**118156**001		
	2052 Micro	1 x 1,5x60; 1 x 2,0x60; 1 x 2,5x60; 1 x 3,0x60
	2054 Micro	1 x 0,9x40; 1 x 1,3x40

2050/6 Screwdriver set and rack for electronic applications



Application: Slotted, Phillips, TORX PLUS® IPR and Microstix® screws

Content: 6-piece set and rack in display carton

05**030181**001		
	2050 PH Micro	1 x PH 000x40 [1]; 1 x PH 00x40 [1]; 1 x PH 0x40 [2]
	2067 IPR Micro	1 x 1 IPR x 44
	2072	1 x mx40
	2035 Micro	1 x 0,35x2,5x40

[1] Optimised for Asian PH screws

[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

2067/6 TORX® BO screwdriver set and rack for electronic applications



Application: TORX® socket screws with safety pin (BO = with bore hole)
Content: 6-piece set and rack in display carton

05**118154**001	
	2067 TORX® BO Micro 1 x TX 7x60; 1 x TX 8x60; 1 x TX 9x60; 1 x TX 10x60; 1 x TX 15x60; 1 x TX 20x60

2069/6 Screwdriver set and rack for electronic applications



Application: Hexagon headed bolts, screws and nuts
Content: 6-piece set and rack in display carton

05**118158**001	
	2069 Micro 1 x 2,0x60; 1 x 2,5x60; 1 x 3,0x60; 1 x 3,5x60; 1 x 4,0x60; 1 x 5,0x60



Screwdrivers with T-handle


The T-handle is useful whenever higher tightening or loosening torque need to be applied.

The exclusive use of hard material in combination with the large contact surface area in the hand ensures an efficient, positive transfer of power.






The ergonomic design of the T-handle fills the palm of the hand. The fingers rest in the soft, rounded recess, and the whole hand is in contact with the handle – so there is no friction loss between the hand and handle.



By using the blade as an extension of your lower arm you can transfer particularly high torque.



The blades are made for superior wear resistance and robustness.


Wera

Series 400 T-Handle

Ideal for high torque

454 T-handle hexdriver



Application: Hexagon socket screws
Blade: Hexagon
Design: Hex-Plus, chamfered, chrome-plated
Handle: T-handle, single-component

		mm	mm	mm	
05**013300**001	2	100	27	61	4"
05**013301**001	2	200	27	61	8"
05**013302**001	2,5	100	27	61	4"
05**013303**001	2,5	200	27	61	8"
05**013304**001	3	100	33	70	4"
05**013305**001	3	150	33	70	6"
05**013330**001	3	200	33	70	8"
05**013331**001	3	350	33	70	14"
05**013332**001	4	100	33	70	4"
05**013306**001	4	150	33	70	6"
05**013307**001	4	200	33	70	8"
05**013333**001	4	350	33	70	14"
05**013334**001	5	100	44	87	4"
05**013308**001	5	150	44	87	6"
05**013309**001	5	200	44	87	8"
05**013335**001	5	350	44	87	18"
05**013337**001	6	100	44	87	4"
05**013338**001	6	150	44	87	6"
05**013310**001	6	200	44	87	8"
05**013339**001	6	350	44	87	14"
05**013311**001	7	200	44	87	8"
05**013341**001	8	150	44	87	6"
05**013312**001	8	200	44	87	8"
05**013314**001	10	200	44	87	8"


454 T-handle hexdriver, imperial



Application: Hexagon socket screws
Blade: Hexagon
Design: Hex-Plus, chamfered, BlackLaser surface
Handle: T-handle, single-component

		mm	mm	mm	
05**344536**001	3/32"	100	27	61	4"
05**344537**001	7/64"	100	27	61	4"
05**344538**001	1/8"	100	33	70	4"
05**344546**001	9/64"	150	33	70	6"
05**344545**001	5/32"	150	33	70	6"
05**344544**001	3/16"	150	44	87	6"
05**344543**001	7/32"	150	44	87	6"
05**344542**001	1/4"	200	44	87	8"
05**344541**001	5/16"	200	44	87	8"
05**344540**001	3/8"	200	44	87	8"

467 T-handle TORX® driver



Application: TORX® screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: T-handle, single-component

		mm	mm	mm		mm
05**013350**001	TX 6	100	27	61	4"	3,0
05**013352**001	TX 7	100	27	61	4"	3,0
05**013354**001	TX 8	100	27	61	4"	3,5
05**013356**001	TX 9	100	27	61	4"	3,5
05**013358**001	TX 10	100	27	61	4"	4,0
05**013360**001	TX 15	100	33	70	4"	4,0
05**013362**001	TX 20	100	33	70	4"	4,5
05**013364**001	TX 20	200	33	70	8"	4,5
05**013366**001	TX 25	100	33	70	4"	5,0
05**013368**001	TX 25	200	33	70	8"	5,0
05**013370**001	TX 27	200	44	87	8"	6,0
05**013372**001	TX 30	200	44	87	8"	6,0
05**013374**001	TX 40	200	44	87	8"	8,0
05**013376**001	TX 45	200	44	87	8"	9,0

495 T-handle nutspinner



Application: Hexagon headed bolts, screws and nuts
Blade: Round
Design: Hexagonal, chrome-plated
Handle: T-handle, single-component

		mm	mm	mm		mm
05**013400**001	5	230	33	70	9"	8,1
05**013399**001	5,5	230	33	70	9"	8,1
05**013401**001	6	230	33	70	9"	9,1
05**013402**001	7	230	44	87	9"	11,0
05**013403**001	8	230	44	87	9"	12,1
05**013404**001	9	230	44	87	9"	13,1
05**013405**001	10	230	44	87	9"	14,1
05**013407**001	11	230	44	87	9"	16,0
05**013409**001	12	230	44	87	9"	17,1
05**013411**001	13	230	44	87	9"	18,1

489 R T-handle Rapidaptor




Application: Suitable for $^{1}/_{4}$" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Drive: $^{1}/_{4}$" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, magnetic

Handle: T-handle, multi-component

		mm	mm	mm	
05**013390**001	$^{1}/_{4}$"	45	44	87	1 $^{25}/_{32}$"



Rapidaptor

Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Chuck-all



The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

ESD Tools

When doing screwdriving jobs on electronic components (like e.g. smartphones and tablet PCs), there should be no electrostatic discharge as this could cause malfunctions and a complete failure.

Therefore, tools that are secure against electrostatic discharge are indispensable.




The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.



The electric surface resistance of the Wera ESD material is ≤ 10^9 ohm. This securely protects components against electrostatic energy and associated damage.



Wera Black Point tips and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.






The fast-turning zone just below the rotating allows rapid twisting.



The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.


Wera
EPA

ESD Series

ESD-safe tools

1578 A Kraftform Micro screwdriver for slotted screws



Application: Slotted screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm	mm	mm	mm	mm		
05**030101**001	0,23	1,5	40	97	2,5	1/16"	1 9/16"
05**030100**001	0,25	1,2	40	97	2,5	0,05"	1 9/16"
05**030102**001	0,30	1,8	60	97	2,5	0,07"	2 3/8"
05**030108**001	0,35	2,5	40	97	2,5	3/32"	1 9/16"
05**030103**001	0,40	2,0	60	97	2,5	5/64"	2 3/8"
05**030104**001	0,40	2,5	80	97	2,5	3/32"	3 1/8"
05**030105**001	0,50	3,0	80	97	3,0	1/8"	3 1/8"
05**030106**001	0,60	3,5	80	97	4,0	9/64"	3 1/8"
05**030107**001	0,80	4,0	80	97	4,0	5/32"	3 1/8"

1550 PH Kraftform Micro screwdriver for Phillips screws



Application: Phillips screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030117**001 [1) 3)]	PH 000	40	97	1,5/2,5	1 9/16"
05**030118**001 [1) 3)]	PH 00	40	97	1,8/2,5	1 9/16"
05**030110**001 [3)]	PH 00	60	97	1,8/2,5	2 3/8"
05**030119**001	PH 0	40	97	3,0	1 9/16"
05**030111**001 [2)]	PH 0	60	97	3,0	2 3/8"
05**030112**001	PH 1	80	97	4,0	3 1/8"

[1)] Optimised for Asian PH screws

[2)] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

[3)] On the output side, the blade is turned to a nominal length of 10 mm.

1555 PZ Kraftform Micro screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030115**001	PZ 0	60	97	3,0	2 3/8"
05**030116**001	PZ 1	80	97	4,0	3 1/8"

1567 TORX® HF Kraftform Micro screwdriver with holding function for TORX® screws



Application: TORX® socket screws
Blade: Round
Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030400**001	TX 4	40	97	2,5	1 9/16"
05**030401**001	TX 5	40	97	3,0	1 9/16"
05**030402**001	TX 6	40	97	3,0	1 9/16"
05**030403**001	TX 7	60	97	3,0	2 3/8"
05**030404**001	TX 8	60	97	3,0	2 3/8"
05**030405**001	TX 9	60	97	4,0	2 3/8"
05**030406**001	TX 10	60	97	4,0	2 3/8"


1567 TORX® Kraftform Micro screwdriver for TORX® screws



Application: TORX® socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030120**001	TX 4	40	97	2,5	1 9/16"
05**030121**001	TX 5	40	97	3,0	1 9/16"
05**030122**001	TX 6	40	97	3,0	1 9/16"

1567 TORX® BO Screwdriver for tamper-proof TORX® screws



Application: TORX® socket screws with safety pin (BO = with bore hole)
Blade: Round
Design: Bore hole in TORX® section, chrome-plated, Black Point
Handle: Kraftform with non-roll feature, single-component

		mm	mm	mm	
05**030131**001	TX 10	80	81	4,0	3 1/8"
05**030127**001	TX 15	80	98	4,0	3 1/8"
05**030128**001	TX 20	100	98	4,5	4"
05**030129**001	TX 25	100	98	5,0	4"
05**030130**001	TX 30	115	98	6,0	4 9/16"

1567 IPR TORX PLUS® screwdriver for electronic applications



Application: TORX PLUS® IPR socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030135**001	1 IPR	40	97	2,0	1 9/16"

Tip

Rotating cap and fast-turning zone



The fast-turning zone just below the rotating cap allow rapid twisting. This makes time-consuming grip adjustments as with other conventional precision screwdrivers unnecessary.

The power zone



The power zone has integrated soft zones near the blade tip to ensure high torque transfer for loosening or tightening screws without losing contact with the screw.

The precision zone



The precision zone directly above the blade gives the user a better feel for the right rotation angle during fine adjustment work.

ESD Series

ESD-safe tools

1572 ESD Kraftform Micro screwdriver for Microstix® screws



Application: Microstix® socket screws
Blade: Round
Design: Chrome-plated, Black Point
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030080**001	m	40	97	2,5	1 9/16"
05**030081**001	00	40	97	2,5	1 9/16"
05**030082**001	F	40	97	2,5	1 9/16"
05**030083**001	0	40	97	2,5	1 9/16"
05**030084**001	1	40	97	2,5	1 9/16"

1569 ESD Nutdriver



Application: Hexagon headed bolts, screws and nuts
Blade: Round
Design: Chrome-plated
Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

		mm	mm	mm	
05**030410**001	1,5	60	97	5,7	2 3/8"
05**030411**001	1,8	60	97	5,7	2 3/8"
05**030412**001	2,0	60	97	5,7	2 3/8"
05**030413**001	2,5	60	97	5,7	2 3/8"
05**030414**001	3,0	60	97	5,7	2 3/8"
05**030415**001	3,2	60	97	5,7	2 3/8"
05**030416**001	3,5	60	97	5,7	2 3/8"
05**030417**001	4,0	60	97	5,7	2 3/8"
05**030418**001	4,5	60	97	6,4	2 3/8"
05**030150**001	5,0	60	97	7,0	2 3/8"
05**030151**001	5,5	60	97	7,8	2 3/8"

1578 A/6 ESD Screwdriver set and rack for electronic applications



Application: Slotted and Phillips screws
Content: 6-piece set and rack in display carton

05**030170**001	
	1550 PH Micro 1 x PH 0x60; 1 x PH 1x80
	1578 A Micro 1 x 0,23x1,5x40; 1 x 0,25x1,2x40; 1 x 0,30x1,8x60; 1 x 0,40x2,5x80

1550/6 ESD Screwdriver set and rack for electronic applications



Application: Slotted, Phillips and Microstix® screws
Content: 6-piece set and rack in display carton

05**030180**001	
	1550 PH Micro 1 x PH 000x40 [1]; 1 x PH 00x40 [1]; 1 x PH 0x40
	1578 A Micro 1 x 0,25x1,2x40; 1 x 0,35x2,5x40
	1572 ESD 1 x mx40

[1] Optimised for Asian PH screws

1013 Kraftform Micro ESD bitholding screwdriver



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck for rapid bit change

Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	mm	mm	
05**300004**001	23	97	1"

816 R ESD bitholding screwdriver, non-magnetic



Application: Suitable for $^1/_4$" DIN ISO 1173-C and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: $^1/_4$" hexagon socket with Wera quick-release chuck and Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051464**001	$^1/_4$"	119

Tip

Chuck-all



The Rapidaptor quick-release chucks hold both ¼" bits as per DIN ISO 1173-C 6,3 (Wera series 1) and E 6,3 (Wera series 4).

Single-hand



All functions of the quick-release chuck such as the inserting or releasing of bits can be done with just one hand. That is faster, more economic and ergonomic. There are no unnecessary manoeuvres.

Rapid-in and self-lock



The bit can be pushed into the chuck without moving the sleeve. It automatically locks with a secure and wobble-free fit as soon as the bit is applied to the screw.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. Particularly helpful: even the smallest bits can be removed without any extra tools.

ESD Series

ESD-safe tools

813 R ESD bitholding screwdriver, non-magnetic



Application: Suitable for 1/4" DIN ISO 1173-C and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: 1/4" hexagon socket with Wera quick-release chuck and Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051273**001	1/4"	90

Kraftform Kompakt 60 ESD



Pouch with 89 mm bits
17-piece set
1 Kraftform bitholding screwdriver 816 R ESD with Rapidaptor quick-release chuck

05**051043**001		
	816 R ESD	1 x 1/4"x119
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89
	800/4 Z	1 x 1,0x5,5x89

Kraftform Kompakt Micro 21 ESD 1



21-piece set
Pouch with 44 mm bits
1 Kraftform Micro ESD bitholding screwdriver

05**135973**001		
	1013 Kraftform Micro ESD	1 x 97
	851/9 C	1 x PH 000x44 [1]; 1 x PH 00x44 [1]; 1 x PH 0x44 [2]
	867/9 C TORX®	1 x TX 1x44; 1 x TX 2x44; 1 x TX 3x44; 1 x TX 4x44; 1 x TX 5x44
	867/9 C TORX PLUS®	1 x 1 IPx44; 1 x 2 IPx44; 1 x 3 IPx44; 1 x 4 IPx44
	867/9 IPR TORX® PLUS	1 x 1 IPRx44
	872/9	1 x mx44; 1 x 00x44; 1 x Fx44; 1 x 0x44
	800/9 C	1 x 0,23x1,5x44; 1 x 0,35x2,5x44
	869/9	1 x 2,5x44,0

[1] Optimised for Asian PH screws
[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

Kraftform Kompakt Micro 20 ESD 1



20-piece set
Pouch with 44 mm bits
1 Kraftform Micro ESD bitholding screwdriver

05**073671**001		
	1013 **Kraftform Micro ESD**	1 x 97
	851/9 C	1 x PH 00x44 [1]; 1 x PH 0x44 [2]; 1 x PH 1x44 [1]
	867/9 C TORX®	1 x TX 1x44; 1 x TX 2x44; 1 x TX 3x44; 1 x TX 4x44; 1 x TX 5x44; 1 x TX 6x44
	867/9 C TORX PLUS®	1 x 1 IPx44; 1 x 2 IPx44; 1 x 3 IPx44; 1 x 4 IPx44
	840/9 C	1 x 1,5x44; 1 x 2,0x44
	800/9 C	1 x 0,23x1,5x44; 1 x 0,40x2,0x44; 1 x 0,50x3,0x44
	867/9 IPR TORX® PLUS	1 x 1 IPRx44

[1] Optimised for Asian PH screws
[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

811/1 ESD bitholding screwdriver



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon socket bits and Wera Series 1

Design: Extra short, 1/4" hexagon insert bits with retaining ring

Handle: Kraftform, single-component

		mm	mm	
05**051106**001	1/4"	10	54	3/8"

Kraftform Kompakt Micro 11 ESD 1



11-piece set
Pouch with 44 mm bits
1 Kraftform Micro ESD bitholding screwdriver

05**073670**001		
	1013 **Kraftform Micro ESD**	1 x 97
	851/9 C	1 x PH 00x44 [1]; 1 x PH 0x44 [2]; 1 x PH 1x44 [1]
	867/9 C TORX®	1 x TX 5x44; 1 x TX 6x44
	800/9 C	1 x 0,23x1,5x44; 1 x 0,40x2,0x44; 1 x 0,50x3,0x44
	840/9 C	1 x 1,5x44; 1 x 2,0x44

[1] Optimised for Asian PH screws
[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

810/1 ESD bitholding screwdriver with retaining ring



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: 1/4" hexagon socket with retaining ring, chrome-plated

Handle: Kraftform with non-roll feature, single-component

		mm	mm	
05**328463**001	1/4"	100	112	4"


Wera

VDE Tools

	Kraftform Stainless VDE	88
	Kraftform Series 100 VDE	92
	Kraftform Kompakt VDE	106
	Kraftform Comfort VDE	120
	The Zyklop VDE Ratchet and accessories	124

Kraftform Stainless Screwdrivers VDE

Why are stainless elements so often affected by rust? One reason: screwdriving jobs are often carried out with a tool out of made from conventional steel which can result in extraneous rust forming. This is annoying. We were confident that this could be prevented by using tools likewise out of stainless steel and meeting the required standard of industrial hardness.

A tool series out of stainless steel. The forming of extraneous rust is prevented and a special vacuum ice-hardening process ensures the required degree of hardness – and they are even VDE-tested, too.



Solution to the rust problem: screw stainless steel together with stainless steel! Wera stainless steel tools are manufactured out of stainless steel so unsightly rust can be avoided.



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.





A precisely-focused laser creates a sharp-edged surface structure. This laser treatment results in an edge hardness of up to 1000 HV 0.3. Wera Lasertip "bites" itself into the screw head and prevents any slips out of the recess. It is available for screwdrivers for slotted, Phillips and Pozidriv screws.



Wera Lasertip reduces the contact pressure required and enhances force transfer – meaning less screwdriving effort is required. Screwdriving becomes safer and easier.




The outstanding design of the Kraftform handle that fits perfectly into the hand prevents hand injuries such as blisters and calluses.





The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin “sticking” to the handle. The surrounding hard zones with large diameters glide like wheels across the hand.



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.



The hexagonal non-roll feature prevents any rolling away at the workplace.

Series Kraftform Screwdrivers Stainless Steel VDE

3160 i VDE Insulated Screwdriver for slotted screws, stainless



Application: Slotted screws

Blade: Insulated, individually tested as per IEC 60900

Design: Conical edge, Lasertip, stainless steel for minimising rust

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm		
05**022729**001 [1]	0,5	3,0	80	81	1/8"	3 1/8"
05**022730**001	0,6	3,5	100	81	9/64"	4"
05**022731**001	0,8	4,0	100	98	5/32"	4"
05**022732**001	1,0	5,5	125	98	7/32"	5"

[1] without Lasertip

3162 i PH VDE Insulated screwdriver for Phillips screws, stainless



Application: Phillips screws

Blade: Insulated, individually tested as per IEC 60900

Design: Lasertip, stainless steel for minimising rust

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

		mm	mm	
05**022733**001	PH 1	80	98	3 1/8"
05**022734**001	PH 2	100	105	4"

3165 i PZ VDE Insulated screwdriver for Pozidriv screws, stainless



Application: Suitable for Pozidriv screws

Blade: Insulated, individually tested as per IEC 60900

Design: Lasertip, stainless steel for minimising rust

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (black = Pozidriv) and size stamp.

		mm	mm	
05**022740**001	PZ 1	80	98	3 1/8"
05**022741**001	PZ 2	100	105	4"

3160 i/7 Screwdriver set, stainless and rack



Kraftform stainless: the safety screwdriver for stainless steel screws, Lasertip blade + voltage tester + rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Phillips screws

Contents: Stainless steel, 7-piece set and rack in display carton

05**022728**001		
	3247	1 x 0,5x3,0x70
	3162 i VDE	1 x PH 1x80; 1 x PH 2x100
	3160 i VDE	1 x 0,5x3,0x80 [1]; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

[1] without Lasertip
[*] Product not available in the USA and Canada.

3165 i/6 Screwdriver set, stainless and rack



Kraftform stainless: the safety screwdriver for stainless steel screws, Lasertip blade + rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Pozidriv screws


Contents: Stainless steel, 6-piece set and rack in display carton

05**022745**001		
	3165 i PZ VDE	1 x PZ 1x80; 1 x PZ 2x100
	3160 i VDE	1 x 0,5x3,0x80 [1]; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

[1] without Lasertip

Tip

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

Tested for dielectric strength



Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.

Kraftform Screwdrivers Series 100 VDE

We want our users to be able to work safely and conveniently.
So we have now transferred the advantages of the Kraftform Plus technology into the VDE segment.



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



Impact strength tested at -40°C, guaranteeing safety even under extreme conditions.



The outstanding design of the Kraftform handle ensures that it fits perfectly into the hand, preventing hand injuries such as blisters and calluses.






The hard materials used for the handle ensure rapid hand repositioning, without any danger of the skin "sticking" to the handle. The softer "anti-slip" zones enable the low-loss transfer of high forces – resulting in less screwdriving effort being required.




A precisely-focused laser creates a sharp-edged surface structure. This laser treatment results in an edge hardness of up to 1000 HV 0.3. Wera Lasertip "bites" itself into the screw head and prevents any slips out of the recess. It is available for screwdrivers for slotted, Phillips and Pozidriv screws.



"Take it easy" tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.





The hexagonal non-roll feature prevents any annoying rolling away at the workplace.

Kraftform Plus – Series 100 VDE

The safety screwdriver for working with live wiring

160 i VDE Insulated screwdriver for slotted screws



Application: Slotted screws

Blade: Insulated, individually tested as per IEC 60900

Design: Conical tip, Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm		
05**006100**001 [1]	0,4	2,5	80	81	3/32"	3 1/8"
05**006105**001 [1]	0,5	3,0	100	81	1/8"	4"
05**006110**001	0,6	3,5	100	81	9/64"	4"
05**006115**001	0,8	4,0	100	98	5/32"	4"
05**006116**001	0,8	4,0	150	98	5/32"	6"
05**006120**001	1,0	5,5	125	98	7/32"	5"
05**006121**001	1,0	5,5	200	98	7/32"	8"
05**006125**001	1,2	6,5	150	105	1/4"	6"
05**006126**001	1,2	6,5	200	105	1/4"	8"
05**006130**001	1,2	8,0	175	112	5/16"	7"
05**006135**001	1,6	8,0	200	112	5/16"	8"
05**006140**001	1,6	10,0	200	112	3/8"	8"

[1] without Lasertip

160 i SB VDE Insulated screwdriver for slotted screws

		4013288
05**100000**001	1 x 0.4x2.5x80 [1]	181466
05**100001**001	1 x 0.5x3.0x100 [1]	181473
05**100002**001	1 x 0.6x3.5x100	181480
05**100003**001	1 x 0.8x4.0x100	181497
05**100004**001	1 x 1.0x5.5x125	181503



160 iS VDE Insulated screwdriver with reduced blade diameter for slotted screws



Application: Slotted screws and actuating tool for spring terminals

Blade: Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900

Design: Conical blade, zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm		
05**006440**001	0,6	3,5	100	81	9/64"	4"
05**006441**001	0,8	4,0	100	98	5/32"	4"
05**006442**001	1,0	5,5	125	98	7/32"	5"

160 iSS VDE Insulated screwdriver with reduced blade diameter for slotted screws



Application: Slotted screws and actuating tool for spring terminals

Blade: Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900

Design: Conical blade, zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (yellow = slotted) and size stamp.

	mm	mm	mm	mm		
05**020129**001	0,8	4,0	100	81	5/32"	4"

162 i PH VDE Insulated screwdriver for Phillips screws



Application: Phillips screws

Blade: Insulated, individually tested as per IEC 60900

Design: Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

		mm	mm	
05**006150**001 [1]	PH 0	80	81	3 1/8"
05**006152**001	PH 1	80	98	3 1/8"
05**006153**001	PH 1	150	98	6"
05**006154**001	PH 2	100	105	4"
05**006159**001	PH 2	200	105	8"
05**006156**001	PH 3	150	112	6"
05**006158**001 [1]	PH 4	200	112	8"

[1] without Lasertip


162 i PH SB VDE Insulated screwdriver for Phillips screws

		4013288
05**100011**001	1 x PH 1x80	181442
05**100012**001	1 x PH 2x100	181459



Tip

VDE-insulated screwdriver with reduced blade diameter



Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900.

LASERTIP


How to prevent the screwdriver from slipping out of the screw head?



It happens time and time again that the tip slips out of the screw head when screwdriving, sometimes damaging valuable surfaces or even causing injury. The tips of the Wera Lasertip screwdrivers are microscopically roughened by means of a laser. This rough surface literally “bites” itself firmly into the screw head. Slipping out becomes a thing of the past.

TAKE IT EASY TOOL FINDER

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

Kraftform Plus – Series 100 VDE

The safety screwdriver for working with live wiring

162 iS PH VDE Insulated screwdriver with reduced blade diameter for Phillips screws



Application: Phillips screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PH screws to be accessed and actuated, individually tested as per IEC 60900

Design: Blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

		mm	mm	
05**006450**001	PH 1	80	98	3 1/8“
05**006451**001	PH 2	100	105	4“

162 iSS PH VDE Insulated screwdriver with reduced blade diameter for Phillips screws



Application: Phillips screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PH screws to be accessed and actuated, individually tested as per IEC 60900

Design: Blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (red = Phillips) and size stamp.

		mm	mm	
05**020131**001	PH 1	80	81	3 1/8"
05**020133**001	PH 2	100	98	4"

165 i PZ VDE Insulated screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Insulated, individually tested as per IEC 60900

Design: Lasertip

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (black = Pozidriv) and size stamp.

		mm	mm	
05**006160**001 [1]	PZ 0	80	81	3 1/8"
05**006162**001	PZ 1	80	98	3 1/8"
05**006163**001	PZ 1	150	98	6"
05**006164**001	PZ 2	100	105	4"
05**006165**001	PZ 2	200	105	8"
05**006166**001	PZ 3	150	112	6"
05**006168**001 [1]	PZ 4	200	112	8"

[1] without Lasertip

165 i PZ SB VDE Insulated screwdriver for Pozidriv screws

		4013288
05**100015**001	1 x PZ 1x80	181510
05**100016**001	1 x PZ 2x100	181527



165 iS PZ VDE Insulated screwdriver with reduced blade diameter for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PZ screws to be accessed and actuated, individually tested as per IEC 60900

Design: Blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (black = Pozidriv) and size stamp.

		mm	mm	
05**006460**001	PZ 1	80	98	3 1/8"
05**006461**001	PZ 2	100	105	4"

162 i PH/S VDE Insulated screwdriver for PlusMinus screws (Phillips/slotted)



Application: PlusMinus screws (Phillips/slotted)

Blade: Insulated, individually tested as per IEC 60900

Design: PlusMinus (Phillips/slotted)

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	
05**006380**001	# 1	80	98	3 1/8"
05**006381**001	# 2	100	105	4"


162 i PH/S SB VDE Insulated screwdriver for PlusMinus screws (Phillips/slotted)

		4013288
05**100019**001	**162 i PH/S VDE** 1 x # 1x80	186560
05**100020**001	**162 i PH/S VDE** 1 x # 2x100	186577



Tip

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

PlusMinus screwdrivers



For the use in terminal blocks, control cabinets, switches, relays, sockets etc.

Non-roll feature



All Kraftform screwdrivers have a non-roll feature at the lower end of the handle. The hexagonal design prevents any annoying rolling away of the screwdriver at the workplace.

Kraftform Plus – Series 100 VDE

The safety screwdriver for working with live wiring

162 iS PH/S VDE Insulated screwdriver with reduced blade diameter for PlusMinus screws (Phillips/slotted)



Application: PlusMinus screws (Phillips/slotted)

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PlusMinus screws to be accessed and actuated, individually tested as per IEC 60900

Design: Combination profile Phillips/slotted, blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	
05**006455**001	# 1	80	98	3 1/8"
05**006456**001	# 2	100	105	4"

165 i PZ/S VDE Insulated screwdriver for PlusMinus screws (Pozidriv/slotted)



Application: For PlusMinus screws (Pozidriv/slotted)

Blade: Insulated, individually tested as per IEC 60900

Design: PlusMinus (Pozidriv/slotted)

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	
05**006190**001	# 1	80	98	3 1/8"
05**006191**001	# 2	100	105	4"

165 i PZ/S SB VDE Insulated screwdriver for PlusMinus screws (Pozidriv/slotted)

		4013288
05**100021**001	**165 i PZ/S VDE** 1 x # 1x80	186584
05**100022**001	**165 i PZ/S VDE** 1 x # 2x100	186591



165 iS PZ/S VDE Insulated screwdriver with reduced blade diameter for PlusMinus screws (Pozidriv/slotted)



Application: For PlusMinus screws (Pozidriv/slotted)

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PlusMinus screws to be accessed and actuated, individually tested as per IEC 60900

Design: PlusMinus (Pozidriv/slotted), blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	
05**006465**001	# 1	80	98	3 1/8"
05**006466**001	# 2	100	105	4"

165 iSS PZ/S VDE Insulated screwdriver with reduced blade diameter for PlusMinus screws (Pozidriv/slotted)



Application: For PlusMinus screws (Pozidriv/slotted)

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PlusMinus screws to be accessed and actuated, individually tested as per IEC 60900

Design: PlusMinus (Pozidriv/slotted), blade zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	
05**020132**001	# 1	80	81	3 1/8"
05**020134**001	# 2	100	98	4"

167 i VDE Insulated screwdriver for TORX® screws



Application: TORX® socket screws

Blade: Insulated, individually tested as per IEC 60900

Design: Zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (green = TORX®) and size stamp.

		mm	mm	
05**006181**001	TX 5	80	81	3 1/8"
05**006182**001	TX 6	80	81	3 1/8"
05**006183**001	TX 7	80	81	3 1/8"
05**006184**001	TX 8	80	81	3 1/8"
05**006169**001	TX 9	80	81	3 1/8"
05**006170**001	TX 10	80	81	3 1/8"
05**006172**001	TX 15	80	98	3 1/8"
05**006174**001	TX 20	80	98	3 1/8"
05**006176**001	TX 25	100	105	4"
05**006177**001	TX 27	100	105	4"
05**006178**001	TX 30	100	105	4"
05**006179**001	TX 40	150	112	6"
05**006186**001	TX 45	150	112	6"

164 i VDE Insulated screwdriver for hexagon socket screws



Application: Hexagon socket screws

Blade: Insulated, individually tested as per IEC 60900

Design: Zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component. “Take it easy” tool finder: colour coding according to profile (blue = hexagon) and size stamp.

	mm	mm	mm	
05**004650**001	2,5	80	98	3 1/8"
05**004655**001	3,0	80	98	3 1/8"
05**004660**001	4,0	80	98	3 1/8"
05**004665**001	5,0	80	105	3 1/8"
05**004670**001	6,0	100	105	4"
05**004675**001	8,0	100	112	4"

Tip


Tested for dielectric strength




Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.



The super slim VDE screwdrivers



The super slim VDE screwdrivers for installation jobs in particularly confined spaces. Not only do the blades have a reduced diameter, the handles also have a very slim design.



Kraftform Plus – Series 100 VDE

The safety screwdriver for working with live wiring

168 i VDE Insulated screwdriver for square socket head screws



Application: Square socket head screws

Blade: Insulated, individually tested as per IEC 60900

Design: Zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component

			mm	mm	
05**004780**001		# 1	80	98	3 1/8"
05**004783**001		# 1	150	98	6"
05**004781**001		# 2	100	105	4"
05**004784**001		# 2	200	105	8"
05**004782**001		# 3	150	112	6"

168 i SB VDE Insulated screwdriver for square socket head screws

		4013288
05**100024**001	1 x # 1x80	181534
05**100025**001	1 x # 2x100	181541
05**100026**001	1 x # 3x150	181558



190 i VDE Insulated nutdriver



Application: Hexagon headed bolts, screws and nuts

Blade: Insulated, individually inspected as per IEC 60900

Design: Zinc-phosphated

Handle: Kraftform with non-roll feature, multi-component

	mm		mm	mm	mm	
05**005300**001	5,5		125	98	11,0	5"
05**005305**001	6,0		125	98	12,0	5"
05**005310**001	7,0		125	105	14,0	5"
05**005315**001	8,0		125	105	15,0	5"
05**005320**001	9,0		125	105	16,0	5"
05**005325**001	10,0		125	112	17,0	5"
05**005330**001	11,0		125	112	19,0	5"
05**005335**001	12,0		125	112	20,0	5"
05**005340**001	13,0		125	112	21,0	5"
05**104900**001	-	3/16"	125	98	11,0	5"
05**345280**001	-	7/32"	125	98	12,0	5"
05**104905**001	-	1/4"	125	98	13,0	5"
05**104901**001	-	5/16"	125	105	15,0	5"
05**104906**001	-	3/8"	125	105	17,0	5"
05**104902**001	-	7/16"	125	112	19,0	5"
05**104904**001	-	1/2"	125	112	21,0	5"
05**104903**001	-	9/16"	125	112	23,0	5"
05**104907**001	-	5/8"	125	112	25,0	5"

247 Single-pole voltage tester



Application: Voltage testing
Standard: ISO 57680/6 and VDE 0680/6 for 150 to 250 V


	mm	mm	mm	mm		
05**005655**001	0,5	3,0	70	3,0	1/8"	2 3/4"

Product not available in the USA and Canada.

247 SB Single-pole voltage tester

		4013288
05**100100**001	1 x 0.5x3.0x70	181664

Product not available in the USA and Canada.



Tip

KRAFTFORM ERGONOMICS

Why is the Kraftform Plus handle made out of several components?



Wera produces the Kraftform handle out of several materials with different properties. A resistant plastic is used for the core which ensures that the blade is held securely even under high strain. A softer material is used for the coloured soft zones, which provides high frictional resistance and allows the transfer of high forces – resulting in less required screwdriving effort. The red sections with their hard surfaces prevent any "sticking" of the hand to the handle, making rapid repositioning of the hand possible.

Impact strength



Impact strength tested at -40°C, guaranteeing safety even under extreme conditions.

Kraftform Plus – Series 100 VDE

The safety screwdriver for working with live wiring

Kraftform Big Pack 100 VDE



Kraftform: The safety screwdriver with Lasertip blade, voltage tester and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips, PlusMinus (Pozidriv/slotted), Pozidriv and TORX® screws

Content: 14-piece set in display carton

05**105631**001		
	162 i PH VDE	1 x PH 1x80; 1 x PH 2x100
	165 i PZ VDE	1 x PZ 1x80; 1 x PZ 2x100
	165 i PZ/S VDE	1 x # 1x80; 1 x # 2x100
	167 i TORX® VDE	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x80
	160 iS	1 x 0,6x3,5x100
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	247	1 x 0,5x3,0x70
	Rack	2 x 190,0x50,0

[1] without Lasertip
[**] Product not available in the USA and Canada.

160 i/6 Rack Screwdriver Set Kraftform Plus Series 100 + Rack



Kraftform: The safety screwdriver. Lasertip blade + rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: For slotted and Phillips screws

Content: 6-pieces set and rack in display carton

05**006145**001		
	162 i PH VDE	1 x PH 1x80; 1 x PH 2x100
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125

[1] without Lasertip

160 i/7 Rack screwdriver set Kraftform Plus Series 100, voltage tester and rack



Kraftform: The safety screwdriver with Lasertip blade, voltage tester and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Phillips screws

Content: 7-piece set and rack in display carton

05**006147**001		
	162 i PH VDE	1 x PH 1x80; 1 x PH 2x100
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	247	1 x 0,5x3,0x70

[1] without Lasertip
[**] Product not available in the USA and Canada.

160 i/165 i/7 Rack screwdriver set Kraftform Plus Series 100, voltage tester and rack



Kraftform: The safety screwdriver with Lasertip blade, voltage tester and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted and Pozidriv screws

Content: 7-piece set and rack in display carton

05**006148**001		
	165 i PZ VDE	1 x PZ 1x80; 1 x PZ 2x100
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	247	1 x 0,5x3,0x70

[1] without Lasertip
[*] Product not available in the USA and Canada.

167 i/6 Screwdriver set Kraftform Plus Series 100



Kraftform: The safety screwdriver. “Take it easy” tool finder: colour coding according to profile and size stamp.


Application: TORX® socket screws

Content: 6-piece set

05**133356**001		
	167 i TORX® VDE	1 x TX 8x80; 1 x TX 9x80; 1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x80; 1 x TX 25x100

Tip

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

Tested for dielectric strength



Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.

Lasertip



A precisely-focused laser creates a sharp-edged surface structure. This laser treatment results in an edge hardness of up to 1000 HV 0.3. Wera Lasertip “bites” itself into the screw head and prevents any slips out of the recess. It is available for screwdrivers for slotted, Phillips and Pozidriv screws.

Kraftform Plus – Series 100 VDE

The safety screwdriver for working with live wiring

160 iS/7 Rack screwdriver set Kraftform Plus Series 100, voltage tester and rack. With reduced blade diameter



Kraftform: The safety screwdriver. With reduced blade diameter, voltage tester and rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips, PlusMinus screws (Pozidriv/slotted)

Content: 7-piece set and rack in display carton

05**006480**001		
	162 iS	1 x PH 1x80; 1 x PH 2x100
	165 iS PZ/S	1 x # 2x100
	160 iS	1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	247	1 x 0,5x3,0x70

**) Product not available in the USA and Canada.

160 iSS/7 screwdriver set Kraftform Plus Series 100. With reduced blade diameter and smaller handle diameters



Kraftform: The safety screwdriver. With reduced blade diameter and partially smaller handle diameters. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips, PlusMinus screws (Pozidriv/slotted)

Content: 7-piece set

05**135961**001		
	160 iSS	1 x 0,8x4,0x100
	160 iS	1 x 0,6x3,5x100; 1 x 1,0x5,5x125
	162 iSS	1 x PH 1x80; 1 x PH 2x100
	165 iSS PZ/S	1 x # 1x80; 1 x # 2x100

160 i/168 i/6 Rack screwdriver set Kraftform Plus Series 100 and rack



Kraftform: The safety screwdriver. Lasertip blade + rack. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: For slotted, Phillips and square socket screws

Content: 6-pieces set and rack in display carton

05**347777**001		
	162 i PH VDE	1 x PH 1x80; 1 x PH 2x100
	160 i VDE	1 x 0,6x3,5x100; 1 x 1,0x5,5x125
	168 i VDE	1 x # 1x80; 1 x # 2x100

160 i/162 i/167 i/9 Screwdriver set Kraftform Plus Series 100



Kraftform: The safety screwdriver. “Take it easy” tool finder: colour coding according to profile and size stamp.

Application: Slotted, Phillips, Pozidriv, PlusMinus (Pozidriv/slotted) and TORX® socket screws


Content: 9-piece set

05**133355**001		
	162 i PH VDE	1 x PH 2x100
	165 i PZ VDE	1 x PZ 2x100
	165 i PZ/S VDE	1 x # 1x80; 1 x # 2x100
	167 i TORX® VDE	1 x TX 15x80; 1 x TX 20x80; 1 x TX 25x100
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 1,0x5,5x125

[1] without Lasertip

Kraftform 2go 100





11 VDE-insulated, Kraftform screwdrivers for cross recess screws Phillips and Pozidriv, TORX® and slotted screws. “Take it easy” tool finder: colour coding according to profile and size stamp.

1 dimensionally stable and robust Tool Quiver, equipped with handle for the storage and transport of tools; high resistance against cuts and stabs; comes with hook and loop fastener zone for docking with the Wera 2go system and includes 1 variably adjustable hook and loop fastener partition for a division into as many as 5 sections.


05**004310**001		
	Wera 2go 4	1 x 165,0x165,0x105
	162 i PH VDE	1 x PH 1x80; 1 x PH 2x100
	165 i PZ VDE	1 x PZ 1x80; 1 x PZ 2x100
	167 i TORX® VDE	1 x TX 10x80; 1 x TX 15x80; 1 x TX 20x80
	160 i VDE	1 x 0,4x2,5x80 [1]; 1 x 0,8x4,0x150; 1 x 1,0x5,5x200
	160 iS	1 x 0,6x3,5x100
	Hook and Loop Fastener Strip 120	1 x 50,0x120,0

[1] without Lasertip

Tip

TAKE IT EASY TOOL FINDER

Screwdrivers “Take it easy”



“Take it easy” tool finder: colour coding according to profile and size stamp. This enables faster and more reliable selection of the correct tool from the tool case.

At the workplace and when out and about




The large set-down area improves the stability of the Tool Quiver. Its large handle means that the quiver can be easily transported or simply hung up at the workplace.

High resistance against cuts and stabs



The robust and dimensionally stable material is very resistant against cuts and stabs. The tools carried are protected against damage and moisture. This enhances the service life of the tool box.

Perfect system supplement



Thanks to its hook and loop fastener zone, the Tool Box can be docked with the Wera 2go 1 Tool Carrier and with the Wera 2go 2 Tool Container.

Kraftform Kompakt VDE

Why is the right tool so often missing at the workplace? The reason: too many tools and overly-heavy tool bags can make it bothersome to carry keep them with you.

So for us it was a clear challenge: to develop a tool that is suitable for a whole host of applications and can be easily taken along to the workplace.

Our solution: Kraftform Kompakt tools. A handle into which blades with a range of different profiles can be inserted. Compactly and protectively housed in a light and robust textile pouch – and they are even VDE-tested, too.





Kraftform Kompakt VDE sets come with an insulated handle and insulated interchangeable blades, that can be exchanged without any special tools.



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.



Each Kraftform Kompakt VDE set has been tested individually at 10,000 volts, in accordance with IEC 60900.This ten-times-higher testing load guarantees safe working at their maximum permitted load of 1,000 volts.





The tools can be stored and carried in a robust belt pouch, keeping them always to hand.



The hard materials used for the handle ensure rapid hand repositioning, without any danger of the skin “sticking” to the handle. The softer “anti-slip” zones enable the low-loss transfer of high forces – resulting in less screwdriving effort being required.



The outstanding design of the Kraftform handle ensures that it fits perfectly into the hand, preventing hand injuries such as blisters and calluses.

Kraftform Kompakt VDE

Versatile tools for work on live wiring

Kraftform Kompakt VDE 15 Torque 1.2-3.0 Nm extra slim 1



1 Series 7400 VDE Kraftform adjustable torque handle (1.2 - 3.0 Nm) for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long) with reduced blade diameter (articles KK 60 i 0,4x2,5 and KK 67 i TX 10 conventional diameter) with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated

15-piece set

05**059291**001		
	7400 VDE	1 x 7441 VDEx1,2-3,0
	KK 62 iS	1 x PH 1x154; 1 x PH 2x154
	KK 65 iS PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 iS PZ/S	1 x # 1x154; 1 x # 2x154
	KK 67 i TORX®	1 x TX 10x154
	KK 67 iS TORX®	1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
	KK 60 i	1 x 0,4x2,5x154
	KK 60 iS	1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154

Kraftform Kompakt VDE 16 Torque 1.2-3.0 Nm extra slim 1



1 Series 7400 VDE Kraftform adjustable torque handle (1.2 - 3.0 Nm) and 1 Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long) with reduced blade diameter (articles KK 60 i 0,4x2,5 and KK 67 i TX 10 conventional diameter) with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated

16-piece set

05**135906**001		
	7400 VDE	1 x 7441 VDE, 1,2-3,0 Nm
	817 VDE	1 x 9x102
	KK 62 iS	1 x PH 1x154; 1 x PH 2x154
	KK 65 iS PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 iS PZ/S	1 x # 1x154; 1 x # 2x154
	KK 67 i TORX®	1 x TX 10x154
	KK 67 iS TORX®	1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
	KK 60 i	1 x 0,4x2,5x154
	KK 60 iS	1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154

Kraftform Kompakt VDE 18 Universal 1



1x Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long)
Single-pole voltage tester
18-piece set

05**003471**001		
	817 VDE	1 x 9x102
	KK 62 i	1 x PH 1x154; 1 x PH 2x154
	KK 62 i PH/S	1 x # 1x154; 1 x # 2x154
	KK 65 i PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 i PZ/S	1 x # 1x154; 1 x # 2x154
	KK 60 i	1 x 0,4x2,5x154; 1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154
	KK 96 VK 6,3	1 x 6,3x89
	KK 97 VK 8,1	1 x 8,1x89
	KK 98 DK	1 x 89
	KK 99 FL	1 x 89
	247	1 x 0,5x3,0x70

Product not available in the USA and Canada.

Tip

Kraftform VDE adjustable torque handle







Simple setting of the required torque by hand.

Easy-to-read scale value. Measurement accuracy is ± 6 % in accordance with the standard EN ISO 6789.

Distinctly audible and noticeable excess-load signal when the preset torque is reached.









Kraftform Kompakt VDE

Versatile tools for work on live wiring

Kraftform Kompakt VDE 18 Imperial 1





2x Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (154 mm long)

18-piece set

05**347108**001		
	817 VDE	2 x 9x102
	KK 62 i	1 x PH 1x154; 1 x PH 2x154
	KK 62 i PH/S	1 x # 1x154; 1 x # 2x154
	KK 65 i PZ/S	1 x # 1x154; 1 x # 2x154
	KK 60 i	1 x 0,4x2,5x154; 1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154
	KK 68 i	1 x # 1x154; 1 x # 2x154
	KK 96 VK 6,3	1 x 6,3x89
	KK 97 VK 8,1	1 x 8,1x89
	KK 98 DK	1 x 89
	KK 99 FL	1 x 89

Kraftform Kompakt VDE 18 Universal 2





2x Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long)
18-piece set

05**347107**001		
	817 VDE	2 x 9x102
	KK 62 i	1 x PH 1x154; 1 x PH 2x154
	KK 62 i PH/S	1 x # 1x154; 1 x # 2x154
	KK 60 i	1 x 1,0x5,5x154; 1 x 0,4x2,5x154; 1 x 0,6x3,5x154; 1 x 0,8x4,0x154
	KK 65 i PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 i PZ/S	1 x # 1x154; 1 x # 2x154
	KK 96 VK 6,3	1 x 6,3x89
	KK 97 VK 8,1	1 x 8,1x89
	KK 98 DK	1 x 89
	KK 99 FL	1 x 89

Kraftform Kompakt VDE 17 Universal 1



2x 817 VDE Kraftform handle for Wera VDE interchangeable blades only

VDE exchangeable blades (each 154 mm long)
17-piece set

05**059030**001		
	817 VDE	2 x 9x102
	KK 62 i	1 x PH 1x154; 1 x PH 2x154
	KK 65 i PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 i PZ/S	1 x # 1x154; 1 x # 2x154
	KK 67 i TORX®	1 x TX 10x154; 1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
	KK 60 i	1 x 0,4x2,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154; 1 x 1,2x6,5x154
	KK 60 iS	1 x 0,6x3,5x154

Tip

One handle – many interchangeable blades



The system “one handle – many interchangeable blades” makes Kraftform Kompakt VDE compact screwdriving sets for in-house as well as mobile electrical applications out of the sets. The belt pouch is practical for tidy storage and transportation. Also available with electrical cabinet keys conforming to the industrial standards.

Tested for dielectric strength



Our screwdrivers are tested for dielectric strength under a 10,000 volt load to make sure that their most important property, their insulation, has been exhaustively tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.

Kraftform Kompakt VDE

Versatile tools for work on live wiring

Kraftform Kompakt VDE 16 Universal 1





1 Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long)
Single-pole voltage tester
16-piece set

05**003474**001		
	817 VDE	1 x 9x102
	KK 62 i	1 x PH 1x154; 1 x PH 2x154
	KK 65 i PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 i PZ/S	1 x # 1x154; 1 x # 2x154
	KK 67 i TORX®	1 x TX 10x154; 1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
	KK 60 i	1 x 0,4x2,5x154; 1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154
	247	1 x 0,5x3,0x70

Product not available in the USA and Canada.

Kraftform Kompakt VDE 16 extra slim 1





1 Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long) with reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated

Single-pole voltage tester

16-piece set

05**003484**001		
	817 VDE	1 x 9x102
	KK 62 iS	1 x PH 1x154; 1 x PH 2x154
	KK 65 iS PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 65 iS PZ/S	1 x # 1x154; 1 x # 2x154
	KK 67 i TORX®	1 x TX 10x154
	KK 67 iS TORX®	1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
	KK 60 i	1 x 0,4x2,5x154
	KK 60 iS	1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154
	247	1 x 0,5x3,0x70

Product not available in the USA and Canada.

Kraftform Kompakt VDE 7 Universal 1



1 Kraftform handle 817 VDE for Wera interchangeable blades only

VDE interchangeable blades (each 154 mm long)

7-piece set

05**003470**001		
◉	**817 VDE**	1 x 9x102
✪	**KK 62 i**	1 x PH 1x154; 1 x PH 2x154
⛀	**KK 60 i**	1 x 0,4x2,5x154; 1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154

Kraftform Kompakt VDE 7 Universal 2



1 Kraftform handle 817 VDE for Wera interchangeable blades only

VDE interchangeable blades (each 154 mm long)

7-piece set

05**003472**001		
◉	**817 VDE**	1 x 9x102
✪	**KK 65 i PZ**	1 x PZ 1x154; 1 x PZ 2x154
⛀	**KK 60 i**	1 x 0,4x2,5x154; 1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154

Kraftform Kompakt VDE 7 Imperial 1



1 Kraftform handle 817 VDE for Wera VDE interchangeable blades only

VDE interchangeable blades (each 154 mm long)
7-piece set

05**003473**001		
◉	**817 VDE**	1 x 9x102
✪	**KK 62 i**	1 x PH 1x154; 1 x PH 2x154
⛀	**KK 60 i**	1 x 0,6x3,5x154; 1 x 1,0x5,5x154
◘	**KK 68 i**	1 x # 1x154; 1 x # 2x154

Kraftform Kompakt VDE

Versatile tools for work on live wiring

Series 7400 VDE Kraftform adjustable torque handle (0.3-3.5 Nm)



Application: For Wera interchangeable Kraftform Kompakt VDE blades only

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale, audible excess-load signal

Handle: Kraftform with non-roll feature, multi-component

		mm	Nm	Nm	mm	
05**074752**001	7440 VDE	9	0,3-1,2	0,05	192	7 9/16"
05**074750**001	7441 VDE	9	1,2-3,0	0,10	192	7 9/16"
05**074757**001	7444 VDE	9	1,7-3,5	0,10	192	7 9/16"

817 VDE Kraftform blade-holding handle



Application: For Wera interchangeable VDE blades only

Handle: Kraftform with non-roll feature, multi-component

	mm	mm
05**003990**001	9	102

Kraftform Kompakt VDE 60 i



Application: Slotted screws

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Conical blade, zinc-phosphated, Black Point

	mm	mm	mm		
05**003400**001	0,4	2,5	154	3/32"	6 1/16"
05**003401**001	0,5	3,0	154	1/8"	6 1/16"
05**003402**001	0,6	3,5	154	9/64"	6 1/16"
05**003403**001	0,8	4,0	154	5/32"	6 1/16"
05**003404**001	1,0	5,5	154	7/32"	6 1/16"
05**003405**001	1,2	6,5	154	1/4"	6 1/16"

Kraftform Kompakt VDE 60 iS



Application: Slotted screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken screws and spring elements to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Conical blade, zinc-phosphated, Black Point

	mm	mm	mm		
05**003406**001	0,6	3,5	154	9/64"	6 1/16"
05**003407**001	0,8	4,0	154	5/32"	6 1/16"
05**003408**001	1,0	5,5	154	7/32"	6 1/16"

Kraftform Kompakt VDE 62 i



Application: Phillips screws

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003410**001	PH 0	154	6 1/16"
05**003411**001	PH 1	154	6 1/16"
05**003412**001	PH 2	154	6 1/16"

Kraftform Kompakt VDE 62 iS





Application: Phillips screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PH screws to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003413**001	PH 1	154	6 1/16"
05**003414**001	PH 2	154	6 1/16"

Kraftform Kompakt VDE 65 i



Application: Pozidriv screws

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003450**001	PZ 0	154	6 1/16"
05**003451**001	PZ 1	154	6 1/16"
05**003452**001	PZ 2	154	6 1/16"

Kraftform Kompakt VDE 65 iS





Application: Pozidriv screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PZ screws to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003455**001	PZ 1	154	6 1/16"
05**003456**001	PZ 2	154	6 1/16"

Tip



Kraftform VDE adjustable torque handle





Simple setting of the required torque by hand.

Easy-to-read scale value. Measurement accuracy is ± 6 % in accordance with the standard EN ISO 6789.

Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.











Kraftform Kompakt VDE

Versatile tools for work on live wiring

Kraftform Kompakt VDE 62 i PH/S



Application: PlusMinus screws, slotted/Phillips

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: PlusMinus, slotted/Phillips, zinc-phosphated, Black Point

	⊕	mm	
05**003440**001	# 1	154	6 1/16"
05**003441**001	# 2	154	6 1/16"

Kraftform Kompakt VDE 62 iS PH/S



Application: PlusMinus screws, slotted/Phillips

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PlusMinus screws to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: PlusMinus, slotted/Phillips, zinc-phosphated, Black Point

	⊕	mm	
05**003442**001	# 1	154	6 1/16"
05**003443**001	# 2	154	6 1/16"

Kraftform Kompakt VDE 65 i PZ/S



Application: PlusMinus screws, slotted/Pozidriv

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: PlusMinus, slotted/Pozidriv, zinc-phosphated, Black Point

	✪	mm	
05**003445**001	# 1	154	6 1/16"
05**003446**001	# 2	154	6 1/16"

Kraftform Kompakt VDE 65 iS PZ/S



Application: PlusMinus screws, slotted/Pozidriv

Blade: Reduced blade diameter with integrated protective insulation, allows sunken PlusMinus screws to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: PlusMinus, slotted/Pozidriv, zinc-phosphated, Black Point

	✪	mm	
05**003447**001	# 1	154	6 1/16"
05**003448**001	# 2	154	6 1/16"

Kraftform Kompakt VDE 67 i TORX®



Application: TORX® socket screws

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

	✪	mm	
05**003429**001 [1]	TX 8	154	6 1/16"
05**003430**001	TX 9	154	6 1/16"
05**003431**001	TX 10	154	6 1/16"
05**003432**001	TX 15	154	6 1/16"
05**003433**001	TX 20	154	6 1/16"
05**003434**001	TX 25	154	6 1/16"
05**003435**001	TX 27	154	6 1/16"
05**003436**001	TX 30	154	6 1/16"

[1] available from May 2018

Kraftform Kompakt VDE 67 iS TORX®



Application: TORX® socket screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken TORX® socket screws to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003437**001	TX 15	154	6 1/16"
05**003438**001	TX 20	154	6 1/16"
05**003439**001	TX 25	154	6 1/16"

Kraftform Kompakt VDE 68 i



Application: Square socket head screws

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003415**001	# 1	154	6 1/16"
05**003416**001	# 2	154	6 1/16"

Kraftform Kompakt VDE 68 iS



Application: Square socket head screws

Blade: Reduced blade diameter with integrated protective insulation, allows sunken square socket head screws to be accessed and actuated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer

Design: Zinc-phosphated, Black Point

		mm	
05**003417**001	# 1	154	6 1/16"
05**003418**001	# 2	154	6 1/16"

Kraftform Kompakt VDE 64 i



Application: Hexagon socket screws

Blade: Insulated, individually tested as per IEC 60900

Drive: 9 mm hexagonal with entry chamfer


Design: Zinc-phosphated, Black Point

	mm	mm	
05**003420**001	2,5	154	6 1/16"
05**003421**001	3,0	154	6 1/16"
05**003422**001	4,0	154	6 1/16"
05**003423**001	5,0	154	6 1/16"
05**003424**001	6,0	154	6 1/16"

Kraftform Kompakt VDE

Versatile tools for work on live wiring

Kraftform Kompakt 96 VK 6,3



Switch cabinet key, 6.3 mm, glass-fibre reinforced

	mm	mm	
05**003460**001	6,3	89	3 9/16"


Kraftform Kompakt 97 VK 8,1



Switch cabinet key, 8.1 mm, glass-fibre reinforced

	mm	mm	
05**003461**001	8,1	89	3 9/16"


Kraftform Kompakt 98 DK



Switch cabinet key, glass-fibre reinforced

	mm		
05**003462**001		89	3 9/16"

Kraftform Kompakt 99 FL



Switch cabinet key, glass-fibre reinforced

	mm		
05**003463**001		89	3 9/16"


ALPHA SPOT

Kraftform Comfort VDE Screwdrivers

The ergonomic introduction to convenient screwdriving.

Handle with Kraftform geometry and blade made from power bit material with Black Point tip for precise fit – and they are even VDE-tested, too.




Multi-component Kraftform handle, for quick and low-exertion working.




Screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case or at the workplace.



Hexagonal non-roll feature prevents any annoying rolling away at the workplace.





Wera Black Point tips and a refined hardening process ensure long service life of the tip, improved corrosion protection and an exact fit.



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



Kraftform Comfort VDE

Convenient, safe, good!

1160 i VDE Insulated screwdriver for slotted screws



Application: Slotted screws

Blade: Insulated, individually tested as per IEC 60900

Design: Conical tip, chrome-plated, Black Point

Handle: Kraftform Comfort with non-roll feature, multi-component

	mm	mm	mm	mm		
05**031580**001	0,4	2,5	80	81	3/32"	3 1/8"
05**031581**001	0,5	3,0	100	81	1/8"	4"
05**031582**001	0,6	3,5	100	81	9/64"	4"
05**031583**001	0,8	4,0	100	98	5/32"	4"
05**031584**001	0,8	4,0	150	98	5/32"	6"
05**031587**001	1,0	5,5	125	98	7/32"	5"
05**031585**001	1,0	5,5	200	98	7/32"	8"
05**031588**001	1,2	6,5	150	105	1/4"	6"
05**031589**001	1,2	8,0	175	112	5/16"	7"

1162 i PH VDE Insulated screwdriver for Phillips screws



Application: Phillips screws

Blade: Insulated, individually tested as per IEC 60900

Design: Chrome-plated, Black Point

Handle: Kraftform Comfort with non-roll feature, multi-component

		mm	mm	
05**031600**001	PH 0	80	81	3 1/8"
05**031601**001	PH 1	80	98	3 1/8"
05**031602**001	PH 1	150	98	6"
05**031603**001	PH 2	100	105	4"
05**031604**001	PH 2	200	105	8"
05**031605**001	PH 3	150	112	6"

1165 i PZ VDE Insulated screwdriver for Pozidriv screws



Application: Suitable for Pozidriv screws

Blade: Insulated, individually tested as per IEC 60900

Design: Chrome-plated, Black Point

Handle: Kraftform Comfort with non-roll feature, multi-component

		mm	mm	
05**031610**001	PZ 0	80	81	3 1/8"
05**031611**001	PZ 1	80	98	3 1/8"
05**031613**001	PZ 2	100	105	4"
05**031615**001	PZ 3	150	112	6"

1160 i/7 Safety screwdriver set Kraftform Comfort VDE and voltage tester



Application: Slotted and Phillips screws

Content: 7-piece set in display carton

05**031575**001	
	1162 i PH VDE 1 x PH 1x80; 1 x PH 2x100
	1160 i VDE 1 x 0,4x2,5x80; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	4115 1 x 0,5x3,0x65

Product not available in the USA and Canada.

1160 i/1165 i/7 Screwdriver set Kraftform Comfort VDE and voltage tester



Application: Slotted and Pozidriv screws
Content: 7-piece set in display carton

05**031576**001		
	1165 i PZ VDE	1 x PZ 1x80; 1 x PZ 2x100
	1160 i VDE	1 x 0,4x2,5x80; 1 x 0,6x3,5x100; 1 x 0,8x4,0x100; 1 x 1,0x5,5x125
	4115	1 x 0,5x3,0x65

Product not available in the USA and Canada.



Zyklop VDE series

We want users of our tools to work safely and comfortably.

The Zyklop VDE ratchet and matching accessories are the right tools for safe working on electrical systems and impress by their advantages even when used in tight conditions.



The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.



The Zyklop VDE sockets and extensions offer increased safety thanks to their 2-component isolation with yellow insulation core under red insulation outer layer.



The ball lock ensures a secure fit of the sockets and accessories and thus also for increased safety during operation. A short press on the release button and the tool can be changed.





The Zyklop VDE ratchet allows a short return angle of only 4.5° thanks to its 80 teeth.



The extremely slim design of the Zyklop VDE ratchet makes it easy to work even in confined spaces.



The reversing lever ensures a comfortable change of direction.



Zyklop VDE ratchet and accessories

Every piece is safety tested

8007 B VDE Zyklop VDE Ratchet with switch lever and $^{3}/_{8}$" drive



Application: $^{3}/_{8}$" square sockets as well as for $^{3}/_{8}$" adaptors with square drive, with ball locking device

Design: Individually tested as per IEC 60900 at 10,000V for safe working at the approved voltage of 1,000V; slim design to enable work in very confined spaces; fine-tooth mechanism with 80 teeth for a return angle of only 4.5°; switch lever for convenient change of direction; secure socket locking function by push button

		mm
05**004966**001	$^{3}/_{8}$"	222,0

8790 B VDE Zyklop $^{3}/_{8}$" socket



Application: Hexagon headed bolts, screws and nuts

Design: Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer.

	mm	mm	mm	mm
05**004950**001	6,0	46,0	14,8	23,0
05**004951**001	7,0	46,0	15,7	23,0
05**004952**001	8,0	46,0	17,0	23,0
05**004953**001	9,0	46,0	18,2	23,0
05**004954**001	10,0	46,0	19,4	23,0
05**004955**001	11,0	46,0	20,7	23,0
05**004956**001	12,0	46,0	23,0	23,0
05**004957**001	13,0	46,0	23,0	23,0
05**004958**001	14,0	46,0	24,7	23,0
05**004959**001	15,0	46,0	26,0	23,0
05**004960**001	16,0	46,0	26,8	23,0
05**004961**001	17,0	46,0	29,0	23,0
05**004962**001	18,0	46,0	29,6	23,0
05**004963**001	19,0	46,0	30,7	23,0


Schütter
Elektro-Service
6
7
8
9
10
12
13
14
15
16
17
18
19
Wera
Wera

Zyklop VDE ratchet and accessories

Every piece is safety tested

8794 LB VDE Zyklop extension, long, $^3/_8$"



Application: For VDE insulated $^3/_8$" square drive sockets with ball lock

Design: Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core under red isolation outer insulating outer layer

	■	mm
05**004965**001	$^3/_8$"	166,0

8794 SB VDE Zyklop extension, short, $^3/_8$"



Application: For VDE insulated $^3/_8$" square drive sockets with ball lock

Design: Insulated, individually tested as per IEC 60900. Increased safety due to 2-component insulation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer.

	■	mm
05**004964**001	$^3/_8$"	91,0





8100 SB VDE 1 Zyklop Ratchet Set with switch lever, $^{3}/_{8}$" drive, metric



17 pieces; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility. Fleece backing and hook and loop fastener system for easy attachment, e. g. on wall, shelf, workshop trolley and the Wera 2go tool transport system. Smooth rotating mechanism for safe storage and easy removal of the Zyklop VDE sockets.

1 Zyklop Ratchet 8007 B VDE, with switch lever, with $^{3}/_{8}$"drive, 14 Zyklop VDE sockets, 2 Zyklop VDE extensions, one long, one short, all tools insulated, individually tested as per IEC 60900 at 10,000 V for safe working at the approved voltage of 1,000 V. The Zyklop VDE sockets and extensions offer increased safety through 2-component isolation with yellow insulation core, which becomes visible in case of damage to the outer red VDE insulation layer.

05**004970**001		
▢	**8007 B VDE**	1 x 3/8"x222,0
◉	**8790 B VDE**	1 x 6,0x46,0; 1 x 7,0x46,0; 1 x 8,0x46,0; 1 x 9,0x46,0; 1 x 10,0x46,0; 1 x 11,0x46,0; 1 x 12,0x46,0; 1 x 13,0x46,0; 1 x 14,0x46,0; 1 x 15,0x46,0; 1 x 16,0x46,0; 1 x 17,0x46,0; 1 x 18,0x46,0; 1 x 19,0x46,0
▣▢	**8794 SB VDE**	1 x 3/8"x91,0
▣▢	**8794 LB VDE**	1 x 3/8"x166,0

Tip

Compatible with Wera 2go



The textile box of the ratchet set 8100 SB VDE 1 is suitable for attachment to wall, shelf, workshop trolley and the Wera 2go system thanks to its hook and loop fastener system on the back.

Increased security



The Zyklop VDE sockets and extensions offer increased safety thanks to their 2-component isolation with yellow insulation core under red insulation outer layer.


Wera
18

Ratchets

The Zyklop Ratchets, 1/4"


Zyklop Speed 144


Zyklop Metal Push 152


Zyklop Metal Switch 154


Zyklop Accessories 156

The Zyklop Ratchets, 3/8"


Zyklop Speed 172


Zyklop Metal Push 176


Zyklop Metal Switch 178


Zyklop Accessories 180

The Zyklop Ratchets, 1/2"


Zyklop Speed 190


Zyklop Hybrid 194


Zyklop Metal Push 198


Zyklop Metal Switch 200


Zyklop Accessories 202

1/2" Koloss ratchet with hammer function


210

Zyklop Mini 1 & 2


214

Wera ratchets

We simply could not believe that it was not possible to improve on existing standards for ratchets.

We took up the challenges confronting users when working with ratchets. Mostly, it is a question of working speed, confined working space and diverse functionality.

We did a lot of research, until we finally came up with suitable problem solutions that we can offer across the entire range.



The Zyklop Speed Ratchet

The Wera Zyklop Speed ratchet combines the advantages of five different types of ratchet in one. And it is a really fast mover.



The Zyklop Hybrid Ratchet

Combines robustness, slim design, and little weight.



The Zyklop Ratchet Metal Push

Extremely slim. Long leverage. With push-through square.



The Zyklop Ratchet Metal Switch

Extremely slim. Long leverage. With switch lever.



The Koloss Ratchet

The heavy-duty ratchet that can also be safely used as a hammer.



The Zyklop Mini Ratchets

For all difficult-to-access applications.

Zyklop Speed ratchet

We just could not believe that it was not possible to make a ratchet work more quickly.
Moreover, we did not like the way users had to apply many different types of ratchet to get a job done.
We therefore questioned everything that was conventional about ratchets. The Zyklop Speed ratchet is what has emerged. The flywheel design of the Zyklop Speed ensures high working speeds.
And: the Zyklop Speed combines the advantages of 5 types of ratchet in a single tool. Additionally, it can be used as a screwdriver.





The outstanding design of the Kraftform handle fits perfectly into the hand, preventing hand injuries such as blisters and calluses. The hard materials used for the handle ensure quick and easy hand repositioning without any danger of the skin "sticking" to the handle, whilst the softer "anti-slip" zones enable the low-loss transfer of high forces – resulting in less screwdriving effort being required. The circular handle design allows rapid turning in the 0° position.

The ratchet head pivots freely and can be locked into any position by using the slide switch that is positioned on either side. It is even possible to work in very confined and difficult-to-access areas with enhanced hand clearance. The pre-defined locking at 0°, 15° and 90°, both to the right and left, ensure safe working without any slipping of the ratchet head.





All Zyklop Speed ratchets feature a thumbwheel that can be used to quickly and easily switch between clockwise and anticlockwise rotation, at any position. No complicated handling, no loss of time!


The Zyklop Speed ratchets are really fast movers. The gyrating mass design means that screwdriving is accelerated. The rotation-symmetric structure of the Kraftform handle and the free-turning sleeve reinforce this rapid twisting process, particularly when the ratchet does not engage due to too little resistance in the thread.






The reversible ratchet with 72 fine-pitched teeth has a low return angle of only 5°. This short stroke allows fast and precise work in all types of installation.





The ball lock holds the sockets and attachments securely, ensuring safe working. A changeover into any predefined position is completed by simply pressing the release button – this is even the case in the 90° position.



The ratchet head has an ergonomic design with finger recesses that offer a perfect contact surface for the hand or fingers to turn the head.



The ratchet can be used as a conventional screwdriver in the 0° position by attaching a bitholding adaptor and a bit.

Zyklop Hybrid ratchet

We wanted to integrate all the mostly-desired ratchet advantages in a single tool.
Our idea was to develop a light ratchet with an ergonomic handle, slim design, long lever and an extension option.

Since the term “hybrid” refers to a combination from various sectors, it was quite easy to decide on the name.



The reversible ratchet with 72 finepitched teeth has a low return angle of only 5°. This short stroke allows fast and precise work in all types of installation.



The ball lock holds the sockets and attachments securely, ensuring safe working.



Multi-component Kraftform handle for optimum pressure and tensile loads.





Very slim ratchet head.



Larger overall length for higher torque transfer.



Even more torque can be applied by using the extension.



Zyklop Metal ratchet

Due to the ever-more confined working environment, space is becoming more and more an issue for the application of ratchets. Our product developers therefore intensively occupied themselves with the issue of confined working spaces, and Wera has now solved this problem.

The extremely slim and robust Zyklop Metal ratchet with a long lever was what emerged. When the change in direction needs to be quick, the Zyklop Metal Switch ratchet is the right tool.


When the socket must not get lost and a coincidental change of direction has to be avoided at all cost, the Zyklop Metal Push is the correct choice.



Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces.



Zyklop Metal Push
Smooth push-through mechanism, that cannot get lost.



Zyklop Metal Push
The dual-ratchet-teeth design means that a 76 fine-toothing division can be achieved from the 38 robust teeth with a return angle of only 4.7°.





The ball lock holds the sockets and attachments securely, ensuring safe working.







Zyklop Metal Switch
Switch lever for convenient change of direction.



Zyklop Metal Switch
Fine-tooth mechanism with 72 teeth for a return angle of only 5°. This short stroke allows fast and precise work in all types of installation.

Zyklop Accessories

We did not just want our creativity to end with the ratchets themselves so we also occupied ourselves intensively with ratchet accessories. That is why our users are now provided with an extension with freely spinning sleeve and flexible lock to enable more secure and more rapid screwdriving.

The sockets have been completely redesigned: we wanted to spare the user the need of having two different series – one for manual and the other for power tool applications.

And: we wanted to enormous simplify the task of finding the right sizes. Technically, our own ambitious goals represented a real challenge: to endow sockets with the advantage of the holding function on screwdrivers and bits. We succeeded in this!





"Take it easy" tool finder system - with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).



The manual and machine sockets can be used both for hand and power tools use (non-impact). Users need just one socket set for all applications.



Zyklop sockets and bit sockets with holding function securely hold the screw on the tool. This is particularly helpful in difficult-to-access working spaces where the second hand cannot be used to hold the screw.





The extensions from the premium lines are also equipped with the unique “flexible-lock-system”. By activating this system, attachments can be fixed to the extension permanently – preventing slipping and any unintentional loss of the attachment. When the system is deactivated, the sockets can be attached as usual and changed in a flash.



The free-turning sleeve on the Zyklop Speed and the Zyklop extension effectively accelerates the turning of screws and nuts.



Typically Wera designed robust textile belt. A smooth Twist to Unlock mechanism ensures a secure fit and simple removal of the sockets. Includes a snap hook for secure fastening to a belt loop or pocket. Supplied with a non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.


COWL CLOSED

Zyklop Ratchets, 1/4"


	Zyklop Speed	144
	Zyklop Metal Push	152
	Zyklop Metal Switch	154
	Zyklop Accessories	156



The Zyklop Speed Ratchets, 1/4"

Combine 5 types of ratchet

8100 SA All-in Zyklop Speed Ratchet Set, 1/4“ drive, with holding function, metric






42-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

1 Zyklop Speed Ratchet with 1/4" drive, 13 Zyklop sockets with 1/4" drive with fastener holding function, 9 Zyklop bit sockets for TORX® screws, with 1/4" drive, with holding function, 8 bit sockets for hexagon socket screws with 1/4" drive with holding function (sizes 2.0 and 2.5 without holding function) and Hex-Plus high torque geometry, 3 Zyklop bit sockets with 1/4" drive for Phillips screws, 3 Zyklop bit sockets with 1/4" drive for Pozidriv screws, 2 Zyklop bit sockets with 1/4“ drive for slotted screws, Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected, 1 tool for the simple removal of nuts from sockets with holding function, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension.

05**003755**001		
	8000 A	1 x 1/4"x152,0
	8796 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8790 HMA HF	1 x 4,0x23,0; 1 x 4,5x23,0; 1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 9,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0; 1 x 14,0x23,0
	8767 A HF	1 x TX 8x28,0; 1 x TX 9x28,0; 1 x TX 10x28,0; 1 x TX 15x28,0; 1 x TX 20x28,0; 1 x TX 25x28,0; 1 x TX 27x28,0; 1 x TX 30x28,0; 1 x TX 40x28,0
	8740 A	1 x 2,0x28,0; 1 x 2,5x28,0
	8740 A HF	1 x 3,0x28,0; 1 x 4,0x28,0; 1 x 5,0x28,0; 1 x 6,0x28,0; 1 x 7,0x28,0; 1 x 8,0x28,0
	8751 A	1 x PH 1x28,0; 1 x PH 2x28,0; 1 x PH 3x28,0
	8755 A	1 x PZ 1x28,0; 1 x PZ 2x28,0; 1 x PZ 3x28,0
	8700 A FL	1 x 0,8x5,5x28,0; 1 x 1,2x6,5x28,0
	Nut Extractor	1 x 14,0x43,0

8100 SA 6 Zyklop Speed Ratchet Set, 1/4" drive, metric





28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

05**004016**001		
	8000 A	1 x 1/4"x152,0
	8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50
	867/4 Z TORX®	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50
	840/4 Z Hex-Plus	1 x 3,0x50; 1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50

8100 SA 9 Zyklop Speed Ratchet Set, 1/4" drive, imperial



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

05**004019**001		
	8000 A	1 x 1/4"x152,0
	8790 HMA	1 x 3/16"x23,0; 1 x 7/32"x23,0; 1 x 1/4"x23,0; 1 x 9/32"x23,0; 1 x 5/16"x23,0; 1 x 11/32"x23,0; 1 x 3/8"x23,0; 1 x 7/16"x23,0; 1 x 1/2"x23,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50
	867/4 Z TORX®	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50
	840/4 Z Hex-Plus	1 x 5/32"x50; 1 x 3/16"x50; 1 x 7/32"x50; 1 x 1/4"x50

Tip

Zyklop “6 in 1”



1. Fine-tooth ratchet
2. Flex-head ratchet
3. Angle ratchet
4. Quick-release ratchet
5. Power ratchet
6. Screwdriver

New set concept



The textile boxes offer dramatically improved portability, and are space-saving to boot! This means you can now carry the same collection of tools, in a much more compact and comfortable package.



The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged.

“Take it easy”



“Take it easy” tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

The Zyklop Speed Ratchets, 1/4"

Combine 5 types of ratchet

Kraftform Kompakt Zyklop MS1 Metal/Speed 1/4"







8-piece set; in surface-protecting, compact textile box, highly robust; low volume and weight for simplified mobility.

1 Zyklop Speed ratchet with 1/4" drive, 1 Zyklop Metal ratchet with switch lever and 1/4" drive, 1 Zyklop extension (long) with rapid spin sleeve and "flexible-lock" system, 2 Zyklop extensions (short and long) with rapid spin sleeve, 1 adaptor with rapid change chuck, 1 wobble extension, 1 universal joint.

05**135949**001		
	8000 A	1 x 1/4"x152,0
	8004 A	1 x 1/4"x141,0
	8796 LA	1 x 1/4"x150,0
	8794 LA	1 x 1/4"x150,0
	8794 SA	1 x 1/4"x75,0
	8784 A1	1 x 1/4"x1/4"x37,0
	8794 A	1 x 1/4"x56,0
	8795 A	1 x 1/4"x35,5





TEMPEST

The Zyklop Speed Ratchets, 1/4"

Combine 5 types of ratchet

8100 SA 2 Zyklop Speed Ratchet Set, 1/4" drive, metric








42-piece set in strong metal case

1 Zyklop ratchet with 1/4" drive, 13 Zyklop sockets (metric), 2 Zyklop "flexible-lock" extensions (short and long) with free-turning sleeve, 1 wobble extension, 1 sliding T-handle, 1 universal joint, 1 adaptor with quick-release chuck, 22 bits

05**003533**001		
	8000 A	1 x 1/4"x152,0
	8790 HMA	1 x 4,0x23,0; 1 x 4,5x23,0; 1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 9,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0; 1 x 14,0x23,0
	8789 A	1 x 1/4"x110,0
	8794 A	1 x 1/4"x56,0
	8795 A	1 x 1/4"x35,5
	8784 A1	1 x 1/4"x1/4"x37,0
	8796 SA	1 x 1/4"x75,0
	8796 LA	1 x 1/4"x150,0
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25
	867/1 Z TORX® BO	1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 Z	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x8,0x25
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25

8100 SA 4 Zyklop Speed Ratchet Set, 1/4" drive, imperial







41-piece set in strong metal case

1 Zyklop ratchet with 1/4" drive, 10 Zyklop sockets (imperial), 2 Zyklop "flexible-lock" extensions (short and long) with free-turning sleeve, 1 wobble extension, 1 sliding T-handle, 1 universal joint, 1 adaptor with quick-release chuck, 24 bits

05**003535**001		
	8000 A	1 x 1/4"x152,0
	8790 HMA	1 x 3/16"x23,0; 1 x 7/32"x23,0; 1 x 1/4"x23,0; 1 x 9/32"x23,0; 1 x 5/16"x23,0; 1 x 11/32"x23,0; 1 x 3/8"x23,0; 1 x 7/16"x23,0; 1 x 1/2"x23,0; 1 x 9/16"x23,0
	8789 A	1 x 1/4"x110,0
	8794 A	1 x 1/4"x56,0
	8795 A	1 x 1/4"x35,5
	8784 A1	1 x 1/4"x1/4"x37,0
	8796 SA	1 x 1/4"x75,0
	8796 LA	1 x 1/4"x150,0
	867/1 Z TORX® BO	1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 Z	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x8,0x25
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25
	840/1 Z Hex-Plus	1 x 5/64"x25; 1 x 3/32"x25; 1 x 1/8"x25; 1 x 9/64"x25; 1 x 5/32"x25; 1 x 3/16"x25; 1 x 7/32"x25

8100 SA/SC 2 Zyklop Speed Ratchet Set, 1/4" drive and 1/2" drive, metric



43 piece set, in strong metal case

1 Zyklop ratchet with 1/4" drive, 1 Zyklop ratchet with 1/2" drive, 21 Zyklop sockets (metric), 2 Zyklop "flexible-lock" extensions (long) with freewheel sleeve, 1 adaptor with quick-release chuck, 1 Kraftform bitholding screwdriver with Rapidaptor quick-release chuck, 16 bits

05**160785**001		
	8000 A	1 x 1/4"x152,0
	8790 HMA	1 x 4,0x23,0; 1 x 4,5x23,0; 1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 9,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	8784 A1	1 x 1/4"x1/4"x37,0
	8796 LA	1 x 1/4"x150,0
	8000 C	1 x 1/2"x277,0
	8790 HMC	1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0; 1 x 21,0x37,0; 1 x 22,0x37,0; 1 x 24,0x37,0
	8796 LC	1 x 1/2"x250,0
	816 R	1 x 1/4"x119
	800/4 Z	1 x 1,0x5,5x89
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89

Tip

How to notice missing tools more quickly



Perfectly conceived in every detail: the storage case for the Zyklop Speed ratchet sets! The two-tone foam insert section means that the tools can be quickly and reliably replaced, and that missing tools can be detected immediately. The tools and their position can be clearly seen in the lid where they have been laser-etched, ensuring that they are legible even when the insert section is covered with grease, dirt or oil. Additionally, the foam section can be removed and placed in the drawer of a tool cabinet or trolley.

"Flexible-lock-system"



The extensions from the premium lines are also equipped with the unique "flexible-lock-system". By activating this system, attachments can be fixed to the extension permanently – preventing slipping and any unintentional loss of the attachment. When the system is deactivated, the sockets can be attached as usual and changed in a flash.

Is it also possible to reverse the drive with oily hands?



The thumbwheel is designed in such a way that it offers outstanding grip and can, therefore, even be operated with oily fingers.

The Zyklop Speed Ratchets, 1/4"

Combine 5 types of ratchet

Kraftform Kompakt Zyklop Speed







26-piece set in a belt pouch

1 Zyklop Speed ratchet with 1/4" drive, 7 Zyklop sockets (metric), 1 Zyklop extension (long) with free-turning sleeve, 1 adaptor, 16 bits of 50 mm in length

05**051045**001		
	8000 A	1 x 1/4"x152,0
	8784 A1	1 x 1/4"x1/4"x37,0
	8794 LA	1 x 1/4"x150,0
	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50
	867/4 Z TORX®	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50
	800/4 Z	1 x 1,0x5,5x50
	840/4 Z Hex-Plus	1 x 3,0x50; 1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0

" To learn more about this product, scan the QR code. "

8000 A Zyklop Speed Ratchet with 1/4" drive





Application: 1/4" square sockets and 1/4" adaptors with square drive, equipped with ball lock

Design: Flywheel design and easy-to-grip free-turning sleeve for faster work, swivel ratchet head, defined lock positions at 0° and 90° to the left and right as well as at 15° before 90° inwards, at 0° it can be used like a conventional screwdriver, pushbutton release, left/right switchover, fine-tooth design, small return angle of 5°

Handle: Multi-component Kraftform handle ensures minimum fatigue

		mm
05**003500**001	1/4"	152,0

8000 A SB Zyklop Speed Ratchet with 1/4" drive

			4013288
05**073260**001		1 x 1/4"x152.0	128034






The Zyklop Metal Ratchets Push, 1/4"

With push-through square

8100 SA 7 Zyklop Metal Ratchet Set with push-through square, 1/4" drive, metric






28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with push-through square and 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

05**004017**001		
	8003 A	1 x 1/4"x141,0
	8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

8100 SA 10 Zyklop Metal Ratchet Set with push-through square, 1/4" drive, imperial





28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with push-through square and 1/4" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 15 bits

05**004020**001		
	8003 A	1 x 1/4"x141,0
	8790 HMA	1 x 3/16"x23,0; 1 x 7/32"x23,0; 1 x 1/4"x23,0; 1 x 9/32"x23,0; 1 x 5/16"x23,0; 1 x 11/32"x23,0; 1 x 3/8"x23,0; 1 x 7/16"x23,0; 1 x 1/2"x23,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 5/32"x25; 1 x 3/16"x25; 1 x 7/32"x25; 1 x 1/4"x25

8003 A Zyklop Metal Ratchet with push-through square and 1/4" drive



Application: 1/4" square sockets as well as for 1/4" adaptors with square drive, with ball locking device

Design: Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces; the dual-ratchet-teeth design means that a 76 fine-toothing division can be achieved from the 38 robust teeth with a return angle of only 4.7°; simple direction change with the undetachable push-through square and very secure socket lock mechanism

		mm	mm	mm
05**004003**001	1/4"	141,0	21	22

”To learn more about this product, scan the QR code.“

Tip

The Zyklop Metal Ratchets Push



Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces.

Textile boxes



The textile boxes offer dramatically improved portability, and are space-saving to boot!



This means you can now carry the same collection of tools, in a much more compact and comfortable package. The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged. And: it leaves absolutely no signs of scratches on sensitive surfaces.

TAKE IT EASY TOOL FINDER

“Take it easy”




“Take it easy” tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

The Zyklop Metal Ratchets Switch, 1/4"

With switch lever

8100 SA 8 Zyklop Metal Ratchet Set with switch lever, 1/4" drive, metric





28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/4" drive, 9 Zyklop sockets,
1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension,
1 adaptor with quick-release chuck, 15 bits

05**004018**001		
	8004 A	1 x 1/4"x141,0
	8790 HMA	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

8100 SA 11 Zyklop Metal Ratchet Set with switch lever, 1/4" drive, imperial





28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/4" drive, 9 Zyklop sockets,
1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension,
1 adaptor with quick-release chuck, 15 bits

05**004021**001		
	8004 A	1 x 1/4"x141,0
	8790 HMA	1 x 3/16"x23,0; 1 x 7/32"x23,0; 1 x 1/4"x23,0; 1 x 9/32"x23,0; 1 x 5/16"x23,0; 1 x 11/32"x23,0; 1 x 3/8"x23,0; 1 x 7/16"x23,0; 1 x 1/2"x23,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 5/32"x25; 1 x 3/16"x25; 1 x 7/32"x25; 1 x 1/4"x25

8100 SA 12 HF Zyklop Metal Ratchet Set with switch lever, 1/4" drive, metric





13-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/4" drive, 9 Zyklop sockets with 1/4" drive with fastener holding function, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 tool for the simple removal of nuts from sockets with holding function.

05**003756**001		
	8004 A	1 x 1/4“x141,0
	8794 LA	1 x 1/4“x150,0
	8794 A	1 x 1/4“x56,0
	8790 HMA HF	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	Nut Extractor	1 x 14,0x43,0

8004 A Zyklop Metal Ratchet with switch lever and 1/4" drive





Application: 1/4" square sockets as well as for 1/4" adaptors with square drive, with ball locking device

Design: Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces; fine-tooth mechanism with 72 teeth for a return angle of only 5°; switch lever for convenient change of direction; secure socket locking function

		mm	mm	mm
05**004004**001	1/4"	141,0	19	22

Tip

The Zyklop Metal Ratchets Switch



Extremely slim. Long leverage. Very robust without any torque limitation. Forged, full metal ratchet out of chrome molybdenum.

Textile boxes





The textile boxes offer dramatically improved portability, and are space-saving to boot!

This means you can now carry the same collection of tools, in a much more compact and comfortable package. The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged. And: it leaves absolutely no signs of scratches on sensitive surfaces.



“Take it easy”



“Take it easy” tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Zyklop accessories, 1/4"

With amazing product benefits

8790 HMA Zyklop 1/4" socket



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, chrome vanadium, brushed chrome-plated finish.
Take it easy toolfinder: Colour coding to enable the desired socket to be easily located.

		mm		mm	mm	mm	mm
05**003501**001		4,0		23,0	6,9	13,0	10,0
05**003502**001		4,5		23,0	7,5	13,0	10,0
05**003503**001		5,0		23,0	8,2	13,0	10,0
05**003504**001		5,5		23,0	8,8	13,0	10,0
05**003505**001		6,0		23,0	9,4	13,0	10,0
05**003506**001		7,0		23,0	11,0	13,0	10,0
05**003507**001		8,0		23,0	12,0	13,0	10,0
05**003508**001		9,0		23,0	13,0	14,0	10,0
05**003509**001		10,0		23,0	14,5	14,5	-
05**003510**001		11,0		23,0	16,0	15,0	13,0
05**003511**001		12,0		23,0	17,0	16,0	13,0
05**003512**001		13,0		23,0	18,0	17,0	13,0
05**003513**001		14,0		23,0	20,0	18,0	13,0
05**003514**001			3/16"	23,0	7,5	13,0	10,0
05**003515**001			7/32"	23,0	8,8	13,0	10,0
05**003516**001			1/4"	23,0	11,0	13,0	10,0
05**003517**001			9/32"	23,0	11,0	13,0	10,0
05**003518**001			5/16"	23,0	12,0	13,0	10,0
05**003519**001			11/32"	23,0	13,0	14,0	10,0
05**003520**001			3/8"	23,0	14,5	14,5	-
05**003521**001			7/16"	23,0	16,0	15,0	13,0
05**003522**001			1/2"	23,0	18,0	17,0	13,0
05**003523**001			9/16"	23,0	20,0	18,0	13,0

8790 HMA HF Zyklop socket with 1/4" drive with holding function



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, with holding function, chrome vanadium, brushed chrome-plated finish. Take it easy tool finder: Colour coding and large stamp to enable the desired socket to be easily located.

		mm	mm	mm	mm	mm
05**003717**001		4,0	23,0	7,0	11,0	6,5
05**003718**001		4,5	23,0	7,8	11,0	6,5
05**003719**001		5,0	23,0	8,9	11,0	6,5
05**003720**001		5,5	23,0	9,2	11,0	6,5
05**003721**001		6,0	23,0	10,5	11,0	6,5
05**003722**001		7,0	23,0	11,9	11,0	6,5
05**003723**001		8,0	23,0	12,9	11,0	6,5
05**003724**001		9,0	23,0	14,1	12,0	6,5
05**003725**001		10,0	23,0	15,6	12,5	10,0
05**003726**001		11,0	23,0	17,4	13,0	10,0
05**003727**001		12,0	23,0	18,4	14,0	10,0
05**003728**001		13,0	23,0	19,5	15,0	10,0
05**003729**001		14,0	23,0	20,8	16,0	10,0

Belt 1 A Zyklop socket set with holding function, $^1/_4$" drive



10-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with $^1/_4$" drive with fastener holding function. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.
1 tool for the simple removal of nuts from $^1/_4$" sockets with holding function.

05**003880**001		
◉	**8790 HMA HF**	1 x 4,0x23,0; 1 x 4,5x23,0; 1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 13,0x23,0
	Nut Extractor	1 x 14,0x43,0
	Belt A 0/9	1 x 39,0x238,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0



Tip

How to avoid the need for two socket sets – one for manual and one for machine operations



The manual and machine sockets can be used both for hand and power tools use (non-impact). Users need just one socket set for all applications.





Sockets with retaining function for hexagon headed bolts, screws and nuts



The clamping of the screw is achieved by two flexible locking balls and a robust, permanently elastic, heat-shrunk tubing. The tubing is effectively protected against mechanical wear and tear by a steel ring. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.



Textile belt



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.



Nut Extractor



Tool made out of synthetic plastic material (TPE) for the simple removal of nuts from sockets with holding function.

	mm	mm
05**050005**001	14,0	43,0

Belt A 4 Zyklop socket set, 1/4" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Smooth turning Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with 1/4" drive. Take it easy tool finder: Colour coding to enable the desired socket to be easily selected.

05**003883**001		
◉	**8790 HMA**	1 x 5,0x23,0; 1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	Belt A 0/9	1 x 39,0x238,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Tip

Nut extractor tool



This tool enables hexagon nuts to be easily removed from sockets with holding function.






Comes with convenient snap hook



The robust textile belt can be secured to a belt loop or pocket by means of the snap hook.

Secure hold and easy removal



The all new smooth turning mechanism guarantees both secure and rattle-free storage, yet allows easy removal of the tool.

Zyklop accessories, 1/4"

With amazing product benefits

Belt A Imperial 1 Zyklop In-Hex-Plus bit socket set with holding function, 1/4" drive




9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 bit sockets for hexagon socket screws with 1/4" drive with holding function (sizes: 5/64", 3/32" and 7/64" without holding function) and Hex-Plus high torque geometry. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.

05**003884**001		
O	**8740 A**	1 x 5/64"x28,0; 1 x 3/32"x28,0; 1 x 7/64"x28,0
O	**8740 A HF**	1 x 1/8"x28,0; 1 x 9/64"x28,0; 1 x 5/32"x28,0; 1 x 3/16"x28,0; 1 x 7/32"x28,0; 1 x 1/4"x28,0
	Belt A 0/8	1 x 39,0x220,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

8767 A HF TORX® Zyklop bit socket with holding function, 1/4" drive



Application: TORX® socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish, holding function for TORX® screws made according to Acument Intellectual Properties specifications. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located

			mm	mm	mm	mm
05**003360**001		TX 8	28,0	12,0	12,5	11,0
05**003361**001		TX 9	28,0	12,0	12,5	11,0
05**003362**001		TX 10	28,0	12,0	12,5	11,0
05**003363**001		TX 15	28,0	12,0	12,5	11,0
05**003364**001		TX 20	28,0	12,0	12,5	11,0
05**003365**001		TX 25	28,0	12,0	12,5	11,0
05**003366**001		TX 25	100,0	12,0	12,5	83,0
05**003367**001		TX 27	28,0	12,0	12,5	11,0
05**003368**001		TX 27	100,0	12,0	12,5	83,0
05**003369**001		TX 30	28,0	12,0	12,5	11,0
05**003370**001		TX 30	100,0	12,0	12,5	83,0
05**003371**001		TX 40	28,0	12,0	12,5	11,0
05**003372**001		TX 40	100,0	12,0	12,5	83,0

Belt A 3 TORX® HF Zyklop bit-socket set with holding function, 1/4" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the tool sockets.

9 Zyklop bit-sockets for TORX® screws, with 1/4" drive, with holding function. Take it easy tool finder: Colour coding to enable the desired bit-socket to be easily selected.

05**003882**001		
	8767 A HF	1 x TX 8x28,0; 1 x TX 9x28,0; 1 x TX 10x28,0; 1 x TX 15x28,0; 1 x TX 20x28,0; 1 x TX 25x28,0; 1 x TX 27x28,0; 1 x TX 30x28,0; 1 x TX 40x28,0
	Belt A 0/9	1 x 39,0x238,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

8767 A TORX® HF 1 Zyklop bit socket set with holding function, 1/4" drive



4-piece set

Pouch with 100 mm bit sockets

4 Zyklop bit sockets for TORX® screws, with 1/4" drive, with holding function. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.

05**003375**001		
	8767 A HF	1 x TX 25x100,0; 1 x TX 27x100,0; 1 x TX 30x100,0; 1 x TX 40x100,0
	Hook and Loop Fastener Strip 70	1 x 50,0x70,0

Tip

HOLDING FUNCTION

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

Extremely short



The bit sockets from Wera are characterized by a particularly short design. Ideal for working in tight spaces.

Wera bit technology



Due to their high-precision profile design and excellent concentricity properties, Wera bit sockets offer safe work and a long product life.

Zyklop accessories, 1/4"

With amazing product benefits

8740 A HF Zyklop bit socket bit socket with holding function, 1/4“ drive



Application: Hexagon socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish, holding function for hexagon socket screws. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located

		mm		mm	mm	mm	mm
05**003332**001		3,0		28,0	12,0	12,5	11,0
05**003333**001		4,0		28,0	12,0	12,5	11,0
05**003334**001		4,0		100,0	12,0	12,5	83,0
05**003335**001		5,0		28,0	12,0	12,5	11,0
05**003336**001		5,0		100,0	12,0	12,5	83,0
05**003337**001		6,0		28,0	12,0	12,5	11,0
05**003338**001		6,0		100,0	12,0	12,5	83,0
05**003341**001		7,0		28,0	12,0	12,5	11,0
05**003342**001		7,0		100,0	12,0	12,5	83,0
05**003339**001		8,0		28,0	12,0	12,5	11,0
05**003340**001		8,0		100,0	12,0	12,5	83,0
05**003383**001			1/8"	28,0	12,0	12,5	11,0
05**003384**001			9/64"	28,0	12,0	12,5	11,0
05**003385**001			5/32"	28,0	12,0	12,5	11,0
05**003386**001			3/16"	28,0	12,0	12,5	11,0
05**003387**001			7/32"	28,0	12,0	12,5	11,0
05**003388**001			1/4"	28,0	12,0	12,5	11,0
05**003389**001			5/16"	28,0	12,0	12,5	11,0

8740 A Zyklop bit socket, with 1/4" drive



Application: Hexagon socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located

		mm		mm	mm	mm	mm
05**003330**001		2,0		28,0	12,0	12,5	11,0
05**003331**001		2,5		28,0	12,0	12,5	11,0
05**003380**001			5/64"	28,0	12,0	12,5	11,0
05**003381**001			3/32"	28,0	12,0	12,5	11,0
05**003382**001			7/64"	28,0	12,0	12,5	11,0

Belt A 2 Zyklop In-Hex-Plus bit-socket set with holding function, 1/4" drive



8-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

8 bit-sockets for hexagon socket screws with 1/4" drive with holding function and Hex-Plus high torque geometry. Take it easy tool finder: Colour coding to enable the desired bit-socket to be easily selected.

05**003881**001		
	8740 A	1 x 2,0x28,0; 1 x 2,5x28,0
	8740 A HF	1 x 3,0x28,0; 1 x 4,0x28,0; 1 x 5,0x28,0; 1 x 6,0x28,0; 1 x 7,0x28,0; 1 x 8,0x28,0
	Belt A 0/8	1 x 39,0x220,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

8740 A HF 1 Zyklop bit socket set with holding function, 1/4" drive



5-piece set

Pouch with 100 mm bit sockets

5 Zyklop bit sockets for hexagon socket screws, with 1/4" drive, with holding function, Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located.

05**003345**001		
O	**8740 A HF**	1 x 4,0x100,0; 1 x 5,0x100,0; 1 x 6,0x100,0; 1 x 7,0x100,0; 1 x 8,0x100,0
	Hook and Loop Fastener Strip 70	1 x 50,0x70,0

Socket rail A (textile belt), 8 location, unloaded



1 robust textile belt, unloaded, for up to 8 sockets and/or bit sockets with 1/4" drive. Comes with a snap hook to enable secure fastening to a belt loop or pocket. Nonwoven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

05**003890**001		
	Belt A 0/8	1 x 39,0x220,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Tip

HOLDING FUNCTION

Bit sockets with retaining function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Comes with convenient snap hook



The robust textile belt can be secured to a belt loop or pocket by means of the snap hook.

WERA 2GO COMPATIBLE

Textile belt



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.

Zyklop accessories, 1/4"

With amazing product benefits

Socket rail A (textile belt), 9 location, unloaded



1 robust textile belt, unloaded, for up to 9 sockets and/or bit sockets, with 1/4" drive. Comes with a snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

05**003891**001		
	Belt A 0/9	1 x 39,0x238,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

8751 A Phillips Zyklop bit socket with 1/4" drive



Application: Phillips screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish. Output colour coding (red = Phillips) and large stamp to enable the desired bit socket to be easily located.

		mm	mm	mm	mm
05**003350**001	PH 1	28,0	12,0	11,0	12,5
05**003351**001	PH 2	28,0	12,0	11,0	12,5
05**003352**001	PH 3	28,0	12,0	11,0	12,5

8755 A Pozidriv Zyklop bit socket with 1/4" drive



Application: Suitable for Pozidriv screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish. Output colour coding (black = Pozidriv) and large stamp to enable the desired bit socket to be easily located.

		mm	mm	mm	mm
05**003353**001	PZ 1	28,0	12,0	11,0	12,5
05**003354**001	PZ 2	28,0	12,0	11,0	12,5
05**003355**001	PZ 3	28,0	12,0	11,0	12,5

8700 A FL Slotted screws Zyklop bit socket with $^1/_4$" drive



Application: Slotted screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish. Output colour coding (yellow = slotted) and large stamp to enable the desired bit socket to be easily located.

	mm	mm	mm	mm	mm	mm
05**003320**001	0,8	5,5	28,0	12,0	11,0	11,0
05**003321**001	1,0	5,5	28,0	12,0	11,0	11,0
05**003322**001	1,2	6,5	28,0	12,0	11,0	11,0

Tip

Comes with convenient snap hook



The robust textile belt can be secured to a belt loop or pocket by means of the snap hook.



WERA 2GO COMPATIBLE


Practical nonwoven strips



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Zyklop accessories, 1/4"

With amazing product benefits

8796 SA Zyklop "flexible-lock" extension with free-turning sleeve, short, 1/4"





Application: 1/4" square drive sockets with ball lock

Design: Flexible-lock-system either for permanent interlocking or fast change of accessories, free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003530**001	1/4"	75,0

8796 LA Zyklop "flexible-lock" extension with free-turning sleeve, long, 1/4"





Application: 1/4" square drive sockets with ball lock

Design: Flexible-lock-system either for permanent interlocking or fast change of accessories, free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003531**001	1/4"	150,0

8789 A Zyklop sliding T-handle, 1/4"



Application: 1/4" square drive sockets with ball lock

Design: Sliding drive, chrome vanadium, brushed chrome-plated finish

		mm
05**003524**001	1/4"	110,0

8794 LA Zyklop extension with free-turning sleeve, long, 1/4"



Application: 1/4" square drive sockets with ball lock

Design: Easy-to-grip free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003526**001	1/4"	150,0

8794 SA Zyklop extension with free-turning sleeve, short, $^1/_4$"



Application: $^1/_4$" square drive sockets with ball lock

Design: Easy-to-grip free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003525**001	$^1/_4$"	75,0

Tip

UNLOCK

"Flexible-lock-system"



The extensions from the premium lines are also equipped with the unique "flexible-lock-system". By activating this system, attachments can be fixed to the extension permanently – preventing slipping and any unintentional loss of the attachment. When the system is deactivated, the sockets can be attached as usual and changed in a flash.

The free-turning sleeve



The free-turning sleeve effectively speeds up the tightening or loosening of screws and bolts.



8795 A Zyklop universal joint, 1/4"



Application: 1/4" square drive sockets with ball lock

Design: Chrome vanadium/chrome molybdenum, brushed chrome-plated finish

		mm
05**003528**001	1/4"	35,5

8794 A Zyklop wobble extension, 1/4"



Application: 1/4" square drive sockets with ball lock

Design: Swivels through 15°, chrome vanadium, brushed chrome-plated finish

		mm
05**003527**001	1/4"	56,0

8784 A1 Zyklop bit adaptor, 1/4"



Application: Suitable for 1/4" hex bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4

Design: Quick-release chuck for fast bit changes, chromium vanadium

			mm
05**003529**001	1/4"	1/4"	37,0

Tip

How to work well in confined installation areas



The Zyklop wobble extensions pivot through 15° in all directions. This enables rapid and precise work in concealed or confined installation areas.



Zyklop Ratchets, 3/8"

 Zyklop Speed 172

 Zyklop Metal Push 176


 Zyklop Metal Switch 178

 Zyklop Accessories 180

The Zyklop Speed Ratchets, $^{3}/_{8}$"

5 types of ratchet in 1 tool

8100 SB 6 Zyklop Speed Ratchet Set, $^{3}/_{8}$" drive, metric






29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with $^{3}/_{8}$" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05**004046**001		
	8000 B	1 x 3/8"x199,0
	8790 HMB	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	8784 B1	1 x 1/4"x3/8"x44,0
	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50; 1 x PZ 3x50
	867/4 Z TORX®	1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50; 1 x TX 40x50
	840/4 Z Hex-Plus	1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50; 1 x 8,0x50
	800/4 Z	1 x 1,0x5,5x50

8100 SB 9 Zyklop Speed Ratchet Set, $^{3}/_{8}$" drive, imperial





29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with $^{3}/_{8}$" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05**004049**001		
	8000 B	1 x 3/8"x199,0
	8790 HMB	1 x 1/4"x29,0; 1 x 5/16"x29,0; 1 x 3/8"x29,0; 1 x 7/16"x29,0; 1 x 1/2"x29,0; 1 x 9/16"x29,0; 1 x 5/8"x30,0; 1 x 11/16"x30,0; 1 x 3/4"x30,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	8784 B1	1 x 1/4"x3/8"x44,0
	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50; 1 x PH 3x50
	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50; 1 x PZ 3x50
	867/4 Z TORX®	1 x TX 20x50; 1 x TX 25x50; 1 x TX 27x50; 1 x TX 30x50; 1 x TX 40x50
	840/4 Z Hex-Plus	1 x 3/16"x50; 1 x 7/32"x50; 1 x 1/4"x50; 1 x 5/16"x50
	800/4 Z	1 x 1,0x5,5x50

8100 SB 2 Zyklop Speed Ratchet Set, $^3/_8$" drive, metric





43-piece set in strong metal case

1 Zyklop ratchet with $^3/_8$" drive, 18 Zyklop sockets (metric), 2 Zyklop "flexible-lock" extensions (short and long) with free-turning sleeve, 1 sliding T-handle, 1 wobble extension, 1 universal joint, 1 adaptor with quick-release chuck, 18 bits

05**003594**001		
	8000 B	1 x 3/8"x199,0
	8790 HMB	1 x 6,0x29,0; 1 x 7,0x29,0; 1 x 8,0x29,0; 1 x 9,0x29,0; 1 x 10,0x29,0; 1 x 11,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 14,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0; 1 x 20,0x30,0; 1 x 21,0x30,0; 1 x 22,0x30,0; 1 x 24,0x32,0
	8789 B	1 x 3/8"x165,0
	8794 B	1 x 3/8"x76,0
	8795 B	1 x 3/8"x50,0
	8784 B1	1 x 1/4"x3/8"x44,0
	8796 SB	1 x 3/8"x125,0
	8796 LB	1 x 3/8"x200,0
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25; 1 x 10,0x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 Z	1 x 1,0x5,5x25
	851/1 Z PH	1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 2x25; 1 x PZ 3x25

Tip

Zyklop "6 in 1"



1. Fine-tooth ratchet
2. Flex-head ratchet
3. Angle ratchet
4. Quick-release ratchet
5. Power ratchet
6. Screwdriver

Textile boxes





The textile boxes offer dramatically improved portability, and are space-saving to boot!

This means you can now carry the same collection of tools, in a much more compact and comfortable package. The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged. And: it leaves absolutely no signs of scratches on sensitive surfaces.



The Zyklop VDE ratchet and accessories



The Zyklop VDE ratchet with 3/8" drive and the accessories can be found on pages 124-129.

The Zyklop Speed Ratchets, $^{3}/_{8}$"

5 types of ratchet in 1 tool

8100 SB 4 Zyklop Speed Ratchet Set, $^{3}/_{8}$" drive, imperial



38-piece set in strong metal case

1 Zyklop ratchet with $^{3}/_{8}$" drive, 12 Zyklop sockets (imperial), 2 Zyklop "flexible-lock" extensions (short and long) with free-turning sleeve, 1 sliding T-handle, 1 wobble extension, 1 universal joint, 1 adaptor with quick-release chuck, 19 bits

05**003596**001		
	8000 B	1 x 3/8"x199,0
	8790 HMB	1 x 1/4"x29,0; 1 x 5/16"x29,0; 1 x 11/32"x29,0; 1 x 3/8"x29,0; 1 x 7/16"x29,0; 1 x 1/2"x29,0; 1 x 9/16"x29,0; 1 x 5/8"x30,0; 1 x 11/16"x30,0; 1 x 3/4"x30,0; 1 x 13/16"x30,0; 1 x 7/8"x30,0
	8789 B	1 x 3/8"x165,0
	8794 B	1 x 3/8"x76,0
	8795 B	1 x 3/8"x50,0
	8784 B1	1 x 1/4"x3/8"x44,0
	8796 SB	1 x 3/8"x125,0
	8796 LB	1 x 3/8"x200,0
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 Z	1 x 1,0x5,5x25
	851/1 Z PH	1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 2x25; 1 x PZ 3x25
	840/1 Z Hex-Plus	1 x 5/64"x25; 1 x 3/32"x25; 1 x 1/8"x25; 1 x 9/64"x25; 1 x 5/32"x25; 1 x 3/16"x25; 1 x 7/32"x25

8000 B Zyklop Speed Ratchet with $^{3}/_{8}$" drive



Application: $^{3}/_{8}$" square drive sockets and $^{3}/_{8}$" adaptors with square drive, equipped with ball lock

Design: Flywheel design and easy-to-grip free-turning sleeve for faster work, swivel ratchet head, defined lock positions at 0° and 90° to the left and right as well as at 15° before 90° inwards, at 0° it can be used like a conventional screwdriver, pushbutton release, left/right switchover, fine-tooth design, small return angle of 5°

Handle: Multi-component Kraftform handle ensures minimum fatigue

		mm
05**003550**001	$^{3}/_{8}$"	199,0

8000 B SB Zyklop Speed Ratchet with $^{3}/_{8}$" drive

			4013288
05**073261**001		1 x 3/8"x199.0	128041





Tip

How to notice missing tools more quickly



Perfectly conceived in every detail: the storage case for the Zyklop Speed ratchet sets! The two-tone foam insert section means that the tools can be quickly and reliably replaced, and that missing tools can be detected immediately. The tools and their position can be clearly seen in the lid where they have been laser-etched, ensuring that they are legible even when the insert section is covered with grease, dirt or oil. Additionally, the foam section can be removed and placed in the drawer of a tool cabinet or trolley.



UNLOCK

“Flexible-lock-system”



The extensions from the premium lines are also equipped with the unique “flexible-lock-system”. By activating this system, attachments can be fixed to the extension permanently – preventing slipping and any unintentional loss of the attachment. When the system is deactivated, the sockets can be attached as usual and changed in a flash.



VDE TOOL

The Zyklop VDE ratchet and accessories




The Zyklop VDE ratchet with 3/8" drive and the accessories can be found on pages 124-129.

The Zyklop Metal Ratchets Push, $^{3}/_{8}$"

With push-through square

8100 SB 7 Zyklop Metal Ratchet Set with push-through square, $^{3}/_{8}$" drive, metric






29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with $^{3}/_{8}$" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05**004047**001		
	8003 B	1 x 3/8"x222,0
	8790 HMB	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	8784 B1	1 x 1/4"x3/8"x44,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25

8100 SB 10 Zyklop Metal Ratchet Set with push-through square, $^{3}/_{8}$" drive, imperial





29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with $^{3}/_{8}$" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05**004050**001		
	8003 B	1 x 3/8"x222,0
	8790 HMB	1 x 1/4"x29,0; 1 x 5/16"x29,0; 1 x 3/8"x29,0; 1 x 7/16"x29,0; 1 x 1/2"x29,0; 1 x 9/16"x29,0; 1 x 5/8"x30,0; 1 x 11/16"x30,0; 1 x 3/4"x30,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	8784 B1	1 x 1/4"x3/8"x44,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
	840/1 Z Hex-Plus	1 x 5/32"x25; 1 x 3/16"x25; 1 x 7/32"x25; 1 x 1/4"x25; 1 x 5/16"x25

8003 B Zyklop Metal Ratchet with push-through square and $^3/_8$" drive



Application: $^3/_8$" square sockets as well as for $^3/_8$" adaptors with square drive, with ball locking device

Design: Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces; the dual-ratchet-teeth design means that a 76 fine-toothing division can be achieved from the 38 robust teeth with a return angle of only 4.7°; simple direction change with the undetachable push-through square and very secure socket lock mechanism

		mm	mm	mm
05**004033**001	$^3/_8$"	222,0	27	29

Tip

The Zyklop Metal Ratchets Push



Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces.

Textile boxes



The textile boxes offer dramatically improved portability, and are space-saving to boot!

This means you can now carry the same collection of tools, in a much more compact and comfortable package. The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged. And: it leaves absolutely no signs of scratches on sensitive surfaces.



The Zyklop VDE ratchet and accessories



The Zyklop VDE ratchet with 3/8" drive and the accessories can be found on pages 124-129.

The Zyklop Metal Ratchets Switch, $^{3}/_{8}$"

With switch lever

8100 SB 8 Zyklop Metal Ratchet Set with switch lever, $^{3}/_{8}$" drive, metric



29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with $^{3}/_{8}$" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05**004048**001		
	8004 B	1 x 3/8"x222,0
	8790 HMB	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	8784 B1	1 x 1/4"x3/8"x44,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25

8100 SB 11 Zyklop Metal Ratchet Set with switch lever, $^{3}/_{8}$" drive, imperial



29-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with $^{3}/_{8}$" drive, 9 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 16 bits

05**004051**001		
	8004 B	1 x 3/8"x222,0
	8790 HMB	1 x 1/4"x29,0; 1 x 5/16"x29,0; 1 x 3/8"x29,0; 1 x 7/16"x29,0; 1 x 1/2"x29,0; 1 x 9/16"x29,0; 1 x 5/8"x30,0; 1 x 11/16"x30,0; 1 x 3/4"x30,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	8784 B1	1 x 1/4"x3/8"x44,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25
	840/1 Z Hex-Plus	1 x 5/32"x25; 1 x 3/16"x25; 1 x 7/32"x25; 1 x 1/4"x25; 1 x 5/16"x25

8100 SB HF 1 Zyklop Metal Ratchet Set with switch lever, $^3/_8$" drive, with holding function, metric





13-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

1 Zyklop Metal Ratchet with $^3/_8$" drive, 9 Zyklop sockets with $^3/_8$" drive with fastener holding function. Take it easy tool finder: Colour coding to enable the desired socket to be easily selected. 1 tool for the simple removal of nuts from sockets with holding function, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension

05**003785**001		
	8004 B	1 x 3/8"x222,0
	8790 HMB HF	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x29,0; 1 x 17,0x29,0; 1 x 18,0x29,0; 1 x 19,0x29,0
	8794 LB	1 x 3/8"x200,0
	8794 B	1 x 3/8"x76,0
	Nut Extractor	1 x 14,0x43,0

8004 B Zyklop Metal Ratchet with switch lever and $^3/_8$" drive



Application: $^3/_8$" square sockets as well as for $^3/_8$" adaptors with square drive, with ball locking device

Design: Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces; fine-tooth mechanism with 72 teeth for a return angle of only 5°; switch lever for convenient change of direction; secure socket locking function

		mm	mm	mm
05**004034**001	$^3/_8$"	222,0	26	29

Tip

The Zyklop Metal Ratchets Switch



Extremely slim. Long leverage. Very robust without any torque limitation. Forged, full metal ratchet out of chrome molybdenum.



The Zyklop VDE ratchet and accessories



The Zyklop VDE ratchet with 3/8" drive and the accessories can be found on pages 124-129.



"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Zyklop Accessories, 3/8"

With amazing product benefits

8790 HMB Zyklop 3/8" socket



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, chrome vanadium, brushed chrome-plated finish
Take it easy toolfinder: Colour coding to enable the desired socket to be easily located.

		mm		mm	mm	mm	mm
05003551001		6,0		29,0	10,5	18,0	12,0
05003552001		7,0		29,0	11,0	18,0	12,0
05003553001		8,0		29,0	12,2	18,0	12,0
05003554001		9,0		29,0	13,5	18,0	12,0
05003555001		10,0		29,0	14,5	18,0	12,0
05003556001		11,0		29,0	16,0	18,0	12,0
05003557001		12,0		29,0	17,0	18,0	12,0
05003558001		13,0		29,0	18,5	20,0	12,0
05003559001		14,0		29,0	19,5	22,0	12,0
05003560001		15,0		29,0	21,0	24,0	12,0
05003561001		16,0		30,0	22,0	24,0	12,0
05003562001		17,0		30,0	23,5	24,0	12,0
05003563001		18,0		30,0	24,5	24,0	18,0
05003564001		19,0		30,0	26,0	24,0	18,0
05003565001		20,0		30,0	28,0	25,0	18,0
05003566001		21,0		30,0	28,0	25,0	18,0
05003567001		22,0		30,0	32,0	25,0	18,0
05003568001		24,0		32,0	32,0	25,0	20,0
05003569001			1/4"	29,0	11,0	18,0	12,0
05003570001			5/16"	29,0	12,2	18,0	12,0
05003571001			11/32"	29,0	13,5	18,0	12,0
05003572001			3/8"	29,0	14,5	18,0	12,0
05003573001			7/16"	29,0	16,0	18,0	12,0
05003574001			1/2"	29,0	18,5	20,0	12,0
05003575001			9/16"	29,0	19,5	22,0	12,0
05003576001			5/8"	30,0	22,0	24,0	12,0
05003577001			11/16"	30,0	23,0	24,0	18,0
05003578001			3/4"	30,0	26,0	24,0	18,0
05003579001			13/16"	30,0	28,0	25,0	18,0
05003580001			7/8"	30,0	32,0	25,0	18,0

8790 HMB HF Zyklop socket with 3/8" drive with holding function



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, with holding function, chrome vanadium, brushed chrome-plated finish. Take it easy tool finder: Colour coding and large stamp to enable the desired socket to be easily located.

	mm	mm	mm	mm	mm
05003740001	6,0	29,0	10,5	17,5	6,5
05003741001	7,0	29,0	11,2	17,5	6,5
05003742001	8,0	29,0	12,2	17,5	6,5
05003743001	9,0	29,0	13,7	17,5	6,5
05003744001	10,0	29,0	15,0	17,5	8,0
05003745001	11,0	29,0	16,2	17,5	9,5
05003746001	12,0	29,0	17,0	17,5	9,5
05003747001	13,0	29,0	18,4	19,5	9,5
05003748001	14,0	29,0	19,5	21,5	12,5
05003749001	15,0	29,0	21,0	23,5	12,5
05003750001	16,0	29,0	22,2	23,5	12,5
05003751001	17,0	29,0	24,0	23,5	12,5
05003752001	18,0	29,0	24,5	23,5	12,5
05003753001	19,0	29,0	26,0	23,5	12,5

Belt B 1 Zyklop socket set with holding function, $^3/_8$" drive



10-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with $^3/_8$" drive with fastener holding function. Take it easy tool finder: Colour coding to enable the desired socket to be easily selected. 1 tool for the simple removal of nuts from sockets with holding function.

05**003970**001		
◉	**8790 HMB HF**	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x29,0; 1 x 17,0x29,0; 1 x 18,0x29,0; 1 x 19,0x29,0
	Nut Extractor	1 x 14,0x43,0
	Belt B 0/9	1 x 45,0x310,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Belt B 4 Zyklop socket set, $^3/_8$" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Smooth turning Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

9 Zyklop sockets with $^3/_8$" drive. Take it easy tool finder: Colour coding to enable the desired socket to be easily selected.

05**003973**001		
◉	**8790 HMB**	1 x 8,0x29,0; 1 x 10,0x29,0; 1 x 12,0x29,0; 1 x 13,0x29,0; 1 x 15,0x29,0; 1 x 16,0x30,0; 1 x 17,0x30,0; 1 x 18,0x30,0; 1 x 19,0x30,0
	Belt B 0/9	1 x 45,0x310,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Tip

How to avoid the need for two socket sets – one for manual and one for machine operations



The manual and machine sockets can be used both for hand and power tools use (non-impact). Users need just one socket set for all applications.



WERA 2GO COMPATIBLE

Textile belt



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Zyklop Accessories, $^3/_8$"

With amazing product benefits

Nut Extractor



Tool made out of synthetic plastic material (TPE) for the simple removal of nuts from sockets with holding function.

	mm	mm
05**050005**001	14,0	43,0

8767 B HF TORX® Zyklop bit socket with holding function, $^3/_8$" drive



Application: TORX® socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish, holding function for TORX® screws made according to Acument Intellectual Properties specifications. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located.

			mm	mm	mm	mm
05**003059**001		TX 10	35,0	12,0	17,5	9,0
05**003060**001		TX 15	35,0	12,0	17,5	9,0
05**003061**001		TX 20	35,0	12,0	17,5	9,0
05**003062**001		TX 25	35,0	12,0	17,5	9,0
05**003063**001		TX 25	107,0	12,0	17,5	81,0
05**003064**001		TX 27	35,0	12,0	17,5	9,0
05**003065**001		TX 27	107,0	12,0	17,5	81,0
05**003066**001		TX 30	35,0	12,0	17,5	9,0
05**003067**001		TX 30	107,0	12,0	17,5	81,0
05**003068**001		TX 40	35,0	12,0	17,5	9,0
05**003069**001		TX 40	107,0	12,0	17,5	81,0
05**003070**001		TX 45	38,5	12,0	17,5	12,5
05**003071**001		TX 45	100,0	12,0	17,5	74,5
05**003072**001		TX 50	38,5	12,0	17,5	12,5
05**003073**001		TX 50	100,0	12,0	17,5	74,5

Belt B 3 TORX® HF Zyklop bit socket set with holding function, $^3/_8$" drive



9-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the tool sockets.

9 Zyklop bit sockets for TORX® screws, with $^3/_8$" drive, with holding function. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.

05**003972**001		
	8767 B HF	1 x TX 10x35,0; 1 x TX 15x35,0; 1 x TX 20x35,0; 1 x TX 25x35,0; 1 x TX 27x35,0; 1 x TX 30x35,0; 1 x TX 40x35,0; 1 x TX 45x38,5; 1 x TX 50x38,5
	Belt B 0/9	1 x 45,0x310,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

8767 B TORX® HF 1 Zyklop bit socket set with holding function, $^3/_8$" drive




6-piece set

Pouch with 100 mm/107 mm bit sockets

6 Zyklop bit sockets for TORX® screws, with $^3/_8$" drive, with holding function. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.

05**003185**001		
	8767 B HF	1 x TX 25x107,0; 1 x TX 27x107,0; 1 x TX 30x107,0; 1 x TX 40x107,0; 1 x TX 45x100,0; 1 x TX 50x100,0

8740 B HF Zyklop bit socket bit socket with holding function, 3/8" drive



Application: Hexagon socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, bit sockets with all the advantages of the Wera bit technology, brushed chrome-plated finish, holding function for hexagon socket screws. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located.

		mm		mm	mm	mm	mm
05003030001		3,0		35,0	12,0	17,5	9,0
05003031001		4,0		35,0	12,0	17,5	9,0
05003032001		4,0		107,0	12,0	17,5	81,0
05003033001		5,0		35,0	12,0	17,5	9,0
05003034001		5,0		107,0	12,0	17,5	81,0
05003035001		6,0		35,0	12,0	17,5	9,0
05003036001		6,0		107,0	12,0	17,5	81,0
05003037001		7,0		38,5	12,0	17,5	12,5
05003038001		7,0		100,0	12,0	17,5	74,5
05003039001		8,0		38,5	12,0	17,5	12,5
05003040001		8,0		100,0	12,0	17,5	74,5
05003041001		9,0		38,5	12,0	17,5	12,5
05003042001		9,0		100,0	12,0	17,5	74,5
05003043001		10,0		38,5	12,0	17,5	12,5
05003044001		10,0		100,0	12,0	17,5	74,5
05003080001			1/8"	35,0	12,0	17,5	9,0
05003081001			1/8"	107,0	12,0	17,5	81,0
05003082001			9/64"	35,0	12,0	17,5	9,0
05003083001			5/32"	35,0	12,0	17,5	9,0
05003084001			5/32"	107,0	12,0	17,5	81,0
05003085001			3/16"	35,0	12,0	17,5	9,0
05003086001			3/16"	107,0	12,0	17,5	81,0
05003087001			7/32"	35,0	12,0	17,5	9,0
05003088001			7/32"	107,0	12,0	17,5	81,0
05003089001			1/4"	35,0	12,0	17,5	9,0
05003090001			1/4"	107,0	12,0	17,5	81,0
05003091001			5/16"	38,5	12,0	17,5	12,5
05003092001			5/16"	100,0	12,0	17,5	74,5
05003093001			3/8"	38,5	12,0	17,5	12,5
05003094001			3/8"	100,0	12,0	17,5	74,5

Tip

Nut extractor tool



This tool enables hexagon nuts to be easily removed from sockets with holding function.







HOLDING FUNCTION

Bit sockets with retaining function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

HOLDING FUNCTION

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

Zyklop Accessories, $^3/_8$"

With amazing product benefits

Belt B 2 Zyklop In-Hex-Plus bit socket set with holding function, $^3/_8$" drive



8-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

8 bit sockets for hexagon socket screws with $^3/_8$" drive with holding function and Hex-Plus high torque geometry. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.

05**003971**001		
O	**8740 B HF**	1 x 3,0x35,0; 1 x 4,0x35,0; 1 x 5,0x35,0; 1 x 6,0x35,0; 1 x 7,0x38,5; 1 x 8,0x38,5; 1 x 9,0x38,5; 1 x 10,0x38,5
	Belt B 0/8	1 x 45,0x275,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

8740 B HF 1 Zyklop bit socket set with holding function, $^3/_8$" drive



7-piece set

Pouch with 100 mm/107 mm bit sockets

7 Zyklop bit sockets for hexagon socket screws, with $^3/_8$" drive, with holding function, Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located.

05**003180**001		
O	**8740 B HF**	1 x 4,0x107,0; 1 x 5,0x107,0; 1 x 6,0x107,0; 1 x 7,0x100,0; 1 x 8,0x100,0; 1 x 9,0x100,0; 1 x 10,0x100,0

8740 B HF Imperial 1 Zyklop bit socket set with holding function, $^3/_8$" drive



7-piece set

Pouch with 100 mm/107 mm bit sockets

7 Zyklop bit sockets for hexagon socket screws, with $^3/_8$" drive, with holding function, Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located.

05**003181**001		
O	**8740 B HF**	1 x 1/8"x107,0; 1 x 5/32"x107,0; 1 x 3/16"x107,0; 1 x 7/32"x107,0; 1 x 1/4"x107,0; 1 x 5/16"x100,0; 1 x 3/8"x100,0

Belt B Imperial 1 Zyklop In-Hex-Plus bit socket set with holding function, $^3/_8$" drive



8-piece; robust textile socket belt, including snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

8 bit sockets for hexagon socket screws with $^3/_8$" drive with holding function and Hex-Plus high torque geometry. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily selected.

05**003974**001		
O	**8740 B HF**	1 x 1/8"x35,0; 1 x 9/64"x35,0; 1 x 5/32"x35,0; 1 x 3/16"x35,0; 1 x 7/32"x35,0; 1 x 1/4"x35,0; 1 x 5/16"x38,5; 1 x 3/8"x38,5
	Belt B 0/8	1 x 45,0x275,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Socket rail B (textile belt), 9 location, unloaded



1 robust textile belt, unloaded, for up to 9 sockets and/or bit sockets, with $^{3}/_{8}$" drive. Comes with a snap hook to enable secure fastening to a belt loop or pocket. Non-woven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

05**003981**001		
	Belt B 0/9	1 x 45,0x310,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Socket rail B (textile belt), 8 location, unloaded



1 robust textile belt, unloaded, for up to 8 sockets and/or bit sockets with $^{3}/_{8}$" drive. Comes with a snap hook to enable secure fastening to a belt loop or pocket. Nonwoven reverse side and hook and loop strips for simple attachment e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system. Fast and easy Twist to Unlock mechanism for secure storage and simple removal of the sockets.

05**003980**001		
	Belt B 0/8	1 x 45,0x275,0
	Hook and Loop Fastener Strip 30	1 x 30,0x200,0

Tip

Bit sockets with retaining function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Textile belt



The textile belt can be attached by means of the nonwoven reverse side and the hook and loop strips e.g. to a wall, shelf, tool trolley and to the Wera 2go tool transport system.

Comes with convenient snap hook



The robust textile belt can be secured to a belt loop or pocket by means of the snap hook.

Zyklop Accessories, 3/8"

With amazing product benefits

8796 SB Zyklop "flexible-lock" extension with free-turning sleeve, short, 3/8"



Application: 3/8" square drive sockets with ball lock

Design: Flexible-lock-system either for permanent interlocking or fast change of accessories, free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003591**001	3/8"	125,0

8794 SB Zyklop extension with free-turning sleeve, short, 3/8"



Application: 3/8" square drive sockets with ball lock

Design: Easy-to-grip free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003582**001	3/8"	125,0

8784 B1 Zyklop bit adaptor, 3/8"



Application: Suitable for 1/4" hex bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4

Design: Quick-release chuck for fast bit changes, chromium vanadium

			mm
05**003590**001	1/4"	3/8"	44,0

8796 LB Zyklop "flexible-lock" extension with free-turning sleeve, long, 3/8"



Application: 3/8" square drive sockets with ball lock

Design: Flexible-lock-system either for permanent interlocking or fast change of accessories, free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003592**001	3/8"	200,0

8794 LB Zyklop extension with free-turning sleeve, long, 3/8"



Application: 3/8" square drive sockets with ball lock

Design: Easy-to-grip free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003583**001	3/8"	200,0

8789 B Zyklop sliding T-handle, $^3/_8$"



Application: $^3/_8$" square drive sockets with ball lock

Design: Sliding drive, chrome vanadium, brushed chrome-plated finish

		mm
05**003581**001	$^3/_8$"	165,0

8795 B Zyklop universal joint, $^3/_8$"



Application: $^3/_8$" square drive sockets with ball lock

Design: Chrome vanadium/chrome molybdenum, brushed chrome-plated finish

		mm
05**003585**001	$^3/_8$"	50,0

8794 B Zyklop wobble extension, $^3/_8$"



Application: $^3/_8$" square drive sockets with ball lock

Design: Swivels through 15°, chrome vanadium, brushed chrome-plated finish

		mm
05**003584**001	$^3/_8$"	76,0

Tip

UNLOCK

"Flexible-lock-system"



The extensions from the premium lines are also equipped with the unique "flexible-lock-system". By activating this system, attachments can be fixed to the extension permanently – preventing slipping and any unintentional loss of the attachment. When the system is deactivated, the sockets can be attached as usual and changed in a flash.

The free-turning sleeve



The free-turning sleeve effectively speeds up the tightening or loosening of screws and bolts.


1/2"

Zyklop Ratchets, 1/2"


	Zyklop Speed	190
	Zyklop Hybrid Ratchet	194
	Zyklop Metal Push	198
	Zyklop Metal Switch	200
	Zyklop Accessories	202
	1/2" Koloss ratchet with hammer function	210



The Zyklop Speed Ratchets, 1/2"

5 types of ratchet in 1 tool

8100 SC 6 Zyklop Speed Ratchet Set, 1/2" drive, metric






28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits

05**004076**001		
	8000 C	1 x 1/2"x277,0
	8790 HMC	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0
	8794 LC	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8784 C2	1 x 5/16"x1/2"x50,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	855/2 Z PZ	1 x PZ 2x32; 1 x PZ 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35
	840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30

8100 SC 9 Zyklop Speed Ratchet Set, 1/2" drive, imperial





28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Speed Ratchet with 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits

05**004079**001		
	8000 C	1 x 1/2"x277,0
	8790 HMC	1 x 3/8"x37,0; 1 x 7/16"x37,0; 1 x 1/2"x37,0; 1 x 9/16"x37,0; 1 x 19/32"x37,0; 1 x 5/8"x37,0; 1 x 11/16"x37,0; 1 x 3/4"x37,0; 1 x 25/32"x37,0; 1 x 13/16"x37,0
	8794 LC	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8784 C2	1 x 5/16"x1/2"x50,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	855/2 Z PZ	1 x PZ 2x32; 1 x PZ 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35
	840/2 Z	1 x 7/32"x30; 1 x 1/4"x30; 1 x 5/16"x30; 1 x 3/8"x30

8100 SC 2 Zyklop Speed Ratchet Set, 1/2" drive, metric



37-piece set in strong metal case

1 Zyklop ratchet with 1/2" drive, 17 Zyklop sockets (metric),

2 Zyklop "flexible-lock" extensions (short and long) with free-tuning sleeve, 1 sliding T-handle, 1 universal joint, 1 wobble extension, 1 adaptor with quick-release chuck, 13 bits

05**003645**001		
	8000 C	1 x 1/2"x277,0
	8790 HMC	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0; 1 x 20,0x37,0; 1 x 21,0x37,0; 1 x 22,0x37,0; 1 x 24,0x37,0; 1 x 27,0x40,0; 1 x 30,0x42,0; 1 x 32,0x42,0
	8789 C	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8795 C	1 x 1/2"x69,0
	8784 C2	1 x 5/16"x1/2"x50,0
	8796 SC	1 x 1/2"x125,0
	8796 LC	1 x 1/2"x250,0
	840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30
	851/2 Z PH	1 x PH 3x32
	855/2 Z PZ	1 x PZ 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35

Tip

Zyklop "6 in 1"



1. Fine-tooth ratchet
2. Flex-head ratchet
3. Angle ratchet
4. Quick-release ratchet
5. Power ratchet
6. Screwdriver

New set concept



The textile boxes offer dramatically improved portability, and are space-saving to boot! This means you can now carry the same collection of tools, in a much more compact and comfortable package.



The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged.

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

The Zyklop Speed Ratchets, 1/2"

5 types of ratchet in 1 tool

8100 SC 4 Zyklop Speed Ratchet Set, 1/2" drive, imperial



38-piece set in strong metal case

1 Zyklop ratchet with 1/2" drive, 18 Zyklop sockets (imperial),

2 Zyklop “flexible-lock” extensions (short and long) with free-tuning sleeve, 1 sliding T-handle, 1 universal joint, 1 wobble extension, 1 adaptor with quick-release chuck, 13 bits

05**003647**001		
	8000 C	1 x 1/2"x277,0
	8790 HMC	1 x 3/8"x37,0; 1 x 7/16"x37,0; 1 x 1/2"x37,0; 1 x 9/16"x37,0; 1 x 19/32"x37,0; 1 x 5/8"x37,0; 1 x 11/16"x37,0; 1 x 3/4"x37,0; 1 x 25/32"x37,0; 1 x 13/16"x37,0; 1 x 7/8"x37,0; 1 x 15/16"x37,0; 1 x 31/32"x37,0; 1 x 1"x40,0; 1 x 1 1/16"x40,0; 1 x 1 1/8"x40,0; 1 x 1 3/16"x42,0; 1 x 1 1/4"x42,0
	8789 C	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8795 C	1 x 1/2"x69,0
	8784 C2	1 x 5/16"x1/2"x50,0
	8796 SC	1 x 1/2"x125,0
	8796 LC	1 x 1/2"x250,0
	851/2 Z PH	1 x PH 3x32
	855/2 Z PZ	1 x PZ 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
	840/2 Z	1 x 7/32"x30; 1 x 1/4"x30; 1 x 5/16"x30; 1 x 3/8"x30

8000 C Zyklop Speed Ratchet with 1/2" drive



Application: 1/2" square drive sockets and 1/2" adapters with square drive, equipped with ball lock

Design: Flywheel design and easy-to-grip free-turning sleeve for faster work, swivel ratchet head, defined lock positions at 0° and 90° to the left and right as well as at 15° before 90° inwards, at 0° it can be used like a conventional screwdriver, pushbutton release, left/right switchover, fine-tooth design, small return angle of 5°

Handle: Multi-component Kraftform handle ensures minimum fatigue

		mm
05**003600**001	1/2"	277,0

8000 C SB Zyklop Speed Ratchet with 1/2" drive

			4013288
05**073262**001		1 x 1/2"x277.0	128058






The Zyklop Hybrid Ratchet, 1/2"

Combines robustness, slim design, and little weight

8006 SC 1 Zyklop Hybrid Ratchet Set, 1/2" drive, metric





13-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Hybrid Ratchet with 1/2" drive, 10 Zyklop sockets with holding function, 1 Zyklop Hybrid Extension with release pin, 1 Zyklop extension (long) with free-turning sleeve

05**004090**001		
	8006 C	1 x 1/2"x281,0
	8797 C	1 x 271,0
	8794 LC	1 x 1/2"x250,0
	8790 HMC HF	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0

Zyklop Hybrid Set



Application: Ratchet function for 1/2" square sockets and 1/2" adaptors with square drive, equipped with ball lock

Design: Fine-tooth mechanism with 72 teeth for a return angle of only 5°; switch lever for convenient change of direction; secure socket locking function

Handle: Multi-component Kraftform handle for optimum pressure, impact and tensile loads, handle end designed for connection of Zyklop Hybrid extension 8797 C

05**004095**001		
	8006 C	1 x 1/2"x281,0
	8797 C	1 x 271,0





Tip

TAKE IT EASY TOOL FINDER

“Take it easy”



“Take it easy” tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Secure hold and easy removal



The all new smooth turning mechanism guarantees both secure and rattle-free storage, yet allows easy removal of the tool.

HOLDING FUNCTION

Sockets with retaining function for hexagon headed bolts, screws and nuts



The clamping of the screw is achieved by two flexible locking balls and a robust, permanently elastic, heat-shrunk tubing. The tubing is effectively protected against mechanical wear and tear by a steel ring. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

The Zyklop Hybrid Ratchet, 1/2"

Combines robustness, slim design, and little weight

8006 C Zyklop Hybrid Ratchet with switch lever and 1/2" drive



Application: 1/2" square sockets as well as for 1/2" adaptors with square drive, with ball locking device

Design: Fine-tooth mechanism with 72 teeth for a return angle of only 5°; switch lever for convenient change of direction; secure socket locking function

Handle: Multi-component Kraftform handle for optimum pressure and tensile loads, handle end designed for connection of Zyklop Hybrid extension

		mm	mm	mm
05**003780**001	1/2"	281,0	34	37

8797 C Zyklop Hybrid extension



Application: Extension for use with Wera Zyklop Hybrid 8006 C to increase torque transfer

Design: Tough, tempered Cr-Mo steel

Handle: Multi-component Kraftform handle for optimum pressure and tensile loads; with extension release pin

	mm	mm
05**003781**001	134,0	137

Unlocking pin



Application: For unlocking the connection between the Koloss Ratchet 8002 C and the Koloss Extension 8780 C as well as the connection between Zyklop Hybrid Ratchet 8006 C and the Zyklop Hybrid Extension 8797 C

Design: Zinc die casting

	mm
05**136400**001	40,5



The Zyklop Metal Ratchets Push, 1/2"

With push-through square

8100 SC 7 Zyklop Metal Ratchet Set with push-through square, 1/2" drive, metric



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with push-through square and 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits

05**004077**001		
	8003 C	1 x 1/2"x281,0
	8790 HMC	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0
	8794 LC	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8784 C2	1 x 5/16"x1/2"x50,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 27x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
	840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30

8100 SC 10 Zyklop Metal Ratchet Set with push-through square, 1/2" drive, imperial



28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with push-through square and 1/2" drive, 10 Zyklop sockets, 1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension, 1 adaptor with quick-release chuck, 14 bits

05**004080**001		
	8003 C	1 x 1/2"x281,0
	8790 HMC	1 x 3/8"x37,0; 1 x 7/16"x37,0; 1 x 1/2"x37,0; 1 x 9/16"x37,0; 1 x 19/32"x37,0; 1 x 5/8"x37,0; 1 x 11/16"x37,0; 1 x 3/4"x37,0; 1 x 25/32"x37,0; 1 x 13/16"x37,0
	8794 LC	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8784 C2	1 x 5/16"x1/2"x50,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 27x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
	840/2 Z	1 x 7/32"x30; 1 x 1/4"x30; 1 x 5/16"x30; 1 x 3/8"x30

8003 C Zyklop Metal Ratchet with push-through square and 1/2" drive



Application: 1/2" square sockets as well as for 1/2" adaptors with square drive, with ball locking device

Design: Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces; the dual-ratchet-teeth design means that a 76 fine-toothing division can be achieved from the 38 robust teeth with a return angle of only 4.7°; simple direction change with the undetachable push-through square and very secure socket lock mechanism

		mm	mm	mm
05**004063**001	1/2"	281,0	36	37

Tip

The Zyklop Metal Ratchets Push



Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces.

Textile boxes





The textile boxes offer dramatically improved portability, and are space-saving to boot!

This means you can now carry the same collection of tools, in a much more compact and comfortable package. The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged. And: it leaves absolutely no signs of scratches on sensitive surfaces.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

The Zyklop Metal Ratchets Switch, 1/2"

With switch lever

8100 SC 8 Zyklop Metal Ratchet Set with switch lever, 1/2" drive, metric






28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/2" drive, 10 Zyklop sockets,
1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension,
1 adaptor with quick-release chuck, 14 bits

05**004078**001		
	8004 C	1 x 1/2"x281,0
	8790 HMC	1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0
	8794 LC	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8784 C2	1 x 5/16"x1/2"x50,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 27x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
	840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30

8100 SC 11 Zyklop Metal Ratchet Set with switch lever, 1/2" drive, imperial





28-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1 Zyklop Metal Ratchet with switch lever and 1/2" drive, 10 Zyklop sockets,
1 Zyklop extension (long) with free-turning sleeve, 1 wobble extension,
1 adaptor with quick-release chuck, 14 bits

05**004081**001		
	8004 C	1 x 1/2"x281,0
	8790 HMC	1 x 3/8"x37,0; 1 x 7/16"x37,0; 1 x 1/2"x37,0; 1 x 9/16"x37,0; 1 x 19/32"x37,0; 1 x 5/8"x37,0; 1 x 11/16"x37,0; 1 x 3/4"x37,0; 1 x 25/32"x37,0; 1 x 13/16"x37,0
	8794 LC	1 x 1/2"x250,0
	8794 C	1 x 1/2"x52,0
	8784 C2	1 x 5/16"x1/2"x50,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	867/2 Z TORX®	1 x TX 20x35; 1 x TX 25x35; 1 x TX 27x35; 1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
	840/2 Z	1 x 7/32"x30; 1 x 1/4"x30; 1 x 5/16"x30; 1 x 3/8"x30

8004 C Zyklop Metal Ratchet with switch lever and 1/2" drive



Application: 1/2" square sockets as well as for 1/2" adaptors with square drive, with ball locking device

Design: Forged, full metal ratchet (chrome-molybdenum) that is extremely robust with a long service life; slim design to enable work in very confined spaces; fine-tooth mechanism with 72 teeth for a return angle of only 5°; switch lever for convenient change of direction; secure socket locking function

		mm	mm	mm
05**004064**001	1/2"	281,0	34	37

Tip

The Zyklop Metal Ratchets Switch



Extremely slim. Long leverage. Very robust without any torque limitation. Forged, full metal ratchet out of chrome molybdenum.

Textile boxes





The textile boxes offer dramatically improved portability, and are space-saving to boot!

This means you can now carry the same collection of tools, in a much more compact and comfortable package. The hassle of running back and forth for the right tools has now become a thing of the past. And the much lower weight of a set makes carrying more convenient than ever before. The textile box including the tool will even survive a fall undamaged. And: it leaves absolutely no signs of scratches on sensitive surfaces.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Zyklop Accessories, 1/2"

With amazing product benefits

HMC Zyklop socket with 1/2" drive



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, chrome vanadium, brushed chrome-plated finish. Colour coding to enable the desired bit socket to be easily located

	mm		mm	mm	mm	mm
05003601001	10,0		37,0	15,5	24,0	17,0
05003602001	11,0		37,0	16,5	24,0	17,0
05003603001	12,0		37,0	17,5	24,0	17,0
05003604001	13,0		37,0	19,0	24,0	17,0
05003605001	14,0		37,0	20,0	24,0	17,0
05003606001	15,0		37,0	21,0	24,0	17,0
05003607001	16,0		37,0	22,5	24,0	17,0
05003608001	17,0		37,0	24,0	26,0	17,0
05003609001	18,0		37,0	25,0	26,0	17,0
05003610001	19,0		37,0	26,5	26,0	20,0
05003611001	20,0		37,0	28,0	26,0	20,0
05003612001	21,0		37,0	29,0	26,0	20,0
05003613001	22,0		37,0	30,5	26,0	20,0
05003614001	24,0		37,0	33,0	28,0	20,0
05003615001	27,0		40,0	36,5	32,0	23,0
05003616001	30,0		42,0	40,0	34,0	25,0
05003617001	32,0		42,0	42,0	36,0	25,0
05003618001		3/8"	37,0	15,5	24,0	17,0
05003619001		7/16"	37,0	16,5	24,0	17,0
05003620001		1/2"	37,0	19,0	24,0	17,0
05003621001		9/16"	37,0	20,0	24,0	17,0
05003622001		19/32"	37,0	21,0	24,0	17,0
05003623001		5/8"	37,0	22,5	24,0	17,0
05003624001		11/16"	37,0	25,5	26,0	17,0
05003625001		3/4"	37,0	26,5	26,0	20,0
05003626001		25/32"	37,0	28,0	26,0	20,0
05003627001		13/16"	37,0	29,0	26,0	20,0
05003628001		7/8"	37,0	30,5	26,0	20,0
05003629001		15/16"	37,0	33,0	28,0	20,0
05003630001		31/32"	37,0	33,0	28,0	20,0
05003631001		1"	40,0	36,5	32,0	23,0
05003632001		1 1/16"	40,0	36,5	32,0	23,0
05003633001		1 1/8"	40,0	40,0	34,0	23,0
05003634001		1 3/16"	42,0	40,0	34,0	25,0
05003635001		1 1/4"	42,0	42,0	36,0	25,0

8790 HMC HF Zyklop socket with 1/2" drive with holding function



Application: Hexagon headed bolts, screws and nuts

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, with holding function, chrome vanadium, brushed chrome-plated finish. Colour coding to enable the desired bit socket to be easily located

	mm	mm	mm	mm	mm
05003730001	10,0	37,0	17,8	23,5	10,4
05003731001	11,0	37,0	18,8	23,5	10,4
05003732001	12,0	37,0	20,4	23,5	11,4
05003733001	13,0	37,0	21,4	23,5	11,4
05003734001	14,0	37,0	22,6	23,5	11,4
05003735001	15,0	37,0	23,6	23,5	12,0
05003736001	16,0	37,0	25,0	23,5	12,0
05003737001	17,0	37,0	26,8	23,5	12,5
05003738001	18,0	37,0	28,0	23,5	12,5
05003739001	19,0	37,0	29,2	23,5	14,0

8790 HF 1 Zyklop socket set with holding function





10-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

10 Zyklop sockets with $^{1}/_{2}$" drive with holding function

05**004203**001	
◉	**8790 HMC HF** 1 x 10,0x37,0; 1 x 11,0x37,0; 1 x 12,0x37,0; 1 x 13,0x37,0; 1 x 14,0x37,0; 1 x 15,0x37,0; 1 x 16,0x37,0; 1 x 17,0x37,0; 1 x 18,0x37,0; 1 x 19,0x37,0

Nut Extractor



Tool made out of synthetic plastic material (TPE) for the simple removal of nuts from sockets with holding function.

	mm	mm
05**050005**001	14,0	43,0

Tip



Sockets with retaining function for hexagon headed bolts, screws and nuts



The clamping of the screw is achieved by two flexible locking balls and a robust, permanently elastic, heat-shrunk tubing. The tubing is effectively protected against mechanical wear and tear by a steel ring. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.



Secure hold and easy removal



The all new smooth turning mechanism of the Zyklop HF Socket sets guarantees both secure and rattle-free storage, yet allows easy removal of the tool.

Nut extractor tool



This tool enables hexagon nuts to be easily removed from sockets with holding function.





Zyklop Accessories, 1/2"

With amazing product benefits

8767 C HF TORX® Zyklop bit socket with 1/2" drive with holding function



Application: TORX® socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, chrome vanadium, brushed chrome-plated finish, holding function for TORX® screws made according to Acument Intellectual Properties specifications. Take it easy tool finder: Colour coding to enable the desired bit socket to be easily located

			mm	mm	mm	mm
05**003830**001		TX 20	60,0	16,4	23,5	21,5
05**003850**001		TX 20	140,0	16,4	23,5	101,5
05**003831**001		TX 25	60,0	16,4	23,5	21,5
05**003851**001		TX 25	140,0	16,4	23,5	101,5
05**003832**001		TX 27	60,0	16,4	23,5	21,5
05**003852**001		TX 27	140,0	16,4	23,5	101,5
05**003833**001		TX 30	60,0	16,4	23,5	21,5
05**003853**001		TX 30	140,0	16,4	23,5	101,5
05**003834**001		TX 40	60,0	16,4	23,5	21,5
05**003854**001		TX 40	140,0	16,4	23,5	101,5
05**003835**001		TX 45	60,0	16,4	23,5	21,5
05**003855**001		TX 45	140,0	16,4	23,5	101,5
05**003836**001		TX 50	60,0	21,4	23,5	21,5
05**003856**001		TX 50	140,0	21,4	23,5	101,5
05**003837**001		TX 55	60,0	21,4	23,5	21,5
05**003857**001		TX 55	140,0	21,4	23,5	101,5
05**003838**001		TX 60	60,0	21,4	23,5	21,5
05**003858**001		TX 60	140,0	21,4	23,5	101,5

8767 C TORX® HF 1 Zyklop bit socket set with 1/2" drive, with holding function



9-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

9 Zyklop bit sockets for TORX® screws, with 1/2" drive, with holding function

05**004202**001		
	8767 C HF	1 x TX 20x60; 1 x TX 25x60; 1 x TX 27x60; 1 x TX 30x60; 1 x TX 40x60; 1 x TX 45x60; 1 x TX 50x60; 1 x TX 55x60; 1 x TX 60x60

8767 C TORX® HF 2 Zyklop bit socket set with 1/2" drive, with holding function



6-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

6 Zyklop bit sockets, 140 mm long, for TORX® screws, with 1/2" drive, with holding function

05**004211**001		
	8767 C HF	1 x TX 20x140; 1 x TX 25x140; 1 x TX 27x140; 1 x TX 30x140; 1 x TX 40x140; 1 x TX 45x140

8767 C TORX® HF 3 Zyklop bit socket set with 1/2" drive, with holding function



9-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

9 Zyklop bit sockets, 140 mm long, for TORX® screws, with 1/2" drive, with holding function

05**004212**001		
	8767 C HF	1 x TX 20x140; 1 x TX 25x140; 1 x TX 27x140; 1 x TX 30x140; 1 x TX 40x140; 1 x TX 45x140; 1 x TX 50x140; 1 x TX 55x140; 1 x TX 60x140

8740 C HF 1 Zyklop bit socket set with 1/2" drive with holding function



9-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

9 Zyklop bit sockets for hexagon socket screws, with 1/2" drive, with holding function

05**004201**001		
	8740 C HF	1 x 4,0x60,0; 1 x 5,0x60,0; 1 x 6,0x60,0; 1 x 7,0x60,0; 1 x 8,0x60,0; 1 x 10,0x60,0; 1 x 12,0x60,0; 1 x 14,0x60,0; 1 x 17,0x60,0

Tip

Bit sockets with holding function for TORX® screws



The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that TORX® screws made according to Acument Intellectual Properties specifications are securely held on the tool!

Bit sockets with retaining function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Secure hold and easy removal



The all new smooth turning mechanism of the Zyklop HF Socket sets guarantees both secure and rattle-free storage, yet allows easy removal of the tool.

Zyklop Accessories, 1/2"

With amazing product benefits

8740 C HF 2 Zyklop bit socket set with 1/2" drive, with holding function





9-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

9 Zyklop bit sockets, 140 mm long, for hexagon socket screws, with 1/2" drive, with holding function

05**004210**001		
O	**8740 C HF**	1 x 4,0x140,0; 1 x 5,0x140,0; 1 x 6,0x140,0; 1 x 7,0x140,0; 1 x 8,0x140,0; 1 x 10,0x140,0

8740 C HF Zyklop bit socket with 1/2" drive with holding function







Application: Hexagon socket screws

Design: Manual and (non-impact) machine applications, ball intercept ring, knurls at base for precision handling in manual operations, chrome vanadium, brushed chrome-plated finish, holding function for hexagon socket screws. Colour coding to enable the desired bit socket to be easily located

		O mm	mm	mm	mm	mm
05**003820**001		4,0	60,0	14,0	21,5	21,5
05**003840**001		4,0	140,0	14,0	21,5	101,5
05**003821**001		5,0	60,0	14,0	21,5	21,5
05**003841**001		5,0	140,0	14,0	21,5	101,5
05**003822**001		6,0	60,0	14,0	21,5	21,5
05**003842**001		6,0	140,0	14,0	21,5	101,5
05**003823**001		7,0	60,0	14,0	23,5	21,5
05**003843**001		7,0	140,0	14,0	23,5	101,5
05**003824**001		8,0	60,0	16,0	23,5	21,5
05**003844**001		8,0	140,0	16,0	23,5	101,5
05**003825**001		10,0	60,0	16,0	23,5	21,5
05**003845**001		10,0	140,0	16,0	23,5	101,5
05**003826**001		12,0	60,0	21,0	23,5	23,0
05**003827**001		14,0	60,0	22,0	23,5	23,0
05**003828**001		17,0	60,0	24,5	25,5	23,0
05**003829**001		19,0	60,0	26,5	27,5	23,0


T30 T27 T25 T20
T40 T45 T50 T55 T60
7 6 5 4
8 10 12 14 17
10 11 12 13 14 15 16 18 19
11 12 13 14 15 16 17
17

Zyklop Accessories, 1/2"

With amazing product benefits

8796 SC Zyklop „flexible-lock“ extension with free-turning sleeve, short, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Flexible lock system either for permanent interlocking or fast change of accessories, free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003642**001	1/2"	125,0

8796 LC Zyklop "flexible-lock" extension with free-turning sleeve, long, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Flexible lock system either for permanent interlocking or fast change of accessories, free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003643**001	1/2"	250,0

8794 SC Zyklop extension with free-turning sleeve, short, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Easy-to-grip free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003637**001	1/2"	125,0

8794 LC Zyklop extension with free-turning sleeve, long, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Easy-to-grip free-turning sleeve for rapid tightening or loosening of screws and nuts, chrome vanadium, brushed chrome-plated finish

		mm
05**003638**001	1/2"	250,0

8789 C Zyklop sliding T-handle, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Sliding drive, chrome vanadium, brushed chrome-plated finish

		mm
05**003636**001	1/2"	250,0

8784 C2 Zyklop Bit adaptor, 1/2", 5/16"



Application: Suitable for 5/16" hex bits as per DIN ISO 1173-C 8 and Wera series 2

Design: Quick-release chuck for fast bit changes, chromium vanadium

			mm
05**003641**001	5/16"	1/2"	50,0

8795 C Zyklop universal joint, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Chrome vanadium/chrome molybdenum, brushed chrome-plated finish

		mm
05**003640**001	1/2"	69,0

8794 C Zyklop wobble extension, 1/2"



Application: 1/2" square drive sockets with ball lock

Design: Swivels through 15°, chrome vanadium, brushed chrome-plated finish

		mm
05**003639**001	1/2"	52,0

The Koloss

Obviously, many users also apply their ratchet as a hammer. This often ruins the ratchet and is dangerous to boot.

That is why we developed the heavy-duty Koloss ratchet whose mechanism is extremely robust, and nearly impossible to destroy through impact.

The Koloss is so robust that it can even be used safely with its extension element.




Non-removable sealed and hardened square drive for tough jobs.



Changing the ratchet direction using a hardened push-through square drive ensures great resilience, since there is no susceptible switching mechanism that could be damaged by hammer blows. This is far more robust than a forward/reverse switch.



Tubular shaft minimises impact vibrations.





Dry-fined hammer face: used with rubber pad attachments to protect materials and surfaces.



The drop-forged hammer head is permanently pinned to the shaft in a form-fit joint. This guarantees an almost non-detachable positioning of the hammer head on the handle.



Dual ratchet teeth: gives the robust 30 saw teeth the precision engineering effect of 60 fine teeth with a 6° return angle.





Newly developed, multi-component Kraftform handle that satisfies both the hammer and ratchet application requirements.



Sockets and accessories can simply and quickly be attached.



The degree of torque applied can be increased by using the Wera extension Koloss 8002 C.

Koloss

This ratchet is a real hit! And that is for sure!

8002 C Koloss All Inclusive Set with ½" drive



Application: Ratchet function for $^1/_2$" square sockets and $^1/_2$" adaptors with square drive, equipped with ball lock, hammer function e.g. to align work pieces

Design: Push-through square drive for forward and reverse operation, fine-tooth ratchet mechanism, small return angle of 6°, can transfer at least 600 Nm of torque, tubular shaft to minimise impact vibrations, drop-forged hammer head, positively pinned, ground striking face

Handle: Multi-component Kraftform handle for optimum pressure, impact and tensile loads, handle end designed for connection of Koloss extension 8780 C and Koloss centering pin 8781 C

05**133862**001		
	8002 C	1 x 1/2"x341,0
	8782 C	1 x 2x50,0
	8780 C	1 x 341,0x137
	8000 E	1 x Unlocking pin
	8000 HLF	1 x Holster

8002 C Koloss ½" with ½" drive



Application: Ratchet function for $^1/_2$" square sockets and $^1/_2$" adaptors with square drive, equipped with ball lock, hammer function e.g. to align work pieces

Design: Push-through square drive for forward and reverse operation, fine-tooth ratchet mechanism, small return angle of 6°, can transfer at least 600 Nm of torque, tubular shaft to minimise impact vibrations, drop-forged hammer head, positively pinned, ground striking face

Handle: Multi-component Kraftform handle for optimum pressure, impact and tensile loads, handle end designed for connection of Koloss extension 8780 C and Koloss centering pin 8781 C

05**003692**001		
	8002 C	1 x 1/2"x341,0
	8782 C	1 x 2x50,0
	8000 HLF	1 x Holster

8780 C Koloss extension



Application: Extension for use with Wera Koloss 8002 C to increase torque transfer

Design: Tough, tempered Cr-Mo steel

Handle: Multi-component Kraftform handle for optimum pressure, impact and tensile loads, laser-engraved safety instructions for permanent recognition

	mm	mm
05**003695**001	341,0	137

8781 C Koloss centring pin



Application: Centering pin for use with Wera Koloss 8002 C to align lugs or drill holes

Design: Tapered pin out of tough, tempered Cr-Mo steel

	mm	mm
05**003696**001	50	135,0

8782 C Koloss pad set



Application: Protective attachment for striking faces for use with Wera Koloss 8002 C to protect materials and surfaces

Design: Flexible, thermoplastic elastomer material for lasting elasticity and maximum protection

	#	mm
05**003697**001	2	50,0

Unlocking pin




Application: For unlocking the connection between the Koloss Ratchet 8002 C and the Koloss Extension 8780 C as well as the connection between Zyklop Hybrid Ratchet 8006 C and the Zyklop Hybrid Extension 8797 C

Design: Zinc die casting

	mm
05**136400**001	40,5

Tip

Dry-fined hammer face



Dry-fined hammer face: used with rubber pad attachments to protect materials and surfaces.

Why do the dual ratchet teeth provide particular robustness?



Dual ratchet teeth: gives the robust 30 saw teeth the precision engineering effect of 60 fine teeth with a 6° return angle.

Who is the Koloss suitable for?



Basically anyone who would like to work with a ½" ratchet. Typical fields of application are mechanical engineering, boatbuilding, mining, aircraft construction, bridge building, commercial vehicle construction and maintenance, railway and road construction and maintenance, industrial plant and equipment construction, high-bay warehouse construction, petroleum industry and many more.

Zyklop Mini

Combines elegant design with incredible resilience. Suitable for rapid fastening even in confined working situations. The Wera Zyklop Mini is applied whenever fastening with a power tool or conventional tools is impossible due to insufficient space.

The Zyklop Mini 1 for the direct attachment of bits; the Zyklop Mini 2 for the direct attachment of the special Wera Zyklop sockets.






The fine tooth mechanism, with its 60 teeth, allows a small return angle of only 6° – ideal for precision work.



Thumbwheel enables rapid screw-driving, even when there isn't sufficient room for ratcheting use.



Simple switching between left/right operations.





Its slim design makes it ideal for all particularly confined working situations.

Zyklop Mini

For confined spaces

Bit-Check 30 Zyklop Mini 1



28 bits, 1 Rapidaptor bit holder, 1 adaptor 870/1 ($^1/_4$" hexagon to $^1/_4$" square), 1 Wera Bit Ratchet, drop-forged full steel design, suitable for $^1/_4$" hex bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4

05**073640**001		
	8001 A	1 x 1/4"x87,0
	870/1	1 x 1/4"x25
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	855/1 TH PZ	1 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	800/1 TZ	1 x 1,0x5,5x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25

Bit-Check 30 Zyklop Mini 2



28 bits, 1 Rapidaptor bit holder, 1 adaptor 870/1 ($^1/_4$" hexagon to $^1/_4$" square), 1 Wera Bit Ratchet, drop-forged full steel design, suitable for $^1/_4$" hex bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4

05**346293**001		
	8001 A	1 x 1/4"x87,0
	870/1	1 x 1/4"x25
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	800/1 TZ	1 x 1,0x5,5x25
	840/1 Z Hex-Plus	1 x 3/32"x25; 1 x 1/8"x25; 1 x 5/32"x25; 1 x 3/16"x25; 1 x 1/4"x25
	868/1 Z	1 x # 1x25; 3 x # 2x25; 1 x # 3x25

Kraftform Kompakt Zyklop Mini 2













1 Wera Bit Ratchet Zyklop Mini 1, drop-forged full steel design, suitable for 1/4" hex bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4. Can also be used with 1/4" sockets by using the Wera socket adaptor 870/1.
1 Wera Ratchet Zyklop Mini 2, drop-forged full steel design, suitable for for Wera sockets 8790 FA. 9 Wera sockets 8790 FA, 1 socket adaptor 870/1, 14 bits, tough, for universal use

05**135918**001		
	8001 A	1 x 1/4"x87,0
	8005	1 x 107
◉	**813**	1 x 1/4"x78
▢○	**870/1**	1 x 1/4"x25
✪	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
✪	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25
✪	**867/1 TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
○	**840/1 Z Hex-Plus**	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25
	8790 FA	1 x 4,0; 1 x 5,0; 1 x 5,5; 1 x 6,0; 1 x 7,0; 1 x 8,0; 1 x 10,0; 1 x 12,0; 1 x 13,0

Tip

Zyklop Mini tool sets



Available in a set with the dependable Wera Bit-Check with socket adaptor and belt clip. Simple fitting and removal of tools. Very robust and a long service life.

Bit-Check as a lever



The Bit-Check itself can be used as a lever.

Zyklop Mini 2



The Zyklop Mini 2 is suitable for the direct attachment of the special Wera Zyklop sockets 8790 FA. These sockets feature a very low height, ideal for confined working spaces.

Zyklop Mini

For confined spaces

Tool-Check PLUS





28 bits, 1 hand holder 813 suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6,3 and Wera connection series 1, 1 Rapidaptor bit holder, 1 adaptor 870/1 (1/4" hexagon to 1/4" square), 7 sockets (1/4");
1 Wera Bit Ratchet, drop-forged full steel design suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6,3 and E 6,3 and Wera connection series 1 and 4; the use of 1/4" sockets is also possible with the application of the Wera adaptor 870/1

05**056490**001		
	8001 A	1 x 1/4"x87,0
	813	1 x 1/4"x78
	889/4/1 K	1 x 1/4"x50
	870/1	1 x 1/4"x25
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	855/1 TH PZ	1 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25
	800/1 TZ	1 x 1,0x5,5x25

" To learn more about this product, scan the QR code. "

Tool-Check PLUS Imperial





28 bits, 1 hand holder 813 suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6,3 and Wera connection series 1, 1 Rapidaptor bit holder, 1 adaptor 870/1 (1/4" hexagon to 1/4" square), 7 sockets (1/4");
1 Wera Bit Ratchet, drop-forged full steel design suitable for the attachment of bits with 1/4" hexagon drive as per DIN ISO 1173-C 6,3 and E 6,3 and Wera connection series 1 and 4; the use of 1/4" sockets is also possible with the application of the Wera adaptor 870/1

05**056491**001		
	8001 A	1 x 1/4"x87,0
	813	1 x 1/4"x78
	889/4/1 K	1 x 1/4"x50
	870/1	1 x 1/4"x25
	8790 HMA	1 x 3/16"x23,0; 1 x 1/4"x23,0; 1 x 5/16"x23,0; 1 x 11/32"x23,0; 1 x 3/8"x23,0; 1 x 7/16"x23,0; 1 x 1/2"x23,0
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	800/1 TZ	1 x 1,0x5,5x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 3/32"x25; 1 x 1/8"x25; 1 x 5/32"x25; 1 x 3/16"x25; 1 x 5/16"x25
	868/1 V	1 x # 1x25; 3 x # 2x25; 1 x # 3x25

Tool-Check 1 SB







28 bits; 1 socket adaptor 870/1 ($^1/_4$" hexagonal to $^1/_4$" square); 7 manual & power tool sockets; 1 Rapidaptor bit holder; 1 Wera Bit Ratchet, with drop-forged steel design suitable for the fitting of bits with $^1/_4$" hexagonal headed drive as per DIN ISO 1173-C 6,3 and E 6,3, i.e. Wera Series 1 and 4. Can also be used with $^1/_4$" sockets by using the socket adaptor (870/1).

05**073220**001		
	8001 A	1 x 1/4"x87,0
	870/1	1 x 1/4"x25
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	855/1 TH PZ	1 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	800/1 TZ	1 x 1,0x5,5x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0

Tip

What parts can be connected to the Zyklop Mini 1?



Bits and sockets. Bits can be connected directly. However, a holder can be connected first and then the bit can be attached to this. This then serves as an extension with a free-turning sleeve. An adaptor e.g. Wera 870/1 is needed for sockets – ¼" hexagonal on a square drive (included in the Bit-Check and with the individual Zyklop Mini 1 in the set).

When is the Zyklop Mini 1 needed?



Particularly when the space is confined and there is not much room for the tool.

Is rapid screwdriving possible with the Zyklop Mini?



High working speeds can be attained with the Zyklop Mini. The thumb wheel is important, enabling more rapid screwdriving, and the Zyklop Mini hande only needs to be used for the final tightening of the screw.



"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Zyklop Mini

For confined spaces

Tool-Check Automotive 1



28 bits; 1 870/1 socket adaptor ($^1/_4$" hexagonal to $^1/_4$" square); 7 manual & power tool sockets; 1 Rapidaptor bit holder; 1 Wera Bit Ratchet, with drop-forged steel design suitable for the fitting of bits with $^1/_4$" hexagonal headed drive as per DIN ISO 1173-C 6,3 and E 6,3, i.e. Wera Series 1 and 4. Can also be used with $^1/_4$" sockets by using the socket adaptor (870/1).

05**200995**001		
	8001 A	1 x 1/4"x87,0
	870/1	1 x 1/4"x25
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	800/1 TZ	1 x 1,0x5,5x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25
	860/1 XZN Vielzahn	1 x M 4x25; 1 x M 5x25; 1 x M 6x25; 1 x M 8x25
	873/1 Five Lobe	1 x 20x25; 1 x 25x25; 1 x 27x25; 1 x 30x25
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0

Bit-Check 10 Zyklop Mini 1



9 bits, tough, for universal use, 1 Wera Bit Ratchet Zyklop Mini 1, drop-forged full steel design, suitable for $^1/_4$" hex bits as per DIN ISO 1173-C 6.3 and E 6.3 and Wera series 1 and 4. Can also be used with $^1/_4$" sockets by using the Wera socket adaptor 870/1.


05**073645**001		
	8001 A	1 x 1/4"x87,0
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25
	840/1 Z Hex-Plus	1 x 4,0x25; 1 x 5,0x25

Bit-Check 10 Zyklop Mini BiTorsion 1



9 bits, BiTorsion for long service life, extra-tough, for universal use.Take it easy toolfinder: Output colour coding (red = Phillips; black = Pozidriv; green = TORX®; blue = hexagon) and large stamp to enable the desired bit to be easily located. , 1 Wera Bit Ratchet Zyklop Mini 1, drop-forged full steel design, suitable for $^1/_4$" hex bits as per DIN ISO 1173-C 6.3 and E 6.3 and Wera series 1 and 4. Can also be used with $^1/_4$" sockets by using the Wera socket adaptor 870/1.

05**057418**001		
	8001 A	1 x 1/4"x87,0
	851/1 BTZ PH	1 x PH 1x25; 1 x PH 2x25
	855/1 BTZ PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 TORX® BTZ	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25
	840/1 BTZ Hex-Plus	1 x 4,0x25; 1 x 5,0x25



Zyklop Mini

For confined spaces

8001 A Zyklop Mini 1 Bit Ratchet ¼" SB with ¼" drive





Application: Suitable for $^{1}/_{4}$" hex bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4, Wera adaptor 870/1 for $^{1}/_{4}$" sockets

Design: Drop-forged full steel design, fine-tooth ratchet mechanism, small return angle of 6°, forward and reverse drive switch

Handle: Kraftform handle with proven Kraftform geometry provides perfectly designed finger contact zones, ergonomic ratchet head and handle

05**073230**001		
	8001 A	1 x 1/4"x87,0
	870/1	1 x 1/4"x25

Zyklop Mini 2



Application: Suitable for Wera sockets 8790 FA

Design: Drop-forged full steel design, fine-tooth ratchet mechanism, small return angle of 6°, forward and reverse drive switch

Handle: Kraftform handle with proven Kraftform geometry provides perfectly designed finger contact zones, ergonomic ratchet head and handle

	mm
05**003660**001	107



8790 FA Zyklop socket with 1/4" and Hexagon 11 drive



Application: Hexagon headed bolts, screws and nuts

Design: 1/4" external square and hexagon size; suitable for 1/4" ratchets and Wera Zyklop Mini 2 ratchet

Handle: Manual applications; ball intercept ring; extremely low height, ideal for confined spaces; chrome vanadium, chrome-plated

	mm	mm	mm	mm	mm
05**003665**001	4,0	11,8	9,5	18,0	6,4
05**003666**001	4,5	11,8	9,5	18,0	7,0
05**003667**001	5,0	11,8	9,5	18,0	7,6
05**003668**001	5,5	11,8	9,5	18,0	8,2
05**003669**001	6,0	11,8	9,5	18,0	9,2
05**003670**001	7,0	11,8	9,5	18,0	10,4
05**003675**001	8,0	11,8	9,5	18,0	11,5
05**003690**001	10,0	11,8	9,5	18,0	13,8
05**003684**001	12,0	11,8	9,5	18,0	16,8
05**003685**001	13,0	11,8	9,5	18,0	17,8

”To learn more about this product, scan the QR code.“

Tip

Is such a small tool sufficiently resilient?



The Zyklop Mini 1 can withstand at least 65 Nm. That is far more power than can normally be transferred to such a small tool.

Zyklop Mini 2



The Zyklop Mini 2 is suitable for the direct attachment of the special Wera Zyklop sockets 8790 FA. These sockets feature a very low height, ideal for confined working spaces.

TAKE IT EASY TOOL FINDER

“Take it easy”



“Take it easy” tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).


JOKER

Joker Wrenches



Joker
Ratcheting combination wrenches **228**




Joker Switch
Ratcheting combination wrenches **230**



Joker open-ended wrenches

When we began to think about open-ended wrenches, we asked ourselves: why does the wrench always have to be flipped over; why does it have an offset design; why does it slip off injuring fingers? The new design of the mouth resulted in a real “Joker” that works even when all other trumps have been played.





The Joker’s holding function means that nuts and bolts can be held in the jaw and easily positioned where they are needed. Fastening on to the thread can then be done quickly and safely, thanks to the innovative special stop-plate which holds the fastener. No more time-wasting searches for dropped nuts and bolts! After applying and positioning the nut or bolt, fastening can begin immediately – no additional tools required.



Constant re-positioning of the wrench? Difficulty holding fasteners in confined spaces? Easing off to avoid any risks of injury or fastener damage? That was yesterday. Today, the Joker prevents slipping off of the fastener head with its integrated limit-stop – no longer is the thumb needed to act as a depth stop. This makes applications much easier and allows signifi cantly more force to be applied during fastening jobs.



The Joker’s clever double-hex geometry delivers a very positive connection with nuts or bolts – it’s a perfect fit. And the exchangeable, hardened metal gripping plate in the Joker’s mouth literally bites itself into the bolt, with its extremely hard tips. Both features combine to prevent slipping, even at higher torque.





Instead of 60°, the Joker only has a 30° return angle thanks to its unique double-hex design. Along with the Joker's straight neck, this means that flipping the wrench has become a thing of the past. With the Joker, you can now loosen and tighten nuts and bolts, in situations where conventional tools fail. Particularly in confined spaces, where conventional open-jawed wrenches cannot be used. The combination of limit stop and small return angle enables eff ective work, even on screw pipe connections.



The ratcheting feature at the ring end boasts an exceptional, fine tooth mechanism – 80 teeth in all – which provides greater flexibility, even in very confined workingspaces.

Joker

Combination ratchet wrenches

Joker Ratcheting combination wrenches



Application: Hexagonal nuts or bolts
Design: Ratcheting combination wrench

		mm	mm	mm	mm	mm	mm
05**073268**001		8	144	20	5,5	18	7
05**073270**001		10	159	22	5,5	21	7,2
05**073271**001		11	165	25	6,3	22	7,5
05**073272**001		12	170,7	26,3	6,6	25	8,5
05**073273**001		13	177	27,3	7	25	8,6
05**073274**001		14	188	29,3	7,5	28	9,2
05**073275**001		15	200	32,3	7,8	28,5	9,2
05**073276**001		16	212	35	8,2	32,7	10,5
05**073277**001		17	224	37,2	8,5	32,7	10,5
05**073278**001		18	235	39	9	33,8	11
05**073279**001		19	246	42	9,5	34,8	11


Joker Ratcheting combination wrenches, imperial



Application: Hexagonal nuts or bolts
Design: Ratcheting combination wrench

			mm	mm	mm	mm	mm
05**073280**001		$^{5}/_{16}$"	144	20	5,5	18	7
05**073281**001		$^{3}/_{8}$"	159	22	5,5	21	7,2
05**073282**001		$^{7}/_{16}$"	165	25	6,3	22	7,5
05**073283**001		$^{1}/_{2}$"	177	27,3	7	25	8,6
05**073284**001		$^{9}/_{16}$"	188	29,3	7,5	28	9,2
05**073285**001		$^{5}/_{8}$"	212	35	8,2	32,7	10,5
05**073286**001		$^{11}/_{16}$"	235	39	9	33,8	11
05**073287**001		$^{3}/_{4}$"	246	42	9,5	34,8	11

Joker Double open-ended wrenches



Application: Hexagon bolts and nuts
Design: Double open-ended wrench

		mm	mm	mm	mm	mm	mm
05**003760**001		10	23	13	27	5,5	7
05**003765**001		17	37	19	42	8,5	9,5

Joker Set of Ratcheting combination wrenches



Set of ratcheting combination wrenches
11-piece set
Durable pouch

05**020013**001		
	Joker	1 x 8x144; 1 x 10x159; 1 x 11x165; 1 x 12x170,7; 1 x 13x177; 1 x 14x188; 1 x 15x200; 1 x 16x212; 1 x 17x224; 1 x 18x235; 1 x 19x246

Joker Set of Ratcheting combination wrenches, imperial



Set of ratcheting combination wrenches
8-piece set
Durable pouch

05**020012**001		
	Joker inch	1 x 5/16"x144; 1 x 3/8"x159; 1 x 7/16"x165; 1 x 1/2"x177; 1 x 9/16"x188; 1 x 5/8"x212; 1 x 11/16"x235; 1 x 3/4"x246

Joker Set of Ratcheting combination / double open-ended wrenches



Ratcheting Combination/Double Open-Ended Wrench Set
6-piece set
Durable pouch

05**020022**001		
	Joker	1 x 10x159; 1 x 13x177; 1 x 17x224; 1 x 19x246
	Joker Double	1 x 10x13x167; 1 x 17x19x235

Tip

Fine tooth mechanism



The ratcheting feature at the ring end boasts an exceptional, fine tooth mechanism – 80 teeth in all – which provides greater flexibility, even in very confined working spaces.

Double open-ended wrench



The Joker double open-ended wrench is ideally suited for locking down nuts and bolts.

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Joker

Combination ratchet wrenches

Joker Set of Ratcheting combination wrenches



Set of ratcheting combination wrenches
4-piece set
Durable pouch

05**073290**001		
	Joker	1 x 10x159; 1 x 13x177; 1 x 17x224; 1 x 19x246

Joker Set of Ratcheting combination wrenches, imperial



Set of ratcheting combination wrenches
4-piece set
Durable pouch

05**073295**001		
	Joker inch	1 x 7/16"x165; 1 x 1/2"x177; 1 x 9/16"x188; 1 x 3/4"x246

" To learn more about this product, scan the QR code. "

Joker Switch Ratcheting combination wrenches, with switch lever



Application: Hexagonal nuts or bolts

Design: Ratcheting combination wrench, switch lever for convenient change of direction; ring end angled at 15° from the handle

		mm	mm	mm	mm	mm	mm
05**020064**001		8	144	20,3	5,5	18	7
05**020065**001		10	159	23	5,5	21,5	7,5
05**020066**001		11	165	24,3	6,3	22	7,5
05**020067**001		12	171	26,3	6,6	25	8,5
05**020068**001		13	179	27,3	7	26	8,5
05**020069**001		14	187	30	7,5	28	9,5
05**020070**001		15	199	32	7,8	28,8	9,5
05**020071**001		16	213	35	8,2	31,7	10,5
05**020072**001		17	225	37	8,5	33	10,5
05**020073**001		18	234	39,5	9	34	11
05**020074**001		19	246	42	9,5	34,7	11

Joker Switch Ratcheting combination wrenches, Imperial, with switch lever



Application: Hexagonal nuts or bolts

Design: Ratcheting combination wrench, switch lever for convenient change of direction; ring end angled at 15° from the handle

			mm	mm	mm	mm	mm
05**020075**001		5/16"	144	20,3	5,5	18	7
05**020076**001		3/8"	159	23	5,5	21,5	7,5
05**020077**001		7/16"	165	24,3	6,3	22	7,5
05**020078**001		1/2"	171	26,3	6,6	25	8,5
05**020079**001		9/16"	187	30	7,5	28	9,5
05**020080**001		5/8"	213	35	8,2	31,7	10,5
05**020081**001		11/16"	234	39,5	9	34	11
05**020082**001		3/4"	246	42	9,5	34,7	11

Joker Switch Set of Ratcheting combination wrenches






Set of ratcheting combination wrenches, reversible

4-piece set

Durable pouch

05**020090**001	
	Joker Switch 1 x 10x159; 1 x 13x179; 1 x 17x225; 1 x 19x246

Joker Switch Set of Ratcheting combination wrenches, imperial





Set of ratcheting combination wrenches, reversible

4-piece set

Durable pouch

05**020092**001	
	Joker Switch inch 1 x 7/16"x165; 1 x 1/2"x171; 1 x 9/16"x187; 1 x 3/4"x246

Tip

Fine tooth mechanism



The ratcheting feature at the ring end boasts an exceptional, fine tooth mechanism – 80 teeth in all – which provides greater flexibility, even in very confined working spaces.

Angled ratchet end



The ratchet end is angled at 15° to the tool axis, making application of the tool in confined spaces much easier.

Joker Switch



The direction of the fine-tooth ratchet mechanism can easily be changed via the smooth switch lever.

Joker

Combination ratchet wrenches

Joker Switch Set of Ratcheting combination wrenches, Imperial





Set of ratcheting combination wrenches, reversible

8-piece set

Durable pouch

05**020093**001	
	Joker Switch inch 1 x 5/16"x144; 1 x 3/8"x159; 1 x 7/16"x165; 1 x 1/2"x171; 1 x 9/16"x187; 1 x 5/8"x213; 1 x 11/16"x234; 1 x 3/4"x246

Joker Switch Set of Ratcheting combination wrenches





Set of ratcheting combination wrenches, reversible

11-piece set

Durable pouch

05**020091**001	
	Joker Switch 1 x 8x144; 1 x 10x159; 1 x 11x165; 1 x 12x171; 1 x 13x179; 1 x 14x187; 1 x 15x199; 1 x 16x213; 1 x 17x225; 1 x 18x234; 1 x 19x246




Wera
Plus 5
Plus 4
Plus 3
Plus 2.5
Plus 2
Plus 1,5

L-Keys



L-Keys for Hexagon Socket Screws **238**



L-Keys for TORX® Screws **250**



Offset Screwdrivers **257**



L-Keys


We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened – and so the user finds the L-key slipping out of the recess.

Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.





Stainless L-keys are hardened to the same strength as conventional (carbon) steel tools, and prevent extraenous rust forming.



SPKL – protects fingers! L-keys with a thermoplastic sleeve (SPKL) are manufactured out of easy-to-grip, circular material. The sleeve ensures that work is safe and comfortable even at low temperatures. High corrosion protection features thanks to the special BlackLaser surface treatment. Colour coding and large stamp to enable the desired L-key to be easily located.



Chrome-plated hexagon L-keys or with BlackLaser surface treatment for outstanding surface protection and long service life. High corrosion protection.





The size of each L-keys has been engraved by a laser. In addition SPKL L-keys have a colour coding according to sizes – for simple and rapid accessing of the required tool. Making it easy to find the right tool.




The wear-resistant clip material ensures that the L-keys are securely held yet are easy to remove.

L-Keys for Hexagon Socket Screws

The Hex-Plus profile extends the service life of hexagon socket screws

3950/9 Hex-Plus Multicolour Stainless 1 L-key set, metric, stainless





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: Stainless steel, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

05**022669**001		
○	**3950 SPKL Multicolour**	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112; 1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195; 1 x 10,0x224

3950/9 Hex-Plus Stainless 1 L-key set, metric, stainless





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: Stainless steel

Tip: Hex-Plus, ball-end hexagon on long arm

05**022720**001		
○	**3950 PKL**	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112; 1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195; 1 x 10,0x224

3950/9 Hex-Plus Stainless 1 SB L-key set, metric, stainless

	4013288	
05**073544**001	180377	
	○ **3950 PKL** 1 x 1.5x90; 1 x 2.0x101; 1 x 2.5x112; 1 x 3.0x123; 1 x 4.0x137; 1 x 5.0x154; 1 x 6.0x172; 1 x 8.0x195; 1 x 10.0x224	



3950/9 Hex-Plus Imperial Stainless 1 L-key set, imperial, stainless



9-piece set in belt pouch

Application: Hexagon socket screws

Design: Stainless steel

Tip: Hex-Plus, ball-end hexagon on long arm

05**022721**001	
	3950 PKL inch 1 x 3/32"x112; 1 x 7/64"x119; 1 x 1/8"x123; 1 x 9/64"x130; 1 x 5/32"x137; 1 x 3/16"x154; 1 x 1/4"x185; 1 x 5/16"x195; 1 x 3/8"x224

Tip

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Why do the SPKL L-keys from Wera have a round design and come with a rubber sleeve?



L-keys made from circular material fit into the hand better and allow less strenuous work over a longer period. Additionally, the rubber sleeve provides a pleasant grip, particularly in applications at low temperatures. Colour coding and large stamp enable the desired L-key to be easily located. Moreover, the round material keys are more robust, particularly where smaller sizes are concerned.

TORX® and hexagon ball tip




The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs. This ball tip geometry – often found on L-keys – is now available on a number of Wera bits.

L-Keys for Hexagon Socket Screws

The Hex-Plus profile extends the service life of hexagon socket screws

950/9 Hex-Plus Multicolour HF 1 L-key set, metric, BlackLaser, with holding function





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm, holding function for hexagon socket screws, sizes: 1.5, 2.0 and 2.5 without holding function

05**022210**001		
O	**950 SPKL Multicolour**	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112
O	**950 SPKL HF Multicolour**	1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195; 1 x 10,0x224

950/9 Hex-Plus Multicolour 1 L-key set, metric, BlackLaser





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

05**022089**001		
O	**950 SPKL Multicolour**	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112; 1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172; 1 x 8,0x195; 1 x 10,0x224

950/9 Hex-Plus Multicolour 1 SB L-key set, metric, BlackLaser

		4013288
05**073593**001		165688
	O **950 SPKL Multicolour** 1 x 1.5x90; 1 x 2.0x101; 1 x 2.5x112; 1 x 3.0x123; 1 x 4.0x137; 1 x 5.0x154; 1 x 6.0x172; 1 x 8.0x195; 1 x 10.0x224	



950/9 Hex-Plus Multicolour Imperial 1 L-key set, imperial, BlackLaser



9-piece set in belt pouch

Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

05**022639**001		
	950 SPKL inch	1 x 5/64"x101; 1 x 3/32"x112; 1 x 1/8"x123; 1 x 5/32"x137; 1 x 3/16"x154; 1 x 7/32"x172; 1 x 1/4"x185; 1 x 5/16"x195; 1 x 3/8"x224

950/7 Hex-Plus Multicolour Magnet 1 L-key set, metric, BlackLaser



7-piece set in a two-component clip. For recessed screws, it's often advantageous for the screw to be held on the L-key by magnetic force. The Wera clips with magnetiser/demagnetiser enable a magnetisation/demagnetisation of L-keys in a flash.

Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

05**022534**001		
	950 SPKL	1 x 1,5x90; 1 x 2,0x101; 1 x 2,5x112; 1 x 3,0x123; 1 x 4,0x137; 1 x 5,0x154; 1 x 6,0x172

Tip

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Holding function on long arm



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Magnetiser/Demagnetiser



For recessed screws, it's often advantageous for the screw to be held on the L-key by magnetic force. The Wera clips with magnetiser/demagnetiser enable a magnetisation/demagnetisation of L-keys in a flash.

Magnetising



Demagnetising

L-Keys for Hexagon Socket Screws

The Hex-Plus profile extends the service life of hexagon socket screws

950/9 Hex-Plus 1 L-key set, metric, chrome-plated





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: Chrome-plated


Tip: Hex-Plus, ball-end hexagon on long arm

05**022087**001		
○	**950 PKL**	1 x 1,5x90 [1]; 1 x 2,0x100; 1 x 2,5x112; 1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180; 1 x 8,0x200; 1 x 10,0x219

[1] Regular hexagon

950/9 Hex-Plus 2 L-key set, metric, chrome-plated





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus

05**021909**001		
○	**950 L**	1 x 1,5x90 [1]; 1 x 2,0x100; 1 x 2,5x112; 1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180; 1 x 8,0x200; 1 x 10,0x219

[1] Regular hexagon

950/9 Hex-Plus 1 SB L-key set, metric, chrome-plated

	4013288
05**073391**001	030160
○ **950 PKL** 1 x 1.5x90 [1]; 1 x 2.0x100; 1 x 2.5x112; 1 x 3.0x126; 1 x 4.0x140; 1 x 5.0x160; 1 x 6.0x180; 1 x 8.0x200; 1 x 10.0x219	



1) Regular hexagon

950/9 Hex-Plus 3 L-key set, metric, chrome-plated





9-piece set in a two-component clip

Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus, ball-end hexagon on long arm

05**133163**001		
○	**950 PKS**	1 x 1,5x50 [1]; 1 x 2,0x56; 1 x 2,5x63; 1 x 3,0x71; 1 x 4,0x80; 1 x 5,0x90; 1 x 6,0x100; 1 x 8,0x112; 1 x 10,0x125

[1] Regular hexagon

950/9 Hex-Plus 4 L-key set, metric, chrome-plated



9-piece set in a two-component clip

Application: Hexagon socket screws


Blade: Chrome plated, with extra short arm for use on screws that are difficult to access

Tip: Hex-Plus, ballpoint hexagon on long arm

05**073594**001		
O	**950 PKLS**	1 x 1,5x90 [1]; 1 x 2,0x100; 1 x 2,5x112; 1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180; 1 x 8,0x200; 1 x 10,0x219

[1] Regular hexagon

950/9 Hex-Plus 5 L-key set, metric, chrome-plated



9-piece set in a two-component clip

Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus

05**021406**001		
O	**950**	1 x 1,5x45 [1]; 1 x 2,0x50; 1 x 2,5x56; 1 x 3,0x63; 1 x 4,0x70; 1 x 5,0x80; 1 x 6,0x90; 1 x 8,0x100; 1 x 10,0x112

[1] Regular hexagon.

Tip

Hex-Plus for hexagon socket screws



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, “around-the-corner” screwdriving jobs.

L-Keys for Hexagon Socket Screws

The Hex-Plus profile extends the service life of hexagon socket screws

950/9 Hex-Plus 6 L-key set, metric, BlackLaser



9-piece set in a two-component clip

Application: Hexagon socket screws

Design: BlackLaser surface

Tip: Hex-Plus, ball-end hexagon on long arm

05**022086**001		
O	**950 PKL BM**	1 x 1,5x90 [1]; 1 x 2,0x100; 1 x 2,5x112; 1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180; 1 x 8,0x200; 1 x 10,0x219

[1] Regular hexagon

950/9 Hex-Plus 6 SB L-key set, metric, BlackLaser

	4013288
05**073596**001	106414
	O **950 PKL BM** 1 x 1.5x90 [1]; 1 x 2.0x100; 1 x 2.5x112; 1 x 3.0x126; 1 x 4.0x140; 1 x 5.0x160; 1 x 6.0x180; 1 x 8.0x200; 1 x 10.0x219



1) Regular hexagon

950/9 Hex-Plus 7 L-key set, metric, BlackLaser



9-piece set in a two-component clip

Application: Hexagon socket screws

Design: BlackLaser surface

Tip: Hex-Plus

05**021737**001		
O	**950 BM**	1 x 1,5x45 [1]; 1 x 2,0x50; 1 x 2,5x56; 1 x 3,0x63; 1 x 4,0x70; 1 x 5,0x80; 1 x 6,0x90; 1 x 8,0x100; 1 x 10,0x112

[1] Regular hexagon.

950/7 Hex-Plus Magnet 1 L-key set, metric, chrome-plated



7-piece set in a two-component clip. For recessed screws, it's often advantageous for the screw to be held on the L-key by magnetic force. The Wera clips with magnetiser/demagnetiser enable a magnetisation/demagnetisation of L-keys in a flash.

Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus, ball-end hexagon on long arm

05**022101**001		
O	**950 PKL**	1 x 1,5x90 [1]; 1 x 2,0x100; 1 x 2,5x112; 1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180

[1] Regular hexagon

950/7 Hex-Plus 1 L-key set, metric, chrome-plated



7-piece set in a two-component clip

Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus, ball-end hexagon on long arm

05**022181**001		
O	**950 PKL**	1 x 1,5x90 [1]; 1 x 2,0x100; 1 x 2,5x112; 1 x 3,0x126; 1 x 4,0x140; 1 x 5,0x160; 1 x 6,0x180

[1] Regular hexagon

950/13 Hex-Plus Imperial 1 L-key set, imperial, BlackLaser



13-piece set in a two-component clip

Application: Hexagon socket screws

Design: BlackLaser surface

Tip: Hex-Plus, ball-end hexagon on long arm

05**0217280**01	
O	**950 PKL inch** 1 x 0,05"x83 [1]; 1 x 1/16"x91 [1]; 1 x 5/64"x100; 1 x 3/32"x112; 1 x 7/64"x119; 1 x 1/8"x126; 1 x 9/64"x132; 1 x 5/32"x140; 1 x 3/16"x160; 1 x 7/32"x180; 1 x 1/4"x190; 1 x 5/16"x200; 1 x 3/8"x212

[1] Regular hexagon

950/9 Hex-Plus Imperial 1 L-key set, imperial, BlackLaser



9-piece set in a two-component clip

Application: Hexagon socket screws

Design: BlackLaser surface

Tip: Hex-Plus, ball-end hexagon on long arm

05**0221710**01	
O	**950 PKL inch** 1 x 5/64"x100; 1 x 3/32"x112; 1 x 1/8"x126; 1 x 5/32"x140; 1 x 3/16"x160; 1 x 7/32"x180; 1 x 1/4"x190; 1 x 5/16"x200; 1 x 3/8"x212


950/9 Hex-Plus Imperial 1 SB L-key set, imperial, BlackLaser

	4013288
05**1331800**01	154118
O	**950 PKL inch** 1 x 5/64"x100; 1 x 3/32"x112; 1 x 1/8"x126; 1 x 5/32"x140; 1 x 3/16"x160; 1 x 7/32"x180; 1 x 1/4"x190; 1 x 5/16"x200; 1 x 3/8"x212



Tip

Are there any advantages of an L-key with an extra short arm?



All users will recognise the need to saw or grind down L-keys to make them shorter for particularly confined screwdriving jobs. This has the disadvantage that they no longer have any corrosion protection at the separation point and secondly, they can become “soft” and therefore useless due to an alteration in the hardening during the shortening process.



L-Keys for Hexagon Socket Screws

The Hex-Plus profile extends the service life of hexagon socket screws

3950 SPKL Multicolour L-key, metric, stainless



Application: Hexagon socket screws

Design: Stainless steel, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

		⬡ mm	L' mm	L mm	L'	L
05**022660**001		1,5	90	14	3 1/2"	9/16"
05**022661**001		2,0	101	16	4"	5/8"
05**022662**001		2,5	112	19	4 7/16"	3/4"
05**022663**001		3,0	123	21	4 7/8"	27/32"
05**022664**001		4,0	137	24	5 3/8"	1"
05**022665**001		5,0	154	27	6 1/16"	1 1/16"
05**022666**001		6,0	172	31	6 3/4"	1 1/4"
05**022667**001		8,0	195	37	7 11/16"	1 7/16"
05**022668**001		10,0	224	42	9"	1 11/16"

3950 PKL L-key, metric, stainless



Application: Hexagon socket screws

Design: Stainless steel

Tip: Hex-Plus, ball-end hexagon on long arm

	⬡ mm	L' mm	L mm	L'	L
05**022700**001	1,5	90	14	3 1/2"	9/16"
05**022701**001	2,0	101	16	4"	5/8"
05**022702**001	2,5	112	19	4 7/16"	3/4"
05**022703**001	3,0	123	21	4 7/8"	27/32"
05**022704**001	4,0	137	24	5 3/8"	1"
05**022705**001	5,0	154	27	6 1/16"	1 1/16"
05**022706**001	6,0	172	31	6 3/4"	1 1/4"
05**022708**001	8,0	195	37	7 11/16"	1 7/16"
05**022709**001	10,0	224	42	9"	1 11/16"

3950 PKL L-key, imperial, stainless



Application: Hexagon socket screws

Design: Stainless steel

Tip: Hex-Plus, ball-end hexagon on long arm

	⬡	L' mm	L mm	L'	L
05**022710**001	3/32"	112	19	4 7/16"	3/4"
05**022711**001	7/64"	119	20	4 3/4"	25/32"
05**022712**001	1/8"	123	21	4 7/8"	27/32"
05**022713**001	9/64"	130	22	5 3/16"	29/32"
05**022714**001	5/32"	137	24	5 3/8"	1"
05**022715**001	3/16"	154	27	6 1/16"	1 1/16"
05**022716**001	1/4"	185	34	7 1/4"	1 5/16"
05**022717**001	5/16"	195	37	7 11/16"	1 7/16"
05**022718**001	3/8"	224	42	9"	1 11/16"

950 SPKL HF L-key Multicolour, metric, with holding function



Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm, holding function for hexagon socket screws

		⬡ mm	L' mm	L mm	L'	L
05**022200**001		3,0	123	21	4 7/8"	27/32"
05**022201**001		4,0	137	24	5 3/8"	1"
05**022202**001		5,0	154	27	6 1/16"	1 1/16"
05**022203**001		6,0	172	31	6 3/4"	1 1/4"
05**022204**001		8,0	195	37	7 11/16"	1 7/16"
05**022205**001		10,0	224	42	9"	1 11/16"

950 SPKL L-key Multicolour, metric



Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

		mm	mm	mm		
05**022600**001		1,5	90	14	3 1/2"	9/16"
05**022602**001		2,0	101	16	4"	5/8"
05**022604**001		2,5	112	19	4 7/16"	3/4"
05**022606**001		3,0	123	21	4 7/8"	27/32"
05**022608**001		4,0	137	24	5 3/8"	1"
05**022610**001		5,0	154	27	6 1/16"	1 1/16"
05**022612**001		6,0	172	31	6 3/4"	1 1/4"
05**022614**001		8,0	195	37	7 11/16"	1 7/16"
05**022616**001		10,0	224	42	9"	1 11/16"

950 SPKL L-key Multicolour, imperial



Application: Hexagon socket screws

Design: BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Hex-Plus, ball-end hexagon on long arm

			mm	mm		
05**022630**001		5/64"	101	16	4"	5/8"
05**022631**001		3/32"	112	19	4 7/16"	3/4"
05**022632**001		1/8"	123	21	4 7/8"	27/32"
05**022633**001		5/32"	137	24	5 3/8"	1"
05**022634**001		3/16"	154	27	6 1/16"	1 1/16"
05**022635**001		7/32"	172	31	6 3/4"	1 1/4"
05**022636**001		1/4"	185	34	7 1/4"	1 5/16"
05**022637**001		5/16"	195	37	7 11/16"	1 7/16"
05**022638**001		3/8"	224	42	9"	1 11/16"

950 PKL L-key, metric, chrome-plated



Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus, ball-end hexagon on long arm

	mm	mm	mm		
05**022050**001 [1]	1,5	90	14	3 1/2"	9/16"
05**022052**001	2,0	100	16	4"	5/8"
05**022054**001	2,5	112	18	4 7/16"	23/32"
05**022056**001	3,0	126	20	5"	25/32"
05**022058**001	4,0	140	25	5 1/2"	1"
05**022060**001	5,0	160	28	6 5/16"	1 3/32"
05**022062**001	6,0	180	32	7 1/16"	1 1/4"
05**022063**001	7,0	190	34	7 1/2"	1 5/16"
05**022064**001	8,0	200	36	8"	1 7/16"
05**022066**001	10,0	219	40	8 11/16"	1 9/16"
05**022067**001	12,0	248	45	10"	1 3/4"

[1] Regular hexagon

950 PKL BM L-key, metric, BlackLaser



Application: Hexagon socket screws

Design: BlackLaser surface

Tip: Hex-Plus, ball-end hexagon on long arm

	mm	mm	mm		
05**027101**001 [1]	1,5	90	14	3 1/2"	9/16"
05**027102**001	2,0	100	16	4"	5/8"
05**027103**001	2,5	112	18	4 7/16"	23/32"
05**027104**001	3,0	126	19	5"	3/4"
05**027105**001	4,0	140	25	5 1/2"	1"
05**027106**001	5,0	160	28	6 5/16"	1 3/32"
05**027107**001	6,0	180	32	7 1/16"	1 1/4"
05**027110**001	7,0	190	34	7 1/2"	1 5/16"
05**027108**001	8,0	200	36	8"	1 7/16"
05**027109**001	10,0	219	40	8 11/16"	1 9/16"
05**027111**001	12,0	248	45	10"	1 3/4"

[1] Regular hexagon

L-Keys for Hexagon Socket Screws

The Hex-Plus profile extends the service life of hexagon socket screws

950 PKL L-key, imperial, BlackLaser



Application: Hexagon socket screws

Design: BlackLaser surface

Tip: Hex-Plus, ball-end hexagon on long arm

	⬡	L' mm	L mm	L'	L
05**022079**001 [1]	0,05"	83	14	3 1/4"	9/16"
05**022081**001 [1]	1/16"	91	15	3 1/2"	19/32"
05**022068**001	5/64"	100	16	4"	5/8"
05**022070**001	3/32"	112	18	4 7/16"	23/32"
05**022071**001	7/64"	119	19	4 3/4"	3/4"
05**022072**001	1/8"	126	20	5"	25/32"
05**022073**001	9/64"	132	23	5 3/16"	29/32"
05**022074**001	5/32"	140	25	5 1/2"	1"
05**022076**001	3/16"	160	25	6 5/16"	1"
05**022078**001	7/32"	180	27	7 1/16"	1 1/16"
05**022080**001	1/4"	190	34	7 1/2"	1 5/16"
05**022082**001	5/16"	200	36	8"	1 7/16"
05**022095**001	3/8"	212	38	8 3/8"	1 1/2"
05**022096**001	1/2"	224	40	9"	1 9/16"

[1] Regular hexagon

950 PKS L-key, metric, chrome-plated



Application: Hexagon socket screws

Design: Short, chrome-plated

Tip: Hex-Plus, ball-end hexagon on long arm

	⬡ mm	L' mm	L mm	L'	L
05**133150**001 [1]	1,5	50	14	2"	9/16"
05**133151**001	2,0	56	16	2 7/32"	5/8"
05**133152**001	2,5	63	18	2 1/2"	23/32"
05**133153**001	3,0	71	20	2 3/4"	25/32"
05**133154**001	4,0	80	22	3"	29/32"
05**133155**001	5,0	90	25	3 1/2"	1"
05**133156**001	6,0	100	28	4"	1 3/32"
05**133157**001	8,0	112	32	4 7/16"	1 1/4"
05**133158**001	10,0	125	36	5"	1 5/16"

[1] Regular hexagon

950 PKLS Long Arm Ballpoint Hex Key, metric, chrome plated



Application: For hexagon socket screws

Design: Chrome plated, with extra short arm for use on screws that are difficult to access

Tip: Hex-Plus, ballpoint hexagon on long arm

	⬡ mm	L' mm	L mm	L'	L
05**022040**001 [1]	1,5	90	4,5	3 1/2"	11/64"
05**022041**001	2,0	100	5,5	4"	7/32"
05**022042**001	2,5	112	6,5	4 7/16"	1/4"
05**022043**001	3,0	126	7,5	5"	19/64"
05**022044**001	4,0	140	10,0	5 1/2"	25/64"
05**022045**001	5,0	160	12	6 5/16"	15/32"
05**022046**001	6,0	180	15	7 1/16"	19/32"
05**022047**001	8,0	200	19	8"	3/4"
05**022048**001	10,0	219	22	8 5/8"	7/8"

[1] Regular hexagon

950 L-key, metric, chrome-plated



Application: Hexagon socket screws

Design: Chrome-plated

Tip: Hex-Plus

	⬡ mm	L' mm	L mm	L'	L
05**021600**001 [1]	1,5	90	14	3 1/2"	9/16"
05**021605**001	2,0	100	16	4"	5/8"
05**021610**001	2,5	112	18	4 7/16"	23/32"
05**021615**001	3,0	126	20	5"	25/32"
05**021620**001	4,0	140	25	5 1/2"	1"
05**021625**001	5,0	160	28	6 5/16"	1 3/32"
05**021630**001	6,0	180	32	7 1/16"	1 1/4"
05**021632**001	7,0	190	30	7 1/2"	1 1/4"
05**021635**001	8,0	200	36	8"	1 7/16"
05**021640**001	10,0	219	40	8 11/16"	1 9/16"
05**021645**001	12,0	250	45	10"	1 3/4"

[1] Regular hexagon

950 L-key, metric, chrome-plated



Application: Hexagon socket screws
Design: Chrome-plated
Tip: Hex-Plus

	⬡ mm	L' mm	L mm	L'	L
05**021005**001 [1]	1,5	45	14	1 3/4"	9/16"
05**021010**001	2,0	50	16	2"	5/8"
05**021015**001	2,5	56	18	2 7/32"	23/32"
05**021020**001	3,0	63	20	2 1/2"	25/32"
05**021025**001	3,5	66	23	2 5/8"	29/32"
05**021030**001	4,0	70	25	2 3/4"	1"
05**021035**001	4,5	75	26	3"	1 1/32"
05**021040**001	5,0	80	28	3 1/8"	1 3/32"
05**021045**001	6,0	90	32	3 1/2"	1 1/4"
05**021050**001	7,0	95	34	3 3/4"	1 5/16"
05**021055**001	8,0	100	36	4"	1 7/16"
05**021060**001	9,0	106	38	4 3/16"	1 1/2"
05**021065**001	10,0	112	40	4 7/16"	1 9/16"
05**021070**001	11,0	120	43	4 3/4"	1 11/16"
05**021075**001	12,0	125	45	5"	1 3/4"
05**021080**001	13,0	132	50	5 3/16"	2"
05**021085**001 [1]	14,0	140	56	5 1/2"	2 7/32"
05**021090**001 [1]	17,0	160	63	6 5/16"	2 1/2"
05**021095**001 [1]	19,0	180	70	7 1/16"	2 3/4"
05**021100**001 [1]	22,0	200	80	8"	3 1/8"
05**021105**001 [1]	24,0	224	90	9"	3 1/2"
05**021110**001 [1]	27,0	250	100	10"	4"

[1] Regular hexagon.

950 BM L-key, metric, BlackLaser



Application: Hexagon socket screws
Design: BlackLaser surface
Tip: Hex-Plus

	⬡ mm	L' mm	L mm	L'	L
05**027201**001 [1]	1,5	45	14	1 3/4"	9/16"
05**027202**001	2,0	50	16	2"	5/8"
05**027203**001	2,5	56	18	2 7/32"	23/32"
05**027204**001	3,0	63	20	2 1/2"	25/32"
05**027205**001	3,5	66	23	2 5/8"	29/32"
05**027206**001	4,0	70	25	2 3/4"	1"
05**027207**001	4,5	75	26	3"	1 1/32"
05**027208**001	5,0	80	28	3 1/8"	1 3/32"
05**027209**001	6,0	90	32	3 1/2"	1 1/4"
05**027210**001	7,0	95	34	3 3/4"	1 5/16"
05**027211**001	8,0	100	36	4"	1 7/16"
05**027213**001	9,0	106	38	4 11/64"	1 1/2"
05**027212**001	10,0	112	40	4 7/16"	1 9/16"
05**027214**001	11,0	120	43	4 23/32"	1 11/16"
05**027215**001	12,0	125	45	5"	1 49/64"

[1] Regular hexagon.



L-Keys for TORX® Screws

Powerful, ergonomic, long service life

967/9 TX XL Multicolour HF 1 L-key set with holding function, long



9-piece set in a two-component clip

Application: TORX® socket screws

Blade: Zinc-phosphated, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications

05**024470**001		
○○	**967 SXL HF TORX® Multicolour**	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112; 1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224

967/9 TX Multicolour HF 1 L-key set with holding function



9-piece set in a two-component clip

Application: TORX® socket screws

Blade: Round

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, BlackLaser surface, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

05**024179**001		
○	**967 SL TORX® HF**	1 x TX 8x76; 1 x TX 9x79; 1 x TX 10x85; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132

967/9 TX XL HF 1 L-key set with holding function, long



9-piece set in a two-component clip

Application: TORX® socket screws

Blade: zinc-phosphated

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications

05**024450**001		
○○	**967 XL HF TORX®**	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112; 1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224

967/9 TX HF 1 L-key set with holding function, BlackLaser



9-piece set in a two-component clip

Application: TORX® socket screws

Blade: Round

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, BlackLaser surface

05**024244**001		
○	**967 L TORX® HF**	1 x TX 8x76; 1 x TX 9x79; 1 x TX 10x85; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132

967/9 TX XL Multicolour 1 Multicolour L-key set for TORX® screws, long



9-piece set in a two-component clip

Application: TORX® socket screws

Design: Zinc-phosphated, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: TORX® on short arm, TORX® ball end on long arm, TX 8, TX 9, TX 10: without ball-end at the long arm

05**024480**001		
	967 SXL TORX® Multicolour	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112
	967 SPKXL TORX® Multicolour	1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224

Tip

The HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

"Take it easy"




"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

L-Keys for TORX® Screws

Powerful, ergonomic, long service life

967/9 TX BO Multicolour 1 L-key set for tamper-proof TORX® screws, BlackLaser





9-piece set in a two-component clip. For recessed screws, it's often advantageous for the screw to be held on the L-key by magnetic force. The Wera clips with magnetiser/demagnetiser enable a magnetisation/demagnetisation of L-keys in a flash.

Application: TORX® socket screws with and without pin (BO = bore hole)

Design: BlackLaser, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: TORX® on short arm, TORX® ball end on long arm

05**024335**001		
	967 SPKL TORX® BO Multicolour	1 x TX 8x76 [1]; 1 x TX 9x79 [1]; 1 x TX 10x85 [2]; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132

[1] Product without bore hole at the short and without ball-end at the long arm.
[2] Product without ball-end at the long arm.

967/9 TX BO Multicolour 1 SB, TORX® BO L-key set for tamper-proof TORX® screws, BlackLaser

	4013288
05**073599**001	170125
	967 SPKL TORX® BO Multicolour 1 x TX 8x76 [1]; 1 x TX 9x79 [1]; 1 x TX 10x85 [2]; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132



[1] Product without bore hole at the short and without ball-end at the long arm.
[2] Product without ball-end at the long arm.

967/9 TX XL 1 TORX® L-key set, long



9-piece set in a two-component clip

Application: TORX® socket screws

Design: Zinc-phosphated

Tip: TORX® on short arm, TORX® ball end on long arm, TX 8, TX 9, TX 10: without ball-end at the long arm

05**024460**001		
	967 XL TORX®	1 x TX 8x90; 1 x TX 9x101; 1 x TX 10x112
	967 PKXL TORX®	1 x TX 15x123; 1 x TX 20x137; 1 x TX 25x154; 1 x TX 27x172; 1 x TX 30x195; 1 x TX 40x224

967/9 TX 1 L-key set, BlackLaser



9-piece set in a two-component clip

Application: TORX® socket screws

Design: BlackLaser surface

Tip: TORX® on short arm, TORX® ball end on long arm

05**024242**001		
	967 PKL TORX®	1 x TX 8x76 [1]; 1 x TX 9x79 [1]; 1 x TX 10x85 [1]; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132

[1] Product without ball-end at the long arm.

967/9 TX 1 SB L-key set, BlackLaser

	4013288
05**073598**001	106438
	967 PKL TORX® 1 x TX 8x76 [1]; 1 x TX 9x79 [1]; 1 x TX 10x85 [1]; 1 x TX 15x90; 1 x TX 20x96; 1 x TX 25x104; 1 x TX 27x112; 1 x TX 30x122; 1 x TX 40x132



[1] Product without ball-end at the long arm.

967 SXL HF TORX® L-key Multicolour with holding function, long



Application: TORX® socket screws

Design: zinc-phosphated, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: Holding function for TORX® screws made according to Acument Intellectual Properties specifications

			mm	mm		
05**024471**001		TX 8	90	16	3 1/2"	5/8"
05**024472**001		TX 9	101	16	4"	5/8"
05**024473**001		TX 10	112	19	4 7/16"	3/4"
05**024474**001		TX 15	123	21	4 7/8"	27/32"
05**024475**001		TX 20	137	24	5 3/8"	1"
05**024476**001		TX 25	154	27	6 1/16"	1 1/16"
05**024477**001		TX 27	172	31	6 3/4"	1 1/4"
05**024478**001		TX 30	195	37	7 11/16"	1 7/16"
05**024479**001		TX 40	224	42	9"	1 11/16"

967 SPKXL TORX® L-key Multicolour, long



Application: TORX® socket screws

Design: zinc-phosphated, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: TORX® on short arm, TORX® ball end on long arm

			mm	mm		
05**024484**001		TX 15	123	21	4 7/8"	27/32"
05**024485**001		TX 20	137	24	5 3/8"	1"
05**024486**001		TX 25	154	27	6 1/16"	1 1/16"
05**024487**001		TX 27	172	31	6 3/4"	1 1/4"
05**024488**001		TX 30	195	37	7 11/16"	1 7/16"
05**024489**001		TX 40	224	42	9"	1 11/16"

Tip

The HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

"Take it easy"



"Take it easy" tool finder system – with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

L-Keys for TORX® Screws

Powerful, ergonomic, long service life

967 SL TORX® HF L-key Multicolour with holding function



Application: TORX® socket screws

Blade: Round

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, BlackLaser, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

		mm	mm		
05**024170**001	TX 8	76	16	3"	5/8"
05**024171**001	TX 9	79	16	3 1/8"	5/8"
05**024172**001	TX 10	85	17	3 1/4"	21/32"
05**024173**001	TX 15	90	18	3 1/2"	23/32"
05**024174**001	TX 20	96	19	3 3/4"	3/4"
05**024175**001	TX 25	104	21	4 1/8"	27/32"
05**024176**001	TX 27	112	22	4 7/16"	29/32"
05**024177**001	TX 30	122	24	4 13/16"	1"
05**024178**001	TX 40	132	27	5 3/16"	1 1/16"

967 SPKL TORX® BO L-key Multicolour



Application: TORX® socket screws with and without pin (BO = bore hole)

Design: BlackLaser, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: TORX® on short arm, TORX® ball end on long arm

		mm	mm		
05**024350**001 [1]	TX 8	76	16	3"	5/8"
05**024351**001 [1]	TX 9	79	16	3 1/8"	5/8"
05**024352**001 [2]	TX 10	85	17	3 3/8"	21/32"
05**024353**001	TX 15	90	18	3 1/2"	23/32"
05**024354**001	TX 20	96	19	3 3/4"	3/4"
05**024355**001	TX 25	104	21	4 1/8"	27/32"
05**024356**001	TX 27	112	22	4 7/16"	29/32"
05**024357**001	TX 30	122	24	4 13/16"	1"
05**024358**001	TX 40	132	27	5 3/16"	1 1/16"

[1] Product without bore hole at the short and without ball-end at the long arm.
[2] Product without ball-end at the long arm.

967 SXL TORX® L-key Multicolour, long



Application: TORX® socket screws

Design: zinc-phosphated, durable plastic sleeve. The contrasting inscriptions on the colour-coded sleeves mean that it is easy to recognise the correct sizes and this makes it simpler to find the right tool.

Tip: TORX®

		mm	mm		
05**024481**001	TX 8	90	16	3 1/2"	5/8"
05**024482**001	TX 9	101	16	4"	5/8"
05**024483**001	TX 10	112	19	4 7/16"	3/4"

967 XL HF TORX® L-key with holding function, long



Application: TORX® socket screws

Design: zinc-phosphated

Tip: Holding function for TORX® screws made according to Acument Intellectual Properties specifications

		mm	mm			
05**024451**001	TX 8	90	16	3 1/2"	5/8"	10
05**024452**001	TX 9	101	16	4"	5/8"	10
05**024453**001	TX 10	112	19	4 7/16"	3/4"	10
05**024454**001	TX 15	123	21	4 7/8"	27/32"	10
05**024455**001	TX 20	137	24	5 3/8"	1"	10
05**024456**001	TX 25	154	27	6 1/16"	1 1/16"	10
05**024457**001	TX 27	172	31	6 3/4"	1 1/4"	10
05**024458**001	TX 30	195	37	7 11/16"	1 7/16"	10
05**024459**001	TX 40	224	42	9"	1 11/16"	10

L-Keys for TORX® Screws

Powerful, ergonomic, long service life

967 PKXL TORX® L-key, long



Application: TORX® socket screws

Design: zinc-phosphated

Tip: TORX® on short arm, TORX® ball end on long arm

		L' mm	L mm	L'	L
05**024464**001	TX 15	123	21	4 7/8"	27/32"
05**024465**001	TX 20	137	24	5 3/8"	1"
05**024466**001	TX 25	154	27	6 1/16"	1 1/16"
05**024467**001	TX 27	172	31	6 3/4"	1 1/4"
05**024468**001	TX 30	195	37	7 11/16"	1 7/16"
05**024469**001	TX 40	224	42	9"	1 1/16"

967 XL TORX® L-key, lang



Application: TORX® socket screws

Design: zinc-phosphated

Tip: TORX®

		L' mm	L mm	L'	L
05**024461**001	TX 8	90	16	3 1/2"	5/8"
05**024462**001	TX 9	101	16	4"	5/8"
05**024463**001	TX 10	112	19	4 7/16"	3/4"

967 PKL TORX® L-key, BlackLaser



Application: TORX® socket screws

Design: BlackLaser surface

Tip: TORX® on short arm, TORX® ball end on long arm

		L' mm	L mm	L'	L
05**024199**001 [1]	TX 8	76	16	3"	5/8"
05**024100**001 [1]	TX 9	79	16	3 1/8"	5/8"
05**024105**001 [1]	TX 10	85	17	3 3/8"	21/32"
05**024200**001	TX 15	90	18	3 1/2"	23/32"
05**024202**001	TX 20	96	19	3 3/4"	3/4"
05**024204**001	TX 25	104	21	4 1/8"	27/32"
05**024206**001	TX 27	112	22	4 7/16"	29/32"
05**024208**001	TX 30	122	24	4 13/16"	1"
05**024210**001	TX 40	132	27	5 3/16"	1 1/16"

[1] Product without ball-end at the long arm.

967 L TORX® HF L-key with holding function, BlackLaser



Application: TORX® socket screws

Blade: Round, BlackLaser surface

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications

		L' mm	L mm	L'	L
05**024160**001	TX 8	76	16	3"	5/8"
05**024161**001	TX 9	79	16	3 1/8"	5/8"
05**024162**001	TX 10	85	17	3 1/4"	21/32"
05**024163**001	TX 15	90	18	3 1/2"	23/32"
05**024164**001	TX 20	96	19	3 3/4"	3/4"
05**024165**001	TX 25	104	21	4 1/8"	27/32"
05**024166**001	TX 27	112	22	4 7/16"	29/32"
05**024167**001	TX 30	122	24	4 13/16"	1"
05**024168**001	TX 40	132	27	5 3/16"	1 1/16"

967 TORX® L-key, BlackLaser



Application: TORX® socket screws

Design: BlackLaser surface

Tip: TORX®

		L' mm	L mm	L'	L
05**024001**001	TX 6	42	16	1 5/8"	5/8"
05**024002**001	TX 7	48	16	1 7/8"	5/8"
05**024003**001	TX 8	48	16	1 7/8"	5/8"
05**024004**001	TX 9	48	16	1 7/8"	5/8"
05**024005**001	TX 10	51	17	2"	21/32"
05**024008**001	TX 15	54	18	2 1/8"	23/32"
05**024010**001	TX 20	57	19	2 1/4"	3/4"
05**024012**001	TX 25	60	20	2 3/8"	25/32"
05**024013**001	TX 27	64	21	2 1/2"	27/32"
05**024015**001	TX 30	70	24	2 3/4"	1"
05**024020**001	TX 40	76	26	3"	1 1/32"

Offset Screwdrivers

Suitable for slotted, Phillips and Pozidriv screws

919 PH Offset Screwdriver



Application: For Phillips screws
Blade: 90° + 180°, mat nickel

		mm	mm		
05**017205**001	PH1+2	125	20	5"	25/32"

919 PZ Offset Screwdriver



Application: Suitable for Pozidriv-screws
Blade: 90° + 180°, BlackLaser

		mm	mm		
05**017305**001	PZ1+2	125	20	5"	25/32"

920 A Offset Screwdriver



Application: For Slotted screws
Blade: 90° + 180°, mat nickel

	mm	mm	mm		
05**017405**001	4,0+4,0	100	12	4"	1/2"
05**017410**001	5,5+5,5	125	16	5"	5/8"
05**017415**001	8,0+8,0	150	20	6"	25/32"




Wera

Kraftform Kompakt

	Kraftform Kompakt 10, 12	262
	Kraftform Kompakt 20, 22, 25, 26, 28	264
	Kraftform Kompakt 40, 41	268
	Kraftform Kompakt 50	269
	Kraftform Kompakt 60, 62	270
	Kraftform Kompakt 70, 71	276
	Kraftform Kompakt 100	278
	Kraftform Kompakt User Sets	280
	Bitholding Screwdrivers and Adaptors	284
	Kraftform Kompakt Vario With Ratchet Function	288
	Kraftform Kompakt Vario Without Ratchet Function	292

Kraftform Kompakt

Why is the right tool so often not at hand? The reason: too many tools and overly-heavy tool bags can make it bothersome to carry them onsite.

So for us it was a clear challenge: to design a tool that is suitable for a whole host of applications and can be easily taken along to jobs at other sites.

Our solution: Kraftform Kompakt tools. A handle into which blades with a range of different profiles can be inserted. Compactly and protectively housed in a light and robust textile pouch or plastic box.





The sets come with a Kraftform handle, quick-release chuck and bits for manual and power tool operations.



The handle/interchangeable blade system permits rapid exchange of the blades needed for a wide range of applications.



The tools can be stored and carried either in a solid plastic case or a robust pouch. In this way the tool is always to hand. Kraftform Kompakt Sets with Zyklop Speed or Zyklop Mini ratchet can be found on pages 146, 216-223.





Kraftform Kompakt user ranges – the new special sets – compact yet very versatile. Suitable for all sanitary, wood, metal or electrical applications.

Kraftform Kompakt 10, 12

A screwdriver set can hardly be more compact.

Kraftform Kompakt 10



10-piece set

1 bitholding screwdriver 813 R Kraftform with quick-release chuck Rapidaptor

05**056653**001		
◉	**813 R**	1 x 1/4"x90
✪	**851/1 TZ PH**	1 x PH 1x25; 1 x PH 2x25
✪	**855/1 TZ PZ**	1 x PZ 1x25; 1 x PZ 2x25
✪	**867/1 TZ TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25
⬬	**800/1 TZ**	1 x 0,5x4,0x25; 1 x 1,0x5,5x25

Kraftform Kompakt 12



10-piece set

1 bitholding screwdriver 813 R Kraftform with quick-release chuck Rapidaptor

05**135942**001		
◉	**813 R**	1 x 1/4"x90
✪	**867/1 TZ TORX®**	1 x TX 5x25; 1 x TX 6x25; 1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25
✪	**851/1 J**	1 x PH 00x25x2,0; 1 x PH 0x25x2,5; 1 x PH 1x25x3,0
✪	**851/1 TZ PH**	1 x PH 2x25




Wera
Kraftform Kompakt
Wera
813 R
051272


Kraftform Kompakt 20, 22, 25, 26, 28

Telescopic blade models

Kraftform Kompakt 20 A







Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon socket insert bits and Wera Series 1 and 4

Design: Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**051019**001		
	889/4 R	1 x 1/4"x100
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	800/1 Z	1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Kraftform Kompakt 20 with pouch








Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon socket insert bits and Wera Series 1 and 4

Design: Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**051021**001		
	889/4 R	1 x 1/4"x100
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	800/1 Z	1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Kraftform Kompakt 20 Tool Finder 1 with pouch







Application: Suitable for 1/4" DIN ISO 1173-C 6.3 and E 6.3 hexagon socket insert bits and Wera Series 1 and 4

Design: Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology; Take it easy toolfinder: Output colour coding and large stamp to enable the desired bit to be easily located

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**051016**001		
	889/4 R	1 x 1/4"x100
	851/1 BTZ PH	1 x PH 1x25; 1 x PH 2x25
	855/1 BTZ PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 TORX® BTZ	1 x TX 25x25
	800/1 BTZ	1 x 0,8x5,5x25

Kraftform Kompakt 22 with pouch







Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon socket insert bits and Wera Series 1 and 4

Design: Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**051023**001		
	889/4 R	1 x 1/4"x100
	855/1 Z PZ	1 x PZ 1x25; 2 x PZ 2x25
	867/1 Z TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25



Kraftform Kompakt 20, 22, 25, 26, 28

Telescopic blade models

Kraftform Kompakt 25 with pouch





Application: Suitable for $^{1}/_{4}$" DIN ISO 1173-C 6,3 and E 6,3 hexagon socket insert bits and Wera Series 1 and 4

Design: Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**051024**001		
	889/4 R	1 x 1/4"x100
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	800/1 Z	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Kraftform Kompakt 26 with pouch





Application: Suitable for $^{1}/_{4}$" DIN ISO 1173-C 6,3 and E 6,3 hexagon socket insert bits and Wera Series 1 and 4


Design: Attachment, telescopic, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**051025**001		
	889/4 R	1 x 1/4"x100
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	800/1 Z	1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	868/1 Z	1 x # 1x25; 1 x # 2x25

Kraftform Kompakt 28 SB






Application: Suitable for $^1/_4$" DIN ISO 1173-C 6,3 hexagon socket insert bits and Wera Series 1

Design: Attachment, telescopic, with stainless steel sleeve, retaining ring, and strong permanent magnet

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**073240**001		
⊕	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
⊕	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25
⊖	**800/1 Z**	1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Kraftform Kompakt 28 with pouch





Application: Suitable for $^1/_4$" DIN ISO 1173-C 6,3 hexagon socket insert bits and Wera Series 1

Design: Attachment, telescopic, with stainless steel sleeve, retaining ring, and strong permanent magnet

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**134491**001		
⊖	**800/1 Z**	1 x 1,0x5,5x25; 1 x 1,2x6,5x25
⊕	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
⊕	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25

Tip

Telescopic blade, integrated bit magazine, Rapidaptor technology




The sets in the series Kraftform Kompakt 20 are really something. A 2 position telescopic blade can be retracted into the handle for confined space operation or extended for more reach. It can also be removed and used as a 100mm bit holder in the power tool. Six bits are conveniently integrated into a push-button opening bit magazine. The Rapidaptor technology ensures rapid one hand bit changes, press-in auto bit lock and a secure positioning when used in power tools thanks to the free-turning sleeve.



The telescopic blade



When the unique telescopic blade is lowered into the handle, fast, easy screw-driving action is possible, even in the tightest spots!



By pushing the clamping sleeve, the telescopic blade can be extended out of the handle and the compact tool becomes a full-sized screwdriver.



If the clamping sleeve is pushed again the telescopic blade can be taken out of the handle, and be used as a machine bit adaptor.



Kraftform Kompakt 40 and 41

Bits of 89 mm in length

Kraftform Kompakt 40







Pouch with 89 mm bits

7-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05**059298**001		
	816 R	1 x 1/4"x119
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89
	800/4 Z	1 x 1,0x5,5x89; 1 x 1,2x6,5x89

Kraftform Kompakt 41








Pouch with 89 mm bits

11-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05**059299**001		
	816 R	1 x 1/4"x119
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 Z TORX® BO	1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89



Kraftform Kompakt 50

Telescopic blade model

Kraftform Kompakt 50









14-piece set
1 Kraftform bitholding screwdriver 817 R and telescopic blade with quick-release chuck Rapidaptor

05**056656**001		
	817 R	1 x 1/4"x133
	889/4 R	1 x 1/4"x100
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 Z	1 x 0,6x4,5x25; 1 x 1,0x5,5x25



Tip



The telescopic blade







When the unique telescopic blade is lowered into the handle, fast, easy screw-driving action is possible, even in the tightest spots!

By pushing the clamping sleeve, the telescopic blade can be extended out of the handle and the compact tool becomes a full-sized screwdriver.

If the clamping sleeve is pushed again the telescopic blade can be taken out of the handle, and be used as a machine bit adaptor.



Kraftform Kompakt 60, 62

Bits of 89 mm in length

Kraftform Kompakt 60 Torque 1.2 - 3.0 Nm



Pouch with 89 mm bits

17-piece set

1 Series 7400 Kraftform adjustable torque screwdriver (1.2-3.0 Nm) with Rapidaptor quick-release chuck

05**059293**001		
◉	**7400**	1 x 7441x1/4"x1,2-3,0x155
✪	**851/4 Z PH**	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
✪	**855/4 Z PZ**	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
✪	**867/4 Z TORX® BO**	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
⬬	**800/4 Z**	1 x 1,0x5,5x89
○	**840/4 Z Hex-Plus**	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89

Kraftform Kompakt 60, stainless



Pouch with 89 mm bits, stainless steel

17-piece set

1 Kraftform stainless bitholding screwdriver 3816 R with Rapidaptor quick-release chuck

05**071116**001		
◉	**3816 R**	1 x 1/4"x119
✪	**3851/4**	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
✪	**3855/4**	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
✪	**3867/4 TORX® BO**	1 x TX 10 BOx89; 1 x TX 15 BOx89; 1 x TX 20 BOx89; 1 x TX 25 BOx89; 1 x TX 30 BOx89
⬬	**3800/4**	1 x 1,0x5,5x89
○	**3840/4 Hex-Plus**	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89

Kraftform Kompakt 60, imperial, stainless



Pouch with 89 mm bits, stainless steel
17-piece set
1 Kraftform stainless bitholding screwdriver 3816 R with Rapidaptor quick-release chuck

05**071117**001		
	3816 R	1 x 1/4"x119
	3851/4	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	3867/4 TORX® BO	1 x TX 10 BOx89; 1 x TX 15 BOx89; 1 x TX 20 BOx89; 1 x TX 25 BOx89; 1 x TX 30 BOx89
	3800/4	1 x 1,0x5,5x89
	3840/4 Hex-Plus	1 x 3/32"x89; 1 x 1/8"x89; 1 x 5/32"x89; 1 x 3/16"x89
	3868/4 Square-Plus	1 x # 1x89; 1 x # 2x89; 1 x # 3x89

Tip

Adjustable torque screwdriver



Simple setting of the required torque by hand. Easy-to-read scale value.

Measurement accuracy is ± 6 % in accordance with the standard EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Vacuum ice-hardened



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

Kraftform Kompakt 60, 62

Bits of 89 mm in length

Kraftform Kompakt 60



Pouch with 89 mm bits

17-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05**059295**001		
	816 R	1 x 1/4"x119
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	800/4 Z	1 x 1,0x5,5x89
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89

Kraftform Kompakt 60, imperial



Pouch with 89 mm bits

17-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05**051042**001		
	816 R	1 x 1/4"x119
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	800/4 Z	1 x 1,0x5,5x89
	840/4 Z Hex-Plus	1 x 3/32"x89; 1 x 1/8"x89; 1 x 5/32"x89; 1 x 3/16"x89
	868/4 Square-Plus	1 x # 1x89; 1 x # 2x89; 1 x # 3x89

Kraftform Kompakt 60 KK



Pouch with 89 mm bits

17-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05**059294**001		
	816 R	1 x 1/4"x119
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 KK	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89; 1 x TX 40x89
	842/4	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89

Kraftform Kompakt 62





Pouch with 89 mm bits

33-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck

05**059297**001		
	816 R	1 x 1/4"x119
	857/4 Z Spanner	1 x 4x89; 1 x 6x89; 1 x 8x89; 1 x 10x89
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 Z TORX® BO	1 x TX 8x89; 1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 27x89; 1 x TX 30x89; 1 x TX 40x89
	800/4 Z	1 x 1,2x6,5x89
	840/4 Z Hex-Plus BO	1 x 2,0x89; 1 x 2,5x89; 1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89
	871/4 TORQ-SET® Mplus	1 x 6x89; 1 x 8x89; 1 x 10x89
	875/4 TRI-WING®	1 x 1x89; 1 x 2x89; 1 x 3x89; 1 x 4x89

Tip



Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

How can time wasted by using the wrong screwdriver be avoided?



Frequently, users have to work with their tools at a fixed workplace location as well as at external sites. Just as frequently, it is only on site that a decision is taken as to whether to work manually or with a power tool.

The Kraftform Kompakt tool sets equip the user for both types of operation with just one single set. Additionally, the sets are kept in belt pouches or plastic cases. This keeps them secure and clean and means that they are clearly arranged for easy tool selection, something that is very practical when they are to be used or transported.





Kraftform Kompakt 70 and 71

Kraftform handle, Rapidaptor and 30 bits

Kraftform Kompakt 70 universal



32-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck, 1 universal bit holder 889/4/1 K Rapidaptor

05**057110**001		
	816 R	1 x 1/4"x119
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	3 x PH 1x25; 3 x PH 2x25; 3 x PH 3x25
	855/1 TZ PZ	3 x PZ 1x25; 3 x PZ 2x25; 3 x PZ 3x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 TZ	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	840/1 Z Hex-Plus	1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

Kraftform Kompakt 71 security



32-piece set

1 Kraftform bitholding screwdriver 816 R with Rapidaptor quick-release chuck, 1 universal bit holder 889/4/1 K Rapidaptor

05**057111**001		
	816 R	1 x 1/4"x119
	889/4/1 K	1 x 1/4"x50
	867/1 Z TORX® BO	1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	840/1 Z Hex-Plus BO	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25
	868/1 Z	1 x # 0x25; 1 x # 1x25; 1 x # 2x25; 1 x # 3x25
	871/1 TORQ-SET® Mplus 25 mm	1 x 6x25; 1 x 8x25; 1 x 10x25; 1 x 1/4"x25
	875/1 TRI-WING® 25 mm	1 x 1x25; 1 x 2x25; 1 x 3x25
	857/1 Z Spanner	1 x 4x25; 1 x 6x25; 1 x 8x25; 1 x 10x25







Kraftform Kompakt 7

Kraftform Kompakt 100

Bits, Bit Holders and L-keys in one tool set

Kraftform Kompakt 100



52-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility.
Compact tool set with 52 screwdriving tools. 1 hand holder Rapidaptor with quick-release chuck; 1 bit holder Rapidaptor with quick-release chuck; 30 BiTorsion bits (25 mm length) for long service life, tough (BTZ), for universal use, extra-hard (BTH), 12 Impaktor bits (50 mm length) for an above-average service life even under extreme conditions, 8 L-keys with Hex-Plus profile (reduces the notching effect that is damaging for the head of the screw) ball-end on long arm; extremely robust textile box, extremely robust, for long service life, can be stored in an spacesaving upright position; textile material for surface protection.

05**057460**001		
◉	**813 R**	1 x 1/4"x90
◉ ○	**889/4/1 K**	1 x 1/4"x50
✪	**851/1 BTZ PH**	2 x PH 1x25; 4 x PH 2x25; 2 x PH 3x25
✪	**851/4 IMP DC**	2 x PH 2x50; 1 x PH 3x50
✪	**855/1 BTH PZ**	2 x PZ 1x25; 4 x PZ 2x25; 2 x PZ 3x25
✪	**855/4 IMP DC**	2 x PZ 2x50; 1 x PZ 3x50
✪	**867/1 TORX® BTZ**	2 x TX 10x25; 2 x TX 15x25; 3 x TX 20x25; 2 x TX 25x25; 2 x TX 30x25; 1 x TX 40x25
✪	**867/4 IMP DC**	1 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50
⬬	**800/1 BTZ**	1 x 0,8x5,5x25; 1 x 1,0x5,5x25
○	**840/4 IMP DC**	1 x 4,0x50; 1 x 5,0x50; 1 x 6,0x50
○	**950 PKS**	1 x 1,5x50 [1]; 1 x 2,0x56; 1 x 2,5x63; 1 x 3,0x71; 1 x 4,0x80; 1 x 5,0x90; 1 x 6,0x100; 1 x 8,0x112

[1] Regular hexagon



Kraftform Kompakt user-specific sets

Kraftform Kompakt W 1 Maintenance





35-piece set; in surface-protecting, compact textile box, highly robust; low volume and weight for simplified mobility.

Compact tool set with the most important screwdriving tools for maintenance jobs both indoors as well as outdoors. VDE hand holder including 12 VDE blades; 1 Joker double open-ended wrench with holding function, limit stop, small return angle and extremely high-grip toothing; incl. the incredibly fast 1/4" Zyklop Speed ratchet with accessories; 8 manual and power tool sockets in the dimensions 5.5-13, 1 universal bit holder; 7 25mm bits; 1 screw gripper to firmly hold screws; 1 voltage tester 247; textile box that is very robust and durable; can be positioned upright in the workshop shelf for tidy storage; additional surface protection thanks to the textile outer material; low weight and volume for simplified mobility.

05**135926**001		
	817 VDE	1 x 9x102
	KK 60 i	1 x 0,4x2,5x154
	KK 60 iS	1 x 0,6x3,5x154; 1 x 0,8x4,0x154; 1 x 1,0x5,5x154
	KK 62 iS	1 x PH 1x154; 1 x PH 2x154
	KK 65 iS PZ	1 x PZ 1x154; 1 x PZ 2x154
	KK 67 i TORX®	1 x TX 10x154
	KK 67 iS TORX®	1 x TX 15x154; 1 x TX 20x154; 1 x TX 25x154
	1440	1 x 4,5 - 6,0x41,0
	247	1 x 0,5x3,0x70
	Joker Double	1 x 10x13x167
	8000 A	1 x 1/4"x152,0
	8784 A1	1 x 1/4"x1/4"x37,0
	8794 SA	1 x 1/4"x75,0
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 11,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	893/4/1 K	1 x 1/4"x50
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25
	867/1 Z TORX®	1 x TX 25x25

Product not available in the USA and Canada.

Kraftform Kompakt H 1 Woodcraft





41-piece set; in surface-protecting, compact textile box, highly robust; low volume and weight for simplified mobility.

Compact tool set with the 41 most important screwdriving tools for jobs involving wood: including the robust Bit Ratchet Zyklop Mini with extension and socket adaptor; 8 manual and power tool sockets in the dimensions 5.5-13; 1 hand holder 816 RA with ratchet function, fine toothing for small return angle, switch-over ring (right, fixed, left), maximum torque 50 Nm and bit take-up with Rapidaptor technology; 1 universal bit holder; 6 bits of 25mm in length; 16 bits of 89 mm in length; 5 twist drill bits for wood with a diameter of 3-8mm; 1 screw gripper to firmly hold screws; 1 voltage tester 247.

05**135939**001		
	816 RA	1 x 1/4"x142,0
	8001 A	1 x 1/4"x87,0
	870/1	1 x 1/4"x25
	8794 SA	1 x 1/4"x75,0
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	893/4/1 K	1 x 1/4"x50
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	867/1 Z TORX®	1 x TX 20x25; 1 x TX 25x25
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89
	800/4 Z	1 x 1,0x5,5x89
	800/1 Z	1 x 1,0x5,5x25
	849 HSS	1 x 3,0x70,0; 1 x 4,0x74,0; 1 x 5,0x85,0; 1 x 6,0x95,0; 1 x 8,0x110,0
	247	1 x 0,5x3,0x70
	1441	1 x 4,5 - 6,0x41,0

Product not available in the USA and Canada.

Kraftform Kompakt M 1 Metal



39-piece set; in surface-protecting, compact textile box, highly robust; low volume and weight for simplified mobility.


Compact tool set with the 39 most important screwdriving tools for jobs involving metal, including the incredibly fast 1/4" Zyklop Speed ratchet with accessories; 7 manual and power tool sockets in the dimensions 5.5-13; 1 bit hand holder; 13 bits of 89 mm in length; 6 combination screw tap bits; 6 twist drill bits for metal with a diameter of 3-10mm; 1 screw gripper to firmly hold screws; 1 voltage tester 247; textile box that is very robust and durable; can be positioned upright in the workshop shelf for tidy storage; additional surface protection thanks to the textile outer material; low weight and volume for simplified mobility.

05**135928**001		
	8000 A	1 x 1/4"x152,0
	8794 LA	1 x 1/4"x150,0
	8794 A	1 x 1/4"x56,0
	8784 A1	1 x 1/4"x1/4"x37,0
	816 R	1 x 1/4"x119
	8790 HMA	1 x 5,5x23,0; 1 x 6,0x23,0; 1 x 7,0x23,0; 1 x 8,0x23,0; 1 x 10,0x23,0; 1 x 12,0x23,0; 1 x 13,0x23,0
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89
	867/4 Z TORX®	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	800/4 Z	1 x 1,0x5,5x89
	847 HSS	1 x 2,5x36,0; 1 x 3,3x39,0; 1 x 4,2x41,0; 1 x 5,0x44,0; 1 x 6,8x51,0; 1 x 8,5x59,0
	848 HSS	1 x 3,0x38,0; 1 x 4,0x44,0; 1 x 5,0x50,0; 1 x 6,0x50,0; 1 x 8,0x51,0; 1 x 10,0x54,0
	1441	1 x 4,5 - 6,0x41,0
	247	1 x 0,5x3,0x70

Product not available in the USA and Canada.

Tip

Kraftform Kompakt H1 Woodcraft



Compact tool set with the 41 most important screwdriving tools for jobs involving wood.

Kraftform Kompakt W1 Maintenance



The perfect set for diverse maintenance jobs both indoors as well as outdoors - applications: electronics, mechatronics, building technology, photovoltaic etc. etc. etc.

Kraftform Kompakt M1 Metall



Compact tool set with the 39 most important screwdriving tools for jobs involving metal.

Kraftform Kompakt user-specific sets

Kraftform Kompakt SH 1 PlumbKit









2 Joker combination ratchet wrenches with special retaining plate to prevent slipping/loss of the screw and more power transfer, 1 Zyklop ratchet 8000 A ($^1/_4$") for rapid, powerful operation, 3 Zyklop sockets 8790 HMA for manual and power tool applications, 1 Zyklop adapter 8784 A1 for bits, 6 TORX® HF bits 867/4 with holding function for TORX® screws for secure hold without any loss of the screw, 1 voltage tester 247, 2 Kraftform Series 100 VDE slotted screwdrivers 160 i and 160 iS for safe work up to 1,000 volts (160 iS has a reduced blade diameter with integrated protective insulation to allow sunken screw and spring elements to be reached and actuated) with "Take it easy" tool finder: colour coding according to profile and size stamp, 1 Kraftform chisel driver 932 A (slotted) with hexagon blade throughout and integrated impact cap for screwdriving and simple chiselling jobs, 2 socket wrench screwdrivers 395 HO with hollow shaft for the tightening or loosening of screws on long bolts as well as for jammed screws.

05**135927**001		
	Joker	1 x 10x159; 1 x 13x177
	8000 A	1 x 1/4"x152,0
	8790 HMA	1 x 7,0x23,0; 1 x 10,0x23,0; 1 x 13,0x23,0
	8784 A1	1 x 1/4"x1/4"x37,0
	867/4 TORX® HF	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89
	247	1 x 0,5x3,0x70
	160 iS	1 x 0,6x3,5x100
	160 i VDE	1 x 1,0x5,5x125
	932 A	1 x 1,2x7,0x125
	395 HO	1 x 10,0x90; 1 x 13,0x90

**) Product not available in the USA and Canada.


JOKER
Wera

Bitholding Screwdrivers and Adaptors

Suitable for hand and power tool applications

3816 R Bit-holding screwdriver with Rapidaptor quick-release chuck, stainless



Application: Suitable for 1/4" hexagon insert bits, DIN ISO 1173-C 6,3 and E 6,3 and Wera Series 1 and 4

Drive: 1/4" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051465**001	1/4"	119

813 R Bitholding screwdriver with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Drive: 1/4" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, magnetic

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051272**001	1/4"	90

816 R Bitholding screwdriver with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Drive: 1/4" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, magnetic

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051462**001	1/4"	119

816 R SB Bitholding screwdriver with Rapidaptor quick-release chuck

		4013288
05**073540**001	1 x 1/4"x119	106032



489 R T-handle Rapidaptor



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Drive: 1/4" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, magnetic

Handle: T-handle, multi-component

		mm	mm	mm	
05**013390**001	1/4"	45	44	87	1 25/32"

817 R Bitholding screwdriver with Rapidaptor quick-release chuck



Application: Suitable for $^1/_4$" DIN ISO 1173-C 6.3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Drive: 2 position telescopic blade, can be retracted into the handle for confined space operation or extended for more reach, can also be removed and used as a 100mm bit holder in the power tool, $^1/_4$" hexagon suitable for power tools with DIN ISO 1173-F 6.3 chuck

Design: $^1/_4$" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, magnetic

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051482**001	$^1/_4$"	133


817 R SB Bitholding screwdriver with Rapidaptor quick-release chuck

		4013288
05**073541**001	1 x 1/4"x133	106025



Rapidaptor

Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Chuck-all



The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Bitholding Screwdrivers and Adaptors

Suitable for hand and power tool applications

820/1/6 Combination screwdriver with strong permanent magnet and bits



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: Strong permanent magnet

Handle: Kraftform, single-component, rotary magazine

05**051620**001		
◉	**819/1 Vario**	1 x 1/4"x120
✪	**867/1 Z TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

819/1/6 Combination screwdriver with strong permanent magnet and bits



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: Strong permanent magnet

Handle: Kraftform, single-component, rotary magazine

05**051615**001		
◉	**819/1 Vario**	1 x 1/4"x120
✪	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
✪	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25
⛀	**800/1 Z**	1 x 0,8x5,5x25; 1 x 1,2x6,5x25

819/1/6 PH Combined Screwdriver with strong permanent magnet and bits



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: With strong permanent magnet

Handle: Kraftform, one component, rotary magazine

05**346280**001		
◉	**819/1 Vario**	1 x 1/4"x120
✪	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
⛀	**800/1 Z**	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

819/1 Combination screwdriver with strong permanent magnet, without bits



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: Strong permanent magnet

Handle: Kraftform, single-component, rotary magazine

	◉	mm	mm	∅ mm	
05**051610**001	1/4"	120	110	10,5	4 3/4"

392 Bitholding screwdriver with flexible shaft



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon bits and Wera Series 1

Design: Wera quick-release chuck

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	
05**028160**001	1/4"	177	98	7"

813 Bitholding screwdriver



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Drive: 1/4" hexagon, magnetic

Handle: Kraftform with non-roll feature, multi-component

		mm	mm
05**051274**001	1/4"	78	68

812/1 Bitholding screwdriver with strong permanent magnet



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: Strong permanent magnet, chrome-plated

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**051205**001	1/4"	120	112	10,5	4 3/4"

811/1 Stubby



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Round

Design: Extra short with strong permanent magnet

Handle: Kraftform, single-component

		mm	mm	
05**051105**001	1/4"	10	54	3/8"

810/1 Bitholding screwdriver with retaining ring



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: Hexagon

Design: Retaining ring, chrome-plated

Handle: Kraftform with non-roll feature, multi-component

		mm	mm	mm	
05**051005**001	1/4"	120	112	10,5	4 3/4"

Kraftform Kompakt Vario

With Ratchet Function

Kraftform Kompakt 60 RA



Pouch with 89 mm bits

17-piece set

1 hand-held bit holder 816 RA Kraftform with ratchet function, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, $^1/_4$" hexagon chuck with Rapidaptor technology i.e. rapid-in, rapid-out, rapid-spin, chuck-all and single-hand function for rapid bit change, magnetic and 16 bits of 89 mm in length suitable for holders as per DIN ISO 1173-F 6,3 or for direct insertion in a power tool

05**051040**001		
	816 RA	1 x 1/4"x142,0
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	855/4 Z PZ	1 x PZ 1x89; 1 x PZ 2x89; 1 x PZ 3x89
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	800/4 Z	1 x 1,0x5,5x89
	840/4 Z Hex-Plus	1 x 3,0x89; 1 x 4,0x89; 1 x 5,0x89; 1 x 6,0x89

Kraftform Kompakt 60 RA, imperial



Pouch with 89 mm bits

17-piece set

1 hand-held bit holder 816 RA Kraftform with ratchet function, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, $^1/_4$" hexagon chuck with Rapidaptor technology i.e. rapid-in, rapid-out, rapid-spin, chuck-all and single-hand function for rapid bit change, magnetic and 16 bits of 89 mm in length suitable for holders as per DIN ISO 1173-F 6,3 or for direct insertion in a power tool

05**051041**001		
	816 RA	1 x 1/4"x142,0
	851/4 Z PH	1 x PH 1x89; 1 x PH 2x89; 1 x PH 3x89
	867/4 Z TORX® BO	1 x TX 10x89; 1 x TX 15x89; 1 x TX 20x89; 1 x TX 25x89; 1 x TX 30x89
	800/4 Z	1 x 1,0x5,5x89
	840/4 Z Hex-Plus	1 x 3/32"x89; 1 x 1/8"x89; 1 x 5/32"x89; 1 x 3/16"x89
	868/4 Square-Plus	1 x # 1x89; 1 x # 2x89; 1 x # 3x89

816 RA Ratchet screwdriver



Application: Suitable for hexagon socket insert bits as per DIN ISO 1173-C 6,3 and E 6,3 and Wera series 1 and 4

Design: Ratchet, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, $^1/_4$" hexagon chuck with Rapidaptor technology i.e. rapid-in, rapid-out, rapid-spin, chuck-all and single-hand function for rapid bit change, magnetic

Handle: Kraftform with non-roll feature, multi-component

		mm
05**051461**001	$^1/_4$"	142,0

80 RA Vario ratchet screwdriver



Application: Suitable for 6 mm Wera Vario blades

Design: Ratchet, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, 6 mm hexagon chuck

Handle: Kraftform with non-roll feature, multi-component

	mm	mm
05**002901**001	6	115,0

Kraftform Kompakt Vario RA SB



Pouch with 175 mm Wera Vario double-ended blades, 6 mm hexagon shaft

7-piece set

1 Kraftform Kompakt Vario RA hand-held bit holder with ratchet function, fine-tooth design for minimal return angle, switchover ring (right, fixed, left), maximum torque of up to 50 Newton meters, 6 mm hexagon chuck for Wera Vario double-ended blades, 6 Vario double-ended blades (= 12 different dimensions)

05**073665**001		
	80 RA	1 x 6x115,0
	85	1 x PH 1xPH 2x175
	86	1 x PZ 1xPZ 2x175
	87	1 x TX 10xTX 15x175; 1 x TX 20xTX 25x175
	81	1 x 0,6x4,0x1,0x6,0x175
	84 [1)]	1 x 4x5x175

[1)] without ball-end

Tip

Fine-tooth design



Fine action 44 tooth system for precision work. Great time savings when screwdriving.

Reverse direction switch



Ergonomic design of the reverse direction switch.

Fine adjustment work



Additionally, the lockable neutral position permits exact adjustment work without having to change the screwdriving direction every time. Lockable neutral position for fine adjustment work.

Kraftform Kompakt Vario RA SB



The 6 mm double-ended blades of 175 mm length are out of high quality bit material which gives them a particularly long service life.

Kraftform Kompakt Vario

With Ratchet Function

Kraftform Kompakt Pistol RA



7-piece set

1 hand-held bit holder 814 RA Kraftform, integrated Magazine, with ratchet function, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, $^1/_4$" hexagon chuck with Rapidaptor technology i.e. rapid-in, rapid-out, rapid-spin, chuck-all and single-hand function for rapid bit change, magnetic and 6 bits of 25 mm in length suitable for holders as per DIN ISO 1173-D 6,3

Holster

05**051030**001		
	814 RA	1 x 1/4"
PH	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
PZ	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25
TX	**867/1 TORX®**	1 x TX 20x25; 1 x TX 25x25

Kraftform Kompakt Pistol RA 4



13-piece set

1 hand-held bit holder 814 RA Kraftform, integrated Magazine, with ratchet function, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, $^1/_4$" hexagon chuck with Rapidaptor technology i.e. rapid-in, rapid-out, rapid-spin, chuck-all and single-hand function for rapid bit change, magnetic, 6 bits of 25 mm in length suitable for holders as per DIN ISO 1173-D 6.3 and 6 bits of 89 mm in length suitable for holders as per DIN ISO 1173-F 6.3

Holster

05**051031**001		
	814 RA	1 x 1/4"
PH	**851/1 BTZ PH**	1 x PH 1x25; 1 x PH 2x25
PZ	**855/1 BTZ PZ**	1 x PZ 1x25; 1 x PZ 2x25
TX	**867/1 TORX® BTZ**	1 x TX 20x25; 1 x TX 25x25
PH	**851/4 Z PH**	1 x PH 1x89; 1 x PH 2x89
PZ	**855/4 Z PZ**	1 x PZ 1x89; 1 x PZ 2x89
TX	**867/4 Z TORX®**	1 x TX 20x89; 1 x TX 25x89

Kraftform Kompakt 27 RA 1 SB



Application: Suitable for hexagon socket insert bits as per DIN ISO 1173-C 6,3 and Wera series 1

Design: Ratchet, fine-tooth design for minimal return angle, switchover ring (right, locked, left), maximum torque of up to 50 Newton metres, hexagon blade with $^1/_4$" hexagon chuck, stainless steel sleeve, strong permanent magnet

Handle: Kraftform with non-roll feature, multi-component, integrated magazine

05**073660**001		
PH	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
PZ	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25
	800/1 Z	1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Kraftform Kompakt 27 RA 2 SB



Application: Suitable for hexagon socket insert bits as per DIN ISO 1173-C 6,3 and Wera series 1

Design: Ratchet, fine tooth system for minimal return angle, switchover ring (clockwise, locked, anticlockwise), maximum torque of up to 50 Newton metres, hexagon blade with $^1/_4$" hexagon chuck, stainless steel sleeve, strong permanent magnet

Handle: Kraftform with non-roll feature, multi-component, integrated magazine for 6 bits (25 mm)

05**073661**002		
PH	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
	800/1 Z	1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	868/1 Z	1 x # 1x25; 1 x # 2x25


Wera

Kraftform Kompakt Vario

Without Ratchet Function

88/1 Vario set



11-piece set, specifically for demanding workshop environments

05**002990**001		
	80	1 x 6x98
	85	1 x PH 1xPH 2x175
	86	1 x PZ 1xPZ 2x175
	87	1 x TX 10xTX 15x175; 1 x TX 20xTX 25x175; 1 x TX 30xTX 40x175
	81	1 x 0,6x4,0x1,0x6,0x175; 1 x 0,8x5,0x1,2x7,0x175
	84	1 x 4x4x175; 1 x 5x5x175; 1 x 6x6x175

80 Vario handle



Application: 6 mm Vario blades and adaptors

Handle: Kraftform with non-roll feature, multi-component, 10 mm bolster

	mm	mm	mm
05**002900**001	6	10	98

95 Vario T-handle



Application: 6 mm Vario blades and adaptors

Handle: T-handle, single-component

	mm	mm	mm	
05**003265**001	6	56	44	2 1/4"

830 Vario bit holder adaptor



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Blade: 6 mm hexagon, chrome-plated

Drive: Wera 1/4" quick-release chuck with strong permanent magnet

	mm	mm	mm	
05**051835**001	1/4"	6	165	6 9/16"

91 Vario extension



Application: Vario blades and adaptors

Blade: 6 mm hexagon, chrome-plated

Drive: 6 mm hexagon socket

	mm	mm	mm	
05**003210**001	6	6	175	7"

712 Vario socket adaptor



Application: Suitable for 1/4" square drive sockets
Blade: 6 mm hexagon, chrome-plated
Drive: 1/4" square head

		mm	mm	
05**040001**001	1/4"	6	175	7"

81 Combination blade for slotted screws



Application: Slotted screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

	mm	mm	mm	mm	mm	mm	
05**002910**001	0,6	4,0	1,0	6,0	6	175	7"
05**002913**001	0,8	5,0	1,2	7,0	6	175	7"

82 Combination blade for slotted/Phillips screws




Application: Slotted screws and Phillips screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

		mm	mm	mm	mm	
05**002920**001	PH 1	0,6	4,0	6	175	7"
05**002923**001	PH 2	1,0	6,0	6	175	7"
05**002926**001	PH 3	1,2	7,0	6	175	7"

Tip

BLACK POINT

Black Point Tip



The Wera Black Point tip provides an exact fit with optimum corrosion protection.

High quality bit material



The 6 mm double-ended blades of 175 mm length are out of high quality bit material which gives them a particularly long service life.

Adaptor



¼" hexagon and square drives as per DIN ISO 1173-C 6,3 and DIN 3120 can also be driven with the 6 mm handles by attaching an adaptor.

Kraftform Kompakt Vario

Without Ratchet Function

83 Combination blade for Phillips/Pozidriv screws



Application: Phillips screws and Pozidriv screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

			mm	mm	
05**002930**001	PH 1	PZ 1	6	175	7"
05**002933**001	PH 2	PZ 2	6	175	7"

84 Combination blade for hexagon socket screws



Application: Hexagon socket screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

			mm	mm	
05**002936**001	2,5	2,5	6	175	7"
05**002938**001	3	3	6	175	7"
05**002940**001	4	4	6	175	7"
05**002943**001	5	5	6	175	7"
05**002948**001[1)]	4	5	6	175	7"
05**002946**001	6	6	6	175	7"

[1)] without ball-end

85 Combination blade for Phillips screws



Application: Phillips screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

			mm	mm	
05**002950**001	PH 1	PH 2	6	175	7"

86 Combination blade for Pozidriv screws



Application: Suitable for Pozidriv screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

			mm	mm	
05**002960**001	PZ 1	PZ 2	6	175	7"
05**140310**001	PZ 2	PZ 3	6	175	7"

87 Combination blade for TORX® screws



Application: TORX® socket screws
Blade: 6 mm hexagon
Design: Chrome-plated, Black Point

			mm	mm	
05**002966**001	TX 6	TX 8	6	175	7"
05**002968**001	TX 7	TX 9	6	175	7"
05**002970**001	TX 10	TX 15	6	175	7"
05**002973**001	TX 20	TX 25	6	175	7"
05**002976**001	TX 30	TX 40	6	175	7"

68 Combination blade for square socket screws



Application: For square socket screws
Blade: 6 mm hexagon
Design: Mat nickel, Black Point

			mm	mm	
05**002980**001	#1	#2	6	175	7"


044 377-0
Unt. Bwg 20.9.72


Wera
Wera
Wera
Wera

Wera 2go

	Wera 2go 1 Tool Carrier	300
	Wera 2go 2 Tool Container	300
	Wera 2go 3 Tool Box	300
	Wera 2go 4 Tool Quiver	300
	Wera 2go 5 Tool Carrier	301
	Wera 2go 6 Shoulder Strap	301
	Hook and Loop Fastener Strips	303



Wera 2go

We wanted to provide our textile boxes and pouches with a mobile home.


After all, increasingly more users are more often out and about with their tools and they frequently complain about too much weight.

So we started searching for an idea which would keep the hands free during walking and with which one could dock and undock the required tools very easily.





Wera 2go 1 – The outside packer
Wera 2go Tool Carrier with hook and loop fastener system. For the docking of the Wera textile boxes and pouches with hook and loop fastener zones. Individually configurable for greater mobility. Hands remain free during transport. Includes an adjustable, detachable Shoulder Strap with a wide padded section.



Wera 2go 2 – The outside and inside packer
Wera 2go Tool Container with inner and outer hook and loop fastener system. Individually configurable for greater mobility. Ideal also for the docking of Wera textile boxes and pouches equipped with hook and loop fastener zones. Easy insertion and removal. Hands remain free during transport.



Wera 2go 3 – The inside packer
Permanently dimensionally stable thanks to the fabric-lined plastic panels. High resistance against cuts and stabs. High protection of the tools transported against damage and moisture. Can be individually equipped.





Wera 2go 4 – Tool Quiver
Dimensionally stable Wera 2go Tool Quiver. High resistance against cuts and stabs. Variable hook and loop fastener partition for a division into as many as 5 inner sections. Large set-down area; handle for carrying and hanging up.

Wera 2go

Tool transport - mobile, flexible, individual

Wera 2go 1 Tool Carrier



1 tool carrier with hook and loop fastener system for the attachment of other Wera 2go components as well as Wera textile boxes and pouches with hook and loop fastener zones; 1 shoulder strap with adjustable-width padding, adjustable in length, detachable.

05**004350**001		
	Wera 2go 5	1 x 135x300x270
	Wera 2go 6	1 x 38x1470

Wera 2go 2 Tool Container



1 dimensionally stable, robust Tool Container with hook and loop fastener system for the attachment of other Wera 2go components as well as Wera textile boxes and pouches with hook and loop fastener zones; high resistance against cuts and stabs; 1 handle and 1 Shoulder Strap with adjustable-width padding, adjustable in length, detachable; 1 removable Tool Quiver with handle and a variable hook and loop fastener partition for a division into as many as 5 inner sections.

05**004351**001		
	Wera 2go Container	1 x 330x355x115
	Wera 2go 6	1 x 38x1470
	Wera 2go 4	1 x 165x165x105

Wera 2go 3 Tool Box



1 dimensionally stable and robust Tool Box, empty, equipped with handle for the storage and transport of tools and small parts; high resistance against cuts and stabs; comes with hook and loop fastener zone for docking with the Wera 2go system.

	mm	mm	mm
05**004352**001	130	325	80

Wera 2go 4 Tool Quiver



1 dimensionally stable and robust Tool Quiver, empty, equipped with handle for the storage and transport of tools; high resistance against cuts and stabs; comes with hook and loop fastener zone for docking with the Wera 2go system and includes 1 variably adjustable hook and loop fastener partition for a division into as many as 5 sections.

	mm	mm	mm
05**004353**001	165	165	105

Wera 2go 5 Tool Carrier



1 Tool Carrier with hook and loop fastener system for the attachment of other Wera 2go components as well as Wera textile boxes and pouches with hook and loop fastener zones.

	mm	mm	mm
05**004354**001	135	300	270

Wera 2go 6 Shoulder Strap



1 Shoulder Strap, adjustable in length with variable-width padding for great carrying comfort and convenience.

	mm	mm
05**004355**001	38	1470


Tip

Robust and dimensionally stable



The robust and dimensionally stable material protects the tools carried against damage and moisture and enhances the service life of the tool container.

Variable thanks to the hook and loop fastener system



The inner and outer hook and loop fastener sections mean that other Wera 2go system components can be just as easily attached as all other Wera tools in boxes and pouches with hook and loop fastener zones. This enables an individual composition of the tools needed for a specific job.

High resistance against cuts and stabs



The robust and dimensionally stable material is very resistant against cuts and stabs. The tools carried are protected against damage and moisture. This enhances the service life of the tool box.



Perfect system supplement



Thanks to its hook and loop fastener zone, the Tool Box can be docked with the Wera 2go 1 Tool Carrier and with the Wera 2go 2 Tool Container.



” To learn more about this product, scan the QR code. “

Hook and Loop Fastener Strip 1



Self-adhesive hook and loop fastener strips. They can be attached to walls or workshop trolleys; suitable for the attachment of Wera 2go components or Wera pouches or textile boxes with nonwoven sections.

05**670446**001	
	Hook and Loop Fastener Strip 70 1 x 50x70

Hook and Loop Fastener Strip 2



Self-adhesive hook and loop fastener strips. They can be attached to walls or workshop trolleys; suitable for the attachment of Wera 2go components or Wera pouches or textile boxes with nonwoven sections.

05**670447**001	
	Hook and Loop Fastener Strip 120 1 x 50x120

Hook and Loop Fastener Strip 3




Self-adhesive hook and loop fastener strips. They can be attached to walls or workshop trolleys; suitable for the attachment of Wera 2go components or Wera pouches or textile boxes with nonwoven sections.

05**670448**001	
	Hook and Loop Fastener Strip 240 1 x 50x240

Tip

Would you like to attach your pouch with a nonwoven section to the wall or workshop trolley?



No problem! In such cases we also have self-adhesive hook and loop fastener strips available.

Which textile boxes can be docked with the Wera 2go system without the need for any additional aids?



Wera packaging bearing this symbol contains tool pouches or textile boxes with nonwoven sections that can be docked with the Wera 2go system.




Wera

Products for Power Tool Use



Bits 308



Holders and Adaptors 404



Sets 430




Wera
BE A TOOL REBEL

Bits

Bits for Phillips Screws	316
Bits for Pozidriv Screws	338
Bits for PlusMinus Screws – Slotted/Phillips	350
Bits for PlusMinus Screws – Slotted/Pozidriv	351
Bits for TORX® Screws	352
Bits for TORX® BO Screws	366
Bits for TORX PLUS® Screws	368
Bits for TORX PLUS® IPR Screws	372
Bits for ASSY® Screws	375
Bits for Slotted Screws, Guide Sleeves	376
Bits for Hexagon Socket Screws	380
Bits for Hexagon Socket BO Screws	387
Bits for Square Socket Screws	388
Bits for TORQ-SET® Screws	392
Bits for TRI-WING®-Screws	395
Bits for Multi-Point Screws	396
Bits for Hi-TORQUE Screws	397
Bits for Microstix® Screws	398
Bits for Spanner Screws	400
Nutsetters	401
Internal Thread Insertion Tool	403



Bits

The right bit for every screw and for every power tool connection. The right quality for every user.

Thanks to the high-precision profile design and the outstanding concentricity properties, Wera bits provide for dependable working and offer great durability. Wera bits are designed for professional applications in industry as well as in the trade.

They enable higher torque transfer and typically have a long service life. Material and manufacturing expertise, established over decades, combined with sophisticated hardening technologies form the foundation upon which our premium quality is based.









Impaktor Bits
Impact bits are needed when a strong power tool is used. Impact bits were specifically developed to withstand high power tool forces.



Stainless Steel Bits
Wera stainless steel bits are manufactured out of stainless steel so unsightly rust can be avoided. The stainless steel bits from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.




BiTorsion Bits
BiTorsion bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits.





Bits with diamond coating
The diamond coating of the DC bits lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head.



“Take it easy”
“Take it easy” tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.



Impaktor Bits

We were not too happy that disintegrating bits flew around users faces as screwdriving with power tools took place with ever-higher power outputs.

We scrutinised the geometry and material properties of the bits for every screw profile. We analysed the destroyed bits, holders and screws in detail. The result is the Impaktor system – our entire know-how from bit manufacturing combined in our very best bit series.




For use with impact screwdrivers. Improve productivity when screwdriving with power tools.



Maximum utilisation of the material properties, a very special geometry – designed particularly to meet the extreme demands – as well a specific manufacturing process mean that Wera Impaktor tools have an above-average service life.



Particularly high strength. Reduce the danger of premature bit breakage.





Torsion zone specially designed to absorb such forces and thereby protect the bit tip.



Another product advantage is the coating of the Impaktor bits with minute diamond particles.



These diamond particles reduce the cam-out effects – particularly high in power tool applications – which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.





Wera's Impaktor system consisting of Impaktor bits and Impaktor holders is today's necessary addition to the BiTorsion system with the creation of the TriTorsion system.



The combination of the double torsion zones in the Impaktor holder and the torsion zone in the Impaktor bit result in the so-called TriTorsion system.




BiTorsion Bits

Peak forces that occur in power tool applications often result in premature wear of bits or damage to the screw head. This usually occurs during initial power-up and the when the screw comes to a standstill.

Screwdriving could become more productive and safer if these peak loads could be minimised. The Wera BiTorsion system prevents premature wear. The service life of the tool is extended and the productivity of power tool applications significantly increased.



The torsion spring integrated into the unique BiTorsion holder absorbs lower levels of peak loads (Phase 1). Any overloading of this spring is effectively prevented by means of a supporting mechanism.




Higher peak loads are minimised through the torsion effect of the bit shaft (Phase 2). This effect is achieved with a specific heat treatment after the hardening process of the bits. This reduces the hardness of the shaft in comparison to the drive tip.



The BiTorsion holder and the BiTorsion bit can, of course, be used independently of one another.





Even the service life of conventional bits is enhanced with the use of the BiTorsion holder and the BiTorsion bit also functions in a normal holder.



The effectiveness of the BiTorsion system comes from a combination of two shock-absorbing spring elements. Both bits as well as holders have a cushioning torsion zone that diverts the kinetic energy away from the drive tip during peak loads.



The optimally coordinated features of the torsion zones on the bit and holder permit a phased yield when under strain. The two-phase system prevents premature wear. Moreover, a long tool service life is also ensured by the hardness of the bits that matches the respective application.


NO STEP

Diamond-coated Bits

One of the greatest problems with power tool applications is that the conventional bit easily slips out of the head of the screw (cam-out). This often destroys both the head of the screw and the tool.

High resulting costs are incurred e.g. from damaged surfaces and screw connections that can no longer be loosened.


Screwdriving will become safer and more economic if this problem of slipping can be minimised.



To solve this fundamental problem, Wera launched a diamond-coated bit on to the market in 1992.



Today, the Wera diamond bit – manufactured with the technology specifically developed by Wera for this application – still sets the standard in terms of resilience and functionality. Wera bits with a diamond coating ensure a secure fit of the bit in the screw head.



Particularly when applications involve sensitive materials or high quality surfaces are involved, bits with a diamond coating ensure that work is done safer, faster and at lower cost.





The minute diamond particles applied to the tip of the tool literally “bite” into the screw and ensure an exact, anti-slip fit in the head of the screw. This secure fit protects the screw. The cam-out forces which compel the user to apply greater pressure to the screw are considerably reduced.



Bits for Phillips Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

851/1 IMP DC Impaktor bits

DIAMOND · IMPACT PROOF · TAKE IT EASY TOOL FINDER



Application: Phillips screws

Drive: ¼" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**057615**001	PH 1	25	1"
05**057616**001	PH 2	25	1"
05**057617**001	PH 3	25	1"

Bit-Box 15 Impaktor PH

		4013288
05**057752**001	**851/1 IMP DC** 15 x PH 2x25	187918



851/1 IMP DC SB Impaktor bits

		4013288
05**073916**001	1 x PH 2x25	158369
05**073917**001	1 x PH 3x25	158376



3851/1 TS bits, stainless

TORSION · INOX STAINLESS · TAKE IT EASY TOOL FINDER



Application: Phillips screws

Drive: ¼" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Stainless steel for minimising rust, special torsion-style design to reduce premature wear. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**071010**001	PH 1	25	1"
05**071011**001	PH 2	25	1"
05**071012**001	PH 3	25	1"

3851/1 TS SB bits, stainless

		4013288
05**073610**001	1 x PH 1x25	112132
05**073611**001	1 x PH 2x25	112149
05**073612**001	1 x PH 3x25	112156



851/1 BDC bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, diamond-coated for secure screw fit. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**056400**001	PH 1	25	1"
05**056402**001	PH 2	25	1"
05**056404**001	PH 3	25	1"

851/1 BDC SB bits

		4013288
05**073332**001	1 x PH 1x25	029324
05**073333**001	1 x PH 2x25	029331
05**073334**001	1 x PH 3x25	029348
05**073335**001	2 x PH 2x25	029355





Tip

IMPACT PROOF

Impaktor-Bits



Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.

EDELSTAHL Rostfrei
INOX STAINLESS


Stainless Steel Bits



Wera stainless steel bits are manufactured out of stainless steel so unsightly rust can be avoided. The stainless steel bits from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.



Bits for Phillips Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

851/1 BTH bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-hard. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**056410**001	PH 1	25	1"
05**056412**001	PH 2	25	1"
05**056414**001	PH 3	25	1"

851/1 BTZ bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**056420**001	PH 1	25	1"
05**056422**001	PH 2	25	1"
05**056424**001	PH 3	25	1"

Bit-Box 20 BTZ PH

		4013288
05**057751**001	**851/1 BTZ PH** 20 x PH 2x25	187956



851/1 ADC bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Diamond-coated for secure screw fit, profiled version

		mm		mm
05**134940**001	PH 1	25	1"	4,5
05**134941**001	PH 2	25	1"	6,0
05**134942**001	PH 3	25	1"	-

851/1 A bits




Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Extra-hard, profiled version

		mm		mm
05**134919**001	PH 1	25	1"	4,5
05**134920**001	PH 2	25	1"	6,0
05**134921**001	PH 3	25	1"	-

851/1 AH bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Industrial version for optimum torque transfer with increased depth of penetration into the screw recess, 1/4" hexagon over the entire bit length, extra-hard, profiled version

		mm	
05**380155**001	PH 1	25	1"
05**380156**001	PH 2	25	1"
05**380157**001	PH 3	25	1"

851/1 RDC bits

DIAMOND



Application: Drywall screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Reduced shaft diameter, diamond-coated for secure screw fit

		mm		mm
05**135008**001	PH 2	25	1"	4,2

851/1 RH bits

REDUCED DIAMETER



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Reduced shaft diameter, extra-hard, profiled version

		mm		mm
05**380158**001	PH 1	25	1"	4,2
05**346281**001	PH 2	25	1"	4,2

Tip

A-Bits



A stands for aviation. A bits are particularly hard bits with a sharp-edged profile which e.g. penetrates screw profiles full of paint (such as on fuselage panels) ensuring a dependable transfer of force between the bit and the screw.

DIAMOND

Bits with diamond coating



The diamond coating of the DC bits lowers the danger of slipping as the minute diamond particles literally "bite" themselves into the screw head.


Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.



851/1 RZ bits



Application: Drywall screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Reduced shaft diameter, tough, for universal use

		mm		mm
05**135009**001	PH 2	25	1"	4,2

Bit-Box 20 RZ PH

		4013288
05**057753**001	**851/1 RZ PH** 20 x PH 2x25	187987



851/1 RZ SB bits

		4013288
05**135005**001	2 x PH 2x25	038456



Tip

REDUCED DIAMETER

Bits with reduced shaft diameter



Bits with reduced shaft diameter ensure that screws can be sunk without damaging the surface. This is particularly necessary in drywall construction applications.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for Phillips Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

851/1 TH bits



Application: Phillips screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, extra-hard

		mm	
05**056605**001	PH 1	25	1"
05**056610**001	PH 2	25	1"
05**056625**001	PH 3	25	1"

851/1 TiN bits



Application: Phillips screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: TiN coating for the hardness needed e.g. in series screwdriving operations

		mm	
05**480171**001	PH 1	25	1"
05**480172**001	PH 2	25	1"
05**480173**001	PH 3	25	1"


851/1 TiN SB bits

		4013288
05**073512**001	2 x PH 1x25	105806
05**073513**001	2 x PH 2x25	106513
05**073514**001	2 x PH 3x25	105820
05**073515**001	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25	105837





851/1 TZ bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use


		mm	
05**056505**001	PH 1	25	1"
05**056510**001	PH 2	25	1"
05**056525**001	PH 3	25	1"

851/1 TZ SB bits

		4013288
05**073323**001	2 x PH 1x25	029249
05**073324**001	2 x PH 2x25	029256
05**073325**001	2 x PH 3x25	029263
05**073326**001	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25	029270



853/1 TZ bits, ACR®



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use, ACR® (Anti Cam-Out Ribs) prevents bits from slipping out of screw head

		mm	
05**056660**001	PH 1	25	1"
05**056662**001	PH 2	25	1"
05**056664**001	PH 3	25	1"

Tip

ACR®-Bits




ACR® stands for “anti-cam-out ribs”. ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® is a registered trademark of Phillips Screw Company.

TiN-Bits



TiN stands for titanium-nitrite. An extremely hard coating to withstand permanent loads such as during continual screwdriving operations in series manufacturing.

TH-Bits



TH-Bits are hard bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.

TZ-Bits



TZ-Bits are tough bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.

Bits for Phillips Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

851/1 Z bits



Application: Phillips screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm	
05**056500**001	PH 0	25	1"
05**072070**001	PH 1	25	1"
05**056507**001	PH 1	50	2"
05**072072**001	PH 2	25	1"
05**056515**001	PH 2	32	1 $^1/_4$"
05**056520**001	PH 2	50	2"
05**072074**001	PH 3	25	1"
05**134905**001	PH 3	50	2"
05**056535**001	PH 4	32	1 $^1/_4$"

Bit-Box 20 PH

			4013288
05**057750**001	✪	**851/1 PH** 20 x PH 2x25	188014



851/1 Z SB bits

			4013288
05**073304**001	✪	2 x PH 1x25	029058
05**073305**001	✪	2 x PH 2x25	029065
05**073306**001	✪	2 x PH 3x25	029072
05**073307**001	✪	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25	029089



851/1 Z DIY bits

			4013288
05**072400**001	✪	10 x PH 1x25	115737
05**072401**001	✪	10 x PH 2x25	115744
05**072402**001	✪	10 x PH 3x25	115751



851/1 Z DIY 100 bits

			4013288
05**072440**001	✪	100 x PH 1x25	138460
05**072441**001	✪	100 x PH 2x25	138477



851/1 J bits



Application: Phillips screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use; PH 0: JCIS (Japanese Camera Industrial Standard)

		mm		mm
05**135040**001	PH 00	25	1"	2,0
05**135041**001	PH 0	25	1"	2,5
05**135042**001	PH 1	25	1"	3,0

Tip

J-Bits



J stands for Japan. J bits have been optimised to suit Asian PH screws. In particular, they are for use with very small dimensions as set out in the Japanese Camera Standard.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for Phillips Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

851/4 IMP DC Impaktor bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**057656**001	PH 2	50	2"
05**057657**001	PH 3	50	2"

851/4 IMP DC SB Impaktor bits

		4013288
05**073956**001	1 x PH 2x50	158482
05**073957**001	1 x PH 3x50	158499



3851/4 Bits, stainless



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust

		mm	
05**071081**001	PH 1	89	3 1/2"
05**071082**001	PH 2	89	3 1/2"
05**071083**001	PH 3	89	3 1/2"

851/4 BDC bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, diamond-coated for secure screw fit. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**059530**001	PH 1	50	2"
05**059532**001	PH 2	50	2"
05**059534**001	PH 3	50	2"

851/4 BTH bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, extra-hard. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**059540**001	PH 1	50	2"
05**059542**001	PH 2	50	2"
05**059544**001	PH 3	50	2"

851/4 BTZ bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (red = Phillips) and large stamp to enable the desired bit to be easily located.

		mm	
05**059550**001	PH 1	50	2"
05**059552**001	PH 2	50	2"
05**059554**001	PH 3	50	2"

Tip



Impaktor-Bits



Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.




BDC-Bits



BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally "bite" themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.



"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.



Bits for Phillips Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

851/4 ADC bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Extra-hard, diamond-coated for secure screw fit, profiled version

		mm		mm
05**134950**001	PH 1	50	2"	4,5
05**134951**001	PH 2	50	2"	6
05**134952**001	PH 3	50	2"	-

851/4 RH Reduced tip bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Reduced shaft diameter, extra-hard

		mm		mm
05**380160**001	PH 1	50	2"	4,2
05**380161**001	PH 2	50	2"	4,2

851/4 A bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Extra-hard, profiled version

		mm		mm
05**134929**001	PH 0	50	2"	3
05**134906**001	PH 0	70	2 3/4"	3
05**134907**001	PH 0	89	3 1/2"	3
05**134908**001	PH 0	152	6"	3
05**134930**001	PH 1	50	2"	4,5
05**134370**001	PH 1	70	2 3/4"	4,5
05**134372**001	PH 1	89	3 1/2"	4,5
05**134909**001	PH 1	152	6"	4,5
05**134931**001	PH 2	50	2"	6
05**134371**001	PH 2	70	2 3/4"	6
05**134373**001	PH 2	89	3 1/2"	6
05**134910**001 [1]	PH 2	152	6"	6
05**134911**001 [2]	PH 2	152	6"	6
05**134932**001	PH 3	50	2"	-
05**134912**001	PH 3	50	2"	8
05**134913**001	PH 3	70	2 3/4"	8
05**134914**001	PH 3	89	3 1/2"	8
05**134915**001	PH 3	152	6"	8
05**160983**001	PH 4	50	2"	10

[1] Length of drive 100 mm
[2] Length of drive 20 mm

Tip

851/4 R Reduced tip bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Reduced shaft diameter

		mm		mm
05**160899**001	PH 2	50	2"	3,0
05**160896**001	PH 2	152	6"	3,0

851/4 TH bits

TORSION



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Torsion-style design to reduce premature wear, extra-hard

		mm	
05**059855**001	PH 1	50	2"
05**059860**001	PH 2	50	2"
05**059865**001	PH 3	50	2"

REDUCED DIAMETER

Bits with reduced shaft diameter



Bits with reduced shaft diameter ensure that screws can be sunk without damaging the surface. This is particularly necessary in drywall construction applications.

A-Bits



A stands for aviation. A bits are particularly hard bits with a sharp-edged profile which e.g. penetrates screw profiles full of paint (such as on fuselage panels) ensuring a dependable transfer of force between the bit and the screw.

DIAMOND

Bits with diamond coating



The diamond coating of the DC bits lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head.

Bits for Phillips Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

851/4 TZ bits





Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use

		mm	
05**059805**001	PH 1	50	2"
05**059810**001	PH 2	50	2"
05**059815**001	PH 3	50	2"

851/4 TZ SB bits

		4013288
05**134380**001	2 x PH 1x50	037947
05**134381**001	2 x PH 2x50	037954
05**134382**001	2 x PH 3x50	037961



851/4 J bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**135530**001	PH 00	50	2"	2,0
05**380200**001	PH 00	89	3 1/2"	2,0
05**135531**001[1)]	PH 0	50	2"	2,5
05**380201**001[1)]	PH 0	89	3 1/2"	2,5
05**135532**001	PH 1	50	2"	4,5
05**380202**001	PH 1	89	3 1/2"	4,5

[1)] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

851/4 Z bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**059755**001	PH 1	70	2 3/4"	4,5
05**059760**001	PH 1	89	3 1/2"	4,5
05**059765**001	PH 1	127	5"	4,5
05**059766**001	PH 1	152	6"	4,5
05**059770**001	PH 2	70	2 3/4"	6,0
05**059775**001	PH 2	89	3 1/2"	6,0
05**059780**001	PH 2	110	4 3/8"	6,0
05**059785**001	PH 2	127	5"	6,0
05**059786**001	PH 2	152	6"	6,0
05**059790**001	PH 3	70	2 3/4"	-
05**059795**001	PH 3	89	3 1/2"	-
05**059800**001	PH 3	110	4 3/8"	-
05**059802**001	PH 3	152	6"	-

851/4 Z SB bits

		4013288
05**073520**001	1 x PH 1x89	105875
05**073521**001	1 x PH 2x89	105882
05**073522**001	1 x PH 3x89	105899



Tip

ACR®-Bits:



ACR® stands for “anti-cam-out ribs”. ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® reg. trademark of Phillips Screw Company.

J-Bits



J stands for Japan. J bits have been optimised to suit Asian PH screws. In particular, they are for use with very small dimensions as set out in the Japanese Camera Standard.

853/4 ACR® bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use, ACR® (Anti Cam-Out Ribs) prevents bit from slipping out of screw head

	⊕	mm		∅ mm
05**346285**001	PH 1	50	2"	3,5
05**346286**001	PH 2	50	2"	5,2
05**346287**001	PH 3	50	2"	5,8

853/4 Harpoon ACR® bits



Application: Phillips screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Reduced shaft diameter, tough, for universal use, ACR® (Anti Cam-Out Ribs) prevents bit from slipping out of screw head

	⊕	mm		∅ mm
05**160901**001	PH 2	50	2"	3,3
05**160895**001	PH 2	70	2 3/4"	3,3
05**160908**001	PH 2	152	6"	3,3

Bits for Phillips Screws

¼" Double-ended bits, ¼" hexagon drive (series 23)

851/23 double-ended bits for Phillips screws



Application: Phillips screws
Drive: 1/4" hexagon
Design: Ball-guide groove 17 mm

		mm	
05**135705**001	PH 2	45	1 25/32"
05**135706**001	PH 2	65	2 9/16"

5/16" 5/16" hexagon drive, suitable for D 8 bit holders or direct drive (series 2)

851/2 Z bits



Application: Phillips screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-D 8 bit holders

Design: Tough, for universal use

		mm		mm
05**057705**001	PH 1	32	1 1/4"	4,5
05**057710**001	PH 2	32	1 1/4"	6,0
05**057715**001	PH 3	32	1 1/4"	7,6
05**057720**001	PH 4	32	1 1/4"	-
05**057725**001	PH 4	38	1 1/2"	10,0

M 4 Thread drive M 4 direct drive (series 11)

851/11 Bits



Application: Phillips screws

Drive: Thread drive M 4

Design: Tough, for universal use

		mm		mm
05**065075**001	PH 1	33	1 1/4"	5,5
05**065081**001	PH 2	33	1 1/4"	6,0

M 5 Thread drive M 5 direct drive (series 12)

851/12 Bits



Application: Phillips screws

Drive: Thread drive M 5

Design: Tough, for universal use

		mm		mm
05**065110**001	PH 2	33	1 1/4"	7,0
05**065112**001	PH 2	35	1 3/8"	7,0
05**065114**001	PH 2	44,5	1 3/4"	6,0
05**065116**001	PH 2	50	2"	6,0

Bits for Phillips Screws

M 6 Thread drive M 6 direct drive (series 15)

851/15 Bits



Application: Phillips screws
Drive: Thread drive M 6
Design: Tough, for universal use

		mm		mm
05**065150**001	PH 2	33	1 1/4"	8,0
05**065152**001	PH 2	35	1 3/8"	8,0
05**065154**001	PH 2	44,5	1 3/4"	8,0

#10/32" Thread drive #10-32 UNF direct drive (series 16)

851/16 Bits



Application: Phillips screws
Drive: Thread drive #10-32 UNF
Design: Tough, for universal use

		mm		mm
05**065197**001	PH 2	44,5	1 3/4"	6,0

4 mm 4 mm Halfmoon direct drive (series 9)

851/9 C J PH bits, halfmoon



Application: Phillips screws

Drive: Halfmoon, 4 mm

Design: Hard

		mm		mm	mm	
05**134605**001 [1]	PH 000	44	1 47/64"	1,5	20	25/32"
05**134606**001 [1]	PH 000	64	2 33/64"	1,5	20	25/32"
05**135270**001 [1]	PH 00	44	1 47/64"	1,8	20	25/32"
05**135271**001 [1]	PH 00	64	2 33/64"	1,8	20	25/32"
05**135272**001 [2]	PH 0	44	1 47/64"	1,8	20	25/32"
05**135273**001 [2]	PH 0	64	2 33/64"	1,8	20	25/32"
05**135274**001 [2]	PH 0	44	1 47/64"	2,0	20	25/32"
05**135275**001 [2]	PH 0	64	2 33/64"	2,2	20	25/32"
05**135278**001 [2]	PH 0	44	1 47/64"	2,2	20	25/32"
05**135276**001 [1]	PH 1	44	1 47/64"	3,0	20	25/32"
05**135277**001 [1]	PH 1	64	2 33/64"	3,0	20	25/32"
05**134607**001	PH 2	44	1 47/64"	4,0	-	
05**134608**001	PH 2	64	2 33/64"	4,0	-	

[1] Optimised for Asian PH screws

[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

4 mm 4 mm HIOS direct drive (series 21)

851/21 J bits



Application: Phillips screws

Drive: HIOS 4 mm

Design: Hard

		mm		mm
05**135280**001 [1]	PH 00	40	1 9/16"	1,8
05**135281**001 [1]	PH 00	60	2 3/8"	1,8
05**135284**001 [2]	PH 0	40	1 9/16"	1,8
05**135285**001 [2]	PH 0	60	2 3/8"	1,8
05**135286**001 [2]	PH 0	40	1 9/16"	2,0
05**135287**001 [2]	PH 0	60	2 3/8"	2,0
05**135288**001 [2]	PH 0	40	1 9/16"	2,5
05**135289**001 [2]	PH 0	60	2 3/8"	2,5
05**135290**001	PH 1	40	1 9/16"	3,0
05**135291**001	PH 1	60	2 3/8"	3,0

[1] Size 00 modificated according to JCIS 00 (Japanese Camera Industrial Standard) modifiziert

[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

Bits for Phillips Screws

5 mm 5 mm HIOS direct drive (series 22)

851/22 J bits



Application: Phillips screws
Drive: HIOS 5 mm
Design: Hard; PH 0: JCIS (Japanese Camera Industrial Standard)

		mm		mm	mm	
05**135380**001 [1]	PH 00	60	2 3/8"	2,0	20	25/32"
05**135381**001 [2]	PH 0	60	2 3/8"	2,0	20	25/32"
05**135382**001 [2]	PH 0	80	3 1/8"	2,0	20	25/32"
05**135383**001 [2]	PH 0	60	2 3/8"	2,5	20	25/32"
05**135384**001 [2]	PH 0	80	3 1/8"	2,5	20	25/32"
05**135385**001	PH 1	60	2 3/8"	3,0	20	25/32"
05**135386**001	PH 1	80	3 1/8"	3,0	20	25/32"
05**135387**001	PH 1	100	4"	3,0	20	25/32"

[1] Size 00 modificated according to JCIS 00 (Japanese Camera Industrial Standard) modifiziert

[2] Size 0 modificated according to JCIS 0 (Japanese Camera Industrial Standard)

5/16" 5/16" external square drive (series 25)

851/25 H bits



Application: Phillips screws
Drive: 5/16" external square
Design: Extra-hard


		mm	
05**380380**001	PH 1	29	1 3/16"
05**380381**001	PH 2	29	1 3/16"
05**380382**001	PH 3	29	1 3/16"
05**380383**001	PH 4	29	1 3/16"


Wera
PH00

Bits for Pozidriv Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

855/1 IMP DC Impaktor bits





Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**057620**001	PZ 1	25	1"
05**057621**001	PZ 2	25	1"
05**057622**001	PZ 3	25	1"

Bit-Box 15 Impaktor PZ

		4013288
05**057763**001	**855/1 IMP DC** 15 x PZ 2x25	187901



855/1 IMP DC SB Impaktor bits

		4013288
05**073921**001	1 x PZ 2x25	158383
05**073922**001	1 x PZ 3x25	158390



3855/1 TS bits, stainless





Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Stainless steel for minimising rust, special torsion-style design to reduce premature wear. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**071020**001	PZ 1	25	1"
05**071021**001	PZ 2	25	1"
05**071022**001	PZ 3	25	1"

3855/1 TS SB bits, stainless

		4013288
05**073613**001	1 x PZ 1x25	112101
05**073614**001	1 x PZ 2x25	112118
05**073615**001	1 x PZ 3x25	112125



855/1 BDC bits



Application: Suitable for Pozidriv screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, diamond-coated for secure screw fit. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**056700**001	PZ 1	25	1"
05**056702**001	PZ 2	25	1"
05**056704**001	PZ 3	25	1"

855/1 BDC SB bits

		4013288
05**073336**001	1 x PZ 1x25	029362
05**073337**001	1 x PZ 2x25	029379
05**073338**001	1 x PZ 3x25	029386
05**073339**001	2 x PZ 2x25	029393





Tip



Impaktor-Bits



Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.




BDC-Bits



BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally "bite" themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.



"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.

Bits for Pozidriv Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

855/1 BTH bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-hard. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**056710**001	PZ 1	25	1"
05**056712**001	PZ 2	25	1"
05**056714**001	PZ 3	25	1"

Bit-Box 20 BTH PZ

		4013288
05**057762**001	**855/1 BTH PZ** 20 x PZ 2x25	187963



855/1 BTZ bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**056720**001	PZ 1	25	1"
05**056722**001	PZ 2	25	1"
05**056724**001	PZ 3	25	1"

Bit-Box 20 BTZ PZ

		4013288
05**057761**001	**855/1 BTZ PZ** 20 x PZ 2x25	187970



855/1 RZ bits



Application: Quick-build Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Reduced shaft diameter, tough, for universal use

		mm		mm
05**135017**001	PZ 1	25	1"	4,2
05**135003**001	PZ 2	25	1"	4,2

855/1 TH bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, extra-hard

		mm	
05**056910**001	PZ 1	25	1"
05**056915**001	PZ 2	25	1"
05**056925**001	PZ 3	25	1"

855/1 TH SB bits

		4013288
05**073370**001	2 x PZ 1x25	029638
05**073371**001	2 x PZ 2x25	029645
05**073372**001	2 x PZ 3x25	029652
05**073373**001	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25	029669



855/1 TiN bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: TiN coating for the hardness needed e.g. in series screwdriving operations

		mm	
05**480221**001	PZ 1	25	1"
05**480222**001	PZ 2	25	1"
05**480223**001	PZ 3	25	1"

855/1 TiN SB bits

		4013288
05**073516**001	2 x PZ 1x25	106445
05**073517**001	2 x PZ 2x25	105844
05**073518**001	2 x PZ 3x25	105851
05**073519**001	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25	105868



Tip

Bits with reduced shaft diameter



Bits with reduced shaft diameter ensure that screws can be sunk without damaging the surface. This is particularly necessary in drywall construction applications.

TiN-Bits



TiN stands for titanium-nitrite. An extremely hard coating to withstand permanent loads such as during continual screwdriving operations in series manufacturing.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for Pozidriv Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

855/1 TZ bits




Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use

		mm	
05**056810**001	PZ 1	25	1"
05**056815**001	PZ 2	25	1"
05**056825**001	PZ 3	25	1"

856/1 TZ, ACR® bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use, ACR® (Anti Cam-Out Ribs) prevents bits from slipping out of screw head

		mm	
05**056937**001	PZ 1	25	1"
05**056938**001	PZ 2	25	1"
05**056939**001	PZ 3	25	1"

855/1 Z bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm	
05**056805**001	PZ 0	25	1"
05**072080**001	PZ 1	25	1"
05**056812**001	PZ 1	50	2"
05**072082**001	PZ 2	25	1"
05**056820**001	PZ 2	50	2"
05**072084**001	PZ 3	25	1"
05**056835**001	PZ 4	32	1 1/4"

Bit-Box 20 PZ

		4013288
05**057760**001	**855/1 Z PZ** 20 x PZ 2x25	188052



855/1 Z SB bits

		4013288
05**073308**001	2 x PZ 1x25	029096
05**073309**001	2 x PZ 2x25	029102
05**073310**001	2 x PZ 3x25	029119
05**073380**001	1 x PZ 4x32	029621
05**073311**001	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25	029126





855/1 Z DIY bits

		4013288
05**072403**001	10 x PZ 1x25	115768
05**072404**001	10 x PZ 2x25	115775
05**072405**001	10 x PZ 3x25	115782



855/1 Z DIY 100 bits

		4013288
05**072443**001	100 x PZ 1x25	138484
05**072444**001	100 x PZ 2x25	138491




Tip

ACR®-Bits:



ACR® stands for “anti-cam-out ribs”. ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® reg. trademark of Phillips Screw Company.



TZ-Bits



TZ-Bits are tough bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for Pozidriv Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

855/4 IMP DC Impaktor bits



Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**057661**001	PZ 2	50	2"
05**057662**001	PZ 3	50	2"

855/4 IMP DC Impaktor bits SB

		4013288
05**073961**001	1 x PZ 2x50	158505
05**073962**001	1 x PZ 3x50	158512



3855/4 Bits, stainless



Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust

		mm	
05**071084**001	PZ 1	89	3 $^{1}/_{2}$"
05**071085**001	PZ 2	89	3 $^{1}/_{2}$"
05**071041**001	PZ 2	50	2"
05**071086**001	PZ 3	89	3 $^{1}/_{2}$"



Bits for Pozidriv Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

855/4 BDC bits



Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, diamond-coated for secure screw fit. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**059900**001	PZ 1	50	2"
05**059902**001	PZ 2	50	2"
05**059904**001	PZ 3	50	2"

855/4 BTH bits



Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, extra-hard. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**059910**001	PZ 1	50	2"
05**059912**001	PZ 2	50	2"
05**059914**001	PZ 3	50	2"

855/4 BTZ bits



Application: Suitable for Pozidriv screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (black = Pozidriv) and large stamp to enable the desired bit to be easily located.

		mm	
05**059920**001	PZ 1	50	2"
05**059922**001	PZ 2	50	2"
05**059924**001	PZ 3	50	2"

855/4 TH bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Torsion-style design to reduce premature wear, extra-hard

		mm	
05**060055**001	PZ 1	50	2"
05**060060**001	PZ 2	50	2"
05**060065**001	PZ 3	50	2"

855/4 TZ bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use

		mm	
05**060005**001	PZ 1	50	2"
05**060010**001	PZ 2	50	2"
05**060015**001	PZ 3	50	2"

855/4 TZ SB bits

		4013288
05**134384**001	2 x PZ 1x50	037985
05**134385**001	2 x PZ 2x50	037992
05**134386**001	2 x PZ 3x50	038005



855/4 Z bits



Application: Suitable for Pozidriv screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**060027**001	PZ 1	70	2 3/4"	4,5
05**060029**001	PZ 1	89	3 1/2"	4,5
05**060031**001	PZ 1	127	5"	4,5
05**060030**001	PZ 1	152	6"	4,5
05**060033**001	PZ 2	70	2 3/4"	6,0
05**060035**001	PZ 2	89	3 1/2"	6,0
05**060037**001	PZ 2	110	4 3/8"	6,0
05**060036**001	PZ 2	127	5"	6,0
05**060038**001	PZ 2	152	6"	6,0
05**060041**001	PZ 3	70	2 3/4"	-
05**060043**001	PZ 3	89	3 1/2"	-
05**060045**001	PZ 3	110	4 3/8"	-
05**060047**001	PZ 3	152	6"	-

855/4 Z SB bits

		4013288
05**073523**001	1 x PZ 1x89	105905
05**073524**001	1 x PZ 2x89	106452
05**073525**001	1 x PZ 3x89	105912



Bits for Pozidriv Screws

5/16" hexagon drive, suitable for D 8 bit holders or direct drive (series 2)

855/2 Z bits



Application: Suitable for Pozidriv screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-D 8 bit holders

Design: Tough, for universal use

		mm		mm
05**058005**001	PZ 1	32	1 1/4"	4,5
05**058010**001	PZ 2	32	1 1/4"	6,0
05**058015**001	PZ 3	32	1 1/4"	7,6
05**058020**001	PZ 4	32	1 1/4"	-
05**058025**001	PZ 4	38	1 1/2"	10,0

M 4 Thread drive M 4 direct drive (series 11)

855/11 Bits



Application: Suitable for Pozidriv screws

Drive: Thread drive M 4

Design: Tough, for universal use

		mm		mm
05**065090**001	PZ 1	33	1 1/4"	5,5
05**065096**001	PZ 2	33	1 1/4"	6,0

M 5 Thread drive M 5 direct drive (series 12)

855/12 Bits



Application: Suitable for Pozidriv screws

Drive: Thread drive M 5

Design: Tough, for universal use

		mm		mm
05**065125**001	PZ 2	33	1 1/4"	7,0
05**065127**001	PZ 2	35	1 3/8"	7,0
05**065129**001	PZ 2	44,5	1 3/4"	6,0

M 6 Thread drive M 6 direct drive (series 15)

855/15 Bits



Application: Suitable for Pozidriv screws

Drive: Thread drive M 6

Design: Tough, for universal use

		mm		mm
05**065167**001	PZ 2	35	1 3/8"	8,0
05**065169**001	PZ 2	44,5	1 3/4"	8,0

Bits for PlusMinus Screws – Phillips/Slotted

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

851/4 PH/S PlusMinus bits





Application: PlusMinus screws (Phillips/slotted)

Drive: $^{1}/_{4}$" hexagon suitable for DIN ISO 1173-F 6,3 bit holders

Design: PlusMinus (Phillips/slotted), tough, ideal for electrical component adjustment jobs e.g. in sheet steel or metal

		mm		mm
05**059720**001	# 1	70	2 $^{3}/_{4}$"	4,5
05**059721**001	# 2	70	2 $^{3}/_{4}$"	6

Bits for PlusMinus Screws – Pozidriv/Slotted

¼" hexagon drive, suitable for F 6,3 bit holders (series 1)

855/4 PZ/S PlusMinus bits





Application: PlusMinus (Pozidriv/slotted) screws

Drive: $^{1}/_{4}$" hexagon suitable for DIN ISO 1173-F 6,3 bit holders

Design: PlusMinus (slotted/Pozidriv), tough, ideal for electrical component adjustment jobs e.g. in sheet steel or metal

		mm		mm
05**059896**001	# 1	70	2 $^{3}/_{4}$"	4,5
05**059897**001	# 2	70	2 $^{3}/_{4}$"	6

Bits for TORX® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

867/1 IMP DC Impaktor TORX® bits





Application: TORX® socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

		mm	
05**057628**001	TX 10	25	1"
05**057623**001	TX 15	25	1"
05**057624**001	TX 20	25	1"
05**057625**001	TX 25	25	1"
05**057626**001	TX 30	25	1"
05**057627**001	TX 40	25	1"

Bit-Box 15 Impaktor TX

		4013288
05**057772**001	**867/1 IMP DC** 15 x TX 20x25	187871
05**057775**001	**867/1 IMP DC** 15 x TX 25x25	187888
05**057776**001	**867/1 IMP DC** 15 x TX 30x25	187895



867/1 IMP DC SB Impaktor bits

		4013288
05**073924**001	1 x TX 20x25	163240
05**073925**001	1 x TX 25x25	158406
05**073926**001	1 x TX 30x25	158413
05**073927**001	1 x TX 40x25	158420



3867/1 TS TORX® bits, stainless





Application: TORX® socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Stainless steel for minimising rust, special torsion-style design to reduce premature wear. Take it easy toolfinder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.


		mm	
05**071030**001	TX 8	25	1"
05**071031**001	TX 9	25	1"
05**071032**001	TX 10	25	1"
05**071033**001	TX 15	25	1"
05**071034**001	TX 20	25	1"
05**071035**001	TX 25	25	1"
05**071036**001	TX 27	25	1"
05**071037**001	TX 30	25	1"
05**071038**001	TX 40	25	1"

3867/1 TS SB TORX® bits, stainless

		4013288
05**073620**001	1 x TX 10x25	117670
05**073621**001	1 x TX 15x25	117687
05**073622**001	1 x TX 20x25	117694
05**073623**001	1 x TX 25x25	117700
05**073624**001	1 x TX 27x25	117717
05**073625**001	1 x TX 30x25	117724
05**073626**001	1 x TX 40x25	117731



867/1 BDC TORX® bits



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, diamond-coated for secure screw fit. Take it easy toolfinder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

		mm	
05**066100**001	TX 10	25	1"
05**066102**001	TX 15	25	1"
05**066104**001	TX 20	25	1"
05**066106**001	TX 25	25	1"
05**342920**001	TX 27	25	1"
05**066108**001	TX 30	25	1"
05**066110**001	TX 40	25	1"

867/1 BDC SB TORX® bits

		4013288
05**134374**001	1 x TX 10x25	099778
05**134375**001	1 x TX 15x25	099785
05**134376**001	1 x TX 20x25	099792
05**134377**001	1 x TX 25x25	099808
05**134378**001	1 x TX 30x25	099822
05**134379**001	1 x TX 40x25	099815



Tip



Impaktor-Bits



Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.




BDC-Bits



BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally "bite" themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.



"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.

Bits for TORX® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

867/1 BTZ TORX® bits



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

		mm	
05**066120**001	TX 10	25	1"
05**066122**001	TX 15	25	1"
05**066124**001	TX 20	25	1"
05**066126**001	TX 25	25	1"
05**066128**001	TX 30	25	1"
05**066130**001	TX 40	25	1"

Bit-Box 20 BTZ TX

		4013288
05**057771**001	**867/1 TORX® BTZ** 20 x TX 20x25	187932
05**057774**001	**867/1 TORX® BTZ** 20 x TX 25x25	187949



867/1 Z TORX® HF bits with holding function



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, tough, for universal use

		mm		mm
05**066070**001	TX 8	25	1"	2,2
05**066071**001	TX 9	25	1"	2,4
05**066072**001	TX 10	25	1"	2,5
05**066073**001	TX 15	25	1"	3,0
05**066074**001	TX 20	25	1"	3,7
05**066075**001	TX 25	25	1"	4,1
05**066076**001	TX 27	25	1"	4,8
05**066077**001	TX 30	25	1"	5,4
05**066078**001	TX 40	25	1"	6,5

867/1 TZ TORX® bits



Application: TORX® socket screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use

		mm		mm
05**066300**001	TX 5	25	1"	4,2
05**066301**001	TX 6	25	1"	4,2
05**066302**001	TX 7	25	1"	4,2
05**066303**001	TX 8	25	1"	4,2
05**066304**001	TX 9	25	1"	4,2
05**066305**001	TX 10	25	1"	4,2
05**066308**001	TX 15	25	1"	4,2
05**066310**001	TX 20	25	1"	4,8
05**066312**001	TX 25	25	1"	5,5
05**066313**001	TX 27	25	1"	5,5
05**066315**001	TX 30	25	1"	6,0
05**066320**001	TX 40	25	1"	-

Tip



The HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!



BTZ-Bits



BTZ-Bits have an additional tempered BiTorsion zone, which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for TORX® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

867/1 TORX® bits



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**135140**001	TX 1	25	1"	1,5
05**135141**001	TX 2	25	1"	1,5
05**135142**001	TX 3	25	1"	2,0
05**135143**001	TX 4	25	1"	2,0
05**066492**001	TX 5	25	1"	3,0
05**066493**001	TX 6	25	1"	3,0
05**066494**001	TX 7	25	1"	3,0
05**066495**001	TX 8	25	1"	3,0
05**066496**001	TX 9	25	1"	3,0
05**066485**001	TX 10	25	1"	4,0
05**066486**001	TX 15	25	1"	4,0
05**066487**001	TX 20	25	1"	5,0
05**066488**001	TX 25	25	1"	5,0
05**066489**001	TX 27	25	1"	6,0
05**066490**001	TX 30	25	1"	6,0
05**066491**001	TX 40	25	1"	-
05**066325**001	TX 45	35	1 3/8"	8,0
05**066330**001	TX 50	35	1 3/8"	9,0
05**066335**001	TX 55	35	1 3/8"	12,0

867/1 SB TORX® bits

		4013288
05**073313**001	2 x TX 10x25	029140
05**073340**001	2 x TX 15x25	029591
05**073314**001	2 x TX 20x25	029157
05**073315**001	2 x TX 25x25	029164
05**073316**001	2 x TX 30x25	029171
05**073317**001	2 x TX 40x25	029188
05**073346**001	1 x TX 50x35	125859
05**073375**001	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25	037503
05**073376**001	1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25	037510



867/1 TORX® bits DIY

		4013288
05**072406**001	10 x TX 10x25	115799
05**072407**001	10 x TX 15x25	115805
05**072408**001	10 x TX 20x25	115812
05**072409**001	10 x TX 25x25	115829
05**072410**001	10 x TX 27x25	115836
05**072411**001	10 x TX 30x25	115843
05**072412**001	10 x TX 40x25	115850



Bit-Box 20 TX

			4013288
05**057770**001	**867/1 TORX®** 20 x TX 20x25		187994
05**057773**001	**867/1 TORX®** 20 x TX 25x25		188007



867/1 TORX® bits DIY 100

		4013288
05**072446**001	100 x TX 10x25	138507
05**072447**001	100 x TX 15x25	138514
05**072448**001	100 x TX 20x25	138521
05**072449**001	100 x TX 25x25	138538
05**072450**001	100 x TX 27x25	138545
05**072451**001	100 x TX 30x25	138552
05**072452**001	100 x TX 40x25	138569



867/1 Z TORX® Wedge bits



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: W = Wedge TORX®, tough, for universal use

		mm	
05**066450**001	TX 10	25	1"
05**066455**001	TX 15	25	1"
05**066460**001	TX 20	25	1"
05**066465**001	TX 25	25	1"
05**066470**001	TX 27	25	1"
05**066475**001	TX 30	25	1"
05**066480**001	TX 40	25	1"

867/1 ZA TORX® bits with central pin



Application: SPAX T-STAR plus screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Central pin, tough, for universal use

		mm		mm
05**066080**001	TX 10	25	1"	4,0
05**066081**001	TX 15	25	1"	4,0
05**066082**001	TX 20	25	1"	5,0
05**066083**001	TX 25	25	1"	5,0
05**066084**001	TX 30	25	1"	6,0
05**066085**001	TX 40	25	1"	-

Tip

TORX® Wedge



The conical TORX® profile provides a better fit in the screw. Combined with a great recess depth this produces a pinch effect.

TORX® bits with central pin



The protruding pin that fits into the borehole of the screw makes it easier to centre the tool in the screw recess.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for TORX® Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

867/4 IMP DC Impaktor TORX® bits



Application: TORX® socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

		mm	
05**057664**001	TX 20	50	2"
05**057665**001	TX 25	50	2"
05**057666**001	TX 30	50	2"
05**057667**001	TX 40	50	2"

867/4 IMP DC SB Impaktor bits

		4013288
05**073964**001	1 x TX 20x50	163257
05**073965**001	1 x TX 25x50	158529
05**073966**001	1 x TX 30x50	158536
05**073967**001	1 x TX 40x50	158543



3867/4 TORX®, stainless



Application: TORX® socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust
Take it easy toolfinder: Output colour coding (green = TORX®) and large stamp to enable the desired bit to be easily located.

		mm	
05**071046**001	TX 20	50	2"
05**071047**001	TX 25	50	2"

867/4 KK TORX® bits



Application: TORX® socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Ball end, tough, for universal use

		mm	
05**059700**001	TX 10	89	3 $^{1}/_{2}$"
05**059701**001	TX 15	89	3 $^{1}/_{2}$"
05**059702**001	TX 20	89	3 $^{1}/_{2}$"
05**059703**001	TX 25	89	3 $^{1}/_{2}$"
05**059704**001	TX 30	89	3 $^{1}/_{2}$"
05**059705**001	TX 40	89	3 $^{1}/_{2}$"

Tip

867/4 TORX® HF bits with holding function



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Holding function for TORX® screws made according to Acument Intellectual Properties specifications, tough, for universal use

		mm		mm
05**060080**001	TX 8	50	2"	3,0
05**060360**001	TX 10	89	3 1/2"	4,0
05**060081**001	TX 10	50	2"	4,0
05**060361**001	TX 15	89	3 1/2"	4,0
05**060082**001	TX 15	50	2"	4,0
05**060362**001	TX 20	89	3 1/2"	4,5
05**060083**001	TX 20	50	2"	4,5
05**060084**001	TX 25	50	2"	6,0
05**060363**001	TX 25	89	3 1/2"	6,0
05**060085**001	TX 27	50	2"	6,0
05**060364**001	TX 27	89	3 1/2"	6,0
05**060086**001	TX 30	50	2"	6,0
05**060365**001	TX 30	89	3 1/2"	6,0
05**060087**001	TX 40	50	2"	-
05**060366**001	TX 40	89	3 1/2"	-

867/4 H TORX® bits



Application: TORX® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6.3 bit holders

Design: Extra-hard

		mm		mm
05**135170**001	TX 5	50	2"	3,0
05**135171**001	TX 5	70	2 3/4"	3,0
05**135172**001	TX 6	50	2"	3,0
05**135180**001	TX 6	70	2 3/4"	3,0
05**135174**001	TX 8	50	2"	3,0
05**135182**001	TX 8	70	2 3/4"	3,0
05**135176**001	TX 10	50	2"	4,0
05**135184**001	TX 10	70	2 3/4"	4,0
05**135185**001	TX 15	50	2"	4,0
05**135186**001	TX 15	70	2 3/4"	4,0

BALL END

TORX® ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

HOLDING FUNCTION

The HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

867/4 H: A vacuum-hardened bit



Vacuum hardening is the cleanest and most environmentally friendly of all hardening methods. The environment inside the vacuum chamber is unreactive, even to alloys which are especially prone to oxidation. For all grades of steel, vacuum heat treatment is the optimum heat treatment, and represents state of the art technology.

Bits for TORX® Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

867/4 Z TORX® bits



Application: TORX® socket screws

Drive: ¼" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: For universal use

		mm		mm
05**135200**001	TX 1	50	2"	2,0
05**135201**001	TX 2	50	2"	2,0
05**135202**001	TX 3	50	2"	2,0
05**135204**001	TX 4	50	2"	3,0
05**135205**001	TX 5	50	2"	3,0
05**308428**001	TX 6	50	2"	3,0
05**134740**001	TX 6	70	2 ¾"	3,0
05**332600**001	TX 6	89	3 ½"	3,0
05**328448**001	TX 6	152	6"	3,0
05**160830**001	TX 7	50	2"	3,0
05**345047**001	TX 7	70	2 ¾"	3,0
05**060131**001	TX 8	50	2"	3,0
05**060098**001	TX 8	70	2 ¾"	3,0
05**060185**001	TX 8	89	3 ½"	3,0
05**060195**001	TX 8	152	6"	3,0
05**319835**001	TX 9	70	2 ¾"	3,0
05**060193**001	TX 9	89	3 ½"	3,0
05**060194**001	TX 9	152	6"	3,0
05**060132**001	TX 10	50	2"	4,0
05**060100**001	TX 10	70	2 ¾"	4,0
05**060186**001	TX 10	89	3 ½"	4,0
05**060196**001	TX 10	152	6"	4,0
05**060133**001	TX 15	50	2"	4,0
05**060105**001	TX 15	70	2 ¾"	4,0
05**060187**001	TX 15	89	3 ½"	4,0
05**060197**001	TX 15	152	6"	4,0
05**060134**001	TX 20	50	2"	4,5
05**060110**001	TX 20	70	2 ¾"	4,5
05**060188**001	TX 20	89	3 ½"	4,5
05**060198**001	TX 20	152	6"	4,5
05**060135**001	TX 25	50	2"	6,0
05**060115**001	TX 25	70	2 ¾"	6,0
05**060189**001	TX 25	89	3 ½"	6,0
05**060199**001	TX 25	152	6"	6,0
05**060136**001	TX 27	50	2"	6,0
05**060120**001	TX 27	70	2 ¾"	6,0
05**060190**001	TX 27	89	3 ½"	6,0
05**060200**001	TX 27	152	6"	6,0
05**060137**001	TX 30	50	2"	6,0
05**060125**001	TX 30	70	2 ¾"	6,0
05**060191**001	TX 30	89	3 ½"	6,0
05**060201**001	TX 30	152	6"	6,0
05**060138**001	TX 40	50	2"	-
05**060130**001	TX 40	70	2 ¾"	-
05**060192**001	TX 40	89	3 ½"	-
05**060202**001	TX 40	152	6"	-

867/4 SB TORX® bits, 89 mm

		4013288
05**073526**001	1 x TX 10x89	105929
05**073527**001	1 x TX 15x89	105936
05**073528**001	1 x TX 20x89	105943
05**073529**001	1 x TX 25x89	105950
05**073530**001	1 x TX 30x89	105967
05**073531**001	1 x TX 40x89	105974




867/4 SB TORX® bits, 50 mm

		4013288
05**073720**001	2 x TX 10x50	132789
05**073721**001	2 x TX 15x50	132796
05**073722**001	2 x TX 20x50	132802
05**073723**001	2 x TX 25x50	132826
05**073724**001	2 x TX 30x50	132833



5/16" 5/16" hexagon drive, suitable for D 8 bit holders or direct drive (series 2)

867/2 Z TORX® bits



Application: TORX® socket screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-D 8 bit holders

Design: Tough, for universal use

		mm		mm
05**066901**001	TX 20	35	1 3/8"	4,5
05**066930**001	TX 20	50	2"	4,5
05**066945**001	TX 20	70	2 3/4"	4,5
05**066935**001	TX 20	100	4"	4,5
05**066900**001	TX 25	35	1 3/8"	5,8
05**066931**001	TX 25	50	2"	5,8
05**066946**001	TX 25	70	2 3/4"	5,8
05**066936**001	TX 25	100	4"	5,8
05**066902**001	TX 27	35	1 3/8"	5,8
05**066932**001	TX 27	50	2"	5,8
05**066937**001	TX 27	100	4"	5,8
05**066905**001	TX 30	35	1 3/8"	6,0
05**066933**001	TX 30	50	2"	6,0
05**066947**001	TX 30	70	2 3/4"	6,0
05**066938**001	TX 30	100	4"	6,0
05**066910**001	TX 40	35	1 3/8"	7,0
05**066934**001	TX 40	50	2"	7,0
05**066948**001	TX 40	70	2 3/4"	7,0
05**066939**001	TX 40	100	4"	7,0
05**066915**001	TX 45	35	1 3/8"	-
05**066940**001	TX 45	50	2"	-
05**066949**001	TX 45	70	2 3/4"	-
05**066942**001	TX 45	100	4"	-
05**066920**001	TX 50	35	1 3/8"	-
05**066941**001	TX 50	50	2"	-
05**066950**001	TX 50	70	2 3/4"	-
05**066943**001	TX 50	100	4"	-
05**066925**001	TX 55	35	1 3/8"	12,0
05**136220**001	TX 60	35	1 3/8"	14,0

Bits for TORX® Screws

M 4 Thread drive M 4 direct drive (series 11)

867/11 TORX® bits



Application: TORX® screws
Drive: Thread drive M 4
Design: Tough, for universal use

		mm		mm
05**064140**001	TX 8	33	1 1/4"	6,0
05**064144**001	TX 10	33	1 1/4"	6,0
05**064146**001	TX 15	33	1 1/4"	6,0

M 5 Thread drive M 5 direct drive (series 12)

867/12 TORX® bits



Application: TORX® socket screws
Drive: Thread drive M 5
Design: Tough, for universal use

		mm		mm
05**064148**001	TX 10	45	1 3/4"	6,0
05**064150**001	TX 15	45	1 3/4"	6,0
05**064155**001	TX 20	45	1 3/4"	6,0
05**064160**001	TX 25	45	1 3/4"	6,0

M 6 Thread drive M 6 direct drive (series 15)

867/15 TORX® bits



Application: TORX® screws
Drive: Thread drive M 6
Design: Tough, for universal use

		mm		mm
05**064166**001	TX 10	45	1 3/4"	8,0
05**064168**001	TX 15	45	1 3/4"	8,0
05**064170**001	TX 20	45	1 3/4"	8,0
05**064175**001	TX 25	45	1 3/4"	8,0
05**064180**001	TX 30	45	1 3/4"	8,0

#10/32" Thread drive #10-32 UNF direct drive (series 16)

867/16 TORX® bits



Application: TORX® screws
Drive: Thread drive #10-32 UNF
Design: Tough, for universal use

		mm		mm
05**064185**001	TX 10	45	1 3/4"	6,0
05**064190**001	TX 15	45	1 3/4"	6,0
05**064200**001	TX 20	45	1 3/4"	6,0

Bits for TORX® Screws

4 mm 4 mm Halfmoon direct drive (series 9)

867/9 C TORX® bits, halfmoon



Application: TORX® socket screws
Drive: Halfmoon, 4 mm
Design: Precision hardened for sensitive applications

		mm		mm
05**135220**001	TX 1	44	1 47/64"	1,5
05**135221**001	TX 2	44	1 47/64"	1,5
05**135222**001	TX 3	44	1 47/64"	1,7
05**345352**001	TX 4	44	1 47/64"	1,8
05**345018**001	TX 4	64	2 33/64"	2,0
05**345351**001	TX 5	44	1 47/64"	3,0
05**345032**001	TX 5	64	2 33/64"	2,0
05**314753**001	TX 5	70	2 3/4"	2,0
05**345350**001	TX 6	44	1 47/64"	3,0
05**345056**001	TX 6	64	2 33/64"	2,0
05**332610**001	TX 6	70	2 3/4"	3,0
05**345035**001	TX 7	64	2 33/64"	2,3
05**345026**001	TX 8	44	1 47/64"	3,0
05**345028**001	TX 8	64	2 33/64"	3,0
05**332609**001	TX 8	70	2 3/4"	3,0
05**332607**001	TX 10	70	2 3/4"	3,0

4 mm 4 mm HIOS direct drive (series 21)

867/21 TORX® bits



Application: TORX® socket screws
Drive: HIOS 4 mm
Design: Precision hardened for sensitive applications

		mm		mm	mm	
05**135400**001 [1]	TX 1	40	1 9/16"	1,5	20	25/32"
05**135401**001 [1]	TX 2	40	1 9/16"	1,5	20	25/32"
05**135402**001 [1]	TX 3	40	1 9/16"	1,7	20	25/32"
05**135403**001	TX 4	40	1 9/16"	1,8	20	25/32"
05**135404**001	TX 5	40	1 9/16"	2,0	20	25/32"
05**135405**001	TX 6	40	1 9/16"	2,0	20	25/32"
05**135406**001	TX 7	40	1 9/16"	2,5	20	25/32"
05**135407**001	TX 8	40	1 9/16"	3,0	20	25/32"
05**135408**001	TX 9	40	1 9/16"	3,0	20	25/32"
05**135409**001	TX 10	40	1 9/16"	3,0	20	25/32"

[1] Delivery on request.



5 mm 5 mm HIOS direct drive (series 22)

867/22 TORX® bits



Application: TORX® screws
Drive: HIOS 5 mm
Design: Tough, for universal use

		mm		mm	mm	
05**135420**001	TX 5	60	2 3/8"	2,0	20	25/32"
05**135421**001	TX 6	60	2 3/8"	2,5	20	25/32"
05**135422**001	TX 7	60	2 3/8"	2,5	20	25/32"
05**135423**001	TX 8	60	2 3/8"	3,0	20	25/32"
05**135424**001	TX 9	60	2 3/8"	3,0	20	25/32"
05**135425**001	TX 10	60	2 3/8"	3,0	20	25/32"

Bits for Tamper-proof TORX® BO Screws with safety pin

¼" ¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

867/1 Z TORX® BO bits



Application: TORX® socket screws with safety pin (BO = with bore hole)

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: TORX® with bore hole, tough, for universal use

		mm	
05**066497**001	TX 7	25	1"
05**066498**001	TX 8	25	1"
05**066499**001	TX 9	25	1"
05**066500**001	TX 10	25	1"
05**066505**001	TX 15	25	1"
05**066510**001	TX 20	25	1"
05**066515**001	TX 25	25	1"
05**066520**001	TX 27	25	1"
05**066525**001	TX 30	25	1"
05**066530**001	TX 40	25	1"

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

3867/4 TORX® BO bits with bore hole, stainless



Application: TORX® socket screws with safety pin (BO = with bore hole)

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust

		mm		mm
05**071089**001	TX 10 BO	89	3 $^{1}/_{2}$"	4,0
05**071090**001	TX 15 BO	89	3 $^{1}/_{2}$"	4,0
05**071091**001	TX 20 BO	89	3 $^{1}/_{2}$"	4,5
05**071092**001	TX 25 BO	89	3 $^{1}/_{2}$"	5,5
05**071094**001	TX 30 BO	89	3 $^{1}/_{2}$"	6,0

867/4 Z TORX® BO bits with bore hole



Application: TORX® socket screws with safety pin (BO = with bore hole)

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: TORX® with bore hole, tough, for universal use

		mm		mm
05**060139**001	TX 8	70	2 $^{3}/_{4}$"	3,0
05**060048**001	TX 8	89	3 $^{1}/_{2}$"	3,0
05**060049**001	TX 9	89	3 $^{1}/_{2}$"	3,0
05**060140**001	TX 10	70	2 $^{3}/_{4}$"	4,0
05**060050**001	TX 10	89	3 $^{1}/_{2}$"	4,0
05**060141**001	TX 15	70	2 $^{3}/_{4}$"	4,0
05**060051**001	TX 15	89	3 $^{1}/_{2}$"	4,0
05**060142**001	TX 20	70	2 $^{3}/_{4}$"	4,5
05**060052**001	TX 20	89	3 $^{1}/_{2}$"	4,5
05**060143**001	TX 25	70	2 $^{3}/_{4}$"	6,0
05**060053**001	TX 25	89	3 $^{1}/_{2}$"	6,0
05**060144**001	TX 27	70	2 $^{3}/_{4}$"	6,0
05**060057**001	TX 27	89	3 $^{1}/_{2}$"	6,0
05**060145**001	TX 30	70	2 $^{3}/_{4}$"	6,0
05**060054**001	TX 30	89	3 $^{1}/_{2}$"	6,0
05**060146**001	TX 40	70	2 $^{3}/_{4}$"	-
05**060056**001	TX 40	89	3 $^{1}/_{2}$"	-

Bits for TORX PLUS® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

867/1 IP TORX PLUS® bits



Application: TORX PLUS® socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm	
05**135120**001	1 IP	25	1"
05**135121**001	2 IP	25	1"
05**160956**001	3 IP	25	1"
05**134695**001	4 IP	25	1"
05**066272**001	5 IP	25	1"
05**066274**001	6 IP	25	1"
05**066276**001	7 IP	25	1"
05**066278**001	8 IP	25	1"
05**066279**001	9 IP	25	1"
05**066280**001	10 IP	25	1"
05**066282**001	15 IP	25	1"
05**066284**001	20 IP	25	1"
05**066286**001	25 IP	25	1"
05**066287**001	27 IP	25	1"
05**066288**001	30 IP	25	1"
05**066290**001	40 IP	25	1"

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

867/4 IP TORX PLUS® bits



Application: TORX PLUS® socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**134664**001	1 IP	50	2"	2,0
05**134665**001	2 IP	50	2"	2,0
05**134668**001	3 IP	50	2"	2,0
05**134691**001	4 IP	50	2"	3,0
05**134678**001	5 IP	50	2"	3,0
05**134680**001	6 IP	50	2"	3,0
05**134667**001	6 IP	89	3 1/2"	3,0
05**134690**001	6 IP	152	6"	3,0
05**134681**001	7 IP	50	2"	3,0
05**134679**001	8 IP	50	2"	3,0
05**134670**001	8 IP	89	3 1/2"	3,0
05**134682**001	8 IP	152	6"	3,0
05**160917**001	9 IP	50	2"	3,0
05**134669**001	9 IP	89	3 1/2"	3,0
05**134683**001	10 IP	50	2"	4,0
05**134684**001	10 IP	70	2 3/4"	4,0
05**134671**001	10 IP	89	3 1/2"	4,0
05**134685**001	15 IP	50	2"	4,0
05**134686**001	15 IP	70	2 3/4"	4,0
05**134672**001	15 IP	89	3 1/2"	4,0
05**134687**001	20 IP	50	2"	4,5
05**134688**001	20 IP	70	2 3/4"	4,5
05**134673**001	20 IP	89	3 1/2"	4,5
05**134674**001	25 IP	89	3 1/2"	6,0
05**134675**001	27 IP	89	3 1/2"	6,0
05**320430**001	30 IP	50	2"	6,0
05**134676**001	30 IP	89	3 1/2"	6,0
05**134677**001	40 IP	89	3 1/2"	-

Bits for TORX PLUS® Screws

4 mm 4 mm Halfmoon direct drive (series 9)

867/9 C IP TORX PLUS® bits, halfmoon



Application: TORX PLUS® screws
Drive: Halfmoon, 4 mm
Design: Precision hardened for sensitive applications

		mm		mm	mm	
05**135230**001	1 IP	44	1 47/64"	1,5	20	25/32"
05**135231**001	2 IP	44	1 47/64"	1,5	20	25/32"
05**135232**001	3 IP	44	1 47/64"	1,7	20	25/32"
05**326310**001	4 IP	44	1 47/64"	2,0	20	25/32"
05**345019**001	4 IP	64	2 33/64"	2,0	20	25/32"
05**135233**001	5 IP	44	1 47/64"	2,0	20	25/32"
05**332612**001	5 IP	70	2 3/4"	3,0	20	25/32"
05**344900**001	6 IP	44	1 47/64"	2,25	20	25/32"
05**135234**001	8 IP	44	1 47/64"	3,0	20	25/32"
05**332606**001	8 IP	70	2 3/4"	3,0	20	25/32"
05**135235**001	10 IP	44	1 47/64"	3,0	20	25/32"

4 mm 4 mm HIOS direct drive (series 21)

867/21 IP TORX PLUS® bits



Application: TORX PLUS® screws
Drive: HIOS 4 mm
Design: Precision hardened for sensitive applications

		mm		mm	mm	
05**135430**001 [1]	1 IP	40	1 9/16"	1,5	20	25/32"
05**135431**001 [1]	2 IP	40	1 9/16"	1,5	20	25/32"
05**135432**001 [1]	3 IP	40	1 9/16"	1,7	20	25/32"
05**302402**001	4 IP	40	1 9/16"	1,8	20	25/32"
05**302403**001	5 IP	40	1 9/16"	2,0	20	25/32"
05**302400**001	6 IP	40	1 9/16"	2,0	20	25/32"
05**135433**001	7 IP	40	1 9/16"	2,5	20	25/32"
05**135434**001	8 IP	40	1 9/16"	3,0	20	25/32"
05**135435**001	9 IP	40	1 9/16"	3,0	20	25/32"
05**135436**001	10 IP	40	1 9/16"	3,0	20	25/32"

[1] Delivery on request.


5 mm 5 mm HIOS direct drive (series 22)

867/22 IP TORX PLUS® bits



Application: TORX PLUS® screws
Drive: HIOS 5 mm
Design: Precision hardened for sensitive applications

		mm		mm	mm	
05**135440**001	5 IP	60	2 3/8"	2,0	20	25/32"
05**344280**001	6 IP	60	2 3/8"	2,5	20	25/32"
05**135441**001	7 IP	60	2 3/8"	2,5	20	25/32"
05**134500**001	8 IP	60	2 3/8"	3,0	20	25/32"
05**344281**001	8 IP	80	3 1/8"	3,0	20	25/32"
05**135442**001	9 IP	60	2 3/8"	3,0	20	25/32"
05**135443**001	10 IP	60	2 3/8"	3,0	20	25/32"
05**344282**001	10 IP	80	3 1/8"	3,0	20	25/32"



Bits for Tamper-proof TORX PLUS® IPR Screws

¼" ¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

867/1 IPR TORX PLUS® bits with bore hole





Application: TORX PLUS® IPR socket screws with safety pin

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm	
05**134699**001	8 IPR	25	1"
05**134698**001	9 IPR	25	1"
05**134700**001	10 IPR	25	1"
05**134701**001	15 IPR	25	1"
05**134702**001	20 IPR	25	1"
05**134703**001	25 IPR	25	1"
05**134704**001	27 IPR	25	1"
05**134705**001	30 IPR	25	1"
05**134706**001	40 IPR	35	1 $^{3}/_{8}$"
05**134707**001	45 IPR	35	1 $^{3}/_{8}$"

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

867/4 IPR TORX PLUS® bits with bore hole





Application: TORX PLUS® IPR socket screws with safety pin

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**134600**001 [1]	1 IPR	50	2"	2,0
05**134601**001 [1]	3 IPR	50	2"	2,0
05**134602**001 [1]	5 IPR	50	2"	3,0
05**134603**001 [1]	6 IPR	50	2"	3,0
05**134604**001	8 IPR	50	2"	3,0
05**160821**001	10 IPR	50	2"	4,0
05**134657**001	10 IPR	89	3 $^{1}/_{2}$"	4,0
05**134654**001	15 IPR	50	2"	4,0
05**134720**001	15 IPR	89	3 $^{1}/_{2}$"	4,0
05**204126**001	20 IPR	50	2"	4,5
05**259135**001	20 IPR	89	3 $^{1}/_{2}$"	4,5
05**134655**001	25 IPR	50	2"	6,0
05**134722**001	25 IPR	89	3 $^{1}/_{2}$"	6,0
05**134656**001	27 IPR	50	2"	6,0
05**134658**001	27 IPR	89	3 $^{1}/_{2}$"	6,0
05**134732**001	30 IPR	50	2"	6,0
05**134723**001	30 IPR	89	3 $^{1}/_{2}$"	6,0

[1] Without bore hole

4 mm 4 mm Halfmoon direct drive (series 9)

867/9 IPR TORX PLUS® bits



Application: TORX PLUS® IPR socket screws

Drive: Halfmoon, 4 mm

Design: Tough, for universal use

		mm		mm
05**200495**001	1 IPR	44	1 $^{47}/_{64}$"	1,5
05**060380**001	1 IPR	44	1 $^{47}/_{64}$"	1,8
05**135226**001	1 IPR	64	2 $^{33}/_{64}$"	1,5
05**135228**001	3 IPR	44	1 $^{47}/_{64}$"	1,8
05**135229**001	3 IPR	64	2 $^{33}/_{64}$"	1,8

Bits for Tamper-proof TORX PLUS® IPR Screws

4 mm 4 mm HIOS direct drive (series 21)

867/21 IPR TORX PLUS® bits



Application: TORX PLUS® IPR socket screws

Drive: HIOS 4 mm

Design: Tough, for universal use

		mm		mm
05**300025**001	1 IPR	40	1 37/64"	1,8
05**300037**001	1 IPR	60	2 3/8"	1,8

Bits for ASSY® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

864/1 BTZ SIT bits



Application: ASSY® screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use

		mm	
05**066040**001	SIT 10	25	1"
05**066041**001	SIT 20	25	1"
05**066042**001	SIT 25	25	1"
05**066043**001	SIT 30	25	1"

864/1 Z SIT bits



Application: ASSY® screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm	
05**066030**001	SIT 10	25	1"
05**066031**001	SIT 20	25	1"
05**066032**001	SIT 25	25	1"
05**066033**001	SIT 30	25	1"

Bits for Slotted Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

3800/1 TS bits for slotted screws, stainless




Application: Slotted screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Stainless steel for minimising rust, special torsion-style design to reduce premature wear. Take it easy toolfinder: Output colour coding (yellow = slotted) and large stamp to enable the desired bit to be easily located.

	mm	mm	mm	
05**071000**001	0,8	5,5	25	1"
05**071001**001	1,0	5,5	25	1"
05**071002**001	1,2	6,5	25	1"

800/1 BTZ bits



Application: Slotted screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (yellow = slotted) and large stamp to enable the desired bit to be easily located.

	mm	mm	mm	
05**056064**001	0,8	5,5	25	1"
05**056066**001	1,0	5,5	25	1"
05**056068**001	1,2	6,5	25	1"

800/1 BDC bits




Application: Slotted screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, diamond-coated for secure screw fit. Take it easy toolfinder: Output colour coding (yellow = slotted) and large stamp to enable the desired bit to be easily located.

	mm	mm	mm	
05**056172**001	0,8	5,5	25	1"
05**056174**001	1,0	5,5	25	1"
05**056176**001	1,2	6,5	25	1"

800/1 TZ bits



Application: Slotted screws

Drive: $^1/_4$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Torsion-style design to reduce premature wear, tough, for universal use

	mm	mm	mm		∅ mm
05**056203**001	0,5	4,0	25	1"	4,0
05**056210**001	0,6	4,5	25	1"	4,5
05**056220**001	0,8	5,5	25	1"	5,5
05**056225**001	1,0	5,5	25	1"	5,5
05**056233**001	1,2	6,5	25	1"	6,2
05**056240**001	1,6	8,0	25	1"	8,0

800/1 Z bits



Application: Slotted screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

	mm	mm	mm		∅ mm
05**056200**001	0,5	3,0	25	1"	3,0
05**056005**001	0,5	3,0	39	1 $^{17}/_{32}$"	3,0
05**072050**001	0,5	4,0	25	1"	4,0
05**056007**001	0,5	4,0	39	1 $^{17}/_{32}$"	4,0
05**056010**001	0,6	3,5	39	1 $^{17}/_{32}$"	3,5
05**072055**001	0,6	4,5	25	1"	4,5
05**056015**001	0,6	4,5	39	1 $^{17}/_{32}$"	4,5
05**072057**001	0,8	5,5	25	1"	5,5
05**056020**001	0,8	4,0	39	1 $^{17}/_{32}$"	4,0
05**056025**001	0,8	5,5	39	1 $^{17}/_{32}$"	5,5
05**072059**001	1,0	5,5	25	1"	5,5
05**056030**001	1,0	5,5	39	1 $^{17}/_{32}$"	5,5
05**072061**001	1,2	6,5	25	1"	6,2
05**072063**001	1,2	8,0	25	1"	8,0
05**056037**001	1,2	6,5	39	1 $^{17}/_{32}$"	6,5
05**056040**001	1,2	8,0	39	1 $^{17}/_{32}$"	8,0
05**072065**001	1,6	8,0	25	1"	8,0
05**056045**001	1,6	8,0	39	1 $^{17}/_{32}$"	8,0

800/1 Z Set SB

		4013288
05**073300**001	1 x 0.6x4.5x25; 1 x 0.8x5.5x25	029010
05**073301**001	1 x 1.0x5.5x25; 1 x 1.2x6.5x25	029027
05**073302**001	1 x 0.6x4.5x25; 1 x 1.0x5.5x25; 1 x 1.2x6.5x25	029034





800/1 Z Set D


		4013288
05**073303**001	1 x 1.0x5.5x25	029041
	1 x PH 2x25	
	1 x PZ 2x25	



Tip

EDELSTAHL Rostfrei INOX STAINLESS


Stainless Steel Bits



Wera stainless steel bits are manufactured out of stainless steel so unsightly rust can be avoided. The stainless steel bits from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

BITORSION DIAMOND


BDC-Bits



BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally "bite" themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.

Bits for Slotted Screws

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

3800/4 Bits for slotted screws, stainless



Application: Slotted screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust

	mm	mm	mm	
05**071080**001	1,0	5,5	89	3 1/2"

800/4 Z bits



Application: Slotted screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

	mm	mm	mm		∅ mm
05**059305**001	0,5	3,0	50	2"	3,0
05**059466**001	0,5	3,0	70	2 3/4"	3,0
05**059307**001	0,5	4,0	50	2"	4,0
05**059310**001	0,6	3,5	50	2"	3,5
05**059472**001	0,6	3,5	70	2 3/4"	3,5
05**059450**001	0,6	3,5	152	6"	3,5
05**059315**001	0,6	4,5	50	2"	4,5
05**059489**001	0,6	4,5	89	3 1/2"	4,5
05**059320**001	0,8	4,0	50	2"	4,0
05**059478**001	0,8	4,0	70	2 3/4"	4,0
05**059480**001	0,8	4,0	89	3 1/2"	4,0
05**059451**001	0,8	4,0	152	6"	4,0
05**059325**001	0,8	5,5	50	2"	5,5
05**059330**001	1,0	5,5	50	2"	5,5
05**059486**001	1,0	5,5	70	2 3/4"	5,5
05**059488**001	1,0	5,5	89	3 1/2"	5,5
05**059452**001	1,0	5,5	152	6"	5,5
05**059335**001	1,0	6,0	50	2"	6,0
05**059337**001	1,2	6,5	50	2"	6,2
05**059492**001	1,2	6,5	70	2 3/4"	6,2
05**059490**001	1,2	6,5	89	3 1/2"	6,2
05**059453**001	1,2	6,5	152	6"	6,2
05**059340**001	1,2	8,0	50	2"	8,0
05**059496**001	1,2	8,0	89	3 1/2"	8,0
05**059345**001	1,6	8,0	50	2"	8,0
05**059500**001	1,6	8,0	89	3 1/2"	8,0

5/16" 5/16" hexagon drive, suitable for D 8 bit holders or direct drive (series 2)

800/2 Z bits



Application: Slotted screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-D 8 bit holders

Design: Tough, for universal use

	mm	mm	mm		mm
05**057210**001	0,8	5,5	41	1 19/32"	5,5
05**057213**001	1,0	5,5	41	1 19/32"	5,5
05**057223**001	1,2	6,5	41	1 19/32"	6,5
05**057225**001	1,2	8,0	41	1 19/32"	7,8
05**057230**001	1,6	8,0	41	1 19/32"	7,8
05**057235**001	1,6	10,0	41	1 19/32"	7,8
05**057240**001	2,0	12,0	41	1 19/32"	12,0
05**057250**001	2,5	14,0	41	1 19/32"	14,0
05**057255**001	2,5	16,0	41	1 19/32"	16,0

4 mm 4 mm Halfmoon direct drive (series 9)

800/9 C bits



Application: Slotted screws
Drive: Halfmoon, 4 mm
Design: Hard

	mm	mm	mm		mm
05**135265**001	0,23	1,5	44	1 47/64"	1,5
05**135264**001	0,35	2,5	44	1 47/64"	2,5
05**135266**001	0,40	2,0	44	1 47/64"	2,0
05**135267**001	0,50	3,0	44	1 47/64"	3,0

Guide Sleeves

807/4 Z bits



Application: Slotted screws with integrated guide sleeve

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

	mm	mm	mm		mm
05**059503**001	0,8	4,0	90	3 1/2"	10
05**059507**001	1,0	5,5	90	3 1/2"	11
05**059515**001	1,2	8,0	90	3 1/2"	13
05**059517**001	1,6	8,0	90	3 1/2"	13

Bits for Hexagon Socket Screws

¼" ¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

840/1 IMP DC Impaktor bits



Application: Hexagon socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (blue = hexagon) and large stamp to enable the desired bit to be easily located.

	mm	mm	
05**057603**001	3,0	25	1"
05**057604**001	4,0	25	1"
05**057605**001	5,0	25	1"
05**057606**001	6,0	25	1"

840/1 IMP DC Impaktor bits SB



		4013288
05**073904**001	1 x 4.0x25	158338
05**073905**001	1 x 5.0x25	158345
05**073906**001	1 x 6.0x25	158352

3840/1 TS bits, stainless



Application: Hexagon socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Hex-Plus, stainless steel for minimising rust, special torsion-style design to reduce premature wear. Take it easy toolfinder: Output colour coding (blue = hexagon) and large stamp to enable the desired bit to be easily located.

	mm		mm	
05**071070**001	1,5		25	1"
05**071071**001	2,0		25	1"
05**071072**001	2,5		25	1"
05**071073**001	3,0		25	1"
05**071074**001	4,0		25	1"
05**071075**001	5,0		25	1"
05**071077**001	5,5		25	1"
05**071076**001	6,0		25	1"
05**071060**001		$^{3}/_{32}$"	25	1"
05**071061**001		$^{7}/_{64}$"	25	1"
05**071062**001		$^{1}/_{8}$"	25	1"
05**071063**001		$^{9}/_{64}$"	25	1"
05**071064**001		$^{5}/_{32}$"	25	1"
05**071065**001		$^{3}/_{16}$"	25	1"
05**071066**001		$^{1}/_{4}$"	25	1"

840/1 BTZ bits



Application: Hexagon socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Hex-Plus, BiTorsion for long service life, extra-tough, for universal use. Take it easy toolfinder: Output colour coding (blue = hexagon) and large stamp to enable the desired bit to be easily located.

	mm	mm	
05**056680**001	1,5	25	1"
05**056681**001	2,0	25	1"
05**056682**001	2,5	25	1"
05**056683**001	3,0	25	1"
05**056684**001	4,0	25	1"
05**056685**001	5,0	25	1"
05**056686**001	5,5	25	1"
05**056687**001	6,0	25	1"

840/1 Z bits



Application: Hexagon socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Hex-Plus, tough, for universal use

	mm		mm	
05**056303**001	1,5		25	1"
05**056305**001	2,0		25	1"
05**056310**001	2,5		25	1"
05**056315**001	3,0		25	1"
05**056320**001	4,0		25	1"
05**056325**001	5,0		25	1"
05**056330**001	6,0		25	1"
05**056332**001	7,0		25	1"
05**056335**001	8,0		25	1"
05**056340**001	10,0		25	1"
05**135060**001		0,05"	25	1"
05**135070**001		1/16"	25	1"
05**135071**001		5/64"	25	1"
05**135072**001		3/32"	25	1"
05**135078**001		7/64"	25	1"
05**135073**001		1/8"	25	1"
05**135069**001		9/64"	25	1"
05**135074**001		5/32"	25	1"
05**135075**001		3/16"	25	1"
05**135079**001		7/32"	25	1"
05**135076**001		1/4"	25	1"
05**135077**001		5/16"	25	1"
05**135068**001		3/8"	25	1"

840/1 Z Set SB

		4013288
05**073342**001	1 x 2.0x25; 1 x 2.5x25; 1 x 3.0x25	029607
05**073344**001	1 x 4.0x25; 1 x 5.0x25; 1 x 6.0x25	029614



842/1 Z bits



Application: Hexagon socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Ball end, tough, for universal use

	mm		mm	
05**056350**001	2,5		25	1"
05**056352**001	3,0		25	1"
05**056354**001	4,0		25	1"
05**056356**001	5,0		25	1"
05**056358**001	6,0		25	1"
05**380103**001		3/32"	25	1"
05**380104**001		7/64"	25	1"
05**380105**001		1/8"	25	1"
05**380106**001		9/64"	25	1"
05**380107**001		5/32"	25	1"
05**380108**001		3/16"	25	1"
05**380109**001		7/32"	25	1"
05**380110**001		1/4"	25	1"

Bits for Hexagon Socket Screws

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

840/4 IMP DC Impaktor bits





Application: Hexagon socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance. Take it easy toolfinder: Output colour coding (blue = hexagon) and large stamp to enable the desired bit to be easily located.

	mm	mm	
05**057644**001	4,0	50	2"
05**057645**001	5,0	50	2"
05**057646**001	6,0	50	2"

840/4 IMP DC Impaktor bits SB

		4013288
05**073944**001	1 x 4.0x50	158451
05**073945**001	1 x 5.0x50	158468
05**073946**001	1 x 6.0x50	158475



3840/4 Bits, stainless



Application: Hexagon socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust

	mm		mm	
05**071101**001	3,0		89	3 $^{1}/_{2}$"
05**071102**001	4,0		89	3 $^{1}/_{2}$"
05**071103**001	5,0		89	3 $^{1}/_{2}$"
05**071049**001	5,5		50	2"
05**071104**001	6,0		89	3 $^{1}/_{2}$"
05**071105**001		$^{3}/_{32}$"	89	3 $^{1}/_{2}$"
05**071106**001		$^{1}/_{8}$"	89	3 $^{1}/_{2}$"
05**071107**001		$^{5}/_{32}$"	89	3 $^{1}/_{2}$"
05**071108**001		$^{3}/_{16}$"	89	3 $^{1}/_{2}$"

840/4 Z bits



Application: Hexagon socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Hex-Plus, tough, for universal use

	mm		mm		mm
05**160885**001	0,9		50	2"	2,6
05**059602**001	1,5		50	2"	2,0
05**059603**001	2,0		50	2"	4,0
05**059628**001	2,0		89	3 1/2"	4,0
05**059604**001	2,5		50	2"	4,0
05**059629**001	2,5		89	3 1/2"	4,0
05**059605**001	3,0		50	2"	4,0
05**059630**001	3,0		89	3 1/2"	4,0
05**380033**001	3,0		152	6"	4,0
05**059610**001	4,0		50	2"	5,0
05**059631**001	4,0		89	3 1/2"	5,0
05**059634**001	4,0		152	6"	5,0
05**059615**001	5,0		50	2"	6,0
05**059632**001	5,0		89	3 1/2"	6,0
05**059635**001	5,0		152	6"	6,0
05**059620**001	6,0		50	2"	5,0
05**059633**001	6,0		89	3 1/2"	-
05**059636**001	6,0		152	6"	-
05**059625**001	8,0		50	2"	-
05**350430**001		0,05"	50	2"	2,5
05**135090**001		1/16"	50	2"	2,5
05**380045**001		1/8"	152	6"	4,0
05**135091**001		5/64"	50	2"	3,0
05**059660**001		5/64"	89	3 1/2"	3,0
05**135092**001		3/32"	50	2"	3,0
05**059661**001		3/32"	89	3 1/2"	3,5
05**135093**001		7/64"	50	2"	3,5
05**059662**001		7/64"	89	3 1/2"	4,0
05**135094**001		1/8"	50	2"	4,0
05**059663**001		1/8"	89	3 1/2"	4,0
05**135095**001		9/64"	50	2"	4,5
05**059664**001		9/64"	89	3 1/2"	4,5
05**380046**001		9/64"	152	6"	4,5
05**135096**001		5/32"	50	2"	5,0
05**059665**001		5/32"	89	3 1/2"	5,0
05**380047**001		5/32"	152	6"	5,0
05**135097**001		3/16"	50	2"	6,0
05**059666**001		3/16"	89	3 1/2"	6,0
05**380048**001		3/16"	152	6"	6,0
05**135098**001		7/32"	50	2"	-
05**059667**001		7/32"	89	3 1/2"	-
05**380049**001		7/32"	152	6"	-
05**135099**001		1/4"	50	2"	-
05**059668**001		1/4"	89	3 1/2"	-
05**380050**001		1/4"	152	6"	-
05**346288**001		5/16"	50	2"	-

Tip

IMPACT PROOF

Impaktor-Bits



Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.

HEX-PLUS


Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

TAKE IT EASY TOOL FINDER

"Take it easy"



"Take it easy" tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.

Bits for Hexagon Socket Screws

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

842/4 Bits





Application: Hexagon socket screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Ball end, tough, for universal use

	mm		mm	
05**059680**001	3,0		89	3 $^{1}/_{2}$"
05**059681**001	4,0		89	3 $^{1}/_{2}$"
05**059682**001	5,0		89	3 $^{1}/_{2}$"
05**059683**001	6,0		89	3 $^{1}/_{2}$"
05**380124**001		$^{3}/_{32}$"	89	3 $^{1}/_{2}$"
05**380125**001		$^{7}/_{64}$"	89	3 $^{1}/_{2}$"
05**380126**001		$^{1}/_{8}$"	89	3 $^{1}/_{2}$"
05**380127**001		$^{9}/_{64}$"	89	3 $^{1}/_{2}$"
05**380128**001		$^{5}/_{32}$"	89	3 $^{1}/_{2}$"
05**380129**001		$^{3}/_{16}$"	89	3 $^{1}/_{2}$"
05**380130**001		$^{7}/_{32}$"	89	3 $^{1}/_{2}$"
05**380131**001		$^{1}/_{4}$"	89	3 $^{1}/_{2}$"

Tip

5/16" hexagon drive, suitable for D 8 bit holders or direct drive (series 2)

840/2 Z Bits



Application: Hexagon socket screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-D 8 bit holders

Design: Hex-Plus, tough, for universal use

	mm		mm	
05**057505**001	3		30	1 3/16"
05**057510**001	4		30	1 3/16"
05**057550**001	4		50	2"
05**057560**001	4		70	2"
05**057570**001	4		100	4"
05**057515**001	5		30	1 3/16"
05**057551**001	5		50	2"
05**057561**001	5		70	2 3/4"
05**057571**001	5		100	4"
05**057520**001	6		30	1 3/16"
05**057552**001	6		50	2"
05**057562**001	6		70	2 3/4"
05**057572**001	6		100	4"
05**057553**001	7		50	2"
05**057573**001	7		100	4"
05**057525**001	8		30	1 3/16"
05**057554**001	8		50	2"
05**057563**001	8		70	2 3/4"
05**057574**001	8		100	4"
05**057530**001	10		30	1 3/16"
05**057555**001	10		50	2"
05**057575**001	10		100	4"
05**221102**001		5/32"	30	1 3/16"
05**057565**001		5/32"	70	2 3/4"
05**135083**001		3/16"	30	1 3/16"
05**135084**001		7/32"	30	1 3/16"
05**057566**001		7/32"	70	2 3/4"
05**135080**001		1/4"	30	1 3/16"
05**057567**001		1/4"	70	2 3/4"
05**135081**001		5/16"	30	1 3/16"
05**057568**001		5/16"	70	2 3/4"
05**135082**001		3/8"	30	1 3/16"

BALL END

Hexagon ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screw-driving jobs.

Bits for Hexagon Socket Screws

4 mm 4 mm Halfmoon direct drive (series 9)

840/9 C bits Hex-Plus



Application: Hexagon socket screws

Drive: Halfmoon, 4 mm

Design: Hard

	mm	mm		mm
05**135268**001	1,5	44	1 47/64"	2,6
05**135269**001	2,0	44	1 47/64"	2,6

Bits for Tamper-Proof Hexagon Socket Screws with safety pin

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

840/1 Z Tamper-proof Hex-Plus BO bits



Application: Hexagon socket screws with safety pin (BO = with bore hole)

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Hex-Plus with bore hole, tough, for universal use

	mm	mm	
05**056341**001	2,0	25	1"
05**056342**001	2,5	25	1"
05**056343**001	3,0	25	1"
05**056344**001	4,0	25	1"
05**056345**001	5,0	25	1"
05**056346**001	6,0	25	1"

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

840/4 Z Tamper-proof Hex-Plus BO bits



Application: Hexagon socket screws with safety pin (BO = with bore hole)

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Hex-Plus with bore hole, tough, for universal use

	mm	mm		∅ mm
05**059640**001	2,0	89	3 1/2"	4,0
05**059641**001	2,5	89	3 1/2"	4,0
05**059642**001	3,0	89	3 1/2"	4,0
05**059643**001	4,0	89	3 1/2"	5,0
05**059644**001	5,0	89	3 1/2"	6,0
05**059645**001	6,0	89	3 1/2"	-

Bits for Square Socket Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

868/1 IMP DC Impaktor Square-Plus bits



Application: Square socket head screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance


		mm	
05**057631**001	# 2	25	1"
05**057632**001	# 3	25	1"

868/1 IMP DC SB Impaktor Square-Plus bits

		4013288
05**073931**001	1 x # 2x25	158437
05**073932**001	1 x # 3x25	158444



3868/1 TS Square-Plus bits, stainless



Application: Square socket head screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Stainless steel for minimising rust, special torsion-style design to reduce premature wear

		mm	
05**071025**001	# 2	25	1"

868/1 BTZ Square-Plus bits



Application: Square socket head screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use

		mm		mm
05**066445**001	# 1	25	1"	4,2
05**066446**001	# 2	25	1"	4,2
05**066447**001	# 3	25	1"	5,5

868/1 Z Square-Plus bits



Application: Square socket head screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**066395**001	# 00	25	1"	3,5
05**066400**001	# 0	25	1"	3,5
05**066405**001	# 1	25	1"	4,5
05**066410**001	# 2	25	1"	6,0
05**066415**001	# 3	25	1"	6,0
05**066420**001	# 4	25	1"	8,0

868/1 V Square-Plus bits



Application: Square socket head screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use, with holding function

		mm		mm
05**340245**001	# 1	25	1"	6,1
05**066394**001	# 2	25	1"	6,1
05**066396**001	# 3	25	1"	6,1

Bit-Box 20 V Robertson

		4013288
05**057790**001	**868/1 V** 20 x # 2x25	188083



Tip


IMPACT PROOF

Impaktor-Bits



For an above-average service life. Maximum utilisation of the material properties, a very special geometry – designed particularly to meet the extreme demands – as well a specific manufacturing process mean that Wera Impaktor tools have an above-average service life. Another product advantage is the coating of the Impaktor bits with minute diamond particles. These diamond particles reduce the cam-out effects – particularly high in power tool applications – which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.

V bits: Holding function for Robertson screws



V bits have a conical profile. The clamping forces thus resulting hold Robertson screws securely on the tip of the tool. Ideal for screwdriving at difficult-to-access places.

Bit-Box



The slide switch allows a simple and gradual removal and reinsertion of the bits. The transparent reverse side means that it is easy to know how many bits are still in the box.

Bits for Square Socket Screws

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

868/4 IMP DC Impaktor Square-Plus bits



Application: Square socket head screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry, particularly suitable for use with conventional impact drivers, the rough diamond coating reduces the danger of any slipping out of the screw head due to the enhanced frictional resistance

		mm	
05**057671**001	# 2	50	2"
05**057672**001	# 3	50	2"

868/4 IMP DC SB Impaktor Square-Plus bits

		4013288
05**073971**001	1 x # 2x50	158550
05**073972**001	1 x # 3x50	158567



3868/4 Square-Plus bits, stainless



Application: Square socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Stainless steel for minimising rust

		mm		mm
05**071097**001	# 1	89	3 1/2"	4,5
05**071098**001	# 2	89	3 1/2"	5,0
05**071099**001	# 3	89	3 1/2"	5,5

868/4 BTZ Square-Plus bits



Application: Square socket head screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: BiTorsion for long service life, extra-tough, for universal use

		mm		mm
05**060147**001	#1	50	2"	4,2
05**060148**001	#2	50	2"	4,2
05**060149**001	#3	50	2"	5,5

Tip

868/4 Square-Plus bits



Application: Square socket head screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**060150**001	# 00	50	2"	3,5
05**060155**001	# 0	50	2"	3,5
05**060160**001	# 1	50	2"	4,5
05**060180**001	# 1	70	2 3/4"	4,5
05**134800**001	# 1	89	3 1/2"	4,5
05**134805**001	# 1	152	6"	4,5
05**060165**001	# 2	50	2"	6,0
05**060182**001	# 2	70	2 3/4"	6,0
05**134801**001	# 2	89	3 1/2"	6,0
05**134806**001	# 2	152	6"	6,0
05**060170**001	# 3	50	2"	6,0
05**060184**001	# 3	70	2 3/4"	6,0
05**134802**001	# 3	89	3 1/2"	6,0
05**134807**001	# 3	152	6"	6,0
05**060175**001	# 4	50	2"	8,0

868/4 V Square-Plus bits



Application: Square socket head screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use, with holding function

		mm		mm
05**060300**001	# 1	50	2"	4,5
05**060297**001	# 1	89	3 1/2"	4,5
05**060301**001	# 2	50	2"	6,0
05**060302**001	# 2	70	2 3/4"	6,0
05**060303**001	# 2	89	3 1/2"	6,0
05**060304**001	# 2	152	6"	6,0
05**060296**001	# 3	50	2"	6,0
05**060298**001	# 3	89	3 1/2"	6,0

BTZ-Bits




BTZ-Bits have an additional tempered BiTorsion zone, which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits.

Stainless Steel Bits



Wera stainless steel bits are manufactured out of stainless steel so unsightly rust can be avoided. The stainless steel bits from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

V bits: Holding function for Robertson screws



V bits have a conical profile. The clamping forces thus resulting hold Robertson screws securely on the tip of the tool. Ideal for screwdriving at difficult-to-access places.

Bits for TORQ-SET® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

871/1 DC TORQ-SET® Mplus bits



Application: TORQ-SET® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Mplus for higher breaking torque and longer service life, diamond-coated for secure screw fit

	mm		mm		mm
05**066638**001	4		25	1"	4,7
05**066640**001	6		25	1"	4,7
05**066642**001	8		25	1"	6,0
05**066644**001	10		25	1"	6,0
05**066646**001		1/4"	32	1 1/4"	11,0

871/1 TORQ-SET® Mplus bits, 25 mm



Application: TORQ-SET® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Mplus for higher breaking torque and longer service life, tough, for universal use

	mm		mm		mm
05**066618**001	0		25	1"	4,7
05**066619**001	1		25	1"	4,7
05**066620**001	2		25	1"	4,7
05**066622**001	3		25	1"	4,7
05**066624**001	4		25	1"	4,7
05**066626**001	5		25	1"	4,7
05**066628**001	6		25	1"	4,7
05**066630**001	8		25	1"	6,0
05**066632**001	10		25	1"	6,0
05**066633**001		1/4"	25	1"	6,0

871/1 TORQ-SET® Mplus bits, 32 mm



Application: TORQ-SET® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Mplus for higher breaking torque and longer service life, tough, for universal use

		mm		mm
05**066634**001	1/4"	32	1 1/4"	11,0
05**066635**001	5/16"	32	1 1/4"	11,0

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

871/4 DC TORQ-SET® Mplus bits



Application: TORQ-SET® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Mplus for higher breaking torque and longer service life, diamond-coated for secure screw fit

	mm		mm	
05**324901**001	2		50	2"
05**066688**001	4		50	2"
05**066690**001	6		50	2"
05**066692**001	8		50	2"
05**066694**001	10		50	2"
05**066696**001		1/4"	50	2"
05**344515**001		5/16"	50	2"

871/4 TORQ-SET® Mplus bits



Application: TORQ-SET® screws


Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Mplus for higher breaking torque and longer service life

	mm		mm	
05**066660**001	2		50	2"
05**066683**001	2		89	3 1/2"
05**066662**001	3		50	2"
05**066684**001	3		89	3 1/2"
05**066664**001	4		50	2"
05**066685**001	4		89	3 1/2"
05**066666**001	5		50	2"
05**066668**001	6		50	2"
05**066676**001	6		70	2 3/4"
05**066686**001	6		89	3 1/2"
05**066670**001	8		50	2"
05**066678**001	8		70	2 3/4"
05**066687**001	8		89	3 1/2"
05**066672**001	10		50	2"
05**066680**001	10		70	2 3/4"
05**066682**001	10		89	3 1/2"
05**066674**001		1/4"	50	2"
05**221110**001		5/16"	50	2"

Tip

TORQ-SET® Mplus



Wera developed the Mplus profile with stronger flanks compared with tools with a conventional TORQ-SET® profile. This results in approximately 70 % extra torsional strength and greatly extends the service life of Wera Mplus tools.

DIAMOND

Bits with diamond coating



The diamond coating of the DC bits lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head.

Bits for TORQ-SET® Screws

5/16" hexagon drive, suitable for D 8 bit holders or direct drive (series 2)

871/2 TORQ-SET® Mplus bits



Application: TORQ-SET® screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-D 8 bit holders

Design: Mplus for higher breaking torque and longer service life, tough, for universal use

	mm		mm	
05**066650**001	8		32	1 1/4"
05**066652**001	10		32	1 1/4"
05**066654**001		1/4"	32	1 1/4"
05**066656**001		5/16"	32	1 1/4"
05**066658**001		3/8"	32	1 1/4"

7/16" hexagon drive, suitable for F 11,2 bit holders or direct drive (series 7)

871/7 TORQ-SET® Mplus bits



Application: TORQ-SET® screws

Drive: 7/16" hexagon, suitable for power tools with DIN ISO 1173-F 11,2 chuck

Design: Mplus for higher breaking torque and longer service life

		mm		mm
05**066740**001	1/4"	35	1 3/8"	11,0
05**066742**001	5/16"	35	1 3/8"	11,0
05**066744**001	3/8"	35	1 3/8"	11,0
05**066746**001	7/16"	35	1 3/8"	11,0

5/16" hexagon drive, suitable for F 8 bit holders or direct drive (series 6)

871/6 TORQ-SET® Mplus bits



Application: TORQ-SET® screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-F 8 bit holders

Design: Mplus for higher breaking torque and longer service life

	mm		mm		mm
05**066700**001	8		35	1 3/8"	6,0
05**066702**001	10		35	1 3/8"	6,0
05**066704**001		1/4"	35	1 3/8"	11,0

5/8" direct drive hexagon (series 19)

871/19 TORQ-SET® Mplus bits



Application: TORQ-SET® screws

Drive: 5/8" hexagon


Design: Mplus for higher breaking torque and longer service life

		mm	
05**066750**001	1/2"	40	1 9/16"
05**066752**001	9/16"	40	1 9/16"
05**066754**001	5/8"	40	1 9/16"

Bits for TRI-WING® Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

875/1 TRI-WING® bits, 25 mm



Application: TRI-WING® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**066758**001	0	25	1"	4,7
05**066760**001	1	25	1"	4,7
05**066762**001	2	25	1"	4,7
05**066764**001	3	25	1"	4,7
05**066766**001	4	25	1"	6,2
05**066768**001	5	25	1"	6,2

875/1 TRI-WING® bits, 32 mm



Application: TRI-WING® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**066770**001	6	32	1 1/4"	11,0
05**066772**001	7	32	1 1/4"	11,0
05**066774**001	8	32	1 1/4"	12,5

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

875/4 TRI-WING® bits



Application: TRI-WING® screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm	
05**066785**001	1	89	3 1/2"
05**066786**001	2	89	3 1/2"
05**066787**001	3	89	3 1/2"
05**066780**001	4	50	2"
05**066788**001	4	89	3 1/2"
05**066782**001	5	50	2"
05**066784**001	6	50	2"

5/16" hexagon drive, suitable for F 8 bit holders or direct drive (series 6)

875/6 TRI-WING® bits



Application: TRI-WING® screws

Drive: 5/16" hexagon, suitable for DIN ISO 1173-F 8 bit holders

Design: Tough, for universal use

		mm		mm
05**066790**001	6	35	1 3/8"	11,0
05**066792**001	7	35	1 3/8"	11,0
05**066794**001	8	35	1 3/8"	12,5

Bits for Multi-Point Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

860/1 XZN Multi-point bits



Application: Multi-point socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**066150**001	M 4	25	1"	4,17
05**066155**001	M 5	25	1"	5,14
05**066160**001	M 6	25	1"	-
05**066165**001	M 8	25	1"	8,0
05**066170**001	M 10	25	1"	10,0

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

860/4 XZN Multi-point bits



Application: Multi-point socket screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**066175**001	M 4	50	2"	4,17
05**066180**001	M 5	50	2"	5,14
05**066185**001	M 6	50	2"	-
05**066190**001	M 8	50	2"	8,0
05**066195**001	M 10	50	2"	10,0
05**066200**001	M 12	50	2"	12,0

Bits for Hi-TORQUE Screws

¼" ¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

800/1 HTN Hi-TORQUE bits



Application: Hi-TORQUE screws

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

		mm	
05**055950**001	1	32	1 $^{1}/_{4}$"
05**055951**001	2	32	1 $^{1}/_{4}$"
05**055952**001	3	32	1 $^{1}/_{4}$"
05**055953**001	4	32	1 $^{1}/_{4}$"

700 A HTS Hi-TORQUE bits



Application: For Hi-TORQUE screws

Drive: $^{1}/_{4}$"-square drive socket

		mm	
05**040030**001	0	25	1"
05**040031**001	1	25	1"
05**040032**001	2	25	1"
05**040033**001	3	25	1"
05**040034**001	4	25	1"

700 B HTS Hi-TORQUE bits



Application: For Hi-TORQUE screws

Drive: $^{3}/_{8}$"-square drive socket

		mm	
05**040040**001	3	25	1"
05**040041**001	4	25	1"
05**040042**001	5	32	1 $^{1}/_{4}$"
05**040043**001	6	32	1 $^{1}/_{4}$"

700 C HTS Hi-TORQUE bits



Application: For Hi-TORQUE screws


Drive: $^{1}/_{2}$"-square drive socket

		mm	
05**040045**001	7	42	1 $^{5}/_{8}$"
05**040046**001	8	42	1 $^{5}/_{8}$"
05**040047**001	9	42	1 $^{5}/_{8}$"
05**040048**001	10	42	1 $^{5}/_{8}$"
05**040049**001	12	60	2 $^{3}/_{8}$"

Bits for Microstix® Screws

4 mm 4 mm Halfmoon direct drive (series 9)

872/9 bits for Microstix® screws




Application: Microstix® socket screws
Drive: Halfmoon, 4 mm
Design: Precision hardened for sensitive applications

		mm	mm	
05**066850**001	m	44	2,0	1 47/64"
05**066851**001	00	44	2,0	1 47/64"
05**066852**001	F	44	2,0	1 47/64"
05**066853**001	0	44	2,0	1 47/64"
05**066854**001	1	44	2,0	1 47/64"

4 mm 4 mm HIOS direct drive (series 21)

872/21 bits for Microstix® screws



Application: Microstix® socket screws
Drive: HIOS 4 mm
Design: Precision hardened for sensitive applications

		mm	mm	
05**066860**001	m	40	2,0	1 9/16"
05**066861**001	00	40	2,0	1 9/16"
05**066862**001	F	40	2,0	1 9/16"
05**066863**001	0	40	2,0	1 9/16"
05**066864**001	1	40	2,0	1 9/16"



Bits for Spanner Screws

¼" hexagon drive, suitable for D 6,3 bit holders (series 1)

857/1 Z Spanner bits



Application: Spanner screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**057150**001	4	25	1"	3,18
05**057151**001	6	25	1"	4,32
05**057152**001	8	25	1"	5,21
05**057153**001	10	25	1"	6,10

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

857/4 Z Spanner bits



Application: Spanner screws

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Tough, for universal use

		mm		mm
05**057160**001	4	89	3 1/2"	3,18
05**057161**001	6	89	3 1/2"	4,32
05**057162**001	8	89	3 1/2"	5,21
05**057163**001	10	89	3 1/2"	6,10

Nutsetters

¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

3869/4 Nutsetters, stainless



Application: Hexagon headed bolts, screws and nuts

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Non-magnetic, retaining spring, stainless steel for minimising rust

	mm		mm	mm
05**071222**001	7,0		50,0	12,5
05**071223**001	8,0		50,0	14,0
05**071224**001	10,0		50,0	16,0
05**071225**001	13,0		50,0	19,5
05**071228**001		$^{3}/_{8}$"	50,0	16,0

869/4 Nutsetters



Application: Hexagon headed bolts, screws and nuts

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Non-magnetic

	mm		mm	mm
05**060400**001	5,5		50,0	11,0
05**060272**001	5,5		65,0	9,5
05**060401**001	6,0		50,0	11,0
05**060274**001	6,0		65,0	11,0
05**060402**001	7,0		50,0	11,0
05**060276**001	7,0		65,0	11,0
05**060403**001	8,0		50,0	12,5
05**060278**001	8,0		65,0	12,5
05**060404**001	9,0		50,0	14,0
05**060280**001	9,0		65,0	14,0
05**060405**001	10,0		50,0	14,0
05**060282**001	10,0		65,0	14,0
05**060406**001	11,0		50,0	16,0
05**060281**001	11,0		65,0	16,0
05**060407**001	12,0		50,0	18,0
05**060283**001	12,0		65,0	17,0
05**060408**001	13,0		50,0	18,0
05**060284**001	13,0		65,0	19,0
05**060409**001		$^{1}/_{4}$"	50,0	11,0
05**060286**001		$^{1}/_{4}$"	65,0	11,0
05**060410**001		$^{5}/_{16}$"	50,0	12,5
05**060290**001		$^{5}/_{16}$"	65,0	12,5
05**060411**001		$^{3}/_{8}$"	50,0	14,0
05**060288**001		$^{3}/_{8}$"	65,0	14,0
05**060412**001		$^{7}/_{16}$"	50,0	16,0

Nutsetters

¼" hexagon drive, suitable for direct drive DIN ISO 1173-F 6,3 machine chucks (series 4)

869/4 M Nutsetters, magnetic



Application: Hexagon headed bolts, screws and nuts

Drive: 1/4" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Strong permanent magnet

	mm		mm	mm
05**060420**001	5,5		50,0	11,0
05**060210**001	5,5		65,0	11,0
05**060421**001	6,0		50,0	11,0
05**060215**001	6,0		65,0	11,0
05**060422**001	7,0		50,0	11,0
05**060220**001	7,0		65,0	11,0
05**060423**001	8,0		50,0	12,5
05**060225**001	8,0		65,0	12,5
05**060424**001	9,0		50,0	14,0
05**060230**001	9,0		65,0	14,0
05**060425**001	10,0		50,0	14,0
05**060235**001	10,0		65,0	14,0
05**060426**001	11,0		50,0	16,0
05**060237**001	11,0		65,0	16,0
05**060427**001	12,0		50,0	18,0
05**060238**001	12,0		65,0	17,0
05**060428**001	13,0		50,0	18,0
05**060240**001	13,0		65,0	19,0
05**060429**001		1/4"	50,0	11,0
05**060255**001		1/4"	65,0	11,0
05**060430**001		5/16"	50,0	12,5
05**060260**001		5/16"	65,0	12,5
05**060431**001		3/8"	50,0	14,0
05**060265**001		3/8"	65,0	14,0
05**060432**001		7/16"	50,0	16,0

869/4 M SB Nutsetters, magnetic



			4013288
05**073500**001	◉	1 x 5.5x50.0	105691
05**073501**001	◉	1 x 6.0x50.0	105707
05**073502**001	◉	1 x 7.0x50.0	106506
05**073503**001	◉	1 x 8.0x50.0	105714
05**073504**001	◉	1 x 9.0x50.0	105721
05**073505**001	◉	1 x 10.0x50.0	105738
05**073506**001	◉	1 x 11.0x50.0	105745
05**073507**001	◉	1 x 12.0x50.0	105752
05**073508**001	◉	1 x 13.0x50.0	105769
05**073509**001	◉	1 x 1/4"x50.0	105776
05**073510**001	◉	1 x 3/8"x50.0	105783

869/4 M Set A SB



8 piece set, with strong permanent magnet, in practical pouch for the belt

				4013288
05**073495**001	**869/4 M**	◉	1 x 7.0x50.0; 1 x 8.0x50.0; 1 x 10.0x50.0; 1 x 12.0x50.0; 1 x 13.0x50.0; 1 x 1/4"x50.0; 1 x 5/16"x50.0; 1 x 3/8"x50.0	144584

4 mm 4 mm Halfmoon direct drive (series 9)

869/9 Nutsetters



Application: Hexagon headed bolts, screws and nuts

Drive: Halfmoon, 4 mm

Design: Non-magnetic

	mm	mm	mm
05**135224**001	2,5	44,0	5,0
05**135225**001	3,0	44,0	5,0

Internal Thread Insertion Tool

¼" ¼" hexagon drive, suitable for F 6,3 bit holders (series 4)

879/4 Internal thread insertion tool



Application: Hanger bolts and threaded rods

Drive: $^{1}/_{4}$" hexagon, suitable for DIN ISO 1173-F 6,3 bit holders

Design: Internal thread

	⊕	mm		∅ mm
05**135902**001	M6	50,0	2"	8,0
05**135903**001	M8	50,0	2"	12,0
05**135904**001	M10	50,0	2"	12,0


Wera
Wera
Wera

Holders and Adaptors

	Impaktor Bit Holders	410
	Rapidaptor Bit Holders	414
	BiTorsion Bit Holders with Quick-Release Chuck	418
	Universal Bit Holders with Quick-Release Chuck	419
	Universal Bit Holders with Retaining Ring	421
	Universal Bit Holders with Stainless Steel Sleeve	422
	Universal Bit Holders with Copper Beryllium Sleeve	424
	Bit Holder with Adjustable Depth-Control Stop	425
	Adaptors	426



Bit Holders and Adaptors

We were not happy that bit change with bit holders was often quite cumbersome. We found out that strong magnets or retaining rings indeed hold the bit securely, but they greatly impede removal from the holder.

So we have developed bit holders that indeed reliably hold the bit, yet still allow for fast and trouble-free bit change. The solution: bit holders with quick-release mechanisms that lift the bit from the magnets. Bit holders which – depending on the requirements – additionally have elastic zones that absorb peak loads. Or rapid-spin sleeves with which the cordless or electric screwdrivers can be guided during the screwdriving process.

Impaktor holder
Suitable for extra high torque e.g. from modern 18 volt impact screwdrivers with particularly high resilience. Reduces the risk of premature breakage of the holder or bit and increases the productivity when screwdriving with power tools.



Rapidaptor stainless steel
Manufactured out of stainless steel thus preventing the formation of unsightly extraneous rust when working with stainless steel. Additionally, it offers all the advantages of the Rapidaptor technology.



BiTorsion holder
Designed with special BiTorsion zone. The energy from peak loads is diverted into the BiTorsion zone. Considerable reduction of the risk of breakage, much longer service life.






Rapidaptor holder
Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool. Also available in a BiTorsion design.



Ring magnet Rapidaptor
Special design powerful ring magnet, for larger and heavier screws. Ideal for overhead work, too.



Holder with quick-release chuck
The magnetic design enables simplified positioning of the screw. The non-magnetic version prevents any unwanted attraction of metal filings.





Universal holder with retaining ring
Proven holder design, optimal fitting of the tool in the holder. Particularly robust for series applications.



Copper Beryllium universal holder with retaining ring
Very strong design thus minimising wear and tear. Particularly suitable for screw-driving jobs with high torque or peak loads. Very high resistance to corrosion.




Universal holder with stainless steel sleeve
The retaining ring and the strong permanent magnet ensure a particularly secure fitting of the bit in the holder.

Impaktor Bits and Holders

Impaktor holder technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry (two coupled torsion zones that perform successively).





The Impaktor stainless steel holder with a retaining ring and magnet satisfies the extreme, dynamic requirements in that there are consciously no small mechanical component parts fitted as they would be more susceptible to failure. It focuses on the basic bit holding function and the cushioning of the extreme impulse peaks with its two different torsion zones. Mainly used in industrial screw assembly applications e.g. with screwdriving robots.



The Impaktor holder with ring magnet additionally holds longer and heavier screws absolutely securely. This enables a speedy and dependable positioning of the screw. It is also ideal for above-head work. Should the magnet function not be required in a particular situation e.g. when working with metal, it can be extracted from the screwdriving area and can thereby be “disabled”. Mainly used in manual power tool applications.



The combination of the double torsion zones in the Impaktor holder and the torsion zone in the Impaktor bit result in the so-called TriTorsion system.





Wera Impaktor bits and holders can also be used individually. However, the best results are achieved with the combination of the two tools that are optimally matched to one another.

Impaktor Bit Holders

For an above-average service life

897/4 IMP Impaktor holder with retaining ring and magnet



Impaktor holder to cushion extreme impulse peaks, special torsion effect from the double-torsion spring, equipped with a retaining ring for a secure fit of the bits in the holder, holder out of stainless steel, fitted with magnet for a secure positioning of the bit and screw.

Output: Suitable for bits with 1/4" hexagon head drive as per DIN ISO 1173-C 6,3 and Wera Series 1

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry (two coupled torsion zones that perform successively), fitted with strong retaining ring and magnet

Drive: 1/4" hexagon, suitable for power driven screwdrivers with DIN ISO 1173-F 6,3 chucks

		mm		
05**057675**001	1/4"	75	3"	1/4"

897/4 IMP R Impaktor holder with retaining ring and ring magnet



Impaktor holder to cushion extreme impulse peaks, special torsion effect from the double-torsion spring, equipped with a ring magnet to easily hold longer and heavier screws, also ideal for above-head work, particularly suitable for use with impact drivers, the magnet can be retracted and in this way be disabled

Output: Suitable for bits with 1/4" hexagon head drive as per DIN ISO 1173-C 6,3 and Wera Series 1

Design: The Impaktor technology ensures an above-average service life even under extreme conditions thanks to a best-possible utilisation of the material properties and optimally designed geometry (two coupled torsion zones that perform successively), fitted with retaining ring and ring magnet

Drive: 1/4" hexagon, suitable for power driven screwdrivers with DIN ISO 1173-F 6,3 chucks

		mm		
05**057676**001	1/4"	75	3"	1/4"

897/4 IMP R SB Impaktor holder with retaining ring and ring magnet

		4013288
05**073990**001	1 x 1/4"x75	157836





Rapidaptor Bit Holders

Wera developed the Rapidaptor that allows rapid bit change without any extra tools with only one hand.





Chuck-all
The Rapidaptor quick-release chucks hold both ¼" bits as per DIN ISO 1173-C 6,3 (Wera series 1) and E 6,3 (Wera series 4).



Single-hand
All functions of the quick-release chuck such as the inserting or releasing of bits can be done with just one hand. That is faster, more economic and ergonomic. There are no unnecessary manoeuvres.



Rapid-in and self-lock
The bit can be pushed into the chuck without moving the sleeve. It automatically locks with a secure and wobble-free fit as soon as the bit is applied to the screw.





Rapid-out
Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. Particularly helpful: even the smallest bits can be removed without any extra tools.



Rapid-spin
The free-turning sleeve allows screw steadying at the start of the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping. It can also be used as a short extension for ¼" applications e.g. in combination with the Wera Zyklop Ratchets.



Rapidaptor with ring magnet
The floating, free-turning magnetic sleeve securely holds even large and heavy screws to enable immediate application. There is no need to hold the screw when applying the tool – something which can be dangerous and painful. Also ideal for overhead work.

Rapidaptor Bit Holders

For rapid bit changes

3888/4/1 K Rapidaptor Universal Bit Holder stainless



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand Technology; stainless steel for minimising rust

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 chuck

		mm			mm
05**071100**001	1/4"	50	2"	1/4"	15,0

3888/4/1 K SB Rapidaptor Universal Bit Holder, stainless

		4013288
05**073616**001	1 x 1/4"x50	112170



897/4 R Rapidaptor BiTorsion Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: BiTorsion for long service life, Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology

Drive: 1/4" hexagon suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**053923**001	1/4"	75	3"	1/4"	15,0

897/4 R SB Rapidaptor BiTorsion Universal Bit Holder

		4013288
05**073420**001	1 x 1/4"x75	099464



889/4/1 K Rapidaptor Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology, with strong permanent magnet

Drive: 1/4" hexagon suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**052502**001	1/4"	50	2"	1/4"	15,0

889/4/1 K SB Rapidaptor Universal Bit Holder

	4013288
05**073421**001	1 x 1/4"x50 099440



Tip

BITORSION

BiTorsion Rapidaptor



BiTorsion holders from Wera have a torsion spring design that absorbs smaller peak loads during screwdriving. The combined use with BiTorsion bits with their torsion zone distinctly extends the service life of the tool. Conveniently, BiTorsion holders from Wera can also be used with conventional bits.

EDELSTAHL Rostfrei INOX STAINLESS

Rapidaptor holder out of stainless steel



Manufactured out of stainless steel thus preventing the formation of unsightly extraneous rust when working with stainless steel. Additionally, it offers all the advantages of the Rapidaptor technology.

Rapidaptor Bit Holders

For rapid bit changes

889/4/1 Rapidaptor Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor easy-in, easy-out, rapid-spin, chuck-all, and single-hand technology, with strong permanent magnet

Drive: 1/4" hexagon suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**052503**001	1/4"	75	3"	1/4"	15,0

888/4/1 K Rapidaptor Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor easy-in, easy-out, rapid-spin, chuck-all, and single-hand technology

Drive: 1/4" hexagon suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**052500**001	1/4"	50	2"	1/4"	15,0

889/4 R Rapidaptor Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Drive: 1/4" hexagon suitable for power tools with DIN ISO 1173-F 6,3 receiver

Design: 1/4" hexagon with Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology, magnetic

		mm			mm
05**052504**001	1/4"	100	4"	1/4"	15,0

887/4 RR Rapidaptor Universal Bit Holder with ring magnet





Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all, and single-hand technology, with ring magnet and stop sleeve for secure screwdriving on the holder

Drive: 1/4" hexagon suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**052490**001	1/4"	57	2 1/4"	1/4"	16
05**160987**001	1/4"	89	3 1/2"	1/4"	16
05**160988**001	1/4"	152	6"	1/4"	16

887/4 RR SB Rapidaptor Universal Bit Holder with ring magnet

		4013288
05**073511**001	1 x 1/4"x57	105790



Tip



Rapidaptor ring magnet



The floating, free-turning sleeve on the Rapidaptor with powerful ring magnet securely holds even large and heavy screws.



There is no need to hold the screw when applying the tool – something which can be dangerous and painful!

BiTorsion Quick-Release Chuck Holders

Adaptor for hexagon to square drive

797 A/4/1 B BiTorsion Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: BiTorsion for long service life, with strong permanent magnet

Drive: 1/4"-female square socket for use with ratchet or power tool

	⬢	mm		■	∅ mm
05**048681**001	1/4"	77	3"	1/4"	14,0

797 B/4/1 B BiTorsion Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: BiTorsion for long service life, with strong permanent magnet

Drive: 3/8"-female square socket for use with ratchet or power tool

	⬢	mm		■	∅ mm
05**048680**001	1/4"	82	3 1/4"	3/8"	14,0

Universal Bit Holders with Quick-Release Chuck

Secure hold and rapid bit changes

894/4/1 K Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With quick-release chuck

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**053522**001	1/4"	51	2"	1/4"	14,3

894/4/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With quick-release chuck

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**053520**001	1/4"	75	3"	1/4"	14,3

894/14/1 Universal Bit Holder

SDS PLUS



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With quick-release chuck

Drive: SDS plus

		mm		mm
05**053560**001	1/4"	75	3"	14,3

895/4/1 K Universal Bit Holder

MAGNETIC



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With strong permanent magnet and quick-release chuck

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**053872**001	1/4"	52	2"	1/4"	14,3

895/4/1 K SB Universal Bit Holder

		4013288
05**073318**001	1 x 1/4"x52	029195



Universal Bit Holder with Quick-Release Chuck

Secure hold and rapid bit changes

895/4/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With strong permanent magnet and quick-release chuck

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**053870**001	1/4"	77	3"	1/4"	14,3

895/14/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With strong permanent magnet and quick-release chuck

Drive: SDS plus

		mm		mm
05**053920**001	1/4"	81	3 1/8"	14,3

898/4 Combination Bit Holder



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

	mm			mm
05**051500**001	50	2"	1/4"	10,0

898/9 Combination Bit Holder



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck

Drive: Halfmoon, 4 mm

	mm		mm
05**051501**001	50	2"	10,0

898/21 Combination Bit Holder



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck

Drive: HIOS 4 mm

	mm		mm
05**051502**001	50	2"	10,0

Universal Bit Holder with Retaining Ring

Proven, secure hold in series manufacturing applications

890/00/0 Universal Bit Holder



Application: Suitable for 4 mm DIN ISO 1173-C 4 bits

Design: With retaining ring

Drive: 3 mm hexagon, suitable for power tools with DIN ISO 1173-B 3 receiver

	mm	mm		mm	mm
05**052505**001	4	57	2 1/4"	3	6,3

890/7/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With retaining ring

Drive: 7/16" hexagon, suitable for power tools with DIN ISO 1173-F 11,2 receiver

		mm			mm
05**052655**001	1/4"	65	2 1/2"	7/16"	11,1

890/4/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With retaining ring

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**052575**001	1/4"	57	2 1/4"	1/4"	11,1

890/7/2 Universal Bit Holder



Application: Suitable for 5/16" DIN ISO 1173-C 8 hexagon insert bits and Wera Series 2

Design: With retaining ring

Drive: 7/16" hexagon, suitable for power tools with DIN ISO 1173-F 11,2 receiver

		mm			mm
05**052725**001	5/16"	65	2 1/2"	7/16"	14,3

890/6/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With retaining ring

Drive: 5/16" hexagon, suitable for power tools with DIN ISO 1173-F 8 receiver

		mm			mm
05**052625**001	1/4"	65	2 1/2"	5/16"	11,1

Universal Bit Holders with Stainless Steel Sleeve

Strong magnet for secure hold

893/4/1 K Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve and strong permanent magnet

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**134480**001	1/4"	50	2"	1/4"	10,5

893/4/1 K SB Universal Bit Holder

		4013288
05**073401**001	1 x 1/4"x50	029133



899/3/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, retaining ring, and strong permanent magnet

Drive: 5.5 mm hexagon, suitable for power tools with DIN ISO 1173-B 5,5 receiver

		mm		mm	mm
05**053425**001	1/4"	72	2 3/4"	5,5	10,5

899/4/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, retaining ring, and strong permanent magnet

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

			mm			mm
05**053457**001	**899/4/1 K**	1/4"	50	2"	1/4"	10,5
05**053455**001	**899/4/1 75**	1/4"	75	3"	1/4"	10,5
05**053459**001	**899/4/1 100**	1/4"	100	4"	1/4"	10,5
05**053458**001	**899/4/1 152**	1/4"	152	6"	1/4"	10,5

899/4/1 SB Universal Bit Holder

		4013288
05**347100**001	1 x **899/4/1 K 50** 1/4"x50	095268
05**073357**001	1 x **899/4/1 75** 1/4"x75	029720
05**134398**001	1 x **899/4/1 152** 1/4"x152	099907



899/4/1 S Universal Bit Holder with strong retaining ring



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, strong retaining ring, and strong permanent magnet

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**160976**001	1/4"	50	2"	1/4"	10,5
05**160924**001	1/4"	75	3"	1/4"	10,5
05**160977**001	1/4"	100	4"	1/4"	10,5
05**160979**001	1/4"	200	8"	1/4"	10,5
05**160981**001	1/4"	300	12"	1/4"	10,5

899/8/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, retaining ring, and strong permanent magnet

Drive: 7 mm, suitable for power tools with DIN ISO 1173-H 7 receiver

		mm		mm	mm
05**053475**001	1/4"	75	3"	7	10,5

899/5/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, retaining ring, and strong permanent magnet

Drive: 5/16" hexagon

		mm			mm
05**053460**001	1/4"	45	1 3/4"	5/16"	10,5

899/8/1 K Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, retaining ring, and strong permanent magnet

Drive: 7 mm, suitable for power tools with DIN ISO 1173-H 7 receiver

		mm		mm	mm
05**053480**001	1/4"	55	2 3/16"	7	10,5

899/14/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With stainless steel sleeve, retaining ring, and strong permanent magnet

Drive: SDS plus

		mm		mm
05**053485**001	1/4"	79	3 1/8"	10,5

899/14/1 SB Universal Bit Holder

		4013288
05**134397**001	1 x 1/4"x79	099891



Universal Bit Holders with Copper Beryllium Sleeve

Very high torque model

891/4/1 Universal Bit Holder




Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With CuBe sleeve, retaining ring, and strong permanent magnet

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm			mm
05**053175**001	1/4"	75	3"	1/4"	10,5

891/8/1 Universal Bit Holder



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With CuBe sleeve, retaining ring, and strong permanent magnet

Drive: 7 mm, suitable for power tools with DIN ISO 1173-H 7 receiver

		mm		mm	mm
05**053275**001	1/4"	75	3"	7	10,5

Bit Holder with Adjustable Depth-Control Stop

With infinite adjustment feature

896/4/1 SB Bit Holder with adjustable depth-control stop



Application: Suitable for $^1/_4$" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: High quality aluminium spacers with infinite adjustment feature

Drive: $^1/_4$" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

			4013288
05**073210**001	**896/4/1**	1 x 1/4"x50	178725

Tip

DEPTH CONTROL

Bit holder with adjustable depth stop



The screw installation depth can be infinitely adjusted and allows the desired degree of countersinking of the screws.



Adaptors

870/1 Adaptor



Application: Nut spinner sockets
Drive: 1/4" external hexagon
Output: 1/4" external square

		mm		
05**136000**001[1]	1/4"	25	1"	1/4"

[1] With friction ball; for manual nut spinner sockets

870/2 Adaptor



Application: Nut spinner sockets
Drive: External hexagon
Output: External square

		mm		
05**136001**001[1]	3/8"	30	1 3/16"	5/16"
05**136002**001[1]	1/2"	35	1 3/8"	5/16"

[1] With friction ball; for manual nut spinner sockets

870/4 Adaptor



Application: Manual nut spinner sockets
Drive: 1/4" hexagon
Output: 1/4" external square

		mm		
05**311517**001[1]	1/4"	50	2"	1/4"

[1] With friction ball; for manual nut spinner sockets

870/4 SB

		4013288
05**134399**001[1]	1 x 1/4"x50	099914

[1] With friction ball; for manual nut spinner sockets



870/4/7 Set A SB



Application: Machine-operated nut spinner sockets

Design: With external square drive

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver; 7/16" hexagon, suitable for power tools with DIN ISO 1173-F 11,2 receiver

05**073200**001		
	870/4	1 x 1/4"x50; 1 x 3/8"x50
	870/7	1 x 1/2"x75

870/4 Adaptor



Application: Machine-operated nut spinner sockets

Design: With external square drive

Drive: 1/4" hexagon, suitable for power tools with DIN ISO 1173-F 6,3 receiver

		mm		
05**050205**001	1/4"	50	2"	1/4"
05**050210**001	1/4"	100	4"	1/4"
05**050215**001	3/8"	50	2"	1/4"
05**050220**001	3/8"	100	4"	1/4"

870/14 Adaptor

SDS PLUS



Application: Machine-operated nut spinner sockets

Design: With external square drive

Drive: SDS plus

		mm	
05**050650**001	1/4"	70	2 3/4"

870/7 Adaptor



Application: Machine-operated nut spinner sockets

Design: With external square drive

Drive: 7/16" hexagon, suitable for power tools with DIN ISO 1173-F 11,2 receiver

		mm		
05**050510**001	1/2"	75	3"	7/16"

Adaptors

784 A 1/4" Adaptor with quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Design: With Wera quick-release chuck

Drive: 1/4" female square

			mm		
05**042750**001	784 A/1	1/4"	30	1 3/16"	1/4"

784 B 3/8" Adaptor with quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and 5/16" DIN ISO 1173-C 8 hexagon insert bits and Wera Series 1 and 2

Design: With Wera quick-release chuck

Drive: 3/8" female square

			mm		
05**042755**001	784 B/1	1/4"	43	1 5/8"	3/8"
05**042765**001	784 B/2	5/16"	50	2"	3/8"

784 C 1/2" Adaptor with quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and 5/16" DIN ISO 1173-C 8 hexagon insert bits and Wera Series 1 and 2

Design: With Wera quick-release chuck

Drive: 1/2" female square

			mm		
05**042760**001	784 C/1	1/4"	50	2"	1/2"
05**042768**001	784 C/2	5/16"	50	2"	1/2"

780 A 1/4" Adaptor



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Drive: 1/4" female square

			mm		
05**042605**001	780 A/1	1/4"	25	1"	1/4"

780 B 3/8" Adaptor



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and 5/16" DIN ISO 1173-C 8 hexagon insert bits and Wera Series 1 and 2

Drive: 3/8" female square

			mm		
05**042655**001	780 B/1	1/4"	30	1 3/16"	3/8"
05**344511**001 [1]	780 B/1-S	1/4"	30	1 3/16"	3/8"
05**042665**001	780 B/2	5/16"	30	1 3/16"	3/8"
05**344512**001 [1]	780 B/2-S	5/16"	30	1 3/16"	3/8"

[1] S = extra strong

780 C 1/2" Adaptor



Application: Suitable for 1/4" DIN ISO 1173-C 6,3, 5/16" DIN ISO 1173-C 8, 7/16" DIN ISO 1173-E 11,2, 5/8" hexagon insert bits and Wera Series 1, 2, 6, 7 and 19

Drive: 1/2" female square

			mm		
05**042705**001	780 C/1	1/4"	35	1 3/8"	1/2"
05**344513**001	780 C/1-S	1/4"	35	1 3/8"	1/2"
05**042715**001	780 C/2	5/16"	35	1 3/8"	1/2"
05**344514**001	780 C/2-S	5/16"	35	1 3/8"	1/2"


Wera
Zyklop


Wera
Bit-Check
BITORSION
DIAMOND
BC 12 Diamond 1

Bit Sets


Bit-Checks Impaktor 434


Bit-Checks Stainless 438


Bit-Checks / Bit-Safes BiTorsion 440


Bit-Checks Diamond 444


Bit-Checks / Bit-Safes Universal 448


Bit-Checks Wood 458


Bit-Checks Metal 460


Bit Sets For Special Applications 461



Bit Ranges

We have had bit ranges in our programme for many years now. In 2016, we put a question mark against everything and came up with a game changer.
We wanted bit ranges with bits whose profiles and sizes could be more easily recognised. We wanted bit ranges that were as compact as possible and which were Wera-like at a first glance. We wanted bit ranges with bits that could be removed and reinserted more easily. We wanted bit ranges with as little weight as possible. The new multi-component Bit-Checks satisfy these requirements; the soft material in the lower section of the Bit-Checks ensures that the bits are firmly held yet easy to remove.





The bit ranges comprise sets of between 6 and 61 pieces. They offer the right tool set for every user.




The Bit-Checks by Wera are extremely compact and are therefore the ideal companion for mobile applications.



The Bit-Checks can be positioned upright at the workplace so the tool is always quickly to hand.





The "Take it easy" Bit-Checks have bits with a sleeve which – from its colour (e.g. red = Phillips) and size designation – make it simple to access the right bit quickly.



The new Bit-Safes provide users with comprehensive bit and holder ranges in a surface-protecting, compact textile box.


Wera
BC A Stainless 1

Bit-Checks Impaktor

For an above-average service life

Bit-Check 30 Impaktor 1





1 Impaktor holder with retaining ring and ring magnet in the chuck for a secure fit of the bits in the holder, 29 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057690**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor R**
✪	**851/1 IMP DC** 2 x PH 1x25; 3 x PH 2x25; 2 x PH 3x25
✪	**855/1 IMP DC** 2 x PZ 1x25; 3 x PZ 2x25; 2 x PZ 3x25
✪	**867/1 IMP DC** 1 x TX 10x25; 1 x TX 15x25; 2 x TX 20x25; 3 x TX 25x25; 2 x TX 30x25; 2 x TX 40x25
○	**840/1 IMP DC** 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

Bit-Check 10 Impaktor 2





1 Impaktor holder with retaining ring and ring magnet in the chuck for a secure fit of the bits in the holder, 9 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057682**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor R**
✪	**851/1 IMP DC** 3 x PH 2x25; 1 x PH 3x25
✪	**867/1 IMP DC** 3 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 10 Impaktor 1





1 Impaktor holder with retaining ring and ring magnet in the chuck for a secure fit of the bits in the holder, 9 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057680**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor R**
✪	**851/1 IMP DC** 1 x PH 2x25; 1 x PH 3x25
✪	**855/1 IMP DC** 1 x PZ 2x25; 1 x PZ 3x25
✪	**867/1 IMP DC** 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
○	**840/1 IMP DC** 1 x 4,0x25; 1 x 5,0x25

Bit-Check 10 Impaktor 1 SB

	4013288
05**073980**001	158574
◉ ○	**897/4 Impaktor R** 1 x 1/4"x75
✪	**851/1 IMP DC** 1 x PH 2x25; 1 x PH 3x25
✪	**855/1 IMP DC** 1 x PZ 2x25; 1 x PZ 3x25
✪	**867/1 IMP DC** 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
○	**840/1 IMP DC** 1 x 4.0x25; 1 x 5.0x25



Bit-Check 10 Impaktor 3





1 Impaktor holder with retaining ring and ring magnet in the chuck for a secure fit of the bits in the holder, 9 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057683**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor R**
✪	**855/1 IMP DC** 3 x PZ 2x25; 1 x PZ 3x25
✪	**867/1 IMP DC** 3 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 10 Impaktor 4



1 Impaktor holder with retaining ring and magnet in the chuck for a secure fit of the bits in the holder, 9 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057417**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor**
✪	**855/1 IMP DC** 3 x PZ 2x25; 1 x PZ 3x25
✪	**867/1 IMP DC** 2 x TX 20x25; 2 x TX 25x25; 1 x TX 30x25

Bit-Check 10 PZ Impaktor 1



1 Impaktor holder with retaining ring and ring magnet in the chuck for a secure fit of the bits in the holder, 9 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057684**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor R**
✪	**855/1 IMP DC** 7 x PZ 2x25; 2 x PZ 3x25

Bit-Check 10 TX Impaktor 1



1 Impaktor holder with retaining ring and ring magnet in the chuck for a secure fit of the bits in the holder, 9 Impaktor bits. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057688**001	
◉ ○	**897/4** 1 x 1/4"x75 **Impaktor R**
✪	**867/1 IMP DC** 3 x TX 20x25; 3 x TX 25x25; 2 x TX 30x25; 1 x TX 40x25

Tip

Impaktor-Bits



Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.

The Impaktor stainless steel holder with a retaining ring and magnet



The Impaktor stainless steel holder with a retaining ring and magnet satisfies the extreme, dynamic requirements in that there are consciously no small mechanical component parts fitted as they would be more susceptible to failure. It focuses on the basic bit holding function and the cushioning of the extreme impulse peaks with its two different torsion zones. Mainly used in industrial screw assembly applications e.g. with screwdriving robots.

The Impaktor holder with ring magnet



The Impaktor holder with ring magnet additionally holds longer and heavier screws absolutely securely. This enables a speedy and dependable positioning of the screw. It is also ideal for above-head work. Should the magnet function not be required in a particular situation e.g. when working with metal, it can be extracted from the screwdriving area and can thereby be “disabled”. Mainly used in manual power tool applications.

Bit-Checks Impaktor

For an above-average service life

Bit-Check 6 Impaktor 1



6 Impaktor bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057695**001	
	851/4 IMP DC 1 x PH 2x50; 1 x PH 3x50
	855/4 IMP DC 1 x PZ 2x50; 1 x PZ 3x50
	867/4 IMP DC 1 x TX 25x50; 1 x TX 30x50

Bit-Check 6 Impaktor 1 SB

	4013288
05**073890**001	158635
	851/4 IMP DC 1 x PH 2x50; 1 x PH 3x50
	855/4 IMP DC 1 x PZ 2x50; 1 x PZ 3x50
	867/4 IMP DC 1 x TX 25x50; 1 x TX 30x50



Bit-Check 6 Impaktor 2



6 Impaktor bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057694**001	
	851/4 IMP DC 1 x PH 2x50; 1 x PH 3x50
	867/4 IMP DC 1 x TX 25x50; 1 x TX 30x50
	868/4 IMP DC 1 x # 2x50; 1 x # 3x50

Bit-Check 6 PH Impaktor 1



6 Impaktor bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057691**001	
	851/4 IMP DC 4 x PH 2x50; 2 x PH 3x50

Bit-Check 6 PZ Impaktor 1



6 Impaktor bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057692**001	
	855/4 IMP DC 4 x PZ 2x50; 2 x PZ 3x50

Bit-Check 6 TX Impaktor 1



6 Impaktor bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057693**001	
	867/4 IMP DC 2 x TX 20x50; 2 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50



” To learn more about this product, scan the QR code. “



Bit-Checks Stainless

Keep rust at bay

Bit-Check 30 Stainless 1





1 Rapidaptor stainless steel bit holder with quick-release chuck, 29 stainless steel bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**071109**001		
◉ ○	**3888/4/1 K**	1 x 1/4"x50
✪	**3851/1 TS PH**	1 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
✪	**3855/1 TS PZ**	2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
✪	**3867/1 TS TORX®**	2 x TX 10x25; 2 x TX 15x25; 3 x TX 20x25; 3 x TX 25x25; 2 x TX 30x25; 1 x TX 40x25
○	**3840/1 TS**	1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 5,5x25

Bit-Check 12 Stainless 1





1 Rapidaptor stainless steel bit holder with quick-release chuck, 11 stainless steel bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057425**001		
◉ ○	**3888/4/1 K**	1 x 1/4"x50
✪	**3851/1 TS PH**	1 x PH 1x25; 1 x PH 2x25
✪	**3855/1 TS PZ**	1 x PZ 1x25; 1 x PZ 2x25
✪	**3867/1 TS TORX®**	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
○	**3840/1 TS**	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25

Bit-Check 10 Stainless 1





1 Rapidaptor stainless steel bit holder with quick-release chuck, 9 stainless steel bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**071110**001		
◉ ○	**3888/4/1 K**	1 x 1/4"x50
✪	**3851/1 TS PH**	1 x PH 2x25
✪	**3855/1 TS PZ**	1 x PZ 1x25; 2 x PZ 2x25
✪	**3867/1 TS TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25

Bit-Check 10 Stainless 1 SB

		4013288
05**073630**001		112163
◉ ○	**3888/4/1 K**	1 x 1/4"x50
✪	**3851/1 TS PH**	1 x PH 2x25
✪	**3855/1 TS PZ**	1 x PZ 1x25; 2 x PZ 2x25
✪	**3867/1 TS TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25



Bit-Check 6 Stainless 1 SB



6 stainless steel bits.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

				4013288
05**073634**001	**3855/4**		2 x PZ 2x50	164636
	3867/4 TORX®		1 x TX 20x50; 2 x TX 25x50	
	3840/4 Hex-Plus		1 x 5.5x50	


Tip

Stainless Steel Bits



The stainless steel tools from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.

“Take it easy”



“Take it easy” tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.

Rapidaptor holder out of stainless steel



Manufactured out of stainless steel thus preventing the formation of unsightly extraneous rust when working with stainless steel. Additionally, it offers all the advantages of the Rapidaptor technology.



Bit-Checks / Bit-Safes BiTorsion

BiTorsion – Distinct extension of service life

Bit-Safe 61 BiTorsion 1





1 bit holder Rapidaptor with quick-release chuck, 49 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit, tough (BTZ), for universal use, extra-hard (BTH).
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057441**001		
	889/4/1 K	1 x 1/4"x50
	851/1 BDC PH	1 x PH 1x25; 2 x PH 2x25; 1 x PH 3x25
	851/1 BTZ PH	2 x PH 1x25; 8 x PH 2x25; 1 x PH 3x25
	855/1 BDC PZ	1 x PZ 1x25; 2 x PZ 2x25; 1 x PZ 3x25
	855/1 BTH PZ	2 x PZ 1x25; 8 x PZ 2x25; 1 x PZ 3x25
	867/1 TORX® BTZ	3 x TX 10x25; 2 x TX 15x25; 4 x TX 20x25; 4 x TX 25x25; 2 x TX 30x25; 1 x TX 40x25
	800/1 BDC	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	840/1 BTZ Hex-Plus	3 x 2,5x25; 3 x 3,0x25; 3 x 4,0x25; 2 x 5,0x25

Bit-Check 30 BiTorsion 1





1 bit holder Rapidaptor with quick-release chuck, 29 BiTorsion bits for long service life, tough, for universal use.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057430**001		
	889/4/1 K	1 x 1/4"x50
	851/1 BTZ PH	2 x PH 1x25; 5 x PH 2x25; 2 x PH 3x25
	855/1 BTZ PZ	2 x PZ 1x25; 6 x PZ 2x25; 2 x PZ 3x25
	867/1 TORX® BTZ	1 x TX 10x25; 2 x TX 15x25; 2 x TX 20x25; 2 x TX 25x25; 2 x TX 30x25; 1 x TX 40x25

Bit-Check 12 BiTorsion 1





1 bit holder Rapidaptor with quick-release chuck, 11 BiTorsion bits for long service life, tough, for universal use.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057420**001		
	889/4/1 K	1 x 1/4"x50
	851/1 BTZ PH	1 x PH 1x25; 2 x PH 2x25
	855/1 BTZ PZ	1 x PZ 1x25; 2 x PZ 2x25
	867/1 TORX® BTZ	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25

Bit-Check 10 BiTorsion 1



1 BiTorsion bit holder Rapidaptor with quick-release chuck, 9 BiTorsion bits for long service life, tough, for universal use.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**056374**001		
	897/4 R	1 x 1/4"x75
	851/1 BTZ PH	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
	855/1 BTZ PZ	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25
	800/1 BTZ	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 10 BiTorsion 2





1 BiTorsion bit holder Rapidaptor with quick-release chuck, 9 BiTorsion bits for long service life, tough, for universal use.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057117**001		
	897/4 R	1 x 1/4"x75
	851/1 BTZ PH	1 x PH 2x25
	855/1 BTZ PZ	1 x PZ 1x25; 2 x PZ 2x25
	867/1 TORX® BTZ	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25

Tip

BiTorsion





The effectiveness of the BiTorsion system comes from a combination of two shock-absorbing spring elements.


Both bits as well as holders have a cushioning torsion zone that diverts the kinetic energy away from the drive tip during peak loads.

BDC-Bits



BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.

“Take it easy”



“Take it easy” tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.

Bit-Checks / Bit-Safes BiTorsion

BiTorsion – Distinct extension of service life

Bit-Check 10 BiTorsion 3 SB



1 BiTorsion bit holder Rapidaptor with quick-release chuck, 9 BiTorsion bits for long service life, tough, for universal use.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

				4013288
05**073418**001	**897/4 R**		1 x 1/4"x75	128157
	851/1 BTZ PH		1 x PH 2x25	
	855/1 BTZ PZ		1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25	
	867/1 TORX® BTZ		1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25	

Bit-Check 10 PZ BiTorsion 1



1 BiTorsion bit holder Rapidaptor with quick-release chuck, 9 BiTorsion bits for long service life, tough, for universal use.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**056368**001		
	897/4 R	1 x 1/4"x75
	855/1 BTZ PZ	7 x PZ 2x25; 2 x PZ 3x25

Bit-Check 10 PZ BiTorsion 2



1 BiTorsion bit holder Rapidaptor with quick-release chuck, 9 BiTorsion bits for long service life, extra-hard.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**347153**001		
	897/4 R	1 x 1/4"x75
	855/1 BTH PZ	1 x PZ 1x25; 7 x PZ 2x25; 1 x PZ 3x25

Bit-Check 7 PZ BiTorsion 1



1 bit holder Rapidaptor with quick-release chuck suitable, 6 BiTorsion bits for long service life, extra-hard.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**340260**001		
	889/4/1 K	1 x 1/4"x50
	855/1 BTH PZ	1 x PZ 1x25; 4 x PZ 2x25; 1 x PZ 3x25

Bit-Check 7 PH BiTorsion 1



1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 BiTorsion bits for long service life, extra-hard. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**056291**001	
◉○	**893/4/1 K** 1 x 1/4"x50
⊕	**851/1 BTH PH** 6 x PH 2x25

Bit-Check 6 PH BiTorsion 1



6 BiTorsion bits for long service life, extra-hard. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**056477**001	
⊕	**851/4 BTH PH** 6 x PH 2x50

Tip

BiTorsion



The BiTorsion holder and the Bi-Torsion bit can, of course, be used independently of one another.

Chuck-all



The Rapidaptor quick-release chucks hold both ¼" bits as per DIN ISO 1173-C 6,3 (Wera series 1) and E 6,3 (Wera series 4).

Rapid-in and self-lock



The bit can be pushed into the chuck without moving the sleeve. It automatically locks with a secure and wobble-free fit as soon as the bit is applied to the screw.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. Particularly helpful: even the smallest bits can be removed without any extra tools.

Bit-Checks Diamond

Bits with “bite”

Bit-Check 30 Diamond 1



1 bit holder Rapidaptor with quick-release chuck, 29 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057431**001		
	889/4/1 K	1 x 1/4"x50
	851/1 BDC PH	2 x PH 1x25; 4 x PH 2x25; 1 x PH 3x25
	855/1 BDC PZ	2 x PZ 1x25; 4 x PZ 2x25; 1 x PZ 3x25
	867/1 TORX® BDC	2 x TX 10x25; 2 x TX 15x25; 3 x TX 20x25; 3 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 BDC	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 10 Diamond 1



1 BiTorsion bit holder Rapidaptor with quick-release chuck, 9 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057116**001		
	897/4 R	1 x 1/4"x75
	851/1 BDC PH	1 x PH 2x25
	855/1 BDC PZ	1 x PZ 1x25; 2 x PZ 2x25
	867/1 TORX® BDC	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25

Bit-Check 12 Diamond 1



1 bit holder Rapidaptor with quick-release chuck, 11 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057421**001		
	889/4/1 K	1 x 1/4"x50
	851/1 BDC PH	1 x PH 1x25; 2 x PH 2x25
	855/1 BDC PZ	1 x PZ 1x25; 2 x PZ 2x25
	867/1 TORX® BDC	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25

Bit-Check 7 Diamond 1







1 bit holder Rapidaptor with quick-release chuck, 6 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057416**001	
	889/4/1 K 1 x 1/4"x50
	851/1 BDC PH 1 x PH 1x25; 1 x PH 2x25
	855/1 BDC PZ 1 x PZ 1x25; 1 x PZ 2x25
	800/1 BDC 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 7 Diamond 1 SB

	4013288
05**073419**001	183682
	889/4/1 K 1 x 1/4"x50
	851/1 BDC PH 1 x PH 1x25; 1 x PH 2x25
	855/1 BDC PZ 1 x PZ 1x25; 1 x PZ 2x25
	800/1 BDC 1 x 1.0x5.5x25; 1 x 1.2x6.5x25



Tip




BDC-Bits



BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.



“Take it easy”



“Take it easy” tool finder with colour coding according to profiles and size stamp – for simple and rapid accessing of the required tool.



BiTorsion Rapidaptor



BiTorsion bit holders are suitable for all bits in accordance with C 6,3 and E 6,3. The optimally coordinated features of the torsion zones on the BiTorsion bits and BiTorsion holder permit a phased yield when under strain. This two-phase system prevents premature wear. The bits and the holder can be used independently of one another. A long tool service life is guaranteed when both elements are used.



Bit-Checks Diamond

Bits with “bite”

Bit-Check 7 PZ Diamond 1







1 bit holder Rapidaptor with quick-release chuck, 6 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057412**001	
◉ ○	**889/4/1 K** 1 x 1/4"x50
✪	**855/1 BDC PZ** 2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25

Bit-Check 7 PH Diamond 1







1 bit holder Rapidaptor with quick-release chuck, 6 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057414**001	
◉ ○	**889/4/1 K** 1 x 1/4"x50
✪	**851/1 BDC PH** 2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25

Bit-Check 7 PZ Diamond 1 SB

	4013288
05**073534**001	180940
	◉ ○ **889/4/1 K** 1 x 1/4"x50 ✪ **855/1 BDC PZ** 2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25



Bit-Check 7 TX Diamond 1







1 bit holder Rapidaptor with quick-release chuck, 6 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit.
The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057415**001		
◉ ○	**889/4/1 K**	1 x 1/4"x50
✪	**867/1 TORX® BDC**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 6 PH Diamond 1



6 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057404**001	
✪	**851/4 BDC PH** 2 x PH 1x50; 3 x PH 2x50; 1 x PH 3x50

Bit-Check 6 PZ Diamond 1



6 BiTorsion bits for long service life, diamond-coated (BDC) for secure screw fit. The “Take it easy” Bit-Checks have bits with a sleeve which – from its colour and size designation – make it simple to access the right bit quickly.

05**057402**001	
✪	**855/4 BDC PZ** 2 x PZ 1x50; 3 x PZ 2x50; 1 x PZ 3x50

Tip

Chuck-all



The Rapidaptor quick-release chucks hold both ¼" bits as per DIN ISO 1173-C 6,3 (Wera series 1) and E 6,3 (Wera series 4).

Single-hand



All functions of the quick-release chuck such as the inserting or releasing of bits can be done with just one hand. That is faster, more economic and ergonomic. There are no unnecessary manoeuvres.

Rapid-in and self-lock




The bit can be pushed into the chuck without moving the sleeve. It automatically locks with a secure and wobble-free fit as soon as the bit is applied to the screw.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. Particularly helpful: even the smallest bits can be removed without any extra tools.

Rapid-spin



The free-turning sleeve allows screw steadying at the start of the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping. It can also be used as a short extension for ¼" applications e.g. in combination with the Wera Zyklop Ratchets.

Bit-Checks / Bit-Safes Universal

For general use

Bit-Safe 61 Universal 1



1 bit holder Rapidaptor with strong permanent magnet and quick-release chuck, 60 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**057122**001		
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	3 x PH 1x25; 10 x PH 2x25; 2 x PH 3x25
	855/1 TZ PZ	3 x PZ 1x25; 10 x PZ 2x25; 2 x PZ 3x25
	867/1 TZ TORX®	2 x TX 10x25; 3 x TX 15x25; 3 x TX 20x25; 3 x TX 25x25; 3 x TX 30x25; 2 x TX 40x25
	800/1 TZ	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	840/1 Z Hex-Plus	3 x 2,5x25; 3 x 3,0x25; 3 x 4,0x25; 2 x 5,0x25

Bit-Safe 61 Universal 2



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 60 bits, tough, for universal use.

05**057455**001		
	899/4/1	1 x 899/4/1 Kx1/4"x50
	851/1 Z PH	10 x PH 1x25; 20 x PH 2x25; 5 x PH 3x25
	855/1 Z PZ	3 x PZ 2x25
	867/1 TORX®	3 x TX 10x25; 5 x TX 15x25; 5 x TX 20x25; 5 x TX 25x25; 2 x TX 30x25; 2 x TX 40x25

Bit-Safe 43 Universal 1



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 42 bits, Torsion-style (T) design to reduce premature wear, tough, for universal use.

05**057450**001		
	899/4/1	1 x 899/4/1 Kx1/4"x50
	851/1 Z PH	1 x PH 2x25
	851/4 TZ PH	1 x PH1x50; 2 x PH2x50
	855/1 Z PZ	2 x PZ 1x25; 5 x PZ 2x25; 2 x PZ 3x25
	855/4 TZ PZ	1 x PZ 1x50; 2 x PZ 2x50
	867/1 TORX®	3 x TX 10x25; 4 x TX 15x25; 4 x TX 20x25; 4 x TX 25x25; 4 x TX 30x25; 1 x TX 40x25
	867/4 Z TORX®	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50

Bit-Check 30 Universal 1



1 bit holder Rapidaptor with quick-release chuck, 29 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use, extra-hard (H).

05**056440**001		
	889/4/1 K	1 x 1/4"x50
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	855/1 TH PZ	2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
	867/1 TZ TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	867/1 Z TORX® BO	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	800/1 TZ	1 x 1,0x5,5x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25; 1 x 8,0x25

Bit-Check 30 TX Universal 1



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 29 bits, tough, for universal use.

05**057908**001		
	899/4/1	1 x 899/4/1 Kx1/4"x50
	867/1 TORX®	3 x TX 10x25; 5 x TX 15x25; 8 x TX 20x25; 7 x TX 25x25; 4 x TX 30x25; 2 x TX 40x25

Bit-Check 12 Universal 1



1 bit holder Rapidaptor with quick-release chuck, 11 bits, tough, for universal use, 851/1 A extra-hard, profiled version, 868/1 V with holding function.

05**057428**001		
	888/4/1 K	1 x 1/4"x50
	851/1 A PH	1 x PH 1x25; 2 x PH 2x25; 1 x PH 3x25
	867/1 TORX®	1 x TX 8x25; 1 x TX 20x25; 1 x TX 25x25
	868/1 V	1 x # 1x25; 2 x # 2x25; 1 x # 3x25

Bit-Check 12 Universal 2



1 magnetic Rapidaptor quick-release bit holder with ringmagnet, 11 bits, tough, for universal use, 851/1 A extra-hard, profiled version, 868/1 V with holding function.

05**057429**001		
	887/4 RR	1 x 1/4“x57
	851/1 A PH	1 x PH 1x25; 2 x PH 2x25; 1 x PH 3x25
	800/1 Z	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	868/1 V	1 x # 1x25; 2 x # 2x25; 1 x # 3x25

Tip

Rapidaptor holder



Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool.

Hex-Plus



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! Good to know: Hex-Plus tools fit into every standard hexagon socket screw!



Bit-Checks / Bit-Safes Universal

For general use

Bit-Check 10 Universal 1



1 bit holder with strong permanent magnet and quick-release chuck, 9 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056161**001		
◉ ○	**895/4/1 K**	1 x 1/4"x52
✪	**851/1 TZ PH**	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
✪	**855/1 TZ PZ**	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25
⊖	**800/1 TZ**	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 10 Universal 2



1 bit holder with strong permanent magnet and quick-release chuck, 9 bits, Torsion-style (T) design to reduce premature wear, tough, for universal use, extra-hard (H).

05**134200**001		
◉ ○	**895/4/1 K**	1 x 1/4"x52
✪	**855/1 TH PZ**	1 x PZ 1x25; 2 x PZ 2x25
✪	**867/1 TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 10 Universal 3



1 bit holder Rapidaptor with quick-release chuck, 9 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056375**001		
◉ ○	**889/4/1 K**	1 x 1/4"x50
✪	**851/1 TZ PH**	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
✪	**855/1 TZ PZ**	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25
⊖	**800/1 TZ**	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 10 Universal 3 SB

	4013288
05**073410**001	099495
	◉ ○ **889/4/1 K** 1 x 1/4"x50 ⊖ **800/1 TZ** 1 x 0.8x5.5x25; 1 x 1.0x5.5x25; 1 x 1.2x6.5x25 ✪ **851/1 TZ PH** 1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25 ✪ **855/1 TZ PZ** 1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25



Bit-Check 10 Universal 4



1 Universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 9 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056159**001		
◉ ○	**899/4/1**	1 x 899/4/1 Kx1/4"x50
✪	**851/1 TZ PH**	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
✪	**855/1 TZ PZ**	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25
⊖	**800/1 TZ**	1 x 0,8x5,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 10 Universal 5 SB



1 Universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 9 bits, tough, for universal use.

			4013288
05**073416**001	**899/4/1**	1 x 899/4/1 Kx1/4"x50	128164
	851/1 Z PH	1 x PH 2x25	
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25; 1 x PZ 3x25	
	867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25	

Bit-Check 10 PZ Universal 1



1 bit holder with strong permanent magnet and quick-release chuck, 9 bits, Torsion-style (T) design to reduce premature wear, extra-hard (H).

05**056163**001		
	895/4/1 K	1 x 1/4"x52
	855/1 TH PZ	3 x PZ 1x25; 3 x PZ 2x25; 3 x PZ 3x25

Bit-Check 10 PZ Universal 2



1 bit holder Rapidaptor with quick-release chuck, 9 bits, Torsion-style (T) design to reduce premature wear, extra-hard (H).

05**056376**001		
	889/4/1 K	1 x 1/4"x50
	855/1 TH PZ	3 x PZ 1x25; 3 x PZ 2x25; 3 x PZ 3x25

Tip

Chuck-all



The Rapidaptor quick-release chucks hold both ¼" bits as per DIN ISO 1173-C 6,3 (Wera series 1) and E 6,3 (Wera series 4).

Single-hand



All functions of the quick-release chuck such as the inserting or releasing of bits can be done with just one hand. That is faster, more economic and ergonomic. There are no unnecessary manoeuvres.

Rapid-in and self-lock




The bit can be pushed into the chuck without moving the sleeve. It automatically locks with a secure and wobble-free fit as soon as the bit is applied to the screw.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. Particularly helpful: even the smallest bits can be removed without any extra tools.

Rapid-spin



The free-turning sleeve allows screw steadying at the start of the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping. It can also be used as a short extension for ¼" applications e.g. in combination with the Wera Zyklop Ratchets.

Bit-Checks / Bit-Safes Universal

For general use

Bit-Check 10 TX Universal 1







1 bit holder with quick-release chuck, 9 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056164**001		
◉ ○	**894/4/1 K**	1 x 1/4"x51
✪	**867/1 TZ TORX®**	1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 27x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 10 TX Universal 2







1 bit holder Rapidaptor with quick-release chuck, 9 bits, tough, for universal use.

05**057115**001		
◉ ○	**888/4/1 K**	1 x 1/4"x50
✪	**867/1 TORX®**	1 x TX 6x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 7 Universal 1





1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, tough (Z), for universal use.

05**056295**001		
◉ ○	**893/4/1 K**	1 x 1/4"x50
✪	**851/1 Z PH**	1 x PH 1x25; 1 x PH 2x25
✪	**855/1 Z PZ**	1 x PZ 1x25; 1 x PZ 2x25
⊖	**800/1 Z**	1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 7 Universal 1 SB

	4013288
05**073406**001	036186
	◉ ○ **893/4/1 K** 1 x 1/4"x50 ✪ **851/1 Z PH** 1 x PH 1x25; 1 x PH 2x25 ✪ **855/1 Z PZ** 1 x PZ 1x25; 1 x PZ 2x25 ⊖ **800/1 Z** 1 x 1.0x5.5x25; 1 x 1.2x6.5x25



Bit-Check 7 Universal 2







1 bit holder with strong permanent magnet and quick-release chuck, 6 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056155**001		
	895/4/1 K	1 x 1/4"x52
	851/1 TZ PH	1 x PH 1x25; 1 x PH 2x25
	855/1 TZ PZ	1 x PZ 1x25; 1 x PZ 2x25
	800/1 TZ	1 x 1,0x5,5x25; 1 x 1,2x6,5x25

Bit-Check 7 Universal 3





1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, tough (Z), for universal use.

05**340322**001		
	893/4/1 K	1 x 1/4"x50
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	800/1 Z	1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	868/1 Z	1 x # 1x25; 1 x # 2x25

Bit-Check 7 Universal 4





1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, tough (Z), for universal use.

05**135810**001		
	893/4/1 K	1 x 1/4"x50
	851/1 Z PH	1 x PH 2x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25

Bit-Check 7 PZ Universal 1





1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, tough (Z), for universal use.

05**056296**001		
	893/4/1 K	1 x 1/4"x50
	855/1 Z PZ	2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25

Bit-Check 7 PZ Universal 1 SB

	4013288
05**073536**001	105998
	893/4/1 K 1 x 1/4"x50 **855/1 Z PZ** 2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25



Bit-Check 7 PZ Universal 2







1 bit holder with strong permanent magnet and quick-release chuck, 6 bits, Torsion-style (T) design to reduce premature wear, extra-hard (H).

05**056157**001		
	895/4/1 K	1 x 1/4"x52
	855/1 TH PZ	2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25



Bit-Checks / Bit-Safes Universal

For general use

Bit-Check 7 TX Universal 1



1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, tough, for universal use.

05**056294**001		
	893/4/1 K	1 x 1/4"x50
	867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 7 TX Universal 1 SB

	4013288
05**073404**001	038111
	893/4/1 K 1 x 1/4"x50 **867/1 TORX®** 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25



Bit-Check 7 TX BO Universal 1



1 bit holder with quick-release chuck, 6 bits, tough (Z), for universal use.

05**056158**001		
	894/4/1 K	1 x 1/4"x51
	867/1 Z TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25;
	BO	1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 7 Hex-Plus 1



1 bit holder with strong permanent magnet and quick-release chuck, 6 bits, tough (Z), for universal use.

05**056168**001		
	895/4/1 K	1 x 1/4"x52
	840/1 Z	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25;
	Hex-Plus	1 x 5,0x25; 1 x 6,0x25

Bit-Check 7 TiN Universal 1



1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, TiN coating for the hardness needed e.g. in series screwdriving operations.

05**056285**001		
	893/4/1 K	1 x 1/4"x50
	851/1 TiN PH	1 x PH 1x25; 1 x PH 2x25
	855/1 TiN PZ	1 x PZ 1x25; 1 x PZ 2x25
	800/1 TiN	1 x 0,8x5,5x25; 1 x 1,2x6,5x25

Bit-Check 7 TiN Universal 1 SB

	4013288
05**073537**001	106001
	893/4/1 K 1 x 1/4"x50 **851/1 TiN PH** 1 x PH 1x25; 1 x PH 2x25 **855/1 TiN PZ** 1 x PZ 1x25; 1 x PZ 2x25 **800/1 TiN** 1 x 0.8x5.5x25; 1 x 1.2x6.5x25



Tip

Bit-Check 7 TiN PZ Universal 1 SB



1 universal bit holder with stainless steel sleeve and strong permanent magnet, 6 bits, TiN coating for the hardness needed e.g. in series screwdriving operations.

			4013288
05**073538**001	**893/4/1 K**	1 x 1/4"x50	106018
	855/1 TiN PZ	2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25	

Bit-Check 6 Universal 1



6 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056474**001		
	851/4 TZ PH	1 x PH 1x50; 1 x PH 2x50
	855/4 TZ PZ	1 x PZ 1x50; 1 x PZ 2x50
	800/4 Z	1 x 1,0x5,5x50; 1 x 1,2x6,5x50

Bit-Check 6 Universal 1 SB

	4013288
05**073635**001	155276
	851/4 TZ PH 1 x PH 1x50; 1 x PH 2x50
	855/4 TZ PZ 1 x PZ 1x50; 1 x PZ 2x50
	800/4 Z 1 x 1.0x5.5x50; 1 x 1.2x6.5x50




TiN-Bits



TiN stands for titanium-nitrite. An extremely hard coating to withstand permanent loads such as during continual screwdriving operations in series manufacturing.

Universal holder with quick-release chuck



For a firm, wobble-free connection between holder and bit with quick-release action. Simply push sleeve forward to change bits.

Universal holder with stainless steel sleeve



The retaining ring and the strong permanent magnet ensure a particularly secure fitting of the bit in the holder.



Bit-Checks / Bit-Safes Universal

For general use

Bit-Check 6 Universal 2





6 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056473**001	
✪	**851/4 TZ PH** 1 x PH 2x50
✪	**855/4 TZ PZ** 1 x PZ 1x50; 1 x PZ 2x50
✪	**867/4 Z TORX®** 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50

Bit-Check 6 Universal 2 SB

	4013288
05**073638**001	155245
	✪ **851/4 TZ PH** 1 x PH 2x50 ✪ **855/4 TZ PZ** 1 x PZ 1x50; 1 x PZ 2x50 ✪ **867/4 Z TORX®** 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50



Bit-Check 6 Universal 3





6 bits, tough (Z), for universal use, 851/4 A extra-hard, profiled version, 868/1 V with holding function.

05**056479**001	
✪	**851/4 A PH** 1 x PH 1x50; 1 x PH 2x50
✪	**867/4 Z TORX®** 1 x TX 25x50; 1 x TX 30x50
✪	**868/4 V** 1 x # 1x50; 1 x # 2x50

Bit-Check 6 TX Universal 1





6 bits, tough (Z), for universal use.

05**056472**001	
✪	**867/4 Z TORX®** 1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50

Bit-Check 6 TX Universal 1 SB

	4013288
05**073637**001	155252
	✪ **867/4 Z TORX®** 1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50



Bit-Check 6 PZ Universal 1





6 bits, Torsion-style (T) design to reduce premature wear, tough (Z), for universal use.

05**056471**001	
✪	**855/4 TZ PZ** 2 x PZ 1x50; 3 x PZ 2x50; 1 x PZ 3x50

Bit-Check 6 TX HF 1



6 bits, holding function for TORX® socket screws made according to Acument Intellectual Properties specifications.

05**056476**001		
✪	**867/4 TORX® HF**	1 x TX 10x50; 1 x TX 15x50; 1 x TX 20x50; 1 x TX 25x50; 1 x TX 30x50; 1 x TX 40x50

Bit-Check 6 V Universal 1



6 bits, tough (Z), for universal use, with holding function.

05**056478**001		
○	**868/4 V**	1 x # 1x50; 3 x # 2x50; 2 x # 3x50


Tip

The HF profile



In tight assembly or disassembly situations, for example in engine compartments, it is not possible to securely hold the screw with the hand on the screwdriver, and the screw subsequently often gets lost. Lengthy searches or the loss of the screw (with the associated danger that could bring about) are the consequence. The HF tools developed by Wera are ideal because they feature an optimised geometry of the original TORX® profile. The wedging forces resulting from the surface pressure between the drive tip and the screw profile mean that the screw is securely held on the tool!

V bits: Holding function for Robertson screws



V bits have a conical profile. The clamping forces thus resulting hold Robertson screws securely on the tip of the tool. Ideal for screwdriving at difficult-to-access places.



Bit-Checks Wood

For wood applications

Bit-Safe 61 Wood 1







1 bit holder with strong permanent magnet and quick-release chuck, 60 bits, tough, for universal use.

05**057442**001		
	895/4/1 K	1 x 1/4"x52
	851/1 Z PH	3 x PH 1x25
	855/1 Z PZ	10 x PZ 1x25; 20 x PZ 2x25; 5 x PZ 3x25
	867/1 TORX®	3 x TX 10x25; 5 x TX 15x25; 5 x TX 20x25; 5 x TX 25x25; 2 x TX 30x25; 2 x TX 40x25

Bit-Check 30 Wood 1







1 magnetic Rapidaptor quick-release bit holder with ringmagnet, 29 bits, Torsion-style (T) design to reduce premature wear, tough, for universal use, extra-hard (H).

05**057433**001		
	887/4 RR	1 x 1/4"x57
	851/1 TZ PH	2 x PH 2x25; 1 x PH 3x25
	855/1 TH PZ	3 x PZ 1x25; 6 x PZ 2x25; 2 x PZ 3x25
	867/1 TZ TORX®	2 x TX 10x25; 2 x TX 15x25; 4 x TX 20x25; 4 x TX 25x25; 2 x TX 30x25; 1 x TX 40x25

Bit-Check 30 Wood 2





1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 29 bits, tough, for universal use.

05**057432**001		
	899/4/1	1 x 899/4/1 Kx1/4"x50
	851/1 Z PH	1 x PH 2x25
	855/1 Z PZ	2 x PZ 1x25; 5 x PZ 2x25; 2 x PZ 3x25
	867/1 TORX®	3 x TX 10x25; 4 x TX 15x25; 4 x TX 20x25; 4 x TX 25x25; 3 x TX 30x25; 1 x TX 40x25

Bit-Check 12 Wood 1







1 magnetic Rapidaptor quick-release bit holder with ringmagnet, 11 bits, Torsion-style (T) design to reduce premature wear, tough, for universal use, extra-hard (H).

05**057423**001		
	887/4 RR	1 x 1/4"x57
	855/1 TH PZ	1 x PZ 1x25; 2 x PZ 2x25; 1 x PZ 3x25
	851/1 TH PH	1 x PH 2x25
	867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 12 Wood 2



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 11 bits, tough, for universal use.

05**057422**001		
◉ ○	**899/4/1**	1 x 899/4/1 Kx1/4"x50
✪	**851/1 Z PH**	1 x PH 2x25
✪	**855/1 Z PZ**	1 x PZ 1x25; 2 x PZ 2x25; 1 x PZ 3x25
✪	**867/1 TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 12 Wood 3



1 universal bit holder with stainless steel sleeve and strong permanent magnet, 11 bits, tough, for universal use, 851/1 A extra-hard, profiled version, 868/1 V with holding function.

05**057426**001		
◉ ○	**893/4/1 K**	1 x 1/4“x50
✪	**851/1 A PH**	1 x PH 1x25; 1 x PH 2x25; 1 x PH 3x25
✪	**867/1 TORX®**	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
○	**868/1 V**	1 x # 2x25; 1 x # 3x25

Bit-Check 12 Wood 4



1 universal bit holder with stainless steel sleeve and strong permanent magnet, 11 bits, extra-hard, profiled version.

05**057427**001		
◉ ○	**893/4/1 K**	1 x 1/4“x50
✪	**851/1 A PH**	2 x PH 1x25; 6 x PH 2x25; 3 x PH 3x25

Tip

RING-MAGNET

Rapidaptor ring magnet




The floating, free-turning sleeve on the Rapidaptor with powerful ring magnet securely holds even large and heavy screws.



There is no need to hold the screw when applying the tool – something which can be dangerous and painful!

Universal holder with quick-release chuck



For a firm, wobble-free connection between holder and bit with quick-release action. Simply push sleeve forward to change bits.

Universal holder with stainless steel sleeve



The retaining ring and the strong permanent magnet ensure a particularly secure fitting of the bit in the holder.



Bit-Checks Metal

For steel applications

Bit-Check 30 Metal 1



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 29 bits, tough (Z), for universal use.

05**057434**001		
	899/4/1	1 x 899/4/1 Kx1/4"x50
	851/1 Z PH	3 x PH 1x25; 3 x PH 2x25; 2 x PH 3x25
	855/1 Z PZ	3 x PZ 1x25; 3 x PZ 2x25; 3 x PZ 3x25
	867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25
	800/1 Z	1 x 0,6x4,5x25; 1 x 1,0x5,5x25; 1 x 1,2x6,5x25
	840/1 Z Hex-Plus	1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

Bit-Check 12 Metal 1



1 universal bit holder with stainless steel sleeve, retaining ring, and strong permanent magnet, 11 bits, tough (Z), for universal use.

05**057424**001		
	899/4/1	1 x 899/4/1 Kx1/4"x50
	851/1 Z PH	1 x PH 1x25; 1 x PH 2x25
	855/1 Z PZ	1 x PZ 1x25; 1 x PZ 2x25
	867/1 TORX®	1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
	840/1 Z Hex-Plus	1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25



Bit Sets for Special Applications

Screwdriving, Drilling, Tapping, Countersinking and Deburring

843 Stepped drill bits, 4-20 mm



Construction: 9 drill steps increasing by 2 mm for material with a max. thickness of 4.5 mm. With edge breaker (sheet metal countersink) at Ø 10 for 1-mm sheet metal

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 holders

	mm
05**104672**001	75,0

844/7 Tap Bits Set



7 pieces in robust case

1 universal bit holder 888/4/1 K Rapidaptor, nonmagnetic, suitable for power tools and electronic drills; single tap bits with 1/4" drive, suitable for holders with DIN ISO 1173-D 6,3 receiver.

05**104654**001		
	888/4/1 K	1 x 1/4"x50
	844	1 x 3,0x33,0; 1 x 4,0x35,0; 1 x 5,0x36,0; 1 x 6,0x40,0; 1 x 8,0x40,0; 1 x 10,0x40,0

844 Single Tap Bits



Application: For cutting metric threads

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 holders

	mm	mm	mm	
05**104666**001	3,0	10,00	33,0	M 3
05**104667**001	4,0	11,00	35,0	M 4
05**104668**001	5,0	12,50	36,0	M 5
05**104669**001	6,0	18,00	40,0	M 6
05**104670**001	8,0	20,00	40,0	M 8
05**104671**001	10,0	20,00	40,0	M 10

845 1-flute Countersink Bits



Application: For countersinking and deburring

Design: 1-flute

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 holders

	mm	mm	mm	
05**104660**001	6,30	21,00	32,0	M 3
05**104661**001	8,30	21,00	32,0	M 4
05**104662**001	10,40	21,00	34,0	M 5
05**104663**001	12,40	21,00	36,0	M 6
05**104664**001	16,50	22,00	40,0	M 8
05**104665**001	20,50	22,00	43,0	M 10



Bit Sets for Special Applications

Screwdriving, Drilling, Tapping, Countersinking and Deburring

845/8 1-flute Countersink Bits Set



8 pieces in robust case

1 Kraftform 816 R Rapidaptor quick release bit holder; 1 universal holder 888/4/1 K Rapidaptor, nonmagnetic, suitable for power tools and electronic drills.

05**104655**001		
	816 R	1 x 1/4"x119
	888/4/1 K	1 x 1/4"x50
	845	1 x 6,30x32,0; 1 x 8,30x32,0; 1 x 10,40x34,0; 1 x 12,40x36,0; 1 x 16,50x40,0; 1 x 20,50x43,0

847 HSS Combined Tap Bits



Application: Drilling, tapping, deburring

Design: HSS

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 holders

	mm	mm	mm	
05**104640**001	2,5	12,00	36,0	M 3
05**104641**001	3,3	12,00	39,0	M 4
05**104642**001	4,2	12,00	41,0	M 5
05**104643**001	5,0	12,00	44,0	M 6
05**104644**001	6,8	12,00	51,0	M 8
05**104645**001	8,5	12,00	59,0	M 10

846 3-flute Countersink Bit



Application: For deburring, chamfering, countersinking

Design: 3-flute 90° DIN 335-C cutter

Drive: 1/4" hexagon suitable for holders with DIN ISO 1173-D 6,3 receiver

	mm	mm	mm	
05**104630**001	6,30	20,00	31,0	M 3
05**104631**001	8,30	20,00	31,0	M 4
05**104632**001	10,40	20,00	34,0	M 5
05**104633**001	12,40	20,00	35,0	M 6
05**104634**001	16,50	20,00	40,0	M 8
05**104635**001	20,50	20,00	41,0	M 10

846/8 3-flute Countersink Bits Set



8 pieces in robust case

1 Kraftform quick release bitholding screwdriver 816 R

1 universal bit holder 888/4/1 K Rapidaptor suitable for power tools and electronic drills; countersink bits with 1/4" drive suitable for power tools with DIN ISO 1173-D 6,3 receiver.

05**104650**001		
	816 R	1 x 1/4"x119
	888/4/1 K	1 x 1/4"x50
	846 HSS	1 x 6,30x31,0; 1 x 8,30x31,0; 1 x 10,40x34,0; 1 x 12,40x35,0; 1 x 16,50x40,0; 1 x 20,50x41,0

847/7 Set Combination Drill Bits Set



7 pieces in robust case

1 Universal bit holder Rapidaptor 888/4/1 K with quick-release chuck suitable for power tools and electronic drills; combination drill bits, 1/4" drive, suitable for power tools with DIN ISO 1173-D 6,3 receiver.

05**104651**001		
	888/4/1 K	1 x 1/4"x50
	847 HSS	1 x 2,5x36,0; 1 x 3,3x39,0; 1 x 4,2x41,0; 1 x 5,0x44,0; 1 x 6,8x51,0; 1 x 8,5x59,0

849 HSS Twist Wood Drill Bits



Application: For point-precision, splinter-free drilling in soft woods, hard woods, and laminated panel material

Design: HSS

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 holders

	mm	mm	mm
05**104600**001	3,0	32,00	70,0
05**104601**001	4,0	32,00	74,0
05**104602**001	5,0	43,00	85,0
05**104603**001	6,0	45,00	95,0
05**104604**001	8,0	60,00	110,0
05**104605**001	10,0	70,00	120,0

848 HSS Metal Twist Drill Bits



Application: For precise drilling in metal

Construction: HSS

Drive: 1/4" hexagon, suitable for DIN ISO 1173-D 6,3 holders

	mm	mm	mm
05**104610**001	3,0	16,00	38,0
05**104611**001	3,1	18,00	40,0
05**104612**001	3,3	18,00	40,0
05**104613**001	4,0	20,00	44,0
05**104614**001	4,1	20,00	44,0
05**104615**001	4,2	20,00	45,0
05**104616**001	5,0	26,00	50,0
05**104617**001	5,1	26,00	50,0
05**104618**001	6,0	26,00	50,0
05**104619**001	6,8	30,00	50,0
05**104620**001	8,0	32,00	51,0
05**104621**001	8,5	33,00	53,0
05**104622**001	10,0	38,00	54,0

848/851/867/19 Metal Twist Drill Bits and Bits Set



19 pieces in robust belt pouch

1 Universal bit holder Rapidaptor 888/4/1 K suitable for power tools and electronic drills; metal twist Drill Bits and Bits with 1/4" drive, suitable for power tools with DIN ISO 1173-D 6,3 receiver.

05**104652**001		
	888/4/1 K	1 x 1/4"x50
	851/1 TZ PH	2 x PH 1x25; 3 x PH 2x25; 1 x PH 3x25
	848 HSS	1 x 3,0x38,0; 1 x 4,0x44,0; 1 x 4,2x45,0; 1 x 5,0x50,0; 1 x 6,0x50,0; 1 x 8,0x51,0
	867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25



849/855/867/18 Wood Twist Drill Bits and Bits Set



18 pieces in robust belt pouch

1 Universal bit holder Rapidaptor 889/4/1 K suitable for power tools and electronic drills; wood Twist Drill Bit and Bits, $^{1}/_{4}$" drive, suitable for power tools with DIN ISO 1173-D 6,3 receiver.

05**104653**001		
	889/4/1 K	1 x 1/4"x50
	849 HSS	1 x 3,0x70,0; 1 x 4,0x74,0; 1 x 5,0x85,0; 1 x 6,0x95,0; 1 x 8,0x110,0
	855/1 TH PZ	2 x PZ 1x25; 3 x PZ 2x25; 1 x PZ 3x25
	867/1 TORX®	1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25; 1 x TX 40x25

Bit-Check 10 Drywall 1



1 bit holder 896/4/1 out of Aluminium with adjustable depth stop suitable for power tools and electronic drills; screw depth can be infinitely adjusted and enables flush alignment of sunken screws; 9 drywall construction bits with modified drive shaft; length 25mm

05**136011**001		
	896/4/1	1 x 1/4"x50
	851/1 RZ PH	9 x PH 2x25

Tip

Bit holder with adjustable depth stop





The screw installation depth can be infinitely adjusted and allows the desired degree of countersinking of the screws.




40-200 Nm
Wera
Wera

Torque Tools

	Series 7400 Adjustable Torque Screwdrivers	470
	Series 7400 Pre-set, Adjustable Torque Screwdrivers	478
	Series Torque-indicators	484
	Series Click-Torque Wrenches	490
	Series Insert Tools	502



Torque Tools

Wera‘s torque tools offer torque-controlled screw tightening so as to avoid damage to the screw or workpiece and to ensure the integrity of the screw connection. This makes work-intensive drilling-out of screws and unproductive downtimes a thing of the past. It is also important whenever repeat accuracy is required.

They come with an ergonomic Kraftform handle and have a distinctly audible and perceptible click signal whenever the required torque value is reached.

No time-consuming blade changes; instead of special blades, conventional bits conforming to C 6,3 and E 6,3 or even ¼" sockets can be used.



Adjustable torque screwdrivers

They can be adjusted by hand to the corresponding scale value. Also available in ESD version (also with take-up for HIOS/Halfmoon bits) and with Kraftform Micro handle.
See page 470.
For the insulated VDE-version see page 114.



Pre-set, adjustable torque screwdrivers

Pre-set torque, adjustable within a defined range. Also available in ESD version (also for HIOS/Halfmoon bits) and with Kraftform Micro handle.
See page 478.





Torque-indicators

Suitable for applications requiring a non-adjustable i.e. a tamperproof torque blade assembly.
See page 484.



Series Click-Torque wrenches

Suitable for controlled tightening using sockets.
See page 490.



Adjustable Torque Screwdrivers

Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.





Simple setting of the required torque by hand.



Easy-to-read scale value.



Measurement accuracy is ± 6 % in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

All Wera torque screwdrivers manufactured according to DIN EN ISO 6789 are supplied with a calibration certificate. Our workshop offers a comprehensive service for all Wera torque tools. Please contact us with any queries regarding service, recalibration or repair on +49 (0)202 40 45 145; Fax: +49 (0)202 40 45 158 or per E-Mail at: torqueservice@wera.de.



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.



Unlimited torque for loosening seized screws.



Multi-component Kraftform handle with hard and soft zones for fast working speeds and protecting the palm of the hand.



For the insulated VDE-version see page 114.

Series 7400 Kraftform Torque Screwdrivers

Variable torque adjustment models

Series 7400 Kraftform adjustable torque screwdrivers (0.1-3.0 Nm) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale, audible excess-load signal

Handle: Kraftform with non-roll feature, multi-component

	Art.No.	mm		Nm	Nm	mm	
05**074770**001 [1]	7430	89	1/4"	0,10-0,34	0,015	142	5 7/16"
05**074772**001 [1]	7431	89	1/4"	0,30-1,00	0,05	142	5 7/16"
05**074774**001 [1]	7432	89	1/4"	0,90-1,50	0,05	142	5 7/16"
05**074700**001	7440	105	1/4"	0,3-1,2	0,05	155	6"
05**074701**001	7441	105	1/4"	1,2-3,0	0,10	155	6"

[1] With attachable magnifying glass, dramatically improving visibility.

Series 7400 Kraftform pistol grip, adjustable torque screwdrivers (3.0-8.8 Nm) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale, audible excess-load signal

Handle: Kraftform pistol grip, multi-component

	Art.No.		Nm	Nm	mm	mm	
05**074702**001	7442	1/4"	3,0-6,0	0,25	150	100	4"
05**074705**001	7443	1/4"	4,0-8,8	0,40	150	100	4"

Series 7400 Kraftform ESD adjustable torque screwdrivers (0.1-3.0 Nm) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, non-magnetic

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale, audible excess-load signal


Handle: Kraftform with non-roll feature, multi-component

	Art.No.	mm		Nm	Nm	mm	
05**074780**001 [1]	7430 ESD	89	1/4"	0,10-0,34	0,015	142	5 7/16"
05**074782**001 [1]	7431 ESD	89	1/4"	0,30-1,00	0,05	142	5 7/16"
05**074784**001 [1]	7432 ESD	89	1/4"	0,90-1,50	0,05	142	5 7/16"
05**074730**001	7440 ESD	105	1/4"	0,3-1,2	0,05	155	6"
05**074731**001	7441 ESD	105	1/4"	1,2-3,0	0,10	155	6"

[1] With attachable magnifying glass, dramatically improving visibility.

Rapidaptor

Rapid-in and self-lock




The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Chuck-all



The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Attachable magnifying glass



Articles 7430, 7431, 7432, 7430 ESD, 7431 ESD, 7432 ESD, 7435 ESD, 7436 ESD, 1430 ESD and 1431 ESD all come with a magnifying glass. This can be easily attached on to the scale, dramatically improving visibility.

Series 7400 Kraftform Torque Screwdrivers

Variable torque adjustment models

Series 7400 Kraftform pistol grip, adjustable torque screwdrivers (25.0-55.0 in. lbs.) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale. Audible excess-load signal

Handle: Kraftform pistol grip, multi-component

	Art.No.		in. lbs.	in. lbs.	mm	mm		
05**074712**001	7447	1/4"	25,0-55,0	2,5	150	100	4"	1

Series 7400 Kraftform adjustable torque screwdrivers (2.5-29.0 in. lbs.) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale. Audible excess-load signal

Handle: Kraftform with non-roll feature, multi-component

	Art.No.		in. lbs.	in. lbs.	mm	
05**074710**001	7445	1/4"	2,5-11,5	0,5	155	6"
05**074711**001	7446	1/4"	11,0-29,0	1,0	155	6"

Series 7400 Kraftform ESD adjustable torque screwdrivers (2.5-29.0 in.lbs.) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology, non-magnetic

Accuracy: ±6 % (DIN EN ISO 6789). Numerical torque value scale. Audible excess-load signal

Handle: Kraftform with non-roll feature, multi-component

	Art.No.		in. lbs.	in. lbs.	mm	
05**074733**001	7445 ESD	1/4"	2,5-11,5	0,5	155	6"
05**074734**001	7446 ESD	1/4"	11,0-29,0	1,0	155	6"

Series 7400 Kraftform ESD adjustable torque screwdrivers (0.1-1.0 Nm)





Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck for rapid bit change

Accuracy: ±6 % (DIN EN ISO 6789)

Handle: Kraftform with non-roll feature, multi-component

	Art.No.	mm	Nm	Nm	mm	
05**074786**001 [1]	7435 ESD	89	0,10-0,34	0,015	142	5 7/16"
05**074788**001 [1]	7436 ESD	89	0,30-1,00	0,05	142	5 7/16"

[1] With attachable magnifying glass, dramatically improving visibility.

1430 Kraftform Micro ESD adjustable torque screwdrivers (0.02-0.11 Nm) with quick-release chuck





Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck for rapid bit change

Accuracy: ± 10%

Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	Art.No.	Nm	Nm	mm	
05**074802**001 [1]	1430 ESD	0,02-0,06	0,0025	141	5 7/16"
05**074804**001 [1]	1431 ESD	0,05-0,11	0,005	141	5 7/16"

[1] With attachable magnifying glass, dramatically improving visibility.

Tip

Attachable magnifying glass



Articles 7435 ESD, 7436 ESD, 1430 ESD and 1431 ESD, all come with a magnifying glass. This can be easily attached on to the scale, dramatically improving visibility.

Why does Wera manufacture adjustable Kraftform torque screwdrivers?



Many screws – particularly in assembly and maintenance applications – have to be tightened with controlled torque to ensure the dependability of the screw connection and/or to avoid damage to the screw or work piece. Wera's adjustable torque screwdrivers are the ideal tool for this. They feature a torque range of 0.3 Nm to 8.8 Nm, two different handles, measurement accuracy of ± 6 % and Rapidaptor technology for rapid bit change.

For Halfmoon and HIOS Bits



The adjustable torque screwdrivers 7435 ESD, 7436 ESD, 1430 ESD and 1431 ESD feature a combination bitholder for both bits with Halfmoon and bits with HIOS drive.

Series 7400 Kraftform Torque Screwdrivers

Variable torque adjustment models

7440/41 Kraftform torque screwdriver set 0.3-3.0 Nm



05**074738**001		
◉	**7400**	1 x 7440x1/4"x0,3-1,2; 1 x 7441x1/4"x1,2-3,0
✪	**867/1 TZ TORX®**	1 x TX 6x25; 1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
✪	**867/1 Z IP TORX PLUS®**	1 x 6 IPx25; 1 x 7 IPx25; 1 x 8 IPx25; 1 x 9 IPx25; 1 x 10 IPx25; 1 x 15 IPx25; 1 x 20 IPx25; 1 x 25 IPx25; 1 x 30 IPx25
○	**840/1 Z Hex-Plus**	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

7440/41/42 Kraftform torque screwdriver set 0.3-6.0 Nm



05**074739**001		
◉	**7400**	1 x 7440x1/4"x0,3-1,2; 1 x 7441x1/4"x1,2-3,0
◉	**7400 Pistole**	1 x 7442x3,0-6,0
✪	**867/1 TZ TORX®**	1 x TX 6x25; 1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
✪	**867/1 Z IP TORX PLUS®**	1 x 6 IPx25; 1 x 7 IPx25; 1 x 8 IPx25; 1 x 9 IPx25; 1 x 10 IPx25; 1 x 15 IPx25; 1 x 20 IPx25; 1 x 25 IPx25; 1 x 30 IPx25
○	**840/1 Z Hex-Plus**	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

7445/46/47 Kraftform torque screwdriver set 2.5-55.0 in.lbs.



05**350451**001		
◉	**7400 inch**	1 x 7445x2,5-11,5; 1 x 7446x11,0-29,0
◉	**7400 Pistole inch**	1 x 7447x25,0-55,0
✪	**867/1 TZ TORX®**	1 x TX 6x25; 1 x TX 7x25; 1 x TX 8x25; 1 x TX 9x25; 1 x TX 10x25; 1 x TX 15x25; 1 x TX 20x25; 1 x TX 25x25; 1 x TX 30x25
✪	**867/1 Z IP TORX PLUS®**	1 x 6 IPx25; 1 x 7 IPx25; 1 x 8 IPx25; 1 x 9 IPx25; 1 x 10 IPx25; 1 x 15 IPx25; 1 x 20 IPx25; 1 x 25 IPx25; 1 x 30 IPx25
○	**840/1 Z Hex-Plus**	1 x 2,0x25; 1 x 2,5x25; 1 x 3,0x25; 1 x 4,0x25; 1 x 5,0x25; 1 x 6,0x25

7443/61/9 Assembly set for tyre pressure control systems



05**074745**001		
◉	**7400 vor**	1 x 7461x3,3 [1]
◉	**7400 Pistole**	1 x 7443x4,0-8,8
✪	**300 TX**	1 x TX 10x1,4
○○	**870/1**	1 x 1/4"x25
◉	**790 A/50**	1 x 11,0x50,0; 1 x 12,0x50,0
✪	**867/4 TORX® HF**	1 x TX 15x50; 1 x TX 20x50
○	**327**	1 x 32

[1] Other pre-set values within the adjustable range <3.3 Nm can be delivered on request

Tip

Assembly sets for tyre control systems




Suitable for all leading system suppliers like Alligator, Beru, CUB, Herth & Buss, Schrader, VDO/ Conti.

Including adjustable and pre-set torque tools, colour-coded valve insertion tool and valve dolly. The robust foam insert provides for a practical arrangement system.





7443/12 Assembly set for tyre pressure control systems





Suitable for all leading system suppliers such as Alligator, Beru, CUB, Herth & Buss, Schrader, VDO/Conti.
1 adjustable torque screwdriver, pistol handle, 4.0-8.8 Nm; 1 pre-set torque screwdriver 3.3 Nm; 1 pre-set torque screwdriver 1.4 Nm TX 10; 1 pre-set torque screwdriver 1.25 Nm TX 10; 1 valve dolly; 1 bit 867/4 HF TX 15 x 50 mm, with holding function for TORX® screws: 1 bit 867/4 HF TX 20 x 50 mm, with holding function for TORX® screws; 1 socket 790 A/50 SW 11.0 x 50 mm 1 socket 790 A/50 SW 12.0 x 50 mm; 1 adaptor 870/1; ¼" hexagon to ¼" square; 1 valve insertion tool, pre-set torque: 0.25 Nm; 1 valve insertion tool, pre-set torque: 0.45 Nm.
Practically arranged in a robust foam insert.

05**074746**001		
◉	**7400 Pistole**	1 x 7443x4,0-8,8
◉	**7400 vor**	1 x 7461x3,3[1)]
✪	**300 TX**	1 x TX 10x1,25; 1 x TX 10x1,4
◉	**790 A/50**	1 x 11,0x50,0; 1 x 12,0x50,0
✪	**867/4 TORX® HF**	1 x TX 15x50; 1 x TX 20x50
▢○	**870/1**	1 x 1/4"x25
⚉	**300 V**	1 x 0,25; 1 x 0,45
○	**327**	1 x 32

[1)] Other pre-set values within the adjustable range < 3.3 Nm can be delivered on request

Pre-set, adjustable Torque Screwdrivers

These tools are ideal for all applications where a constant, identical torque is required and where a high degree of repeat accuracy is needed. The torque value can be adjusted within the measuring range.





Unlimited torque for loosening seized screws.



Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.





Multi-component Kraftform handle with hard and soft zones for fast working speeds and protecting the palm of the hand.

All Wera torque screwdrivers manufactured according to DIN EN ISO 6789 are supplied with a calibration certificate. Our workshop offers a comprehensive service for all Wera torque tools. Please contact us with any queries regarding service, recalibration or repair on +49 (0)202 40 45 145; Fax: +49 (0)202 40 45 158 or per E-Mail at: torqueservice@wera.de.

Series 7400 Kraftform Torque Screwdrivers

Pre-set, adjustable torque models

Serie 7400 Kraftform pre-set adjustable torque screwdrivers (0.1-3.0 Nm) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Pre-set torque: 0.1 Nm, 0.3 Nm, 0.9 Nm, 1.2 Nm

Accuracy: ± 6% (DIN EN ISO 6789)

Handle: Kraftform with non-roll feature, multi-component

	Art.No.	mm		Nm	Nm	mm	
05**074790**001	7450	89	1/4"	0,1	0,1-0,34	133	5 1/4"
05**074790**010 [1]	7450	89	1/4"	0,1	0,1-0,34	133	5 1/4"
05**074792**001	7451	89	1/4"	0,3	0,3-1,0	133	5 1/4"
05**074792**010 [1]	7451	89	1/4"	0,3	0,3-1,0	133	5 1/4"
05**074794**001	7452	89	1/4"	0,9	0,9-1,5	133	5 1/4"
05**074794**010 [1]	7452	89	1/4"	0,9	0,9-1,5	133	5 1/4"
05**074715**001	7460	105	1/4"	0,3	0,3-1,2	155	6"
05**074715**010 [1]	7460	105	1/4"	0,3	0,3-1,2	155	6"
05**074716**001	7461	105	1/4"	1,2	1,2-3,0	155	6"
05**074716**010 [1]	7461	105	1/4"	1,2	1,2-3,0	155	6"

[1] Other pre-set values within the adjustable range can be delivered on request

Series 7400 Kraftform pistol grip, pre-set adjustable torque screwdrivers (3.0-8.8 Nm) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Pre-set torque: 3.0 Nm, 4.0 Nm

Accuracy: ±6 % (DIN EN ISO 6789)

Handle: Kraftform pistol grip, multi-component

	Art.No.		Nm	Nm	mm	mm		
05**074717**001	7462	1/4"	3,0	3,0-6,0	150	100	6"	4"
05**074717**010 [1]	7462	1/4"	3,0	3,0-6,0	150	100	6"	4"
05**074728**001	7463	1/4"	4,0	4,0-8,8	150	100	6"	4"
05**074728**010 [1]	7463	1/4"	4,0	4,0-8,8	150	100	6"	4"

[1] Other pre-set values within the adjustable range can be delivered on request

Serie 7400 Kraftform ESD pre-set adjustable torque screwdrivers (0.1-1.2 Nm) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Pre-set torque: 0.1 Nm, 0.3 Nm, 0.9 Nm, 1.2 Nm

Accuracy: ± 6% (DIN EN ISO 6789)

Handle: Kraftform with non-roll feature, multi-component

	Art.No.	mm		Nm	Nm	mm	
05**074820**001	7450 ESD	89	1/4"	0,1	0,1-0,34	133	5 1/4"
05**074820**010 [1]	7450 ESD	89	1/4"	0,1	0,1-0,34	133	5 1/4"
05**074822**001	7451 ESD	89	1/4"	0,3	0,3-1,0	133	5 1/4"
05**074822**010 [1]	7451 ESD	89	1/4"	0,3	0,3-1,0	133	5 1/4"
05**074824**001	7452 ESD	89	1/4"	0,9	0,9-1,5	133	5 1/4"
05**074824**010 [1]	7452 ESD	89	1/4"	0,9	0,9-1,5	133	5 1/4"
05**074840**001	7460 ESD	105	1/4"	0,3	0,3-1,2	155	6"
05**074840**010 [1]	7460 ESD	105	1/4"	0,3	0,3-1,2	155	6"
05**074842**001	7461 ESD	105	1/4"	1,2	1,2-3,0	155	6"
05**074842**010 [1]	7461 ESD	105	1/4"	1,2	1,2-3,0	155	6"

[1] Other pre-set values within the adjustable range can be delivered on request

Tip

Why does Wera manufacture pre-set, adjustable Kraftform torque screwdrivers?



These torque screwdrivers are supplied with a fixed pre-set torque value. This is ideal for all applications that require constant, identical torque. They feature a pre-set torque range of 0.3 Nm to 4.0 Nm (adjustable between 0.3 Nm – 8.8 Nm), two different handles, measurement accuracy of ± 6 % and Rapidaptor chuck technology for rapid bit change.

Customized pre-setting



The pre-set torque screwdrivers of the Kraftform 7400 series can be individually pre-set within the specified adjustable range.



Series 7400 Kraftform Torque Screwdrivers

Pre-set, adjustable torque models

Series 7400 Kraftform pre-set adjustable torque screwdrivers (2.5-29.0 in. lbs.) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Pre-set torque: 2.5 in.lbs., 11.0 in.lbs.

Accuracy: ±6 % (DIN EN ISO 6789)

Handle: Kraftform with non-roll feature, multi-component

	Art.No.		in. lbs.	in. lbs.	mm	
05**074720**001	7465	1/4"	2,5	2,5-11,5	155	6"
05**074720**010 [1]	7465	1/4"	2,5	2,5-11,5	155	6"
05**074722**001	7466	1/4"	11,0	11,0-29,0	155	6"
05**074722**010 [1]	7466	1/4"	11,0	11,0-29,0	155	6"

[1] Other pre-set values within the adjustable range can be delivered on request

Series 7400 Kraftform pistol grip, pre-set adjustable torque screwdriver (25.0-55.0 in. lbs.) with Rapidaptor quick-release chuck



Application: Suitable for 1/4" DIN ISO 1173-C 6,3 and E 6,3 hexagon insert bits and Wera Series 1 and 4

Design: Rapidaptor rapid-in, rapid-out, rapid-spin, chuck-all and single-hand technology

Pre-set torque: 25.0 in. lbs.

Accuracy: ±6 % (DIN EN ISO 6789)

Handle: Kraftform pistol grip, multi-component

	Art.No.		in. lbs.	in. lbs.	mm	mm		
05**074721**001	7467	1/4"	25,0	25,0-55,0	150	100	6"	4"
05**074721**010 [1]	7467	1/4"	25,0	25,0-55,0	150	100	6"	4"

[1] Other pre-set values within the adjustable range can be delivered on request

Serie 7400 Kraftform pre-set adjustable torque screwdrivers (0.1-1.0 Nm) with quick-release chuck



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck for rapid bit change

Pre-set torque: 0.1 Nm, 0.3 Nm

Accuracy: ± 6% (DIN EN ISO 6789)

Handle: Kraftform with non-roll feature, multi-component

	Art.No.	mm	Nm	Nm	mm	
05**074826**001	7455 ESD	89	0,015	0,1-0,34	138	5 1/4"
05**074826**010 [1]	7455 ESD	89	0,015	0,1-0,34	138	5 1/4"
05**074828**001	7456 ESD	89	0,035	0,3-1,0	138	5 1/4"
05**074828**010 [1]	7456 ESD	89	0,035	0,3-1,0	138	5 1/4"

[1] Other pre-set values within the adjustable range can be delivered on request

1460 Kraftform Micro ESD pre-set adjustable torque screwdrivers (0.02-0.11 Nm) with quick-release chuck



Application: Suitable for bits with 4 mm Halfmoon drive (and Wera Serie 9) and 4 mm HIOS drive (and Wera Series 21)

Design: With quick-release chuck for rapid bit change

Pre-set torque: 0.035 Nm, 0.05 Nm

Accuracy: ± 10%

Handle: Kraftform Micro with non-roll feature and rotating cap, multi-component

	Art.No.	Nm	Nm	mm	
05**074800**001	1460 ESD	0,035	0,02-0,06	131	5 1/4"
05**074800**010 [1]	1460 ESD	0,035	0,02-0,06	131	5 1/4"
05**074810**001	1461 ESD	0,050	0,05-0,11	131	5 1/4"
05**074810**010 [1]	1461 ESD	0,050	0,05-0,11	131	5 1/4"

[1] Other pre-set values within the adjustable range can be delivered on request

Tip

ESD-safe tools



The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.

For Halfmoon and HIOS Bits



The adjustable torque screwdrivers 7455 ESD, 7456 ESD, 1460 ESD and 1461 ESD feature a combination bitholder for both bits with Halfmoon and bits with HIOS drive.

Customized pre-setting



The pre-set torque screwdrivers of the Kraftform 7400 series can be individually pre-set within the specified adjustable range.

Torque-indicators

Wera torque-indicators have been factory pre-set to values recommended by leading carbide tool manufacturers. These tightening values relate specifically to the size of the TORX®, TORX PLUS® or hexagon socket screw. Torque indicators ensure safe and easy loosening of screw connections. Precision : ± 10 %



Torque blade assembly precisely adjusted to the respective screw size for the TORX®, TORX PLUS® and hexagon socket screw profiles.



Non-adjustable and tamperproof.




Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.






Slim 4 mm hexagon blades to reach screws in difficult-to-access places.



Unlimited torque for loosening seized screws.



Multi-component Kraftform handle with hard and soft zones for fast working speeds and protecting the palm of the hand.


TX 10
20 Nm

Series
Torque-indicators
Pre-set torque models

300 Hex torque-indicator



Application: Hexagon socket screws

Pre-set torque: 1.4 Nm-3.0 Nm (1.0 ft.lb.-2.2 ft.lb.), fixed pre-sets

Accuracy: ±10 %

Blade: Hexagonal, 4 mm, reduced diameter tip

Design: Hex-Plus, Black Point

Handle: Kraftform with non-roll feature, multi-component

		Nm	ft. lb.	mm	mm	mm	mm	
05**027910**001	2,0	1,4	1,0	4	3,5	65	105	2 9/16"
05**027911**001	2,5	2,0	1,5	4	3,8	65	105	2 9/16"
05**027912**001	3,0	3,0	2,2	4	3,8	65	105	2 9/16"

300 IP TORX PLUS® torque-indicator



Application: TORX PLUS® socket screws

Pre-set torque: 0.6 Nm-3.0 Nm (0.4 ft.lb.-3.0 ft.lb.), fixed pre-sets

Accuracy: ±10 %

Blade: Hexagonal, 4 mm, reduced diameter tip

Design: Black Point

Handle: Kraftform with non-roll feature, multi-component

		Nm	ft. lb.	mm	mm	mm	mm	
05**028040**001	6 IP	0,6	0,4	4	3,5	65	105	2 9/16"
05**028041**001	7 IP	0,9	0,7	4	3,5	65	105	2 9/16"
05**028042**001	8 IP	1,2	0,9	4	3,5	65	105	2 9/16"
05**028043**001	9 IP	1,4	1,0	4	3,5	65	105	2 9/16"
05**028044**001	10 IP	2,0	1,5	4	3,8	65	105	2 9/16"
05**028045**001	15 IP	3,0	2,2	4	3,8	65	105	2 9/16"

300 Hex torque-indicator, pistol grip



Application: Hexagon socket screws

Pre-set torque: 5.0 Nm (3.7 ft. lb.), fixed pre-set

Accuracy: ±10 %

Blade: Hexagonal, 8 mm, reduced diameter tip

Design: Hex-Plus, Black Point

Handle: Kraftform pistol grip, multi-component

		mm	mm	mm		mm	
05**027913**001	4,0	160	100	65	2 9/16"	25	1"

300 TX TORX® torque-indicator



Application: TORX® socket screws

Pre-set torque: 0.6 Nm-3.0 Nm (0.4 ft.lb.-2.2 ft.lb.), fixed pre-sets

Accuracy: ±10 %

Blade: Hexagonal, 4 mm, reduced diameter tip

Design: Black Point

Handle: Kraftform with non-roll feature, multi-component

		Nm	ft. lb.	mm	mm	mm	mm	
05**027930**001	TX 6	0,6	0,4	4	3,5	65	105	2 9/16"
05**027931**001	TX 7	0,9	0,7	4	3,5	65	105	2 9/16"
05**027932**001	TX 8	1,2	0,9	4	3,5	65	105	2 9/16"
05**027933**001	TX 9	1,4	1,0	4	3,5	65	105	2 9/16"
05**027934**001	TX 10	2,0	1,5	4	3,8	65	105	2 9/16"
05**027935**001	TX 15	3,0	2,2	4	3,8	65	105	2 9/16"

300 IP TORX PLUS® torque-indicator, pistol grip



Application: TORX PLUS® socket screws
Pre-set torque: 5.0 Nm (3.7 ft. lb.), fixed pre-set
Accuracy: ±10 %
Blade: Hexagonal, 8 mm, reduced diameter tip
Design: Black Point
Handle: Kraftform pistol grip, multi-component

		mm	mm	mm		mm	
05**028046**001	20 IP	160	100	65	2 9/16"	25	1"

300 TX TORX® torque-indicator, pistol grip



Application: TORX® socket screws
Pre-set torque: 5.0 Nm (3.7 ft. lb.), fixed pre-set
Accuracy: ±10 %
Blade: Hexagonal, 8 mm, reduced diameter tip
Design: Black Point
Handle: Kraftform pistol grip, multi-component

		mm	mm	mm		mm	
05**027936**001	TX 20	160	100	65	2 9/16"	25	1"

Tip

Less is often more



Some screw connections require specific torque values so that they can be tightened or loosened easily. Wera torque-indicators are pre-set to torque values recommended by leading carbide tool manufacturers. Pre-set torque between 0.6 Nm and 5.0 Nm, for TORX®, TORX PLUS® and hexagon socket screws, unlimited loosening torque, two handles, tamper-proof.




SINUMERIK
Betriebsart EINRICHTEN, Funktionsanwahl

Click-Torque Wrench Series

We wanted working with torque wrenches to be simple and accurate – which is why we developed the Click-Torque wrenches.

With the ability to set and save the default values and with the unmistakable, robust Wera design, these torque wrenches are the ideal tools for all bolting applications that require torque-controlled tightening (clockwise torque wrenches) and tightening and loosening (torque wrenches for insert tools).



Precise to ± 3% as per DIN EN ISO 6789-1:2017-07.




Easy setting and saving of the desired torque value; readable on the main and fine scales.




With audible and tactile clicks when adjusting the scale values.





When the set torque value is reached, an audible and tactile mechanism triggers.



Very robust design with reversible ratchet (45 teeth) or for insert tools (9x12 mm or 14x18 mm) and ergonomic 2-component handle.



The reversible Click-Torque wrenches are for right-handed use, the Click-Torque wrenches for insert tools are suitable for right-hand and left-hand uses.





The Click-Torque wrenches are available for clockwise torque-controlled tightening with a reversible ratchet (¼", $^{3}/_{8}$", ½" and ¾" drive) or for insert tools (9x12 mm, 14x18 mm) for torque ranges from 2.5 Nm to 1000 Nm.

All Wera Click-Torque wrenches manufactured according to DIN EN ISO 6789 are supplied with a Declaration of conformity. Our workshop offers a comprehensive service for all Wera torque tools. Please contact us with any queries regarding service, recalibration or repair on +49 (0)202 40 45 145; Fax: +49 (0)202 40 45 158 or per E-Mail at: torqueservice@wera.de.

Series
Click-Torque
Adjustable torque wrenches

Click-Torque A 5 torque wrench with reversible ratchet





Application: For clockwise torque-control

Precision: ± 4% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With ¼" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075604**001	1/4"	2,5-25	0,10	1-18	290	121	42	25	11,5	11 27/64"	4 49/64"	1 21/32"	1"	7/16"

Click-Torque A 6 torque wrench with reversible ratchet





Application: For clockwise torque-control

Precision: ± 4% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With ¼" hex drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075605**001	1/4"	2,5-25	0,10	1-18	290	121	42	25	11,5	11 27/64"	4 49/64"	1 21/32"	1"	7/16"


Audi
80

Series
Click-Torque
Adjustable torque wrenches

Click-Torque B 1 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With $^{3}/_{8}$" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075610**001	$^{3}/_{8}$"	10-50	0,25	8-36	360	140	47	35	16,5	14 $^{11}/_{64}$"	5 $^{33}/_{64}$"	1 $^{27}/_{32}$"	1 $^{3}/_{8}$"	$^{5}/_{8}$"

Click-Torque B 2 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With $^{3}/_{8}$" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075611**001	$^{3}/_{8}$"	20-100	0,5	15-73	405	140	47	43	18,5	15 $^{15}/_{16}$"	5 $^{33}/_{64}$"	1 $^{27}/_{32}$"	1 $^{11}/_{16}$"	$^{45}/_{64}$"

Click-Torque C 1 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With 1/2" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075620**001	1/2"	10-50	0,25	8-36	360	140	47	35	16,5	14 11/64"	5 33/64"	1 27/32"	1 3/8"	5/8"

Click-Torque C 2 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With 1/2" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075621**001	1/2"	20-100	0,5	15-73	405	140	47	43	18,5	15 15/16"	5 33/64"	1 27/32"	1 11/16"	45/64"

Series
Click-Torque
Adjustable torque wrenches

Click-Torque C 3 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With $^{1}/_{2}$" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075622**001	$^{1}/_{2}$"	40-200	1,0	30-146	510	140	47	43	18,5	20 $^{5}/_{64}$"	5 $^{33}/_{64}$"	1 $^{27}/_{32}$"	1 $^{11}/_{16}$"	$^{45}/_{64}$"

Click-Torque C 4 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With $^{1}/_{2}$" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075623**001	$^{1}/_{2}$"	60-300	1,0	45-220	595	140	47	43	18,5	23 $^{27}/_{64}$"	5 $^{33}/_{64}$"	1 $^{27}/_{32}$"	1 $^{11}/_{16}$"	$^{45}/_{64}$"

Click-Torque C 5 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: Accuracy ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07; application range with up to max. 400 Nm above standard DIN EN ISO 6789-1: 2017-07 (maximum value: 340 Nm)


Design: With $^{1}/_{2}$" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075624**001	$^{1}/_{2}$"	80-400	1,0	60-295	680	140	47	43	18,5	26 $^{49}/_{64}$"	5 $^{33}/_{64}$"	1 $^{27}/_{32}$"	1 $^{11}/_{16}$"	$^{45}/_{64}$"

*) available from September 2018

Click-Torque E 1 torque wrench with reversible ratchet



Application: For clockwise torque-control

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: With $^{3}/_{4}$" square drive, reversible ratchet, 45 teeth; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075630**001	$^{3}/_{4}$"	200-1000	1,0	148-737	1250	140	47	63	30	49 $^{7}/_{32}$"	5 $^{33}/_{64}$"	1 $^{27}/_{32}$"	2 $^{31}/_{64}$"	1 $^{3}/_{16}$"

*) available from January 2019

Series
Click-Torque
Adjustable torque wrenches

Click-Torque X 1 torque wrench for insert tools



Application: For right and left-handed use

Precision: ± 4% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 9x12 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075651**001	9x12	2,5-25	0,10	4-18	283	121	42	24	20	11 9/64"	4 49/64"	1 21/32"	15/16"	25/32"

Click-Torque X 2 torque wrench for insert tools



Application: For right and left-handed use

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 9x12 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075652**001	9x12	10-50	0,25	8-36	338	140	47	29	20	13 5/16"	5 33/64"	1 27/32"	1 9/64"	25/32"

Click-Torque X 3 torque wrench for insert tools



Application: For right and left-handed use

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 9x12 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075653**001	9x12	20-100	0,5	15-73	372	140	47	29	20	14 41/64"	5 33/64"	1 27/32"	1 9/64"	25/32"

Click-Torque X 4 torque wrench for insert tools



Application: For right and left-handed use

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 14x18 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075654**001	14x18	40-200	1,0	30-146	480	140	47	32	26	18 57/64"	5 33/64"	1 27/32"	1 17/64"	1 1/32"

Series
Click-Torque
Adjustable torque wrenches

Click-Torque X 5 torque wrench for insert tools



Application: For right and left-handed use

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07

Design: For 14x18 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075655**001	14x18	60-300	1,0	45-220	570	140	47	32	26	22 7/16"	5 33/64"	1 27/32"	1 17/64"	1 1/32"

Click-Torque X 6 torque wrench for insert tools



Application: For right and left-handed use

Precision: ± 3% of set value, as per DIN EN ISO 6789-1: 2017-07; application range with up to max. 400 Nm above standard DIN EN ISO 6789-1: 2017-07 (maximum value: 340 Nm)

Design: For 14x18 mm interchangeable insert tools; easy setting and saving of the desired torque value, with audible and tactile locking when the scale values are reached (fine scale only in Newton meters), audible and tactile release mechanism when the set torque value is reached

Handle: Ergonomic 2-component handle

		Nm	Nm	lbf. ft.	mm	mm	mm	mm	mm					
05**075656**001	14x18	80-400	1,0	60-295	655	140	47	32	26	25 25/32"	5 33/64"	1 27/32"	1 17/64"	1 1/32"

*) available from September 2018


40-200 N·m
30-146 lbf·ft

Series Insert Tools

Suitable for Series Click-Torque X torque wrenches.

7770 Open end insert

Form A

05**078600**001
05**078601**001
05**078602**001
05**078603**001
05**078604**001
05**078605**001



Form B

05**078606**001
05**078607**001
05**078608**001
05**078609**001
05**078610**001
05**078611**001
05**078612**001



Application: Hexagon screw heads or nuts
Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder
Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm
05**078600**001	7	39,0	22,0	22,0	5,0
05**078601**001	8	39,0	22,0	22,0	5,0
05**078602**001	9	39,0	22,0	22,0	5,0
05**078603**001	10	39,0	22,0	22,0	5,0
05**078604**001	11	39,0	22,0	22,0	5,0
05**078605**001	12	39,0	22,0	22,0	5,0
05**078606**001	13	41,0	24,0	30,0	7,0
05**078607**001	14	41,0	24,0	30,0	7,0
05**078608**001	15	41,0	24,0	30,0	7,0
05**078609**001	16	41,0	24,0	30,0	7,0
05**078610**001	17	41,0	24,0	30,0	7,0
05**078611**001	18	41,0	24,0	30,0	7,0
05**078612**001	19	41,0	24,0	30,0	7,0

7780 Open end insert

Form A

05**078670**001



Form B

05**078671**001
05**078672**001
05**078673**001
05**078674**001
05**078675**001
05**078676**001



Form C

05**078677**001
05**078678**001
05**078679**001
05**078680**001
05**078681**001



Form D

05**078682**001
05**078683**001
05**078684**001
05**078685**001
05**078686**001
05**078687**001



Application: Hexagon screw heads or nuts
Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder
Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm
05**078670**001	13	56,0	32,0	30,0	7,0
05**078671**001	14	58,0	33,0	32,0	7,0
05**078672**001	15	58,0	33,0	32,0	7,0
05**078673**001	16	58,0	33,0	32,0	7,0
05**078674**001	17	58,0	33,0	32,0	7,0
05**078675**001	18	58,0	33,0	32,0	7,0
05**078676**001	19	58,0	33,0	32,0	7,0
05**078677**001	21	61,0	36,0	52,0	12,0
05**078678**001	22	61,0	36,0	52,0	12,0
05**078679**001	24	61,0	36,0	52,0	12,0
05**078680**001	26	61,0	36,0	52,0	12,0
05**078681**001	27	61,0	36,0	52,0	12,0
05**078682**001	29	61,0	36,0	52,0	12,0
05**078683**001	30	61,0	36,0	52,0	12,0
05**078684**001	32	61,0	36,0	52,0	12,0
05**078685**001	36	61,0	36,0	52,0	12,0
05**078686**001	38	61,0	36,0	52,0	12,0
05**078687**001	41	61,0	36,0	52,0	12,0

7771 Ring spanner insert

Form A

05**078620**001
05**078621**001
05**078622**001
05**078623**001
05**078624**001



Form B

05**078625**001
05**078626**001
05**078627**001
05**078628**001
05**078629**001
05**078630**001
05**078631**001
05**078632**001



Form C

05**078633**001



Application: Hexagon screw heads or nuts

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm
05**078620**001	7	41,0	24,0	22,0	8,0
05**078621**001	8	41,0	24,0	22,0	8,0
05**078622**001	9	41,0	24,0	22,0	8,0
05**078623**001	10	41,0	24,0	22,0	8,0
05**078624**001	11	41,0	24,0	22,0	8,0
05**078625**001	12	44,0	27,0	22,0	11,0
05**078626**001	13	44,0	27,0	22,0	11,0
05**078627**001	14	44,0	27,0	22,0	11,0
05**078628**001	15	44,0	27,0	22,0	11,0
05**078629**001	16	44,0	27,0	22,0	11,0
05**078630**001	17	44,0	27,0	22,0	11,0
05**078631**001	18	44,0	27,0	22,0	11,0
05**078632**001	19	44,0	27,0	22,0	11,0
05**078633**001	21	51,0	34,0	33,0	15,0

7781 Ring spanner insert

Form A

05**078690**001
05**078691**001
05**078692**001



Form B

05**078693**001
05**078694**001
05**078695**001
05**078696**001
05**078697**001
05**078698**001
05**078699**001



Form C

05**078700**001
05**078701**001
05**078702**001
05**078703**001
05**078704**001
05**078705**001



Application: Hexagon screw heads or nuts

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm
05**078690**001	13	62,0	37,0	30,0	11,0
05**078691**001	14	62,0	37,0	30,0	11,0
05**078692**001	15	62,0	37,0	30,0	11,0
05**078693**001	16	64,0	39,0	28,0	12,0
05**078694**001	17	64,0	39,0	28,0	12,0
05**078695**001	18	64,0	39,0	28,0	12,0
05**078696**001	19	64,0	39,0	28,0	12,0
05**078697**001	21	64,0	39,0	28,0	12,0
05**078698**001	22	64,0	39,0	28,0	12,0
05**078699**001	24	64,0	39,0	28,0	12,0
05**078700**001	27	81,0	56,0	53,0	21,0
05**078701**001	30	81,0	56,0	53,0	21,0
05**078702**001	32	81,0	56,0	53,0	21,0
05**078703**001	34	81,0	56,0	53,0	21,0
05**078704**001	36	81,0	56,0	53,0	21,0
05**078705**001	41	81,0	56,0	53,0	21,0



Series Insert Tools

Suitable for Series Click-Torque X torque wrenches.

7772 A Ratchet insert, reversible



Application: For $^{1}/_{4}$" square socket wrench inserts and $^{1}/_{4}$" connecting parts with square drive

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: With reversing ratchet, push-button release, forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078635**001	$^{1}/_{4}$"	49,0	32,0	28,0	15,0

7772 B Ratchet insert, reversible



Application: For $^{3}/_{8}$" square socket wrench inserts and $^{3}/_{8}$" connecting parts with square drive

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: With reversing ratchet, push-button release, forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078636**001	$^{3}/_{8}$"	52,0	35,0	35,0	21,0

7772 C Ratchet insert, reversible



Application: For $^{1}/_{2}$" square socket wrench inserts and $^{1}/_{2}$" connecting parts with square drive

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: With reversing ratchet, push-button release, forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078637**001	$^{1}/_{2}$"	58,0	41,0	42,0	23,0

7782 E Ratchet insert, reversible



Application: For $^{3}/_{4}$" square socket wrench inserts and $^{3}/_{4}$" connecting parts with square drive

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: With reversing ratchet, push-button release, forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078708**001	$^{3}/_{4}$"	90,0	65,0	65,0	36,0

7782 C Ratchet insert, reversible



Application: For $^{1}/_{2}$" square socket wrench inserts and $^{1}/_{2}$" connecting parts with square drive

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: With reversing ratchet, push-button release, forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078707**001	$^{1}/_{2}$"	66,0	41,0	42,0	23,0

7773 A Square drive insert



Application: For $^{1}/_{4}$" square socket wrench inserts and $^{1}/_{4}$" connecting parts with square drive

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm		
05**078200**001	$^{1}/_{4}$"	44,0	28,0	21,0	14,0

7773 B Square drive insert



Application: For $^{3}/_{8}$" square socket wrench inserts and $^{3}/_{8}$" connecting parts with square drive

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm		
05**078205**001	$^{3}/_{8}$"	44,0	28,0	21,0	14,0

7773 C Square drive insert



Application: For $^{1}/_{2}$" square socket wrench inserts and $^{1}/_{2}$" connecting parts with square drive

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078210**001	$^{1}/_{2}$"	44,0	28,0	21,0	14,0

7783 E Push-through square insert tool

SWITCH



Application: For $^{1}/_{2}$" square socket wrench inserts and $^{3}/_{4}$" connecting parts with square drive

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: With push-through square with ball lock, forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078710**001	$^{3}/_{4}$"	70,0	45,0	40,0	25,0

7783 C Square drive insert



Application: For $^{1}/_{2}$" square socket wrench inserts and $^{1}/_{2}$" connecting parts with square drive

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm		
05**078345**001	$^{1}/_{2}$"	65,0	40,0	30,0	18,0

7774/1 Bit adapter insert, $^{1}/_{4}$"



Application: Suitable for $^{1}/_{4}$" DIN ISO 1173-C 6,3 hexagon insert bits and Wera Series 1

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078640**001	$^{1}/_{4}$"	42,0	25,0	22,0	12,5

7774/2 Bit adapter insert, $^{5}/_{16}$"



Application: Suitable for $^{5}/_{16}$" DIN ISO 1173-E 8 hexagon insert bits and Wera Series 2

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078641**001	$^{5}/_{16}$"	42,0	25,0	22,0	12,5

Series Insert Tools

Suitable for Series Click-Torque X torque wrenches.

7774/3 Bit adapter insert, $^5/_{16}$"



Application: Suitable for $^5/_{16}$" DIN ISO 1173-E 8 hexagon insert bits and Wera Series 2

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078642**001	$^5/_{16}$"	58,0	33,0	30,0	13,0

7776 External TORX® insert

Form A

05**078660**001
05**078661**001
05**078662**001
05**078663**001



Form B

05**078664**001



Application: External TORX® screws

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078660**001	TX 6	40,0	23,0	22,0	8,0
05**078661**001	TX 8	40,0	23,0	22,0	8,0
05**078662**001	TX 10	40,0	23,0	22,0	8,0
05**078663**001	TX 12	40,0	23,0	22,0	8,0
05**078664**001	TX 14	45,0	28,0	22,0	11,0

7775 Open ring spanner insert

Form A

05**078650**001
05**078651**001
05**078652**001
05**078653**001
05**078654**001
05**078655**001



Form B

05**078656**001
05**078657**001
05**078658**001



Application: Hexagon screw heads or nuts

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm
05**078650**001	10	44,0	27,0	22,0	11,0
05**078651**001	11	44,0	27,0	22,0	11,0
05**078652**001	12	44,0	27,0	22,0	11,0
05**078653**001	13	44,0	27,0	22,0	11,0
05**078654**001	14	44,0	27,0	22,0	11,0
05**078655**001	17	44,0	27,0	22,0	11,0
05**078656**001	18	49,0	32,0	33,0	15,0
05**078657**001	19	49,0	32,0	33,0	15,0
05**078658**001	22	49,0	32,0	33,0	15,0

7786 External TORX® insert

Form A

05**078714**001
05**078715**001



Form B

05**078716**001
05**078717**001



Application: External TORX® screws

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: Forged, chrome-vanadium steel, matt chrome-plated; with safety pin

		mm	mm	mm	mm
05**078714**001	TX 14	37,0	62,0	30,0	11,0
05**078715**001	TX 18	37,0	62,0	30,0	11,0
05**078716**001	TX 20	40,0	65,0	32,0	12,0
05**078717**001	TX 24	40,0	65,0	32,0	12,0

7779/1 Adapter insert



Application: For the use of square plug-in tools 14x18 mm in torque wrenches with internal square 9x12 mm

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm	mm
05**078666**001	14x18	9x12	49,0	33,0	32,0	26,0

7779/2 Adapter insert



Application: For the use of square plug-in tools 9x12 mm in torque wrenches with internal square 14x18 mm

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: Forged, chrome vanadium steel, matt chrome plated; with safety pin

	mm	mm	mm	mm	mm	mm
05**078667**001	9x12	14x18	52,0	27,0	28,0	21,0

7790/1 Push-fit weld-on adapter



Application: For welding on specifically required tools

Drive: 9x12 mm; for torque wrenches of the Click-Torque X series with 9x12 mm holder

Design: Forged, phosphated, with safety pin

	mm	mm	mm	mm
05**078720**001	24,0	8,0	22,0	14,0

7790/2 Push-fit weld-on adapter



Application: For welding on specifically required tools

Drive: 14x18 mm; for torque wrenches of the Click-Torque X series with 14x18 mm holder

Design: Forged, phosphated, with safety pin

	mm	mm	mm	mm	
05**078721**001	38,0	13,0	31,0	22,0	26,0




Wera
Wera

Impact Driver and Soft-faced Hammers



Impact Driver 510



Soft-faced Hammers 512



Impact driver

It has to be possible that even the most seized screw can be loosened.

Impact drivers are the solution whenever manual power is insufficient and a pneumatic screwdriver is not to hand.

The Wera impact driver has particularly high efficiency thanks to its robust double-curved design. Impact forces are converted into rotary motion and so there is no need for the use of pneumatic appliances.





Seized screws can be loosened or tightened without power tools.



The double-curved design is particularly efficient.



2090 Impact driver 90 Nm



Application: Screws M 4 - M 8
Output: $^{5}/_{16}$" hexagon socket

	mm	
05**072014**001	142,0	5 $^{19}/_{32}$"

2090/17 Impact driver set



17-piece set; in a surface-preserving, compact and extremely robust textile box; low volume and weight for simplified mobility

1x 2090 impact driver 90 Nm, $^{5}/_{16}$" hexagon socket; 1 adaptor $^{5}/_{16}$" external hexagon/ $^{3}/_{8}$" external square, 1 adaptor $^{5}/_{16}$" external hexagon/ $^{1}/_{2}$" external square, 14 bits


05**072017**001		
	2090 90 Nm	1 x 142,0
	851/2 Z PH	1 x PH 2x32; 1 x PH 3x32
	851/2 PH	1 x PH 4x32
	800/2	1 x 2,0x12,0x41
	840/2 Z	1 x 5x30; 1 x 6x30; 1 x 8x30; 1 x 10x30
	840/2	1 x 7,0x30
	867/2 Z TORX®	1 x TX 30x35; 1 x TX 40x35; 1 x TX 45x35; 1 x TX 50x35; 1 x TX 55x35
	870/2	1 x 3/8"x5/16"; 1 x 1/2"x5/16"

Soft-faced hammers

Powerful hammering with surface protection.



They come in soft, medium and hard designs for a wide range of applications from universal use to splinter-free applications on sharp-edged work pieces.



Powerful work is ensured with handles out of high quality ash wood.



Colour guidance system

- Yellow = Repair/maintenance work with high demands
- Red = Suitable for hammering sharp-edged work pieces; bodyshops, automotive, engineering
- White = Suitable for metal processing and removal of dents; tent, large building and exhibition stand construction



The double-sided conical design creates an unbreakable and secure link between the handle and head of the hammer.



Versatile use thanks to the soft faced heads that can be retrospectively fitted.




Wera

Series Soft-Faced Hammers

Powerful hammering with surface protection

100 Soft-faced hammer with Cellidor head sections



Application: Demanding repair/maintenance work
Head: Cellidor, hard
Handle: Ashwood

	#	mm	mm	mm
05**000005**001	1	22	75	250,0
05**000010**001	2	27	90	265,0
05**000015**001	3	32	95	280,0
05**000020**001	4	35	105	290,0
05**000025**001	5	40	110	320,0
05**000030**001	6	50	115	340,0
05**000035**001	7	60	135	380,0

101 Soft-faced hammer with nylon head sections



Application: Metal processing, removal of dents as well as tent, large building and exhibition stand construction
Head: Nylon, very hard
Handle: Ashwood

	#	mm	mm	mm
05**000305**001	1	22	75	250,0
05**000310**001	2	27	90	265,0
05**000315**001	3	32	95	280,0
05**000320**001	4	35	105	290,0
05**000325**001	5	40	110	320,0
05**000330**001	6	50	115	340,0
05**000335**001	7	60	135	380,0

102 Soft-faced hammer with urethane head sections



Application: Bodyshops, automotive, engineering
Head: Urethane, medium-hard
Handle: Ashwood

	#	mm	mm	mm
05**000505**001	1	22	75	250,0
05**000510**001	2	27	90	265,0
05**000515**001	3	32	95	280,0
05**000520**001	4	35	105	290,0
05**000525**001	5	40	110	320,0
05**000530**001	6	50	115	340,0
05**000535**001	7	60	135	380,0

100 S Replacement ashwood handles for hammers 100, 101, 102



	#	mm
05**000205**001	1	250,0
05**000210**001	2	265,0
05**000215**001	3	280,0
05**000220**001	4	290,0
05**000225**001	5	320,0
05**000230**001	6	340,0
05**000235**001	7	380,0

100 L Replacement head sections out of Cellidor for hammer 100



Application: Demanding repair/maintenance work

	#	
05**000105**001	1	22,0
05**000110**001	2	27,0
05**000115**001	3	32,0
05**000120**001	4	35,0
05**000125**001	5	40,0
05**000130**001	6	50,0
05**000135**001	7	60,0

101 L Replacement head sections out of nylon for hammer 101



Application: Metal processing, removal of dents as well as tent, large building and exhibition stand construction

	#	
05**000405**001	1	22,0
05**000410**001	2	27,0
05**000415**001	3	32,0
05**000420**001	4	35,0
05**000425**001	5	40,0
05**000430**001	6	50,0
05**000435**001	7	60,0

102 L Replacement head sections out of urethane for hammer 102



Application: Bodyshops, automotive, engineering

	#	
05**000605**001	1	22,0
05**000610**001	2	27,0
05**000615**001	3	32,0
05**000620**001	4	35,0
05**000625**001	5	40,0
05**000630**001	6	50,0
05**000635**001	7	60,0


Wera
10 11 12 13 14 15 16 17 18 19

TechLex - Technical data and information

Wera ABC	518
TORQUE Test Values	522
Dimensions Of Profiles	523
TORQUE Conversion Table	524
Conversion Of Inches To Millimeters	525
Code No. Index	526
Article No. Index	540
Alphabetical Index	551

Wera ABC

Bit-Check

We have had bit ranges in our programme for many years now. In 2016, we put a question mark against everything and came up with a game changer. We wanted bit ranges with bits whose profiles and sizes could be more easily recognised. We wanted bit ranges that were as compact as possible and which were Wera-like at a first glance. We wanted bit ranges with bits that could be removed and reinserted more easily. We wanted bit ranges with as little weight as possible. The new multi-component Bit-Checks satisfy these requirements; the soft material in the lower section of the Bit-Checks ensures that the bits are firmly held yet easy to remove.

BiTorsion

BiTorsion bits have a tempered torsion zone that diverts the kinetic energy of peak loads away from the drive tip. This greatly reduces the risk of breakage and significantly extends the tools' service life. To find these bits in the catalogue look for the letter B after the article number. BiTorsion holders have a torsion zone that diverts the kinetic energy of peak loads away from the drive tip. The combined use of both the BiTorsion bit and holder increases the service life of the tools considerably and thus ensures higher productivity. BiTorsion bits and holders can, however, be used independently of each other and with conventional tools.

Bits, diamond coated

Please see -> diamond coated bits

Bits, extra hard

Please see -> extra hard bits

Bits, titanium nitride coated

Please see -> Titanium nitride coated bits

Bits, tough absorbing

Please see -> tough absorbing bits

BlackLaser

BlackLaser hardened blades for excellent surface protection and a long service life. High corrosion protection.

Black Point Tip

The Wera Black Point tip and a refined hardening process guarantee a long service life and increased corrosion protection.

Click-Torque Wrenchesp

Click-Torque wrenches in the unmistakable, robust Wera design with high accuracy as per DIN EN ISO 6789-1: 2017-07.

Chiseldriver

The chiseldriver is the solution for jobs that require more than just screwdriving. For fastening, chiselling and loosening seized screws or hose clamps. With an integrated impact cap that extends service live and reduces the risk of splintering. With a pound-thru hexagon blade made from high-grade material for zero-loss transfer of high forces when struck with a hammer. The tough viscous tempered material prevents the blade from splintering or breaking. More TORQUE can be transferred by attaching an open-jawed or ring spanner to the integrated hexagon bolster.

Diamond coated bits

The minute diamond particles on the tip of the bit literally bite into the screw. The secure hold means that less contact pressure is required, which reduces the risk of slipping. To find diamond coated bits in the catalogue look for the letters DC after the article number.

Extra hard bits

Ideal for soft screwdriving. TORQUE increases continuously without any peaks during fastening until the head of the screw reaches the surface of the material. Extra hard bits are made from a special material that extends the tools' service life and reduces the risk of material breakage. To find these bits in the catalogue look for the letter H after the article number.

Flexible Lock System

All rigid Zyklop extensions are fitted with a freewheel sleeve which lets you tighten and loosen screws and bolts quickly and effectively. The premium extensions are also fitted with the flexible lock system. With this system activated, drive handles can be attached permanently to the extension, preventing slipping or accidental loss of the tool. When the system is deactivated the sockets can be attached as usual and changed in a flash.

Hex-Plus Profile

The problem with hexagon socket screws is the easily “rounded” screw recess. This is caused by the sharp edges of the tool pressing against the inside of the screw profile. Gradual wear eventually grinds and destroys the head of the screw. Wera’s Hex-Plus tools provide more contact surface inside the screw profile, which reduces the notching effect and ultimately the deformation of the screw. Hex-Plus tools can also transfer up to 20 % more TORQUE.

Impact bits

Impact bits are designed for use in powerful impact screwdrivers. Impact bits were specifically developed to withstand high power tool forces.

Individual Testing

Our VDE screwdrivers are tested for dielectric strength under a 10,000-volt load to make sure that their most important property, their insulation, has been adequately tested. Each individual Wera VDE screwdriver is subjected to this test to guarantee safe working up to 1,000 volts.

Joker wrenches

The Joker's holding function means that nuts and bolts can be held in the jaw and easily positioned where they are needed. Fastening on to the thread can then be done quickly and safely, thanks to the innovative special stop-plate which holds the fastener. No more time-wasting searches for dropped nuts and bolts!

Koloss

The ratchet that can also be used officially as a hammer. The Koloss can be used as a reversible, heavy-duty, fine action ratchet that can withstand loads of at least 600 Nm.

Kraftform Handle

The Kraftform handle has been designed to fit snugly in your hand, making blisters and calluses a thing of the past even after long-term use. The hard materials used for the handle promote fast grip adjustments and prevent the skin from sticking to the handle. The softer, anti-slip zones facilitate zero-loss transfer of high forces. This is an unbeatable combination! Work is done with a flick of the wrist!

Kraftform Kompakt

Wera’s compact tools are suitable for manual or machine use. The type of operation often becomes clear only after you’ve arrived at the site. The compact handle/interchangeable blade system offers you mobility and flexibility. The sets come with a Kraftform handle, quick-release chuck and bits for manual and machine use. The handle/interchangeable blade system permits rapid tool changes for a wide range of applications. Tools can be stored and carried in a strong plastic box or a robust belt pouch so that they are always at hand. The sets of series 20 have hidden depths: a telescopic blade that retracts into the handle (which can also be removed and attached to a power tool as a bit holder) and an integrated bit magazine. Rapidaptor technology ensures rapid bit changes.

Kraftform Micro

The three-zone concept of Kraftform Micro screwdrivers reduces fastening times and the cost per screw connection. The hand support on the easy-turning cap and the fast-turning zone below the cap accelerate the screwdriving process. This makes time-consuming grip adjustments, which are required with conventional precision screwdrivers, unnecessary. The power zone has integrated soft zones near the tip of the blade to transfer high tightening or loosening forces without losing contact with the screw. The precision zone directly above the blade provides a better feel for the rotation angle during fine adjustment work. The Wera Black Point tip and a refined hardening process guarantee a long service life and increased corrosion protection.

Lasertip

Wera Lasertip screwdrivers have been microscopically roughened by a laser. This rough surface literally “bites” into the head of the screw. Accidental slipping becomes a thing of the past.

Low-temperature Impact Strength

VDE tools are often used under extreme conditions, such as very low temperatures. Safety must be guaranteed even under these conditions. The plastics used for the handle of Wera VDE screwdrivers are guaranteed to meet the more stringent test requirements for low-temperature impact strength at -40 °C.

Multi-component Screwdriver Handle

The Kraftform handle has been designed to fit snugly in your hand, making blisters and calluses a thing of the past even after long-term use. The hard materials used for the handle promote fast grip adjustments and prevent the skin from sticking to the handle. The softer, anti-slip zones facilitate zero-loss transfer of high forces. This is an unbeatable combination! Work is done with a flick of the wrist!

Wera ABC

Rapidaptor

Wera developed the Rapidaptor that allows you to change bits quickly with just one hand and without extra tools.

Rapid-in and self-lock

The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

Rapid-out

Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

Rapid-spin

The free-spinning outer sleeve stabilises battery or mains-powered tools during the screwdriving process. This makes it easier to apply the tool to the screw and prevents slipping.

Chuck-all

The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173 C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

Single-hand function

Every function of the Rapidaptor quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

Rapidaptor with ring magnet

The floating, free-spinning magnetic sleeve holds even large and heavy screws very securely for fast application, eliminating the need to hold the screw, which can be dangerous and painful. Perfect for overhead work.

SPKL L-keys

L-keys with a rubber sleeve (SPKL) are made from easy-to-grip round bars. The sleeve ensures comfortable and safe working even at low temperatures. High corrosion protection.

Stainless Steel Tools

Wera Stainless tools are made from 100 % stainless steel. Their wear debris consists of rustproof stainless steel particles, which prevents unsightly extraneous rust. Wera stainless steel tools are vacuum ice-hardened to give them the necessary hardness and rigidity for industrial applications.

Take it easy Tool Finder

"Take it easy" tool finder with colour coding according to sizes – for simple and rapid accessing of the required tool.

Titanium nitride coated bits

Industrial applications are subject to permanent stresses that place high demands on the durability of the tool. Bits for these applications are coated with extremely hard titanium nitride. This abrasion-proof coating provides the necessary hardness that is required on a mass production line.

TORQ-SET® Mplus

Wera developed the Mplus profile with stronger flanks compared with tools with a conventional TORQ-SET® profile. This results in approximately 70 % extra torsional strength and greatly extends the service life of Wera Mplus tools.

TORQUE-indicators

Wera TORQUE-indicators have been factory pre-set to TORQUE values recommended by leading carbide tool manufacturers. Tightening values are precisely related to the size of the TORX®, TORX PLUS® or hexagon socket screw. TORQUE-indicators ensure safe and easily loosened screw connections.

TORQUE Screwdrivers

Adjustable TORQUE screwdrivers:

TORQUE can be set to the required scale value by hand without special tools.

Pre-set adjustable TORQUE screwdrivers:

With pre-set TORQUE, adjustable within a defined range.

Torsion bits

By diverting TORQUE peaks into the Torsion zone of the bit, premature wear and tear is avoided and dramatically improved service life is achieved.

TORX® BO with borehole

TORX® tools with a borehole prevent the unauthorised unfastening of safety screws. The screws contain a pin that protrudes into the drive profile so that "normal" TORX® tools cannot be used. This pin fits into the borehole of TORX® BO tools allowing safety screws to be unfastened.

TORX® with holding function (HF)

The optimised profile wedges the screw to the tool. This is very important in situations where a magnetic screw holder cannot or must not be used (for instance, jobs involving power tools where metal filings attracted by a magnet could affect the screwdriving process, or jobs requiring wedging forces and stainless steel tools, which are non-magnetic because of the nature of the material). The wedging effect can be guaranteed only for tools made to Acument Global Technologies Inc. specifications.

TORX® with pin

The protruding pin that fits into the borehole of the screw makes it easier to centre the tool in the screw recess.

TORX® Wedge

The conical TORX® profile provides a better fit in the screw. Combined with a great recess depth this produces a pinch effect.

TORX PLUS®

Compared with the “normal”, round TORX® profile the elliptical profile of TORX PLUS® tools makes it possible to increase the size of the 6 flanks that transfer TORQUE between the tool and the screw. The force applied by the user is distributed across a larger surface area allowing more TORQUE to be transferred and extending the service life of both the screw and the tool.

TORX PLUS® IPR

A 5-flank TORX PLUS® profile with a borehole. This drive geometry has only five flanks instead of the usual six and a borehole to protect safety screws against unauthorised unfastening. The screws cannot be turned with conventional, widely available tools.

Tough absorbing bits (Z)

Tough absorbing bits for hard materials, e.g. sheet steel or metal. Here the screw initially turns smoothly inside the defined thread. As soon as the head of the screw touches the surface of the material large amounts of peak TORQUE are generated that affects both the screw and the tool. Bits that are too hard are likely to break under these conditions.

Two-component clip for L-keys

The durable clip material ensures that L-keys are securely fixed and easy to remove. Abrasion resistant markings help you find the right size tool straight away.

Wrenches, Joker

The Joker's holding function means that nuts and bolts can be held in the jaw and easily positioned where they are needed. Fastening on to the thread can then be done quickly and safely, thanks to the innovative special stop-plate which holds the fastener. No more time-wasting searches for dropped nuts and bolts!

Zyklop ratchets

Zyklop Speed	– A really fast mover.
Zyklop Hybrid	– Combines robustness, slim design, and little weight.
Zyklop Metal	– Extremely slim. Long leverage.
Zyklop Mini	– Rapid fastening even in confined working situations.
Zyklop ratchet VDE	– Insulated and 100% individually tested Zyklop VDE ratchet for safe working up to 1,000 volts.

Zyklop Mini 1

The strong ¼" Bit Ratchet that can withstand at least 65 Nm. Suitable for bits directly driven and sockets (using adaptor). Fine tooth mechanism with 60 teeth, simple switching between left/right operations. Ideal for very confined spaces, where conventional screwdrivers are just too big. Drop-forged full steel design.

Zyklop Mini 2

The Zyklop Mini 2 is suitable for the direct attachment of the special Wera Zyklop sockets 8790 FA. These sockets feature a very low height, ideal for confined working spaces.

TORQUE Test Values

Slotted Tools
Drives: DIN ISO 2380, VSM 35601.
TORQUE values evaluated in test gages according to DIN ISO 2380 on TORQUE testing equipment.

Hexagon Tools
Drives: DIN ISO 2936. TORQUE values evaluated in test gages according to DIN ISO 2936 on TORQUE testing equipment.

PH and PZ Tools
Drives: DIN 5260, ISO 8764 and SMS-SS 1687.
TORQUE values evaluated in test gages according to DIN 5261, ISO 8764 on TORQUE testing equipment.

Tools with TORQ-SET® drive
TORQUE values evaluated with testing gages of Phillips Screw Company, licensor of TORQ-SET®, on TORQUE testing equipment.

a x b mm	TORQUE in Nm (min) handuse	poweruse
0,3 x 2,0	0,18	0,20
0,4 x 2,0	0,30	0,35
0,4 x 2,5	0,40	0,45
0,5 x 3,0	0,70	0,80
0,5 x 3,5	0,90	0,98
0,6 x 3,5	1,30	1,40
0,6 x 4,0	1,40	1,61
0,6 x 4,5	-	1,80
0,8 x 4,0	2,60	2,90
0,8 x 4,5	2,88	
0,8 x 5,0	3,20	3,58
0,8 x 5,5	3,50	3,90
1,0 x 5,5	5,50	6,20
1,0 x 6,5	6,50	7,28
1,0 x 7,0	7,0	7,80
1,2 x 6,5	9,40	10,50
1,2 x 7,0	10,0	11,28
1,2 x 8,0	11,5	12,90
1,4 x 9,0	17,6	19,70
1,5 x 13	29	32
1,6 x 8,0	20,5	22,9
1,6 x 9,0	23	25
1,6 x 10	25,6	28,7
2,0 x 12	48,0	53
2,0 x 13	52	58
2,5 x 14	87	98
2,5 x 16	100	112
3,0 x 18	162	181

Important device:
After TORQUE testing with the minimum value, screwdrivers shall not show any deformation or injuries at the tip.

SW (mm)	TORQUE in Nm (min)
0,7	0,08
0,9	0,18
1,3	0,53
1,5	0,82
2,0	1,9
2,5	3,8
3	6,6
3,5	11
4	16
4,5	24
5	30
6	52
7	78
8	120
9	180
10	220
11	295
12	370
13	480
14	590
17	1000
19	1000
22	1000
24	1000
27	1000

	TORQUE in Nm (min) handuse	poweruse
0	1,0	1,0
1	3,5	3,9
2	8,2	10,3
3	19,5	32,0
4	38,0	88,7

Tools with TORX® and TORX PLUS® drive
TORQUE values evaluated with testing gages of Acument Global Technologies Inc., licensor of TORX® and TORX PLUS®.

	TORQUE in Nm (min) Bits	Screw-drivers
2	1,1	1,1
3	1,7	1,7
4	2,8	2,8
5	4,0	4,0
6	5,1	5,1
8	8,5	8,5
10	11,3	11,3
1/4"	28	17
5/16"	56	28
3/8"	102	62
7/16"	147	
1/2"	249	
9/16"	271	
5/8"	339	

	TORQUE in Nm (min.) **TORX®** Bit	Resis-Bit	Screw-driver	**TORX PLUS®** Bit	Resis-Bit	Screw-driver
1	0,10	-	0,08	0,11		
2	0,14	-	0,12	0,16		
3	0,25	-	0,21	0,28		
4	0,37	-	0,31	0,44		
5	0,51	-	0,43	0,61		
6	0,91	-	0,75	1,11		0,92
7	1,7	1,4	1,4	2,10		1,68
8	2,6	2,2	2,2	3,21	2,5	2,79
9	3,4	2,9	2,8	4,19	3,3	3,49
10	4,5	3,8	3,7	5,42	4,3	4,47
15	7,7	6,5	6,4	9,62	7,3	8,06
20	12,7	10,8	10,5	16,15	11,9	13,41
25	19,0	16,1	15,9	23,50	17,4	19,58
27	26,9	22,9	22,5	34,62	25,1	28,95
30	37,4	31,8	31,1	47,18	33,5	39,34
40	65,1	55,3	54,1	82,08	59,4	68,40
45	104	88	86	137,38	97,3	114,44
50	159	135	132	194,54	152,4	162,14
55	257	218	218	352,10	291,5	299,25
60	445	379	379	566,11	483,0	481,24
70	701	596	600	910,40	713,3	773,91

Dimensions Of Profiles

TORX® Recess Screws

	A Ref. (mm)
TX 1	0,84
TX 2	0,94
TX 3	1,12
TX 4	1,30
TX 5	1,37
TX 6	1,65
TX 7	1,97
TX 8	2,30
TX 9	2,48
TX 10	2,72
TX 15	3,26
TX 20	3,84
TX 25	4,40
TX 27	4,96
TX 30	5,49
TX 40	6,60
TX 45	7,77
TX 50	8,79
TX 55	11,17
TX 60	13,20
TX 70	15,49

TORX PLUS® Recess Screws

	A Ref. (mm)
1 IP	0,84
2 IP	0,95
3 IP	1,13
4 IP	1,29
5 IP	1,41
6 IP	1,69
7 IP	1,97
8 IP	2,29
9 IP	2,48
10 IP	2,72
15 IP	3,25
20 IP	3,84
25 IP	4,39
27 IP	4,95
30 IP	5,49
40 IP	6,60
45 IP	7,77
50 IP	8,79
55 IP	11,16
60 IP	13,20
70 IP	15,48

TORQ-SET® Recess Screws

	A Ref. (mm)
0	0,43
1	0,43
2	0,43
3	0,48
4	0,56
5	0,63
6	0,71
8	0,84
10	0,96
1/4"	1,27
5/16"	1,60
3/8"	1,90
7/16"	2,23
1/2"	2,54

TRI-WING® Recess Screws

	A Ref. (mm)
0	0,45
1	0,57
2	0,75
3	0,95
4	1,08
5	1,23
6	1,54
7	1,87
8	2,17
9	2,48
10	2,78

XZN Recess Screws

	A Ref. (mm)
M 4	3,83
M 5	4,80
M 6	6,00
M 8	7,20
M 10	9,60
M 12	11,41
M 14	13,22
M 16	15,63
M 18	16,85
M 20	19,25

Square Recess Screws

	A Ref. (mm)	A Ref. (mm)
00	1,27	1,4
0	1,78	2
1	2,31	2,5
2	2,85	3,1
3	3,37	3,7
4	4,84	5,1

Spanner Recess Screws

	A Ref. (mm)
4	1,52
6	2,41
8	2,79
10	3,30

TORQUE Conversion Table

Conversion

Units	SI Units			Metric scale		USA GB scale		
	cNm	**dNm**	**Nm**	**cmkg**	**mkg**	**ft.lb**	**in.lb**	**in.oz**
1 cNm =	1	0,1	0,01	0,1020	0,0010	0,0074	0,0885	1,4161
1 dNm =	10	1	0,1	1,0197	0,0102	0,0738	0,8851	14,1612
1 Nm =	100	10	1	10,1972	0,1020	0,7376	8,8508	141,6123
1 cmkg =	9,8067	0,9807	0,0981	1	0,0100	0,0723	0,8680	13,8874
1 mkg =	980,6650	98,0665	9,8067	100	1	7,2330	86,7964	1388,7422
1 ft.lb =	135,5818	13,5581	1,3558	13,8255	0,1383	1	12	192
1 in.lb =	11,2985	1,1298	0,1130	1,1521	0,0115	0,0833	1	16
1 in. oz =	0,7062	0,0706	0,0071	0,0720	0,0007	0,0052	0,0625	1

Example 1

1 Nm = 0,102 mkg

17,4 Nm = 17,4 x 0,102 mkg

17,4 Nm = 1,775 mkg

Example 2

1 mkg = 9,8067 Nm

12,5 mkg = 12,5 x 9,8067 Nm

12,5 mkg = 122,58 Nm

Conversion Nm in mkg — **1 Nm = 0,10197 mkg**

Nm	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**
0	0,00	0,10	0,20	0,31	0,41	0,51	0,61	0,71	0,82	0,92
10	1,02	1,12	1,22	1,33	1,43	1,53	1,63	1,73	1,84	1,94
20	2,04	2,14	2,24	2,35	2,45	2,55	2,65	2,75	2,86	2,96
30	3,06	3,16	3,26	3,37	3,47	3,57	3,67	3,77	3,87	3,98
40	4,08	4,18	4,28	4,38	4,49	4,59	4,69	4,79	4,89	5,00
50	5,10	5,20	5,30	5,40	5,51	5,61	5,71	5,81	5,91	6,02
60	6,12	6,22	6,32	6,42	6,53	6,63	6,73	6,83	6,93	7,04
70	7,14	7,24	7,34	7,44	7,55	7,65	7,75	7,85	7,95	8,06
80	8,16	8,26	8,36	8,46	8,57	8,67	8,77	8,87	8,97	9,08
90	9,18	9,28	9,38	9,48	9,59	9,69	9,79	9,89	9,99	10,10
100	10,20	10,30	10,40	10,50	10,60	10,71	10,81	10,91	11,01	11,11

Conversion mkg in Nm — **1 mkg = 9,80665 Nm**

mkg	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**
0	0,00	9,81	19,61	29,42	39,23	49,03	58,84	68,65	78,45	88,26
10	98,07	107,87	117,68	127,49	137,29	147,10	156,91	166,71	176,52	186,33
20	196,13	205,94	215,75	225,55	235,36	245,17	254,97	264,78	274,59	284,39
30	294,20	304,01	313,81	323,62	333,43	343,23	353,04	362,85	372,65	382,46
40	392,27	402,07	411,88	421,69	431,49	441,30	451,11	460,91	470,72	480,53
50	490,33	500,14	509,95	519,75	529,56	539,37	549,17	558,98	568,79	578,59
60	588,40	598,21	608,01	617,82	627,63	637,43	647,24	657,05	666,85	676,66
70	686,47	696,27	706,08	715,89	725,69	735,50	745,31	755,11	764,92	774,73
80	784,53	794,34	804,15	813,95	823,76	833,57	843,37	853,18	862,99	872,79
90	882,60	892,41	902,21	912,02	921,83	931,63	941,44	951,25	961,05	970,86
100	980,67	990,47	1000,28	1010,08	1019,89	1029,70	1039,50	1049,31	1059,12	1068,92

Conversion Nm in ft.lb — **1 Nm = 0,73756 ft.lb**

Nm	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**
0	0,00	0,74	1,48	2,21	2,95	3,69	4,43	5,16	5,90	6,64
10	7,38	8,11	8,85	9,59	10,33	11,06	11,80	12,54	13,28	14,01
20	14,75	15,49	16,23	16,96	17,70	18,44	19,18	19,91	20,65	21,39
30	22,13	22,86	23,60	24,34	25,08	25,81	26,55	27,29	28,03	28,76
40	29,50	30,24	30,98	31,72	32,45	33,19	33,93	34,67	35,40	36,14
50	36,88	37,62	38,35	39,09	39,83	40,57	41,30	42,04	42,78	43,52
60	44,25	44,99	45,73	46,47	47,20	47,94	48,68	49,42	50,15	50,89
70	51,63	52,37	53,10	53,84	54,58	55,32	56,05	56,79	57,53	58,27
80	59,00	59,74	60,48	61,22	61,96	62,69	63,43	64,17	64,91	65,64
90	66,38	67,12	67,86	68,59	69,33	70,07	70,81	71,54	72,28	73,02
100	73,76	74,49	75,23	75,97	76,71	77,44	78,18	78,92	79,66	80,39

Conversion ft.lb in Nm — **1 ft.lb = 1,35581 Nm**

ft.lb	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**
0	0,00	1,36	2,71	4,07	5,42	6,78	8,13	9,49	10,85	12,20
10	13,56	14,91	16,27	17,63	18,98	20,34	21,69	23,05	24,40	25,76
20	27,12	28,47	29,83	31,18	32,54	33,90	35,25	36,61	37,96	39,32
30	40,67	42,03	43,39	44,74	46,10	47,45	48,81	50,16	51,52	52,88
40	54,23	55,59	56,94	58,30	59,66	61,01	62,37	63,72	65,08	66,43
50	67,79	69,15	70,50	71,86	73,21	74,57	75,93	77,28	78,64	79,99
60	81,35	82,70	84,06	85,42	86,77	88,13	89,48	90,84	92,20	93,55
70	94,91	96,26	97,62	98,97	100,33	101,69	103,04	104,40	105,75	107,11
80	108,46	109,82	111,18	112,53	113,89	115,24	116,60	117,96	119,31	120,67
90	122,02	123,38	124,73	126,09	127,45	128,80	130,16	131,51	132,87	134,23
100	135,58	136,94	138,29	139,65	141,00	142,36	143,72	145,07	146,43	147,78

Conversion Nm in in.lb — **1 Nm = 8,85077 in.lb**

Nm	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**
0	0,00	8,85	17,70	26,55	35,40	44,25	53,10	61,96	70,81	79,66
10	88,51	97,36	106,21	115,06	123,91	132,76	141,61	150,46	159,31	168,16
20	177,02	185,87	194,72	203,57	212,42	221,27	230,12	238,97	247,82	256,67
30	265,52	274,37	283,22	292,08	300,93	309,78	318,63	327,48	336,33	345,18
40	354,03	362,88	371,73	380,58	389,43	398,28	407,14	415,99	424,84	433,69
50	442,54	451,39	460,24	469,09	477,94	486,79	495,64	504,49	513,34	522,20
60	531,05	539,90	548,75	557,60	566,45	575,30	584,15	593,00	601,85	610,70
70	619,55	628,40	637,26	646,11	654,96	663,81	672,66	681,51	690,36	699,21
80	708,06	716,91	725,76	734,61	743,46	752,32	761,17	770,02	778,87	787,72
90	796,57	805,42	814,27	823,12	831,97	840,82	849,67	858,52	867,38	876,23
100	885,08	893,93	902,78	911,63	920,48	929,33	938,18	947,03	955,88	964,73

Conversion in.lb in Nm — **1 in.lb = 0,11298 Nm**

in.lb	**0**	**1**	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**
0	0,00	0,11	0,23	0,34	0,45	0,56	0,68	0,79	0,90	1,02
10	1,13	1,24	1,36	1,47	1,58	1,69	1,81	1,92	2,03	2,15
20	2,26	2,37	2,49	2,60	2,71	2,82	2,94	3,05	3,16	3,28
30	3,39	3,50	3,62	3,73	3,84	3,95	4,07	4,18	4,29	4,41
40	4,52	4,63	4,75	4,86	4,97	5,08	5,20	5,31	5,42	5,54
50	5,65	5,76	5,87	5,99	6,10	6,21	6,33	6,44	6,55	6,67
60	6,78	6,89	7,00	7,12	7,23	7,34	7,46	7,57	7,68	7,80
70	7,91	8,02	8,13	8,25	8,36	8,47	8,59	8,70	8,81	8,93
80	9,04	9,15	9,26	9,38	9,49	9,60	9,72	9,83	9,94	10,06
90	10,17	10,28	10,39	10,51	10,62	10,73	10,85	10,96	11,07	11,19
100	11,30	11,41	11,52	11,64	11,75	11,86	11,98	12,09	12,20	12,31

Conversion Of Inches To Millimeters

Inches		0	1	2	3	4	5	6	7	8	9
			25.400	50.800	76.200	101.600	127.000	152.400	177.800	203.200	228.600
1/64	0.015625	0.397	25.797	51.197	76.597	101.997	127.397	152.797	178.197	203.597	228.997
1/32	0.03125	0.794	26.194	51.594	76.994	102.394	127.794	153.194	178.594	203.994	229.394
3/64	0.046875	1.191	26.591	51.991	77.391	102.791	128.191	153.591	178.991	204.391	229.791
1/16	0.0625	1.588	26.988	52.388	77.788	103.188	128.588	153.988	179.388	204.788	230.188
5/64	0.078125	1.984	27.384	52.784	78.184	103.584	128.984	154.384	179.784	205.184	230.584
3/32	0.09375	2.381	27.781	53.181	78.581	103.981	129.381	154.781	180.181	205.581	230.981
7/64	0.109375	2.778	28.178	53.578	78.978	104.378	129.778	155.178	180.578	205.978	231.378
1/8	0.125	3.175	28.575	53.975	79.375	104.775	130.175	155.575	180.975	206.375	231.775
9/64	0.140625	3.572	28.972	54.372	79.772	105.172	130.572	155.972	181.372	206.772	232.172
5/32	0.15625	3.969	29.369	54.769	80.169	105.569	130.969	156.369	181.769	207.169	232.569
11/64	0.171875	4.366	29.766	55.166	80.566	105.966	131.366	156.766	182.166	207.566	232.966
3/16	0.1875	4.762	30.162	55.562	80.962	106.362	131.762	157.162	182.562	207.962	233.362
13/64	0.203125	5.159	30.559	55.959	81.359	106.759	132.159	157.559	182.959	208.359	233.759
7/32	0.21875	5.556	30.956	56.356	81.756	107.156	132.556	157.956	183.356	208.756	234.156
15/64	0.234375	5.953	31.353	56.753	82.153	107.553	132.953	158.353	183.753	209.153	234.553
1/4	0.25	6.350	31.750	57.150	82.550	107.950	133.350	158.750	184.150	209.550	234.950
17/64	0.265625	6.747	32.147	57.547	82.947	108.347	133.747	159.147	184.547	209.947	235.347
9/32	0.28125	7.144	32.544	57.944	83.344	108.744	134.144	159.544	184.944	210.344	235.744
19/64	0.296875	7.541	32.941	58.341	83.741	109.141	134.541	159.941	185.341	210.741	236.141
5/16	0.3125	7.938	33.338	58.738	84.138	109.538	134.938	160.338	185.738	211.138	236.538
21/64	0.328125	8.334	33.734	59.134	84.534	109.934	135.334	160.734	186.134	211.534	236.934
11/32	0.34375	8.731	34.131	59.531	84.931	110.331	135.731	161.131	186.531	211.931	237.331
23/64	0.359375	9.128	34.528	59.928	85.328	110.728	136.128	161.528	186.928	212.328	237.728
3/8	0.375	9.525	34.925	60.325	85.725	111.125	136.525	161.925	187.325	212.725	238.125
25/64	0.390625	9.922	35.322	60.722	86.122	111.522	136.922	162.322	187.722	213.122	238.522
13/32	0.40625	10.319	35.719	61.119	86.519	111.919	137.319	162.719	188.119	213.519	238.919
27/64	0.421875	10.716	36.116	61.516	86.916	112.316	137.716	163.116	188.516	213.916	239.316
7/16	0.4375	11.112	36.512	61.912	87.312	112.712	138.112	163.512	188.912	214.312	239.712
29/64	0.453125	11.509	36.909	62.309	87.709	113.109	138.509	163.909	189.309	214.709	240.109
15/32	0.46875	11.906	37.306	62.706	88.106	113.506	138.906	164.306	189.706	215.106	240.506
31/64	0.484375	12.303	37.703	63.103	88.503	113.903	139.303	164.703	190.103	215.503	240.903
1/2	0.5	12.700	38.100	63.500	88.900	114.300	139.700	165.100	190.500	215.900	241.300
33/64	0.515625	13.097	38.497	63.897	89.297	114.697	140.097	165.497	190.897	216.297	241.697
17/32	0.53125	13.494	38.894	64.294	89.694	115.094	140.494	165.894	191.294	216.694	242.094
35/64	0.546875	13.891	39.291	64.691	90.091	115.491	140.891	166.291	191.691	217.091	242.491
9/16	0.5625	14.288	39.688	65.088	90.488	115.888	141.288	166.688	192.088	217.488	242.888
37/64	0.578125	14.684	40.084	65.484	90.884	116.284	141.684	167.084	192.484	217.884	243.284
19/32	0.59375	15.081	40.481	65.881	91.281	116.681	142.081	167.481	192.881	218.281	243.681
39/64	0.609375	15.478	40.878	66.278	91.678	117.078	142.478	167.878	193.278	218.678	244.078
5/8	0.625	15.875	41.275	66.675	92.075	117.475	142.875	168.275	193.675	219.075	244.475
41/64	0.640625	16.272	41.672	67.072	92.472	117.872	143.272	168.672	194.072	219.472	244.872
21/32	0.65625	16.669	42.069	67.469	92.869	118.269	143.669	169.069	194.469	219.869	245.269
43/64	0.671875	17.066	42.466	67.866	93.266	118.666	144.066	169.466	194.866	220.266	245.666
11/16	0.6875	17.462	42.862	68.262	93.662	119.062	144.462	169.862	195.262	220.662	246.062
45/64	0.703125	17.859	43.259	68.659	94.059	119.459	144.859	170.259	195.659	221.059	246.459
23/32	0.71875	18.256	43.656	69.056	94.456	119.856	145.256	170.656	196.056	221.456	246.856
47/64	0.734375	18.653	44.053	69.453	94.853	120.253	145.653	171.053	196.453	221.853	247.253
3/4	0.75	19.050	44.450	69.850	95.250	120.650	146.050	171.450	196.850	222.250	247.650
49/64	0.765625	19.447	44.847	70.247	95.647	121.047	146.447	171.847	197.247	222.647	248.047
25/32	0.78125	19.844	45.244	70.644	96.044	121.444	146.844	172.244	197.644	223.044	248.444
51/64	0.796875	20.241	45.641	71.041	96.441	121.841	147.241	172.641	198.041	223.441	248.841
13/16	0.8125	20.638	46.038	71.438	96.838	122.238	147.638	173.038	198.438	223.838	249.238
53/64	0.828125	21.034	46.434	71.834	97.234	122.634	148.034	173.434	198.834	224.234	249.634
27/32	0.84375	21.431	46.831	72.231	97.631	123.031	148.431	173.831	199.231	224.631	250.031
55/64	0.859375	21.828	47.228	72.628	98.028	123.428	148.828	174.228	199.628	225.028	250.428
7/8	0.875	22.225	47.625	73.025	98.425	123.825	149.225	174.625	200.025	225.425	250.825
57/64	0.890625	22.622	48.022	73.422	98.822	124.222	149.622	175.022	200.422	225.822	251.222
29/32	0.90625	23.019	48.419	73.819	99.219	124.619	150.019	175.419	200.819	226.219	251.619
59/64	0.921875	23.416	48.816	74.216	99.616	125.016	150.416	175.816	201.216	226.616	252.016
15/16	0.9375	23.812	49.212	74.612	100.012	125.412	150.812	176.212	201.612	227.012	252.412
61/64	0.953125	24.209	49.609	75.009	100.409	125.809	151.209	176.609	202.009	227.409	252.809
31/32	0.96875	24.606	50.006	75.406	100.806	126.206	151.606	177.006	202.406	227.806	253.206
63/64	0.984375	25.003	50.403	75.803	101.203	126.603	152.003	177.403	202.803	228.203	253.603

Values in mm

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **000005** 001	514	05 **002946** 001	294	05 **003321** 001	165	05 **003417** 001	117
05 **000010** 001	514	05 **002948** 001	294	05 **003322** 001	165	05 **003418** 001	117
05 **000015** 001	514	05 **002950** 001	294	05 **003330** 001	162	05 **003420** 001	117
05 **000020** 001	514	05 **002960** 001	294	05 **003331** 001	162	05 **003421** 001	117
05 **000025** 001	514	05 **002966** 001	294	05 **003332** 001	162	05 **003422** 001	117
05 **000030** 001	514	05 **002968** 001	294	05 **003333** 001	162	05 **003423** 001	117
05 **000035** 001	514	05 **002970** 001	294	05 **003334** 001	162	05 **003424** 001	117
05 **000105** 001	515	05 **002973** 001	294	05 **003335** 001	162	05 **003429** 001	116
05 **000110** 001	515	05 **002976** 001	294	05 **003336** 001	162	05 **003430** 001	116
05 **000115** 001	515	05 **002980** 001	294	05 **003337** 001	162	05 **003431** 001	116
05 **000120** 001	515	05 **002990** 001	292	05 **003338** 001	162	05 **003432** 001	116
05 **000125** 001	515	05 **003030** 001	183	05 **003339** 001	162	05 **003433** 001	116
05 **000130** 001	515	05 **003031** 001	183	05 **003340** 001	162	05 **003434** 001	116
05 **000135** 001	515	05 **003032** 001	183	05 **003341** 001	162	05 **003435** 001	116
05 **000205** 001	514	05 **003033** 001	183	05 **003342** 001	162	05 **003436** 001	116
05 **000210** 001	514	05 **003034** 001	183	05 **003345** 001	163	05 **003437** 001	117
05 **000215** 001	514	05 **003035** 001	183	05 **003350** 001	164	05 **003438** 001	117
05 **000220** 001	514	05 **003036** 001	183	05 **003351** 001	164	05 **003439** 001	117
05 **000225** 001	514	05 **003037** 001	183	05 **003352** 001	164	05 **003440** 001	116
05 **000230** 001	514	05 **003038** 001	183	05 **003353** 001	164	05 **003441** 001	116
05 **000235** 001	514	05 **003039** 001	183	05 **003354** 001	164	05 **003442** 001	116
05 **000305** 001	514	05 **003040** 001	183	05 **003355** 001	164	05 **003443** 001	116
05 **000310** 001	514	05 **003041** 001	183	05 **003360** 001	160	05 **003445** 001	116
05 **000315** 001	514	05 **003042** 001	183	05 **003361** 001	160	05 **003446** 001	116
05 **000320** 001	514	05 **003043** 001	183	05 **003362** 001	160	05 **003447** 001	116
05 **000325** 001	514	05 **003044** 001	183	05 **003363** 001	160	05 **003448** 001	116
05 **000330** 001	514	05 **003059** 001	182	05 **003364** 001	160	05 **003450** 001	115
05 **000335** 001	514	05 **003060** 001	182	05 **003365** 001	160	05 **003451** 001	115
05 **000405** 001	515	05 **003061** 001	182	05 **003366** 001	160	05 **003452** 001	115
05 **000410** 001	515	05 **003062** 001	182	05 **003367** 001	160	05 **003455** 001	115
05 **000415** 001	515	05 **003063** 001	182	05 **003368** 001	160	05 **003456** 001	115
05 **000420** 001	515	05 **003064** 001	182	05 **003369** 001	160	05 **003460** 001	118
05 **000425** 001	515	05 **003065** 001	182	05 **003370** 001	160	05 **003461** 001	118
05 **000430** 001	515	05 **003066** 001	182	05 **003371** 001	160	05 **003462** 001	118
05 **000435** 001	515	05 **003067** 001	182	05 **003372** 001	160	05 **003463** 001	118
05 **000505** 001	514	05 **003068** 001	182	05 **003375** 001	161	05 **003470** 001	113
05 **000510** 001	514	05 **003069** 001	182	05 **003380** 001	162	05 **003471** 001	109
05 **000515** 001	514	05 **003070** 001	182	05 **003381** 001	162	05 **003472** 001	113
05 **000520** 001	514	05 **003071** 001	182	05 **003382** 001	162	05 **003473** 001	113
05 **000525** 001	514	05 **003072** 001	182	05 **003383** 001	162	05 **003474** 001	112
05 **000530** 001	514	05 **003073** 001	182	05 **003384** 001	162	05 **003484** 001	112
05 **000535** 001	514	05 **003080** 001	183	05 **003385** 001	162	05 **003500** 001	150
05 **000605** 001	515	05 **003081** 001	183	05 **003386** 001	162	05 **003501** 001	156
05 **000610** 001	515	05 **003082** 001	183	05 **003387** 001	162	05 **003502** 001	156
05 **000615** 001	515	05 **003083** 001	183	05 **003388** 001	162	05 **003503** 001	156
05 **000620** 001	515	05 **003084** 001	183	05 **003389** 001	162	05 **003504** 001	156
05 **000625** 001	515	05 **003085** 001	183	05 **003400** 001	114	05 **003505** 001	156
05 **000630** 001	515	05 **003086** 001	183	05 **003401** 001	114	05 **003506** 001	156
05 **000635** 001	515	05 **003087** 001	183	05 **003402** 001	114	05 **003507** 001	156
05 **002900** 001	292	05 **003088** 001	183	05 **003403** 001	114	05 **003508** 001	156
05 **002901** 001	289	05 **003089** 001	183	05 **003404** 001	114	05 **003509** 001	156
05 **002910** 001	293	05 **003090** 001	183	05 **003405** 001	114	05 **003510** 001	156
05 **002913** 001	293	05 **003091** 001	183	05 **003406** 001	114	05 **003511** 001	156
05 **002920** 001	293	05 **003092** 001	183	05 **003407** 001	114	05 **003512** 001	156
05 **002923** 001	293	05 **003093** 001	183	05 **003408** 001	114	05 **003513** 001	156
05 **002926** 001	293	05 **003094** 001	183	05 **003410** 001	114	05 **003514** 001	156
05 **002930** 001	294	05 **003180** 001	184	05 **003411** 001	114	05 **003515** 001	156
05 **002933** 001	294	05 **003181** 001	184	05 **003412** 001	114	05 **003516** 001	156
05 **002936** 001	294	05 **003185** 001	182	05 **003413** 001	115	05 **003517** 001	156
05 **002938** 001	294	05 **003210** 001	292	05 **003414** 001	115	05 **003518** 001	156
05 **002940** 001	294	05 **003265** 001	292	05 **003415** 001	117	05 **003519** 001	156
05 **002943** 001	294	05 **003320** 001	165	05 **003416** 001	117	05 **003520** 001	156

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **003521** 001	156	05 **003608** 001	202	05 **003726** 001	156	05 **003852** 001	204
05 **003522** 001	156	05 **003609** 001	202	05 **003727** 001	156	05 **003853** 001	204
05 **003523** 001	156	05 **003610** 001	202	05 **003728** 001	156	05 **003854** 001	204
05 **003524** 001	166	05 **003611** 001	202	05 **003729** 001	156	05 **003855** 001	204
05 **003525** 001	167	05 **003612** 001	202	05 **003730** 001	202	05 **003856** 001	204
05 **003526** 001	166	05 **003613** 001	202	05 **003731** 001	202	05 **003857** 001	204
05 **003527** 001	169	05 **003614** 001	202	05 **003732** 001	202	05 **003858** 001	204
05 **003528** 001	169	05 **003615** 001	202	05 **003733** 001	202	05 **003880** 001	157
05 **003529** 001	169	05 **003616** 001	202	05 **003734** 001	202	05 **003881** 001	162
05 **003530** 001	166	05 **003617** 001	202	05 **003735** 001	202	05 **003882** 001	161
05 **003531** 001	166	05 **003618** 001	202	05 **003736** 001	202	05 **003883** 001	159
05 **003533** 001	148	05 **003619** 001	202	05 **003737** 001	202	05 **003884** 001	160
05 **003535** 001	148	05 **003620** 001	202	05 **003738** 001	202	05 **003890** 001	163
05 **003550** 001	174	05 **003621** 001	202	05 **003739** 001	202	05 **003891** 001	164
05 **003551** 001	180	05 **003622** 001	202	05 **003740** 001	180	05 **003970** 001	181
05 **003552** 001	180	05 **003623** 001	202	05 **003741** 001	180	05 **003971** 001	184
05 **003553** 001	180	05 **003624** 001	202	05 **003742** 001	180	05 **003972** 001	182
05 **003554** 001	180	05 **003625** 001	202	05 **003743** 001	180	05 **003973** 001	181
05 **003555** 001	180	05 **003626** 001	202	05 **003744** 001	180	05 **003974** 001	184
05 **003556** 001	180	05 **003627** 001	202	05 **003745** 001	180	05 **003980** 001	185
05 **003557** 001	180	05 **003628** 001	202	05 **003746** 001	180	05 **003981** 001	185
05 **003558** 001	180	05 **003629** 001	202	05 **003747** 001	180	05 **003990** 001	114
05 **003559** 001	180	05 **003630** 001	202	05 **003748** 001	180	05 **004003** 001	153
05 **003560** 001	180	05 **003631** 001	202	05 **003749** 001	180	05 **004004** 001	155
05 **003561** 001	180	05 **003632** 001	202	05 **003750** 001	180	05 **004016** 001	144
05 **003562** 001	180	05 **003633** 001	202	05 **003751** 001	180	05 **004017** 001	152
05 **003563** 001	180	05 **003634** 001	202	05 **003752** 001	180	05 **004018** 001	154
05 **003564** 001	180	05 **003635** 001	202	05 **003753** 001	180	05 **004019** 001	145
05 **003565** 001	180	05 **003636** 001	209	05 **003755** 001	144	05 **004020** 001	152
05 **003566** 001	180	05 **003637** 001	208	05 **003756** 001	155	05 **004021** 001	154
05 **003567** 001	180	05 **003638** 001	208	05 **003760** 001	228	05 **004033** 001	177
05 **003568** 001	180	05 **003639** 001	209	05 **003765** 001	228	05 **004034** 001	179
05 **003569** 001	180	05 **003640** 001	209	05 **003780** 001	196	05 **004046** 001	172
05 **003570** 001	180	05 **003641** 001	209	05 **003781** 001	196	05 **004047** 001	176
05 **003571** 001	180	05 **003642** 001	208	05 **003785** 001	179	05 **004048** 001	178
05 **003572** 001	180	05 **003643** 001	208	05 **003820** 001	206	05 **004049** 001	172
05 **003573** 001	180	05 **003645** 001	191	05 **003821** 001	206	05 **004050** 001	176
05 **003574** 001	180	05 **003647** 001	192	05 **003822** 001	206	05 **004051** 001	178
05 **003575** 001	180	05 **003660** 001	222	05 **003823** 001	206	05 **004063** 001	199
05 **003576** 001	180	05 **003665** 001	223	05 **003824** 001	206	05 **004064** 001	201
05 **003577** 001	180	05 **003666** 001	223	05 **003825** 001	206	05 **004076** 001	190
05 **003578** 001	180	05 **003667** 001	223	05 **003826** 001	206	05 **004077** 001	198
05 **003579** 001	180	05 **003668** 001	223	05 **003827** 001	206	05 **004078** 001	200
05 **003580** 001	180	05 **003669** 001	223	05 **003828** 001	206	05 **004079** 001	190
05 **003581** 001	187	05 **003670** 001	223	05 **003829** 001	206	05 **004080** 001	198
05 **003582** 001	186	05 **003675** 001	223	05 **003830** 001	204	05 **004081** 001	200
05 **003583** 001	186	05 **003684** 001	223	05 **003831** 001	204	05 **004090** 001	194
05 **003584** 001	187	05 **003685** 001	223	05 **003832** 001	204	05 **004095** 001	194
05 **003585** 001	187	05 **003690** 001	223	05 **003833** 001	204	05 **004201** 001	205
05 **003590** 001	186	05 **003692** 001	212	05 **003834** 001	204	05 **004202** 001	204
05 **003591** 001	186	05 **003695** 001	212	05 **003835** 001	204	05 **004203** 001	203
05 **003592** 001	186	05 **003696** 001	213	05 **003836** 001	204	05 **004210** 001	206
05 **003594** 001	173	05 **003697** 001	213	05 **003837** 001	204	05 **004211** 001	204
05 **003596** 001	174	05 **003717** 001	156	05 **003838** 001	204	05 **004212** 001	205
05 **003600** 001	192	05 **003718** 001	156	05 **003840** 001	206	05 **004310** 001	105
05 **003601** 001	202	05 **003719** 001	156	05 **003841** 001	206	05 **004313** 001	46
05 **003602** 001	202	05 **003720** 001	156	05 **003842** 001	206	05 **004350** 001	300
05 **003603** 001	202	05 **003721** 001	156	05 **003843** 001	206	05 **004351** 001	300
05 **003604** 001	202	05 **003722** 001	156	05 **003844** 001	206	05 **004352** 001	300
05 **003605** 001	202	05 **003723** 001	156	05 **003845** 001	206	05 **004353** 001	300
05 **003606** 001	202	05 **003724** 001	156	05 **003850** 001	204	05 **004354** 001	301
05 **003607** 001	202	05 **003725** 001	156	05 **003851** 001	204	05 **004355** 001	301

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **004650** 001	99	05 **006162** 001	96	05 **008710** 001	36	05 **013362** 001	76
05 **004655** 001	99	05 **006163** 001	96	05 **008712** 001	36	05 **013364** 001	76
05 **004660** 001	99	05 **006164** 001	96	05 **008715** 001	36	05 **013366** 001	76
05 **004665** 001	99	05 **006165** 001	96	05 **008720** 001	36	05 **013368** 001	76
05 **004670** 001	99	05 **006166** 001	96	05 **008723** 001	36	05 **013370** 001	76
05 **004675** 001	99	05 **006168** 001	96	05 **008725** 001	36	05 **013372** 001	76
05 **004780** 001	100	05 **006169** 001	99	05 **008730** 001	36	05 **013374** 001	76
05 **004781** 001	100	05 **006170** 001	99	05 **008735** 001	36	05 **013376** 001	76
05 **004782** 001	100	05 **006172** 001	99	05 **008740** 001	36	05 **013390** 001	77
05 **004783** 001	100	05 **006174** 001	99	05 **008750** 001	36	05 **013399** 001	77
05 **004784** 001	100	05 **006176** 001	99	05 **008751** 001	36	05 **013400** 001	77
05 **004950** 001	126	05 **006177** 001	99	05 **008752** 001	36	05 **013401** 001	77
05 **004951** 001	126	05 **006178** 001	99	05 **008753** 001	36	05 **013402** 001	77
05 **004952** 001	126	05 **006179** 001	99	05 **008775** 001	44	05 **013403** 001	77
05 **004953** 001	126	05 **006181** 001	99	05 **008780** 001	44	05 **013404** 001	77
05 **004954** 001	126	05 **006182** 001	99	05 **008782** 001	44	05 **013405** 001	77
05 **004955** 001	126	05 **006183** 001	99	05 **009305** 001	37	05 **013407** 001	77
05 **004956** 001	126	05 **006184** 001	99	05 **009310** 001	37	05 **013409** 001	77
05 **004957** 001	126	05 **006186** 001	99	05 **009312** 001	37	05 **013411** 001	77
05 **004958** 001	126	05 **006190** 001	98	05 **009313** 001	37	05 **017005** 001	28
05 **004959** 001	126	05 **006191** 001	98	05 **009315** 001	37	05 **017010** 001	28
05 **004960** 001	126	05 **006380** 001	97	05 **009317** 001	37	05 **017015** 001	28
05 **004961** 001	126	05 **006381** 001	97	05 **009319** 001	37	05 **017020** 001	28
05 **004962** 001	126	05 **006440** 001	94	05 **009320** 001	37	05 **017040** 001	28
05 **004963** 001	126	05 **006441** 001	94	05 **009325** 001	37	05 **017041** 001	28
05 **004964** 001	128	05 **006442** 001	94	05 **009330** 001	44	05 **017050** 001	29
05 **004965** 001	128	05 **006450** 001	96	05 **009335** 001	44	05 **017052** 001	29
05 **004966** 001	126	05 **006451** 001	96	05 **009337** 001	44	05 **017054** 001	29
05 **004970** 001	129	05 **006455** 001	98	05 **009340** 001	37	05 **017056** 001	29
05 **005300** 001	100	05 **006456** 001	98	05 **009341** 001	37	05 **017205** 001	257
05 **005305** 001	100	05 **006460** 001	97	05 **009342** 001	37	05 **017305** 001	257
05 **005310** 001	100	05 **006461** 001	97	05 **009343** 001	37	05 **017405** 001	257
05 **005315** 001	100	05 **006465** 001	98	05 **013300** 001	76	05 **017410** 001	257
05 **005320** 001	100	05 **006466** 001	98	05 **013301** 001	76	05 **017415** 001	257
05 **005325** 001	100	05 **006480** 001	104	05 **013302** 001	76	05 **018005** 001	60
05 **005330** 001	100	05 **007355** 001	35	05 **013303** 001	76	05 **018010** 001	60
05 **005335** 001	100	05 **007610** 001	34	05 **013304** 001	76	05 **018015** 001	60
05 **005340** 001	100	05 **007620** 001	34	05 **013305** 001	76	05 **018020** 001	60
05 **005655** 001	101	05 **007621** 001	34	05 **013306** 001	76	05 **018025** 001	60
05 **006100** 001	94	05 **007635** 001	34	05 **013307** 001	76	05 **018030** 001	60
05 **006105** 001	94	05 **007640** 001	34	05 **013308** 001	76	05 **018035** 001	60
05 **006110** 001	94	05 **007670** 001	34	05 **013309** 001	76	05 **018040** 001	60
05 **006115** 001	94	05 **007671** 001	34	05 **013310** 001	76	05 **018251** 001	60
05 **006116** 001	94	05 **007672** 001	34	05 **013311** 001	76	05 **018260** 001	28
05 **006120** 001	94	05 **007673** 001	34	05 **013312** 001	76	05 **018262** 001	28
05 **006121** 001	94	05 **007674** 001	34	05 **013314** 001	76	05 **018264** 001	28
05 **006125** 001	94	05 **007675** 001	34	05 **013330** 001	76	05 **018266** 001	28
05 **006126** 001	94	05 **007676** 001	34	05 **013331** 001	76	05 **018268** 001	28
05 **006130** 001	94	05 **007677** 001	34	05 **013332** 001	76	05 **018270** 001	28
05 **006135** 001	94	05 **007680** 001	48	05 **013333** 001	76	05 **018272** 001	28
05 **006140** 001	94	05 **007681** 001	48	05 **013334** 001	76	05 **018274** 001	28
05 **006145** 001	102	05 **008006** 001	34	05 **013335** 001	76	05 **018282** 001	30
05 **006147** 001	102	05 **008007** 001	34	05 **013337** 001	76	05 **018283** 001	30
05 **006148** 001	103	05 **008008** 001	34	05 **013338** 001	76	05 **018287** 001	31
05 **006150** 001	95	05 **008009** 001	34	05 **013339** 001	76	05 **018300** 001	28
05 **006152** 001	95	05 **008015** 001	34	05 **013341** 001	76	05 **018301** 001	28
05 **006153** 001	95	05 **008027** 001	34	05 **013350** 001	76	05 **018302** 001	28
05 **006154** 001	95	05 **008055** 001	34	05 **013352** 001	76	05 **018350** 001	60
05 **006156** 001	95	05 **008060** 001	34	05 **013354** 001	76	05 **018352** 001	60
05 **006158** 001	95	05 **008061** 001	34	05 **013356** 001	76	05 **018354** 001	60
05 **006159** 001	95	05 **008705** 001	36	05 **013358** 001	76	05 **018355** 001	60
05 **006160** 001	96	05 **008706** 001	36	05 **013360** 001	76	05 **020012** 001	229

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **020013** 001	228	05 **021640** 001	248	05 **022630** 001	247	05 **022920** 001	38
05 **020022** 001	229	05 **021645** 001	248	05 **022631** 001	247	05 **022925** 001	38
05 **020064** 001	230	05 **021728** 001	245	05 **022632** 001	247	05 **022930** 001	38
05 **020065** 001	230	05 **021737** 001	244	05 **022633** 001	247	05 **022935** 001	38
05 **020066** 001	230	05 **021909** 001	242	05 **022634** 001	247	05 **023105** 001	38
05 **020067** 001	230	05 **022040** 001	248	05 **022635** 001	247	05 **023107** 001	38
05 **020068** 001	230	05 **022041** 001	248	05 **022636** 001	247	05 **023110** 001	38
05 **020069** 001	230	05 **022042** 001	248	05 **022637** 001	247	05 **023115** 001	38
05 **020070** 001	230	05 **022043** 001	248	05 **022638** 001	247	05 **023120** 001	38
05 **020071** 001	230	05 **022044** 001	248	05 **022639** 001	241	05 **023125** 001	38
05 **020072** 001	230	05 **022045** 001	248	05 **022660** 001	246	05 **023130** 001	38
05 **020073** 001	230	05 **022046** 001	248	05 **022661** 001	246	05 **023305** 001	60
05 **020074** 001	230	05 **022047** 001	248	05 **022662** 001	246	05 **023307** 001	60
05 **020075** 001	230	05 **022048** 001	248	05 **022663** 001	246	05 **023309** 001	60
05 **020076** 001	230	05 **022050** 001	247	05 **022664** 001	246	05 **024001** 001	256
05 **020077** 001	230	05 **022052** 001	247	05 **022665** 001	246	05 **024002** 001	256
05 **020078** 001	230	05 **022054** 001	247	05 **022666** 001	246	05 **024003** 001	256
05 **020079** 001	230	05 **022056** 001	247	05 **022667** 001	246	05 **024004** 001	256
05 **020080** 001	230	05 **022058** 001	247	05 **022668** 001	246	05 **024005** 001	256
05 **020081** 001	230	05 **022060** 001	247	05 **022669** 001	238	05 **024008** 001	256
05 **020082** 001	230	05 **022062** 001	247	05 **022700** 001	246	05 **024010** 001	256
05 **020090** 001	231	05 **022063** 001	247	05 **022701** 001	246	05 **024012** 001	256
05 **020091** 001	232	05 **022064** 001	247	05 **022702** 001	246	05 **024013** 001	256
05 **020092** 001	231	05 **022066** 001	247	05 **022703** 001	246	05 **024015** 001	256
05 **020093** 001	232	05 **022067** 001	247	05 **022704** 001	246	05 **024020** 001	256
05 **020129** 001	94	05 **022068** 001	248	05 **022705** 001	246	05 **024100** 001	256
05 **020131** 001	96	05 **022070** 001	248	05 **022706** 001	246	05 **024105** 001	256
05 **020132** 001	98	05 **022071** 001	248	05 **022708** 001	246	05 **024160** 001	256
05 **020133** 001	96	05 **022072** 001	248	05 **022709** 001	246	05 **024161** 001	256
05 **020134** 001	98	05 **022073** 001	248	05 **022710** 001	246	05 **024162** 001	256
05 **021005** 001	249	05 **022074** 001	248	05 **022711** 001	246	05 **024163** 001	256
05 **021010** 001	249	05 **022076** 001	248	05 **022712** 001	246	05 **024164** 001	256
05 **021015** 001	249	05 **022078** 001	248	05 **022713** 001	246	05 **024165** 001	256
05 **021020** 001	249	05 **022079** 001	248	05 **022714** 001	246	05 **024166** 001	256
05 **021025** 001	249	05 **022080** 001	248	05 **022715** 001	246	05 **024167** 001	256
05 **021030** 001	249	05 **022081** 001	248	05 **022716** 001	246	05 **024168** 001	256
05 **021035** 001	249	05 **022082** 001	248	05 **022717** 001	246	05 **024170** 001	254
05 **021040** 001	249	05 **022086** 001	244	05 **022718** 001	246	05 **024171** 001	254
05 **021045** 001	249	05 **022087** 001	242	05 **022720** 001	238	05 **024172** 001	254
05 **021050** 001	249	05 **022089** 001	240	05 **022721** 001	239	05 **024173** 001	254
05 **021055** 001	249	05 **022095** 001	248	05 **022728** 001	91	05 **024174** 001	254
05 **021060** 001	249	05 **022096** 001	248	05 **022729** 001	90	05 **024175** 001	254
05 **021065** 001	249	05 **022101** 001	244	05 **022730** 001	90	05 **024176** 001	254
05 **021070** 001	249	05 **022171** 001	245	05 **022731** 001	90	05 **024177** 001	254
05 **021075** 001	249	05 **022181** 001	244	05 **022732** 001	90	05 **024178** 001	254
05 **021080** 001	249	05 **022200** 001	246	05 **022733** 001	90	05 **024179** 001	250
05 **021085** 001	249	05 **022201** 001	246	05 **022734** 001	90	05 **024199** 001	256
05 **021090** 001	249	05 **022202** 001	246	05 **022740** 001	90	05 **024200** 001	256
05 **021095** 001	249	05 **022203** 001	246	05 **022741** 001	90	05 **024202** 001	256
05 **021100** 001	249	05 **022204** 001	246	05 **022745** 001	91	05 **024204** 001	256
05 **021105** 001	249	05 **022205** 001	246	05 **022795** 001	38	05 **024206** 001	256
05 **021110** 001	249	05 **022210** 001	240	05 **022800** 001	38	05 **024208** 001	256
05 **021406** 001	243	05 **022534** 001	241	05 **022805** 001	38	05 **024210** 001	256
05 **021600** 001	248	05 **022600** 001	247	05 **022810** 001	38	05 **024242** 001	252
05 **021605** 001	248	05 **022602** 001	247	05 **022815** 001	38	05 **024244** 001	250
05 **021610** 001	248	05 **022604** 001	247	05 **022820** 001	38	05 **024335** 001	212
05 **021615** 001	248	05 **022606** 001	247	05 **022825** 001	38	05 **024350** 001	254
05 **021620** 001	248	05 **022608** 001	247	05 **022830** 001	38	05 **024351** 001	254
05 **021625** 001	248	05 **022610** 001	247	05 **022835** 001	38	05 **024352** 001	254
05 **021630** 001	248	05 **022612** 001	247	05 **022905** 001	38	05 **024353** 001	254
05 **021632** 001	248	05 **022614** 001	247	05 **022910** 001	38	05 **024354** 001	254
05 **021635** 001	248	05 **022616** 001	247	05 **022915** 001	38	05 **024355** 001	254

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **024356** 001	254	05 **027101** 001	247	05 **028033** 001	40	05 **029463** 001	43
05 **024357** 001	254	05 **027102** 001	247	05 **028034** 001	40	05 **029464** 001	43
05 **024358** 001	254	05 **027103** 001	247	05 **028035** 001	40	05 **029465** 001	43
05 **024400** 001	29	05 **027104** 001	247	05 **028036** 001	40	05 **029466** 001	43
05 **024401** 001	29	05 **027105** 001	247	05 **028037** 001	40	05 **029501** 001	43
05 **024402** 001	29	05 **027106** 001	247	05 **028038** 001	40	05 **029502** 001	43
05 **024403** 001	29	05 **027107** 001	247	05 **028040** 001	486	05 **029503** 001	43
05 **024404** 001	29	05 **027108** 001	247	05 **028041** 001	486	05 **029504** 001	43
05 **024405** 001	29	05 **027109** 001	247	05 **028042** 001	486	05 **029505** 001	43
05 **024410** 001	31	05 **027110** 001	247	05 **028043** 001	486	05 **029506** 001	43
05 **024450** 001	250	05 **027111** 001	247	05 **028044** 001	486	05 **029507** 001	43
05 **024451** 001	254	05 **027201** 001	249	05 **028045** 001	486	05 **029510** 001	51
05 **024452** 001	254	05 **027202** 001	249	05 **028046** 001	487	05 **030080** 001	82
05 **024453** 001	254	05 **027203** 001	249	05 **028048** 001	38	05 **030081** 001	82
05 **024454** 001	254	05 **027204** 001	249	05 **028049** 001	38	05 **030082** 001	82
05 **024455** 001	254	05 **027205** 001	249	05 **028050** 001	38	05 **030083** 001	82
05 **024456** 001	254	05 **027206** 001	249	05 **028051** 001	38	05 **030084** 001	82
05 **024457** 001	254	05 **027207** 001	249	05 **028052** 001	38	05 **030100** 001	80
05 **024458** 001	254	05 **027208** 001	249	05 **028053** 001	38	05 **030101** 001	80
05 **024459** 001	254	05 **027209** 001	249	05 **028054** 001	38	05 **030102** 001	80
05 **024460** 001	252	05 **027210** 001	249	05 **028055** 001	38	05 **030103** 001	80
05 **024461** 001	256	05 **027211** 001	249	05 **028056** 001	38	05 **030104** 001	80
05 **024462** 001	256	05 **027212** 001	249	05 **028059** 001	50	05 **030105** 001	80
05 **024463** 001	256	05 **027213** 001	249	05 **028062** 001	51	05 **030106** 001	80
05 **024464** 001	256	05 **027214** 001	249	05 **028070** 001	38	05 **030107** 001	80
05 **024465** 001	256	05 **027215** 001	249	05 **028071** 001	38	05 **030108** 001	80
05 **024466** 001	256	05 **027405** 001	62	05 **028072** 001	38	05 **030110** 001	80
05 **024467** 001	256	05 **027455** 001	62	05 **028073** 001	38	05 **030111** 001	80
05 **024468** 001	256	05 **027456** 001	69	05 **028074** 001	50	05 **030112** 001	80
05 **024469** 001	256	05 **027910** 001	486	05 **028116** 001	42	05 **030115** 001	80
05 **024470** 001	250	05 **027911** 001	486	05 **028118** 001	42	05 **030116** 001	80
05 **024471** 001	253	05 **027912** 001	486	05 **028120** 001	42	05 **030117** 001	80
05 **024472** 001	253	05 **027913** 001	486	05 **028122** 001	42	05 **030118** 001	80
05 **024473** 001	253	05 **027930** 001	486	05 **028124** 001	42	05 **030119** 001	80
05 **024474** 001	253	05 **027931** 001	486	05 **028126** 001	42	05 **030120** 001	81
05 **024475** 001	253	05 **027932** 001	486	05 **028130** 001	40	05 **030121** 001	81
05 **024476** 001	253	05 **027933** 001	486	05 **028132** 001	40	05 **030122** 001	81
05 **024477** 001	253	05 **027934** 001	486	05 **028134** 001	40	05 **030127** 001	81
05 **024478** 001	253	05 **027935** 001	486	05 **028136** 001	40	05 **030128** 001	81
05 **024479** 001	253	05 **027936** 001	487	05 **028148** 001	42	05 **030129** 001	81
05 **024480** 001	251	05 **027950** 001	40	05 **028150** 001	42	05 **030130** 001	81
05 **024481** 001	254	05 **027952** 001	40	05 **028152** 001	42	05 **030131** 001	81
05 **024482** 001	254	05 **027954** 001	40	05 **028160** 001	287	05 **030135** 001	81
05 **024483** 001	254	05 **027956** 001	40	05 **028205** 001	42	05 **030150** 001	82
05 **024484** 001	253	05 **027958** 001	40	05 **028210** 001	42	05 **030151** 001	82
05 **024485** 001	253	05 **028000** 001	39	05 **028215** 001	42	05 **030160** 001	68
05 **024486** 001	253	05 **028001** 001	39	05 **028220** 001	42	05 **030170** 001	82
05 **024487** 001	253	05 **028002** 001	39	05 **028225** 001	42	05 **030180** 001	82
05 **024488** 001	253	05 **028003** 001	39	05 **028230** 001	42	05 **030181** 001	72
05 **024489** 001	253	05 **028004** 001	39	05 **029405** 001	42	05 **030400** 001	80
05 **026350** 001	61	05 **028005** 001	39	05 **029410** 001	42	05 **030401** 001	80
05 **026351** 001	61	05 **028008** 001	39	05 **029415** 001	42	05 **030402** 001	80
05 **026352** 001	61	05 **028010** 001	39	05 **029420** 001	42	05 **030403** 001	80
05 **026353** 001	61	05 **028012** 001	39	05 **029425** 001	42	05 **030404** 001	80
05 **026354** 001	61	05 **028013** 001	39	05 **029430** 001	42	05 **030405** 001	80
05 **026360** 001	61	05 **028015** 001	39	05 **029435** 001	42	05 **030406** 001	80
05 **026361** 001	61	05 **028020** 001	39	05 **029440** 001	42	05 **030410** 001	82
05 **026363** 001	61	05 **028025** 001	39	05 **029445** 001	42	05 **030411** 001	82
05 **026372** 001	61	05 **028029** 001	40	05 **029450** 001	42	05 **030412** 001	82
05 **026373** 001	61	05 **028030** 001	40	05 **029460** 001	43	05 **030413** 001	82
05 **026374** 001	61	05 **028031** 001	40	05 **029461** 001	43	05 **030414** 001	82
05 **026382** 001	61	05 **028032** 001	40	05 **029462** 001	43	05 **030415** 001	82

Code No.	Page
05 **030416** 001	82
05 **030417** 001	82
05 **030418** 001	82
05 **031400** 001	54
05 **031401** 001	54
05 **031402** 001	54
05 **031403** 001	54
05 **031405** 001	54
05 **031406** 001	54
05 **031408** 001	54
05 **031409** 001	54
05 **031411** 001	54
05 **031412** 001	54
05 **031413** 001	54
05 **031416** 001	54
05 **031420** 001	54
05 **031421** 001	54
05 **031422** 001	54
05 **031424** 001	54
05 **031425** 001	54
05 **031426** 001	54
05 **031427** 001	54
05 **031440** 001	54
05 **031441** 001	54
05 **031442** 001	54
05 **031444** 001	54
05 **031445** 001	54
05 **031447** 001	54
05 **031460** 001	54
05 **031461** 001	54
05 **031463** 001	54
05 **031466** 001	54
05 **031500** 001	55
05 **031501** 001	55
05 **031502** 001	55
05 **031503** 001	55
05 **031504** 001	55
05 **031505** 001	55
05 **031506** 001	55
05 **031507** 001	55
05 **031508** 001	55
05 **031509** 001	55
05 **031510** 001	55
05 **031511** 001	55
05 **031512** 001	55
05 **031551** 001	56
05 **031552** 001	56
05 **031553** 001	56
05 **031554** 001	56
05 **031575** 001	122
05 **031576** 001	123
05 **031580** 001	122
05 **031581** 001	122
05 **031582** 001	122
05 **031583** 001	122
05 **031584** 001	122
05 **031585** 001	122
05 **031587** 001	122
05 **031588** 001	122
05 **031589** 001	122
05 **031600** 001	122
05 **031601** 001	122
05 **031602** 001	122
05 **031603** 001	122
05 **031604** 001	122
05 **031605** 001	122
05 **031610** 001	122
05 **031611** 001	122
05 **031613** 001	122
05 **031615** 001	122
05 **032001** 001	22
05 **032002** 001	22
05 **032003** 001	22
05 **032004** 001	22
05 **032005** 001	22
05 **032006** 001	22
05 **032007** 001	22
05 **032020** 001	22
05 **032021** 001	22
05 **032022** 001	22
05 **032023** 001	22
05 **032030** 001	22
05 **032031** 001	22
05 **032032** 001	22
05 **032033** 001	22
05 **032050** 001	23
05 **032051** 001	23
05 **032052** 001	23
05 **032053** 001	23
05 **032054** 001	23
05 **032055** 001	23
05 **032056** 001	23
05 **032057** 001	23
05 **032058** 001	23
05 **032060** 001	24
05 **032061** 001	24
05 **032063** 001	25
05 **032070** 002	23
05 **032071** 002	23
05 **040001** 001	293
05 **040030** 001	397
05 **040031** 001	397
05 **040032** 001	397
05 **040033** 001	397
05 **040034** 001	397
05 **040040** 001	397
05 **040041** 001	397
05 **040042** 001	397
05 **040043** 001	397
05 **040045** 001	397
05 **040046** 001	397
05 **040047** 001	397
05 **040048** 001	397
05 **040049** 001	397
05 **042605** 001	428
05 **042655** 001	428
05 **042665** 001	428
05 **042705** 001	428
05 **042715** 001	428
05 **042750** 001	428
05 **042755** 001	428
05 **042760** 001	428
05 **042765** 001	428
05 **042768** 001	428
05 **048680** 001	418
05 **048681** 001	418
05 **050005** 001	159, 182, 203
05 **050205** 001	427
05 **050210** 001	427
05 **050215** 001	427
05 **050220** 001	427
05 **050510** 001	427
05 **050650** 001	427
05 **051005** 001	287
05 **051010** 001	45
05 **051011** 001	46
05 **051016** 001	264
05 **051019** 001	264
05 **051021** 001	264
05 **051023** 001	264
05 **051024** 001	266
05 **051025** 001	266
05 **051030** 001	290
05 **051031** 001	290
05 **051040** 001	288
05 **051041** 001	288
05 **051042** 001	272
05 **051043** 001	84
05 **051045** 001	150
05 **051105** 001	287
05 **051106** 001	85
05 **051205** 001	287
05 **051272** 001	284
05 **051273** 001	84
05 **051274** 001	287
05 **051276** 001	70
05 **051461** 001	288
05 **051462** 001	284
05 **051464** 001	83
05 **051465** 001	284
05 **051482** 001	285
05 **051500** 001	420
05 **051501** 001	420
05 **051502** 001	420
05 **051610** 001	286
05 **051615** 001	286
05 **051620** 001	286
05 **051835** 001	292
05 **052490** 001	417
05 **052500** 001	416
05 **052502** 001	415
05 **052503** 001	416
05 **052504** 001	416
05 **052505** 001	421
05 **052575** 001	421
05 **052625** 001	421
05 **052655** 001	421
05 **052725** 001	421
05 **053175** 001	424
05 **053275** 001	424
05 **053425** 001	422
05 **053455** 001	422
05 **053457** 001	422
05 **053458** 001	422
05 **053459** 001	422
05 **053460** 001	423
05 **053475** 001	423
05 **053480** 001	423
05 **053485** 001	423
05 **053520** 001	419
05 **053522** 001	419
05 **053560** 001	419
05 **053870** 001	420
05 **053872** 001	419
05 **053920** 001	420
05 **053923** 001	414
05 **055950** 001	397
05 **055951** 001	397
05 **055952** 001	397
05 **055953** 001	397
05 **056005** 001	377
05 **056007** 001	377
05 **056010** 001	377
05 **056015** 001	377
05 **056020** 001	377
05 **056025** 001	377
05 **056030** 001	377
05 **056037** 001	377
05 **056040** 001	377
05 **056045** 001	377
05 **056064** 001	376
05 **056066** 001	376
05 **056068** 001	376
05 **056155** 001	453
05 **056157** 001	453
05 **056158** 001	454
05 **056159** 001	450
05 **056161** 001	450
05 **056163** 001	451
05 **056164** 001	452
05 **056168** 001	454
05 **056172** 001	376
05 **056174** 001	376
05 **056176** 001	376
05 **056200** 001	377
05 **056203** 001	376
05 **056210** 001	376
05 **056220** 001	376
05 **056225** 001	376
05 **056233** 001	376
05 **056240** 001	376
05 **056285** 001	454
05 **056291** 001	443
05 **056294** 001	454
05 **056295** 001	452
05 **056296** 001	453
05 **056303** 001	381
05 **056305** 001	381
05 **056310** 001	381
05 **056315** 001	381
05 **056320** 001	381
05 **056325** 001	381
05 **056330** 001	381
05 **056332** 001	381
05 **056335** 001	381
05 **056340** 001	381
05 **056341** 001	387
05 **056342** 001	387

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **056343** 001	387	05 **056714** 001	340	05 **057434** 001	460	05 **057672** 001	390
05 **056344** 001	387	05 **056720** 001	340	05 **057441** 001	440	05 **057675** 001	410
05 **056345** 001	387	05 **056722** 001	340	05 **057442** 001	458	05 **057676** 001	410
05 **056346** 001	387	05 **056724** 001	340	05 **057450** 001	448	05 **057680** 001	434
05 **056350** 001	381	05 **056805** 001	342	05 **057455** 001	448	05 **057682** 001	434
05 **056352** 001	381	05 **056810** 001	342	05 **057460** 001	278	05 **057683** 001	434
05 **056354** 001	381	05 **056812** 001	342	05 **057505** 001	385	05 **057684** 001	435
05 **056356** 001	381	05 **056815** 001	342	05 **057510** 001	385	05 **057688** 001	435
05 **056358** 001	381	05 **056820** 001	342	05 **057515** 001	385	05 **057690** 001	434
05 **056368** 001	442	05 **056825** 001	342	05 **057520** 001	385	05 **057691** 001	436
05 **056374** 001	441	05 **056835** 001	342	05 **057525** 001	385	05 **057692** 001	436
05 **056375** 001	450	05 **056910** 001	341	05 **057530** 001	385	05 **057693** 001	436
05 **056376** 001	451	05 **056915** 001	341	05 **057550** 001	385	05 **057694** 001	436
05 **056400** 001	317	05 **056925** 001	341	05 **057551** 001	385	05 **057695** 001	436
05 **056402** 001	317	05 **056937** 001	342	05 **057552** 001	385	05 **057705** 001	332
05 **056404** 001	317	05 **056938** 001	342	05 **057553** 001	385	05 **057710** 001	332
05 **056410** 001	318	05 **056939** 001	342	05 **057554** 001	385	05 **057715** 001	332
05 **056412** 001	318	05 **057110** 001	276	05 **057555** 001	385	05 **057720** 001	332
05 **056414** 001	318	05 **057111** 001	276	05 **057560** 001	385	05 **057725** 001	332
05 **056420** 001	318	05 **057115** 001	452	05 **057561** 001	385	05 **057750** 001	324
05 **056422** 001	318	05 **057116** 001	444	05 **057562** 001	385	05 **057751** 001	318
05 **056424** 001	318	05 **057117** 001	441	05 **057563** 001	385	05 **057752** 001	316
05 **056440** 001	448	05 **057122** 001	448	05 **057565** 001	385	05 **057753** 001	321
05 **056471** 001	456	05 **057150** 001	400	05 **057566** 001	385	05 **057760** 001	342
05 **056472** 001	456	05 **057151** 001	400	05 **057567** 001	385	05 **057761** 001	340
05 **056473** 001	456	05 **057152** 001	400	05 **057568** 001	385	05 **057762** 001	340
05 **056474** 001	455	05 **057153** 001	400	05 **057570** 001	385	05 **057763** 001	338
05 **056476** 001	457	05 **057160** 001	400	05 **057571** 001	385	05 **057770** 001	356
05 **056477** 001	443	05 **057161** 001	400	05 **057572** 001	385	05 **057771** 001	354
05 **056478** 001	457	05 **057162** 001	400	05 **057573** 001	385	05 **057772** 001	352
05 **056479** 001	456	05 **057163** 001	400	05 **057574** 001	385	05 **057773** 001	356
05 **056490** 001	218	05 **057210** 001	379	05 **057575** 001	385	05 **057774** 001	354
05 **056491** 001	218	05 **057213** 001	379	05 **057603** 001	380	05 **057775** 001	352
05 **056500** 001	324	05 **057223** 001	379	05 **057604** 001	380	05 **057776** 001	352
05 **056505** 001	323	05 **057225** 001	379	05 **057605** 001	380	05 **057790** 001	389
05 **056507** 001	324	05 **057230** 001	379	05 **057606** 001	380	05 **057908** 001	449
05 **056510** 001	323	05 **057235** 001	379	05 **057615** 001	316	05 **058005** 001	348
05 **056515** 001	324	05 **057240** 001	379	05 **057616** 001	316	05 **058010** 001	348
05 **056520** 001	324	05 **057250** 001	379	05 **057617** 001	316	05 **058015** 001	348
05 **056525** 001	323	05 **057255** 001	379	05 **057620** 001	338	05 **058020** 001	348
05 **056535** 001	324	05 **057402** 001	447	05 **057621** 001	338	05 **058025** 001	348
05 **056605** 001	322	05 **057404** 001	447	05 **057622** 001	338	05 **059030** 001	111
05 **056610** 001	322	05 **057412** 001	446	05 **057623** 001	352	05 **059291** 001	108
05 **056625** 001	322	05 **057414** 001	446	05 **057624** 001	352	05 **059293** 001	270
05 **056653** 001	262	05 **057415** 001	446	05 **057625** 001	352	05 **059294** 001	272
05 **056656** 001	269	05 **057416** 001	445	05 **057626** 001	352	05 **059295** 001	272
05 **056660** 001	323	05 **057417** 001	435	05 **057627** 001	352	05 **059297** 001	273
05 **056662** 001	323	05 **057418** 001	220	05 **057628** 001	352	05 **059298** 001	268
05 **056664** 001	323	05 **057420** 001	440	05 **057631** 001	388	05 **059299** 001	268
05 **056680** 001	380	05 **057421** 001	444	05 **057632** 001	388	05 **059305** 001	378
05 **056681** 001	380	05 **057422** 001	459	05 **057644** 001	382	05 **059307** 001	378
05 **056682** 001	380	05 **057423** 001	458	05 **057645** 001	382	05 **059310** 001	378
05 **056683** 001	380	05 **057424** 001	460	05 **057646** 001	382	05 **059315** 001	378
05 **056684** 001	380	05 **057425** 001	438	05 **057656** 001	326	05 **059320** 001	378
05 **056685** 001	380	05 **057426** 001	459	05 **057657** 001	326	05 **059325** 001	378
05 **056686** 001	380	05 **057427** 001	459	05 **057661** 001	344	05 **059330** 001	378
05 **056687** 001	380	05 **057428** 001	449	05 **057662** 001	344	05 **059335** 001	378
05 **056700** 001	339	05 **057429** 001	449	05 **057664** 001	358	05 **059337** 001	378
05 **056702** 001	339	05 **057430** 001	440	05 **057665** 001	358	05 **059340** 001	378
05 **056704** 001	339	05 **057431** 001	444	05 **057666** 001	358	05 **059345** 001	378
05 **056710** 001	340	05 **057432** 001	458	05 **057667** 001	358	05 **059450** 001	378
05 **056712** 001	340	05 **057433** 001	458	05 **057671** 001	390	05 **059451** 001	378

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **059452** 001	378	05 **059700** 001	358	05 **060056** 001	367	05 **060199** 001	360
05 **059453** 001	378	05 **059701** 001	358	05 **060057** 001	367	05 **060200** 001	360
05 **059466** 001	378	05 **059702** 001	358	05 **060060** 001	347	05 **060201** 001	360
05 **059472** 001	378	05 **059703** 001	358	05 **060065** 001	347	05 **060202** 001	360
05 **059478** 001	378	05 **059704** 001	358	05 **060080** 001	359	05 **060210** 001	402
05 **059480** 001	378	05 **059705** 001	358	05 **060081** 001	359	05 **060215** 001	402
05 **059486** 001	378	05 **059720** 001	350	05 **060082** 001	359	05 **060220** 001	402
05 **059488** 001	378	05 **059721** 001	350	05 **060083** 001	359	05 **060225** 001	402
05 **059489** 001	378	05 **059755** 001	330	05 **060084** 001	359	05 **060230** 001	402
05 **059490** 001	378	05 **059760** 001	330	05 **060085** 001	359	05 **060235** 001	402
05 **059492** 001	378	05 **059765** 001	330	05 **060086** 001	359	05 **060237** 001	402
05 **059496** 001	378	05 **059766** 001	330	05 **060087** 001	359	05 **060238** 001	402
05 **059500** 001	378	05 **059770** 001	330	05 **060098** 001	360	05 **060240** 001	402
05 **059503** 001	379	05 **059775** 001	330	05 **060100** 001	360	05 **060255** 001	402
05 **059507** 001	379	05 **059780** 001	330	05 **060105** 001	360	05 **060260** 001	402
05 **059515** 001	379	05 **059785** 001	330	05 **060110** 001	360	05 **060265** 001	402
05 **059517** 001	379	05 **059786** 001	330	05 **060115** 001	360	05 **060272** 001	401
05 **059530** 001	326	05 **059790** 001	330	05 **060120** 001	360	05 **060274** 001	401
05 **059532** 001	326	05 **059795** 001	330	05 **060125** 001	360	05 **060276** 001	401
05 **059534** 001	326	05 **059800** 001	330	05 **060130** 001	360	05 **060278** 001	401
05 **059540** 001	327	05 **059802** 001	330	05 **060131** 001	360	05 **060280** 001	401
05 **059542** 001	327	05 **059805** 001	330	05 **060132** 001	360	05 **060281** 001	401
05 **059544** 001	327	05 **059810** 001	330	05 **060133** 001	360	05 **060282** 001	401
05 **059550** 001	327	05 **059815** 001	330	05 **060134** 001	360	05 **060283** 001	401
05 **059552** 001	327	05 **059855** 001	329	05 **060135** 001	360	05 **060284** 001	401
05 **059554** 001	327	05 **059860** 001	329	05 **060136** 001	360	05 **060286** 001	401
05 **059602** 001	383	05 **059865** 001	329	05 **060137** 001	360	05 **060288** 001	401
05 **059603** 001	383	05 **059896** 001	351	05 **060138** 001	360	05 **060290** 001	401
05 **059604** 001	383	05 **059897** 001	351	05 **060139** 001	367	05 **060296** 001	391
05 **059605** 001	383	05 **059900** 001	346	05 **060140** 001	367	05 **060297** 001	391
05 **059610** 001	383	05 **059902** 001	346	05 **060141** 001	367	05 **060298** 001	391
05 **059615** 001	383	05 **059904** 001	346	05 **060142** 001	367	05 **060300** 001	391
05 **059620** 001	383	05 **059910** 001	346	05 **060143** 001	367	05 **060301** 001	391
05 **059625** 001	383	05 **059912** 001	346	05 **060144** 001	367	05 **060302** 001	391
05 **059628** 001	383	05 **059914** 001	346	05 **060145** 001	367	05 **060303** 001	391
05 **059629** 001	383	05 **059920** 001	346	05 **060146** 001	367	05 **060304** 001	391
05 **059630** 001	383	05 **059922** 001	346	05 **060147** 001	390	05 **060360** 001	359
05 **059631** 001	383	05 **059924** 001	346	05 **060148** 001	390	05 **060361** 001	359
05 **059632** 001	383	05 **060005** 001	347	05 **060149** 001	390	05 **060362** 001	359
05 **059633** 001	383	05 **060010** 001	347	05 **060150** 001	391	05 **060363** 001	359
05 **059634** 001	383	05 **060015** 001	347	05 **060155** 001	391	05 **060364** 001	359
05 **059635** 001	383	05 **060027** 001	347	05 **060160** 001	391	05 **060365** 001	359
05 **059636** 001	383	05 **060029** 001	347	05 **060165** 001	391	05 **060366** 001	359
05 **059640** 001	387	05 **060030** 001	347	05 **060170** 001	391	05 **060380** 001	373
05 **059641** 001	387	05 **060031** 001	347	05 **060175** 001	391	05 **060400** 001	401
05 **059642** 001	387	05 **060033** 001	347	05 **060180** 001	391	05 **060401** 001	401
05 **059643** 001	387	05 **060035** 001	347	05 **060182** 001	391	05 **060402** 001	401
05 **059644** 001	387	05 **060036** 001	347	05 **060184** 001	391	05 **060403** 001	401
05 **059645** 001	387	05 **060037** 001	347	05 **060185** 001	360	05 **060404** 001	401
05 **059660** 001	383	05 **060038** 001	347	05 **060186** 001	360	05 **060405** 001	401
05 **059661** 001	383	05 **060041** 001	347	05 **060187** 001	360	05 **060406** 001	401
05 **059662** 001	383	05 **060043** 001	347	05 **060188** 001	360	05 **060407** 001	401
05 **059663** 001	383	05 **060045** 001	347	05 **060189** 001	360	05 **060408** 001	401
05 **059664** 001	383	05 **060047** 001	347	05 **060190** 001	360	05 **060409** 001	401
05 **059665** 001	383	05 **060048** 001	367	05 **060191** 001	360	05 **060410** 001	401
05 **059666** 001	383	05 **060049** 001	367	05 **060192** 001	360	05 **060411** 001	401
05 **059667** 001	383	05 **060050** 001	367	05 **060193** 001	360	05 **060412** 001	401
05 **059668** 001	383	05 **060051** 001	367	05 **060194** 001	360	05 **060420** 001	402
05 **059680** 001	384	05 **060052** 001	367	05 **060195** 001	360	05 **060421** 001	402
05 **059681** 001	384	05 **060053** 001	367	05 **060196** 001	360	05 **060422** 001	402
05 **059682** 001	384	05 **060054** 001	367	05 **060197** 001	360	05 **060423** 001	402
05 **059683** 001	384	05 **060055** 001	347	05 **060198** 001	360	05 **060424** 001	402

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **060425** 001	402	05 **066085** 001	357	05 **066450** 001	357	05 **066682** 001	393
05 **060426** 001	402	05 **066100** 001	353	05 **066455** 001	357	05 **066683** 001	393
05 **060427** 001	402	05 **066102** 001	353	05 **066460** 001	357	05 **066684** 001	393
05 **060428** 001	402	05 **066104** 001	353	05 **066465** 001	357	05 **066685** 001	393
05 **060429** 001	402	05 **066106** 001	353	05 **066470** 001	357	05 **066686** 001	393
05 **060430** 001	402	05 **066108** 001	353	05 **066475** 001	357	05 **066687** 001	393
05 **060431** 001	402	05 **066110** 001	353	05 **066480** 001	357	05 **066688** 001	393
05 **060432** 001	402	05 **066120** 001	354	05 **066485** 001	356	05 **066690** 001	393
05 **064140** 001	362	05 **066122** 001	354	05 **066486** 001	356	05 **066692** 001	393
05 **064144** 001	362	05 **066124** 001	354	05 **066487** 001	356	05 **066694** 001	393
05 **064146** 001	362	05 **066126** 001	354	05 **066488** 001	356	05 **066696** 001	393
05 **064148** 001	362	05 **066128** 001	354	05 **066489** 001	356	05 **066700** 001	394
05 **064150** 001	362	05 **066130** 001	354	05 **066490** 001	356	05 **066702** 001	394
05 **064155** 001	362	05 **066150** 001	396	05 **066491** 001	356	05 **066704** 001	394
05 **064160** 001	362	05 **066155** 001	396	05 **066492** 001	356	05 **066740** 001	394
05 **064166** 001	363	05 **066160** 001	396	05 **066493** 001	356	05 **066742** 001	394
05 **064168** 001	363	05 **066165** 001	396	05 **066494** 001	356	05 **066744** 001	394
05 **064170** 001	363	05 **066170** 001	396	05 **066495** 001	356	05 **066746** 001	394
05 **064175** 001	363	05 **066175** 001	396	05 **066496** 001	356	05 **066750** 001	394
05 **064180** 001	363	05 **066180** 001	396	05 **066497** 001	366	05 **066752** 001	394
05 **064185** 001	363	05 **066185** 001	396	05 **066498** 001	366	05 **066754** 001	394
05 **064190** 001	363	05 **066190** 001	396	05 **066499** 001	366	05 **066758** 001	395
05 **064200** 001	363	05 **066195** 001	396	05 **066500** 001	366	05 **066760** 001	395
05 **065075** 001	333	05 **066200** 001	396	05 **066505** 001	366	05 **066762** 001	395
05 **065081** 001	333	05 **066272** 001	368	05 **066510** 001	366	05 **066764** 001	395
05 **065090** 001	348	05 **066274** 001	368	05 **066515** 001	366	05 **066766** 001	395
05 **065096** 001	348	05 **066276** 001	368	05 **066520** 001	366	05 **066768** 001	395
05 **065110** 001	333	05 **066278** 001	368	05 **066525** 001	366	05 **066770** 001	395
05 **065112** 001	333	05 **066279** 001	368	05 **066530** 001	366	05 **066772** 001	395
05 **065114** 001	333	05 **066280** 001	368	05 **066618** 001	392	05 **066774** 001	395
05 **065116** 001	333	05 **066282** 001	368	05 **066619** 001	392	05 **066780** 001	395
05 **065125** 001	349	05 **066284** 001	368	05 **066620** 001	392	05 **066782** 001	395
05 **065127** 001	349	05 **066286** 001	368	05 **066622** 001	392	05 **066784** 001	395
05 **065129** 001	349	05 **066287** 001	368	05 **066624** 001	392	05 **066785** 001	395
05 **065150** 001	334	05 **066288** 001	368	05 **066626** 001	392	05 **066786** 001	395
05 **065152** 001	334	05 **066290** 001	368	05 **066628** 001	392	05 **066787** 001	395
05 **065154** 001	334	05 **066300** 001	355	05 **066630** 001	392	05 **066788** 001	395
05 **065167** 001	349	05 **066301** 001	355	05 **066632** 001	392	05 **066790** 001	395
05 **065169** 001	349	05 **066302** 001	355	05 **066633** 001	392	05 **066792** 001	395
05 **065197** 001	334	05 **066303** 001	355	05 **066634** 001	392	05 **066794** 001	395
05 **066030** 001	375	05 **066304** 001	355	05 **066635** 001	392	05 **066850** 001	398
05 **066031** 001	375	05 **066305** 001	355	05 **066638** 001	392	05 **066851** 001	398
05 **066032** 001	375	05 **066308** 001	355	05 **066640** 001	392	05 **066852** 001	398
05 **066033** 001	375	05 **066310** 001	355	05 **066642** 001	392	05 **066853** 001	398
05 **066040** 001	375	05 **066312** 001	355	05 **066644** 001	392	05 **066854** 001	398
05 **066041** 001	375	05 **066313** 001	355	05 **066646** 001	392	05 **066860** 001	398
05 **066042** 001	375	05 **066315** 001	355	05 **066650** 001	394	05 **066861** 001	398
05 **066043** 001	375	05 **066320** 001	355	05 **066652** 001	394	05 **066862** 001	398
05 **066070** 001	354	05 **066325** 001	356	05 **066654** 001	394	05 **066863** 001	398
05 **066071** 001	354	05 **066330** 001	356	05 **066656** 001	394	05 **066864** 001	398
05 **066072** 001	354	05 **066335** 001	356	05 **066658** 001	394	05 **066900** 001	361
05 **066073** 001	354	05 **066394** 001	389	05 **066660** 001	393	05 **066901** 001	361
05 **066074** 001	354	05 **066395** 001	389	05 **066662** 001	393	05 **066902** 001	361
05 **066075** 001	354	05 **066396** 001	389	05 **066664** 001	393	05 **066905** 001	361
05 **066076** 001	354	05 **066400** 001	389	05 **066666** 001	393	05 **066910** 001	361
05 **066077** 001	354	05 **066405** 001	389	05 **066668** 001	393	05 **066915** 001	361
05 **066078** 001	354	05 **066410** 001	389	05 **066670** 001	393	05 **066920** 001	361
05 **066080** 001	357	05 **066415** 001	389	05 **066672** 001	393	05 **066925** 001	361
05 **066081** 001	357	05 **066420** 001	389	05 **066674** 001	393	05 **066930** 001	361
05 **066082** 001	357	05 **066445** 001	388	05 **066676** 001	393	05 **066931** 001	361
05 **066083** 001	357	05 **066446** 001	388	05 **066678** 001	393	05 **066932** 001	361
05 **066084** 001	357	05 **066447** 001	388	05 **066680** 001	393	05 **066933** 001	361

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **066934** 001	361	05 **071090** 001	367	05 **072451** 001	356	05 **073342** 001	381
05 **066935** 001	361	05 **071091** 001	367	05 **072452** 001	356	05 **073344** 001	381
05 **066936** 001	361	05 **071092** 001	367	05 **073200** 001	427	05 **073346** 001	356
05 **066937** 001	361	05 **071094** 001	367	05 **073210** 001	425	05 **073357** 001	422
05 **066938** 001	361	05 **071097** 001	390	05 **073220** 001	219	05 **073370** 001	341
05 **066939** 001	361	05 **071098** 001	390	05 **073230** 001	222	05 **073371** 001	341
05 **066940** 001	361	05 **071099** 001	390	05 **073240** 001	267	05 **073372** 001	341
05 **066941** 001	361	05 **071100** 001	414	05 **073260** 001	150	05 **073373** 001	341
05 **066942** 001	361	05 **071101** 001	382	05 **073261** 001	174	05 **073375** 001	356
05 **066943** 001	361	05 **071102** 001	382	05 **073262** 001	192	05 **073376** 001	356
05 **066945** 001	361	05 **071103** 001	382	05 **073268** 001	228	05 **073380** 001	342
05 **066946** 001	361	05 **071104** 001	382	05 **073270** 001	228	05 **073391** 001	242
05 **066947** 001	361	05 **071105** 001	382	05 **073271** 001	228	05 **073401** 001	422
05 **066948** 001	361	05 **071106** 001	382	05 **073272** 001	228	05 **073403** 001	62
05 **066949** 001	361	05 **071107** 001	382	05 **073273** 001	228	05 **073404** 001	454
05 **066950** 001	361	05 **071108** 001	382	05 **073274** 001	228	05 **073406** 001	452
05 **071000** 001	376	05 **071109** 001	438	05 **073275** 001	228	05 **073410** 001	450
05 **071001** 001	376	05 **071110** 001	438	05 **073276** 001	228	05 **073416** 001	451
05 **071002** 001	376	05 **071116** 001	270	05 **073277** 001	228	05 **073418** 001	442
05 **071010** 001	316	05 **071117** 001	271	05 **073278** 001	228	05 **073419** 001	445
05 **071011** 001	316	05 **071222** 001	401	05 **073279** 001	228	05 **073420** 001	414
05 **071012** 001	316	05 **071223** 001	401	05 **073280** 001	228	05 **073421** 001	415
05 **071020** 001	338	05 **071224** 001	401	05 **073281** 001	228	05 **073495** 001	402
05 **071021** 001	338	05 **071225** 001	401	05 **073282** 001	228	05 **073500** 001	402
05 **071022** 001	338	05 **071228** 001	401	05 **073283** 001	228	05 **073501** 001	402
05 **071025** 001	388	05 **072014** 001	511	05 **073284** 001	228	05 **073502** 001	402
05 **071030** 001	352	05 **072017** 001	511	05 **073285** 001	228	05 **073503** 001	402
05 **071031** 001	352	05 **072050** 001	377	05 **073286** 001	228	05 **073504** 001	402
05 **071032** 001	352	05 **072055** 001	377	05 **073287** 001	228	05 **073505** 001	402
05 **071033** 001	352	05 **072057** 001	377	05 **073290** 001	230	05 **073506** 001	402
05 **071034** 001	352	05 **072059** 001	377	05 **073295** 001	230	05 **073507** 001	402
05 **071035** 001	352	05 **072061** 001	377	05 **073300** 001	377	05 **073508** 001	402
05 **071036** 001	352	05 **072063** 001	377	05 **073301** 001	377	05 **073509** 001	402
05 **071037** 001	352	05 **072065** 001	377	05 **073302** 001	377	05 **073510** 001	402
05 **071038** 001	352	05 **072070** 001	324	05 **073303** 001	377	05 **073511** 001	417
05 **071041** 001	344	05 **072072** 001	324	05 **073304** 001	324	05 **073512** 001	322
05 **071046** 001	358	05 **072074** 001	324	05 **073305** 001	324	05 **073513** 001	322
05 **071047** 001	358	05 **072080** 001	342	05 **073306** 001	324	05 **073514** 001	322
05 **071049** 001	382	05 **072082** 001	342	05 **073307** 001	324	05 **073515** 001	322
05 **071060** 001	380	05 **072084** 001	342	05 **073308** 001	342	05 **073516** 001	341
05 **071061** 001	380	05 **072400** 001	324	05 **073309** 001	342	05 **073517** 001	341
05 **071062** 001	380	05 **072401** 001	324	05 **073310** 001	342	05 **073518** 001	341
05 **071063** 001	380	05 **072402** 001	324	05 **073311** 001	342	05 **073519** 001	341
05 **071064** 001	380	05 **072403** 001	343	05 **073313** 001	356	05 **073520** 001	330
05 **071065** 001	380	05 **072404** 001	343	05 **073314** 001	356	05 **073521** 001	330
05 **071066** 001	380	05 **072405** 001	343	05 **073315** 001	356	05 **073522** 001	330
05 **071070** 001	380	05 **072406** 001	356	05 **073316** 001	356	05 **073523** 001	347
05 **071071** 001	380	05 **072407** 001	356	05 **073317** 001	356	05 **073524** 001	347
05 **071072** 001	380	05 **072408** 001	356	05 **073318** 001	419	05 **073525** 001	347
05 **071073** 001	380	05 **072409** 001	356	05 **073323** 001	323	05 **073526** 001	360
05 **071074** 001	380	05 **072410** 001	356	05 **073324** 001	323	05 **073527** 001	360
05 **071075** 001	380	05 **072411** 001	356	05 **073325** 001	323	05 **073528** 001	360
05 **071076** 001	380	05 **072412** 001	356	05 **073326** 001	323	05 **073529** 001	360
05 **071077** 001	380	05 **072440** 001	324	05 **073332** 001	317	05 **073530** 001	360
05 **071080** 001	378	05 **072441** 001	324	05 **073333** 001	317	05 **073531** 001	360
05 **071081** 001	326	05 **072443** 001	343	05 **073334** 001	317	05 **073534** 001	446
05 **071082** 001	326	05 **072444** 001	343	05 **073335** 001	317	05 **073536** 001	453
05 **071083** 001	326	05 **072446** 001	356	05 **073336** 001	339	05 **073537** 001	454
05 **071084** 001	344	05 **072447** 001	356	05 **073337** 001	339	05 **073538** 001	455
05 **071085** 001	344	05 **072448** 001	356	05 **073338** 001	339	05 **073540** 001	284
05 **071086** 001	344	05 **072449** 001	356	05 **073339** 001	339	05 **073541** 001	285
05 **071089** 001	367	05 **072450** 001	356	05 **073340** 001	356	05 **073544** 001	238

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **073593** 001	240	05 **073964** 001	358	05 **074822** 001	481	05 **078640** 001	505
05 **073594** 001	243	05 **073965** 001	358	05 **074822** 010	481	05 **078641** 001	505
05 **073596** 001	244	05 **073966** 001	358	05 **074824** 001	481	05 **078642** 001	506
05 **073598** 001	252	05 **073967** 001	358	05 **074824** 010	481	05 **078650** 001	506
05 **073599** 001	252	05 **073971** 001	390	05 **074826** 001	483	05 **078651** 001	506
05 **073610** 001	316	05 **073972** 001	390	05 **074826** 010	483	05 **078652** 001	506
05 **073611** 001	316	05 **073980** 001	434	05 **074828** 001	483	05 **078653** 001	506
05 **073612** 001	316	05 **073990** 001	410	05 **074828** 010	483	05 **078654** 001	506
05 **073613** 001	338	05 **074700** 001	472	05 **074840** 001	481	05 **078655** 001	506
05 **073614** 001	338	05 **074701** 001	472	05 **074840** 010	481	05 **078656** 001	506
05 **073615** 001	338	05 **074702** 001	472	05 **074842** 001	481	05 **078657** 001	506
05 **073616** 001	414	05 **074705** 001	472	05 **074842** 010	481	05 **078658** 001	506
05 **073620** 001	352	05 **074710** 001	474	05 **075604** 001	492	05 **078660** 001	506
05 **073621** 001	352	05 **074711** 001	474	05 **075605** 001	492	05 **078661** 001	506
05 **073622** 001	352	05 **074712** 001	474	05 **075610** 001	494	05 **078662** 001	506
05 **073623** 001	352	05 **074715** 001	480	05 **075611** 001	494	05 **078663** 001	506
05 **073624** 001	352	05 **074715** 010	480	05 **075620** 001	495	05 **078664** 001	506
05 **073625** 001	352	05 **074716** 001	480	05 **075621** 001	495	05 **078666** 001	507
05 **073626** 001	352	05 **074716** 010	480	05 **075622** 001	496	05 **078667** 001	507
05 **073630** 001	438	05 **074717** 001	480	05 **075623** 001	496	05 **078670** 001	502
05 **073634** 001	439	05 **074717** 010	480	05 **075624** 001	497	05 **078671** 001	502
05 **073635** 001	455	05 **074720** 001	482	05 **075630** 001	497	05 **078672** 001	502
05 **073637** 001	456	05 **074720** 010	482	05 **075651** 001	498	05 **078673** 001	502
05 **073638** 001	456	05 **074721** 001	482	05 **075652** 001	498	05 **078674** 001	502
05 **073640** 001	216	05 **074721** 010	482	05 **075653** 001	499	05 **078675** 001	502
05 **073645** 001	220	05 **074722** 001	482	05 **075654** 001	499	05 **078676** 001	502
05 **073660** 001	290	05 **074722** 010	482	05 **075655** 001	500	05 **078677** 001	502
05 **073661** 002	290	05 **074728** 001	480	05 **075656** 001	500	05 **078678** 001	502
05 **073665** 001	289	05 **074728** 010	480	05 **078200** 001	504	05 **078679** 001	502
05 **073670** 001	85	05 **074730** 001	473	05 **078205** 001	505	05 **078680** 001	502
05 **073671** 001	85	05 **074731** 001	473	05 **078210** 001	505	05 **078681** 001	502
05 **073675** 001	70	05 **074733** 001	474	05 **078345** 001	505	05 **078682** 001	502
05 **073676** 001	71	05 **074734** 001	474	05 **078600** 001	502	05 **078683** 001	502
05 **073677** 001	70	05 **074738** 001	476	05 **078601** 001	502	05 **078684** 001	502
05 **073680** 001	63	05 **074739** 001	476	05 **078602** 001	502	05 **078685** 001	502
05 **073681** 001	63	05 **074745** 001	476	05 **078603** 001	502	05 **078686** 001	502
05 **073720** 001	360	05 **074746** 001	477	05 **078604** 001	502	05 **078687** 001	502
05 **073721** 001	360	05 **074750** 001	114	05 **078605** 001	502	05 **078690** 001	503
05 **073722** 001	360	05 **074752** 001	114	05 **078606** 001	502	05 **078691** 001	503
05 **073723** 001	360	05 **074757** 001	114	05 **078607** 001	502	05 **078692** 001	503
05 **073724** 001	360	05 **074770** 001	472	05 **078608** 001	502	05 **078693** 001	503
05 **073890** 001	436	05 **074772** 001	472	05 **078609** 001	502	05 **078694** 001	503
05 **073904** 001	380	05 **074774** 001	472	05 **078610** 001	502	05 **078695** 001	503
05 **073905** 001	380	05 **074780** 001	473	05 **078611** 001	502	05 **078696** 001	503
05 **073906** 001	380	05 **074782** 001	473	05 **078612** 001	502	05 **078697** 001	503
05 **073916** 001	316	05 **074784** 001	473	05 **078620** 001	503	05 **078698** 001	503
05 **073917** 001	316	05 **074786** 001	475	05 **078621** 001	503	05 **078699** 001	503
05 **073921** 001	338	05 **074788** 001	475	05 **078622** 001	503	05 **078700** 001	503
05 **073922** 001	338	05 **074790** 001	480	05 **078623** 001	503	05 **078701** 001	503
05 **073924** 001	352	05 **074790** 010	480	05 **078624** 001	503	05 **078702** 001	503
05 **073925** 001	352	05 **074792** 001	480	05 **078625** 001	503	05 **078703** 001	503
05 **073926** 001	352	05 **074792** 010	480	05 **078626** 001	503	05 **078704** 001	503
05 **073927** 001	352	05 **074794** 001	480	05 **078627** 001	503	05 **078705** 001	503
05 **073931** 001	388	05 **074794** 010	480	05 **078628** 001	503	05 **078707** 001	504
05 **073932** 001	388	05 **074800** 001	483	05 **078629** 001	503	05 **078708** 001	504
05 **073944** 001	382	05 **074800** 010	483	05 **078630** 001	503	05 **078710** 001	505
05 **073945** 001	382	05 **074802** 001	475	05 **078631** 001	503	05 **078714** 001	506
05 **073946** 001	382	05 **074804** 001	475	05 **078632** 001	503	05 **078715** 001	506
05 **073956** 001	326	05 **074810** 001	483	05 **078633** 001	503	05 **078716** 001	506
05 **073957** 001	326	05 **074810** 010	483	05 **078635** 001	504	05 **078717** 001	506
05 **073961** 001	344	05 **074820** 001	481	05 **078636** 001	504	05 **078720** 001	507
05 **073962** 001	344	05 **074820** 010	481	05 **078637** 001	504	05 **078721** 001	507

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **100000** 001	94	05 **104621** 001	463	05 **110055** 001	35	05 **118064** 001	68
05 **100001** 001	94	05 **104622** 001	463	05 **110068** 001	44	05 **118066** 001	68
05 **100002** 001	94	05 **104630** 001	462	05 **110069** 001	44	05 **118068** 001	68
05 **100003** 001	94	05 **104631** 001	462	05 **110070** 001	44	05 **118070** 001	68
05 **100004** 001	94	05 **104632** 001	462	05 **110075** 001	44	05 **118072** 001	68
05 **100011** 001	95	05 **104633** 001	462	05 **110078** 001	44	05 **118074** 001	68
05 **100012** 001	95	05 **104634** 001	462	05 **110104** 001	34	05 **118075** 001	68
05 **100015** 001	96	05 **104635** 001	462	05 **110105** 001	34	05 **118076** 001	68
05 **100016** 001	96	05 **104640** 001	462	05 **110150** 001	35	05 **118078** 001	68
05 **100019** 001	97	05 **104641** 001	462	05 **110151** 001	35	05 **118080** 001	68
05 **100020** 001	97	05 **104642** 001	462	05 **117680** 001	41	05 **118082** 001	68
05 **100021** 001	98	05 **104643** 001	462	05 **117681** 001	41	05 **118089** 001	68
05 **100022** 001	98	05 **104644** 001	462	05 **117682** 001	41	05 **118090** 001	68
05 **100024** 001	100	05 **104645** 001	462	05 **117683** 001	41	05 **118092** 001	68
05 **100025** 001	100	05 **104650** 001	462	05 **117684** 001	41	05 **118094** 001	68
05 **100026** 001	100	05 **104651** 001	463	05 **117685** 001	41	05 **118096** 001	68
05 **100030** 001	35	05 **104652** 001	463	05 **117686** 001	41	05 **118098** 001	68
05 **100031** 001	35	05 **104653** 001	465	05 **117687** 001	41	05 **118100** 001	68
05 **100042** 001	34	05 **104654** 001	461	05 **117688** 001	41	05 **118102** 001	68
05 **100043** 001	34	05 **104655** 001	462	05 **117689** 001	41	05 **118103** 001	68
05 **100044** 001	34	05 **104660** 001	461	05 **117691** 001	41	05 **118106** 001	68
05 **100050** 001	36	05 **104661** 001	461	05 **117990** 001	66	05 **118108** 001	69
05 **100051** 001	36	05 **104662** 001	461	05 **117991** 001	66	05 **118109** 001	69
05 **100052** 001	36	05 **104663** 001	461	05 **117992** 001	66	05 **118110** 001	69
05 **100055** 001	37	05 **104664** 001	461	05 **117993** 001	66	05 **118112** 001	69
05 **100056** 001	37	05 **104665** 001	461	05 **117994** 001	66	05 **118114** 001	69
05 **100057** 001	37	05 **104666** 001	461	05 **117995** 001	66	05 **118116** 001	69
05 **100060** 001	39	05 **104667** 001	461	05 **117997** 001	66	05 **118118** 001	69
05 **100061** 001	39	05 **104668** 001	461	05 **118000** 001	66	05 **118120** 001	69
05 **100062** 001	39	05 **104669** 001	461	05 **118002** 001	66	05 **118122** 001	69
05 **100063** 001	39	05 **104670** 001	461	05 **118003** 001	66	05 **118124** 001	69
05 **100064** 001	39	05 **104671** 001	461	05 **118004** 001	66	05 **118126** 001	69
05 **100070** 001	41	05 **104672** 001	461	05 **118005** 001	66	05 **118128** 001	69
05 **100071** 001	41	05 **104900** 001	100	05 **118006** 001	66	05 **118130** 001	69
05 **100072** 001	41	05 **104901** 001	100	05 **118007** 001	66	05 **118132** 001	69
05 **100075** 001	28	05 **104902** 001	100	05 **118008** 001	66	05 **118134** 001	69
05 **100076** 001	28	05 **104903** 001	100	05 **118010** 001	66	05 **118135** 001	69
05 **100077** 001	28	05 **104904** 001	100	05 **118012** 001	66	05 **118136** 001	69
05 **100080** 001	29	05 **104905** 001	100	05 **118014** 001	66	05 **118137** 001	69
05 **100081** 001	29	05 **104906** 001	100	05 **118017** 001	66	05 **118145** 001	68
05 **100082** 001	29	05 **104907** 001	100	05 **118019** 001	66	05 **118150** 001	71
05 **100085** 001	28	05 **105622** 001	49	05 **118020** 001	66	05 **118152** 001	72
05 **100086** 001	28	05 **105630** 001	45	05 **118022** 001	66	05 **118154** 001	73
05 **100087** 001	28	05 **105631** 001	102	05 **118023** 001	66	05 **118156** 001	72
05 **100100** 001	101	05 **105650** 001	48	05 **118024** 001	66	05 **118158** 001	73
05 **104600** 001	463	05 **105656** 001	48	05 **118026** 001	66	05 **118180** 001	66
05 **104601** 001	463	05 **110000** 001	34	05 **118030** 001	66	05 **118181** 001	66
05 **104602** 001	463	05 **110001** 001	34	05 **118032** 001	66	05 **118182** 001	66
05 **104603** 001	463	05 **110002** 001	34	05 **118035** 001	67	05 **118183** 001	66
05 **104604** 001	463	05 **110003** 001	34	05 **118036** 001	67	05 **118184** 001	66
05 **104605** 001	463	05 **110004** 001	34	05 **118037** 001	67	05 **118185** 001	66
05 **104610** 001	463	05 **110005** 001	34	05 **118039** 001	67	05 **118186** 001	66
05 **104611** 001	463	05 **110006** 001	34	05 **118040** 001	67	05 **133150** 001	248
05 **104612** 001	463	05 **110007** 001	34	05 **118042** 001	67	05 **133151** 001	248
05 **104613** 001	463	05 **110008** 001	34	05 **118044** 001	67	05 **133152** 001	248
05 **104614** 001	463	05 **110010** 001	34	05 **118046** 001	67	05 **133153** 001	248
05 **104615** 001	463	05 **110011** 001	34	05 **118048** 001	67	05 **133154** 001	248
05 **104616** 001	463	05 **110050** 001	35	05 **118050** 001	67	05 **133155** 001	248
05 **104617** 001	463	05 **110051** 001	35	05 **118052** 001	67	05 **133156** 001	248
05 **104618** 001	463	05 **110052** 001	35	05 **118054** 001	67	05 **133157** 001	248
05 **104619** 001	463	05 **110053** 001	35	05 **118060** 001	68	05 **133158** 001	248
05 **104620** 001	463	05 **110054** 001	35	05 **118062** 001	68	05 **133163** 001	242

Code No. Index

Code No.	Page	Code No.	Page	Code No.	Page	Code No.	Page
05 **133180** 001	245	05 **134683** 001	369	05 **135060** 001	381	05 **135235** 001	370
05 **133285** 001	30	05 **134684** 001	369	05 **135068** 001	381	05 **135264** 001	379
05 **133355** 001	104	05 **134685** 001	369	05 **135069** 001	381	05 **135265** 001	379
05 **133356** 001	103	05 **134686** 001	369	05 **135070** 001	381	05 **135266** 001	379
05 **133862** 001	212	05 **134687** 001	369	05 **135071** 001	381	05 **135267** 001	379
05 **134001** 001	63	05 **134688** 001	369	05 **135072** 001	381	05 **135268** 001	386
05 **134002** 001	62	05 **134690** 001	369	05 **135073** 001	381	05 **135269** 001	386
05 **134200** 001	450	05 **134691** 001	369	05 **135074** 001	381	05 **135270** 001	335
05 **134370** 001	328	05 **134695** 001	368	05 **135075** 001	381	05 **135271** 001	335
05 **134371** 001	328	05 **134698** 001	372	05 **135076** 001	381	05 **135272** 001	335
05 **134372** 001	328	05 **134699** 001	372	05 **135077** 001	381	05 **135273** 001	335
05 **134373** 001	328	05 **134700** 001	372	05 **135078** 001	381	05 **135274** 001	335
05 **134374** 001	353	05 **134701** 001	372	05 **135079** 001	381	05 **135275** 001	335
05 **134375** 001	353	05 **134702** 001	372	05 **135080** 001	385	05 **135276** 001	335
05 **134376** 001	353	05 **134703** 001	372	05 **135081** 001	385	05 **135277** 001	335
05 **134377** 001	353	05 **134704** 001	372	05 **135082** 001	385	05 **135278** 001	335
05 **134378** 001	353	05 **134705** 001	372	05 **135083** 001	385	05 **135280** 001	335
05 **134379** 001	353	05 **134706** 001	372	05 **135084** 001	385	05 **135281** 001	335
05 **134380** 001	330	05 **134707** 001	372	05 **135090** 001	383	05 **135284** 001	335
05 **134381** 001	330	05 **134720** 001	373	05 **135091** 001	383	05 **135285** 001	335
05 **134382** 001	330	05 **134722** 001	373	05 **135092** 001	383	05 **135286** 001	335
05 **134384** 001	347	05 **134723** 001	373	05 **135093** 001	383	05 **135287** 001	335
05 **134385** 001	347	05 **134732** 001	373	05 **135094** 001	383	05 **135288** 001	335
05 **134386** 001	347	05 **134740** 001	360	05 **135095** 001	383	05 **135289** 001	335
05 **134397** 001	423	05 **134800** 001	391	05 **135096** 001	383	05 **135290** 001	335
05 **134398** 001	422	05 **134801** 001	391	05 **135097** 001	383	05 **135291** 001	335
05 **134399** 001	426	05 **134802** 001	391	05 **135098** 001	383	05 **135380** 001	336
05 **134480** 001	422	05 **134805** 001	391	05 **135099** 001	383	05 **135381** 001	336
05 **134491** 001	267	05 **134806** 001	391	05 **135120** 001	368	05 **135382** 001	336
05 **134500** 001	370	05 **134807** 001	391	05 **135121** 001	368	05 **135383** 001	336
05 **134600** 001	373	05 **134905** 001	324	05 **135140** 001	356	05 **135384** 001	336
05 **134601** 001	373	05 **134906** 001	328	05 **135141** 001	356	05 **135385** 001	336
05 **134602** 001	373	05 **134907** 001	328	05 **135142** 001	356	05 **135386** 001	336
05 **134603** 001	373	05 **134908** 001	328	05 **135143** 001	356	05 **135387** 001	336
05 **134604** 001	373	05 **134909** 001	328	05 **135170** 001	359	05 **135400** 001	364
05 **134605** 001	335	05 **134910** 001	328	05 **135171** 001	359	05 **135401** 001	364
05 **134606** 001	335	05 **134911** 001	328	05 **135172** 001	359	05 **135402** 001	364
05 **134607** 001	335	05 **134912** 001	328	05 **135174** 001	359	05 **135403** 001	364
05 **134608** 001	335	05 **134913** 001	328	05 **135176** 001	359	05 **135404** 001	364
05 **134654** 001	373	05 **134914** 001	328	05 **135180** 001	359	05 **135405** 001	364
05 **134655** 001	373	05 **134915** 001	328	05 **135182** 001	359	05 **135406** 001	364
05 **134656** 001	373	05 **134919** 001	318	05 **135184** 001	359	05 **135407** 001	364
05 **134657** 001	373	05 **134920** 001	318	05 **135185** 001	359	05 **135408** 001	364
05 **134658** 001	373	05 **134921** 001	318	05 **135186** 001	359	05 **135409** 001	364
05 **134664** 001	369	05 **134929** 001	328	05 **135200** 001	360	05 **135420** 001	365
05 **134665** 001	369	05 **134930** 001	328	05 **135201** 001	360	05 **135421** 001	365
05 **134667** 001	369	05 **134931** 001	328	05 **135202** 001	360	05 **135422** 001	365
05 **134668** 001	369	05 **134932** 001	328	05 **135204** 001	360	05 **135423** 001	365
05 **134669** 001	369	05 **134940** 001	318	05 **135205** 001	360	05 **135424** 001	365
05 **134670** 001	369	05 **134941** 001	318	05 **135220** 001	364	05 **135425** 001	365
05 **134671** 001	369	05 **134942** 001	318	05 **135221** 001	364	05 **135430** 001	370
05 **134672** 001	369	05 **134950** 001	328	05 **135222** 001	364	05 **135431** 001	370
05 **134673** 001	369	05 **134951** 001	328	05 **135224** 001	402	05 **135432** 001	370
05 **134674** 001	369	05 **134952** 001	328	05 **135225** 001	402	05 **135433** 001	370
05 **134675** 001	369	05 **135003** 001	340	05 **135226** 001	373	05 **135434** 001	370
05 **134676** 001	369	05 **135005** 001	321	05 **135228** 001	373	05 **135435** 001	370
05 **134677** 001	369	05 **135008** 001	319	05 **135229** 001	373	05 **135436** 001	370
05 **134678** 001	369	05 **135009** 001	321	05 **135230** 001	370	05 **135440** 001	370
05 **134679** 001	369	05 **135017** 001	340	05 **135231** 001	370	05 **135441** 001	370
05 **134680** 001	369	05 **135040** 001	325	05 **135232** 001	370	05 **135442** 001	370
05 **134681** 001	369	05 **135041** 001	325	05 **135233** 001	370	05 **135443** 001	370
05 **134682** 001	369	05 **135042** 001	325	05 **135234** 001	370	05 **135530** 001	330

Code No.	Page
05 **135531** 001	330
05 **135532** 001	330
05 **135705** 001	332
05 **135706** 001	332
05 **135810** 001	453
05 **135902** 001	403
05 **135903** 001	403
05 **135904** 001	403
05 **135906** 001	108
05 **135918** 001	217
05 **135926** 001	280
05 **135927** 001	282
05 **135928** 001	281
05 **135938** 001	71
05 **135939** 001	280
05 **135942** 001	262
05 **135949** 001	146
05 **135961** 001	104
05 **135973** 001	84
05 **136000** 001	426
05 **136001** 001	426
05 **136002** 001	426
05 **136011** 001	465
05 **136220** 001	361
05 **136400** 001	196, 213
05 **137810** 001	60
05 **138070** 001	38
05 **138250** 001	51
05 **138257** 001	40
05 **138258** 001	40
05 **138259** 001	40
05 **138260** 001	40
05 **138261** 001	40
05 **138262** 001	40
05 **138263** 001	40
05 **138264** 001	40
05 **138265** 001	40
05 **138266** 001	40
05 **138268** 001	40
05 **138269** 001	40
05 **138270** 001	40
05 **140310** 001	294
05 **160785** 001	149
05 **160821** 001	373
05 **160830** 001	360
05 **160885** 001	383
05 **160895** 001	331
05 **160896** 001	329
05 **160899** 001	329

Code No.	Page
05 **160901** 001	331
05 **160908** 001	331
05 **160917** 001	369
05 **160924** 001	423
05 **160956** 001	368
05 **160976** 001	423
05 **160977** 001	423
05 **160979** 001	423
05 **160981** 001	423
05 **160983** 001	328
05 **160987** 001	417
05 **160988** 001	417
05 **200495** 001	373
05 **200995** 001	220
05 **204126** 001	373
05 **221102** 001	385
05 **221110** 001	393
05 **223161** 001	50
05 **259135** 001	373
05 **300004** 001	83
05 **300025** 001	374
05 **300037** 001	374
05 **302400** 001	370
05 **302402** 001	370
05 **302403** 001	370
05 **308428** 001	360
05 **311517** 001	426
05 **314753** 001	364
05 **319835** 001	360
05 **320430** 001	369
05 **320540** 001	50
05 **324901** 001	393
05 **326310** 001	370
05 **328448** 001	360
05 **328463** 001	85
05 **332600** 001	360
05 **332606** 001	370
05 **332607** 001	364
05 **332609** 001	364
05 **332610** 001	364
05 **332612** 001	370
05 **340245** 001	389
05 **340260** 001	442
05 **340322** 001	453
05 **340330** 001	34
05 **342920** 001	353
05 **344280** 001	370
05 **344281** 001	370
05 **344282** 001	370

Code No.	Page
05 **344511** 001	428
05 **344512** 001	428
05 **344513** 001	428
05 **344514** 001	428
05 **344515** 001	393
05 **344536** 001	76
05 **344537** 001	76
05 **344538** 001	76
05 **344540** 001	76
05 **344541** 001	76
05 **344542** 001	76
05 **344543** 001	76
05 **344544** 001	76
05 **344545** 001	76
05 **344546** 001	76
05 **344900** 001	370
05 **345018** 001	364
05 **345019** 001	370
05 **345026** 001	364
05 **345028** 001	364
05 **345032** 001	364
05 **345035** 001	364
05 **345047** 001	360
05 **345056** 001	364
05 **345280** 001	100
05 **345281** 001	69
05 **345282** 001	69
05 **345284** 001	68
05 **345285** 001	68
05 **345290** 001	66
05 **345350** 001	364
05 **345351** 001	364
05 **345352** 001	364
05 **346280** 001	286
05 **346281** 001	319
05 **346285** 001	331
05 **346286** 001	331
05 **346287** 001	331
05 **346288** 001	383
05 **346293** 001	216
05 **347100** 001	422
05 **347106** 001	46
05 **347107** 001	110
05 **347108** 001	110
05 **347153** 001	442
05 **347735** 002	49
05 **347736** 002	50
05 **347743** 001	37
05 **347777** 001	104

Code No.	Page
05 **347778** 001	51
05 **350430** 001	383
05 **350451** 001	476
05 **380033** 001	383
05 **380045** 001	383
05 **380046** 001	383
05 **380047** 001	383
05 **380048** 001	383
05 **380049** 001	383
05 **380050** 001	383
05 **380103** 001	381
05 **380104** 001	381
05 **380105** 001	381
05 **380106** 001	381
05 **380107** 001	381
05 **380108** 001	381
05 **380109** 001	381
05 **380110** 001	381
05 **380124** 001	384
05 **380125** 001	384
05 **380126** 001	384
05 **380127** 001	384
05 **380128** 001	384
05 **380129** 001	384
05 **380130** 001	384
05 **380131** 001	384
05 **380155** 001	319
05 **380156** 001	319
05 **380157** 001	319
05 **380158** 001	319
05 **380160** 001	328
05 **380161** 001	328
05 **380200** 001	330
05 **380201** 001	330
05 **380202** 001	330
05 **380380** 001	336
05 **380381** 001	336
05 **380382** 001	336
05 **380383** 001	336
05 **480171** 001	322
05 **480172** 001	322
05 **480173** 001	322
05 **480221** 001	341
05 **480222** 001	341
05 **480223** 001	341
05 **670446** 001	303
05 **670447** 001	303
05 **670448** 001	303

Article No. Index

1

100 514
100 L 515
100 S 514
101 514
101 L 515
102 514
102 L 515
160 i SB 94
160 i VDE 94
160 i/162 i/167 i/9 104
160 i/165 i/7 Rack 103
160 i/168 i/6 Rack 104
160 i/6 Rack 102
160 i/7 Rack 102
160 iS 94
160 iS/7 104
160 iSS 94
160 iSS/7 104
162 i PH SB 95
162 i PH VDE 95
162 i PH/S SB 97
162 i PH/S VDE 97
162 iS 96
162 iS PH/S 98
162 iSS 96
164 i VDE 99
165 i PZ SB 96
165 i PZ VDE 96
165 i PZ/S SB 98
165 i PZ/S VDE 98
165 iS 97
165 iS PZ/S 98
165 iSS PZ/S 98
167 i TORX® VDE 99
167 i/6 103
168 i SB 100
168 i VDE 100
190 i VDE 100
1013 Kraftform Micro 70
1013 Kraftform Micro ESD 83
1160 i VDE 122
1160 i/1165 i/7 VDE 123
1160 i/7 VDE 122
1162 i PH VDE 122
1165 i PZ VDE 122
1267 A TORX PLUS® 61
1267 A TORX® 61
1267 B TORX PLUS® 61
1267 B TORX® 61
1334 54
1334/1355/6 56
1334/6 56
1335 54
1335/1350/1355/6 56
1350 PH 54
1355 PZ 54
1367 TORX® 55
1367/6 TORX® 56
1427 62
1428 62
1429 69
1430 ESD 475
1440/1442 63
1441 63
1460 Micro ESD 483
1550 PH Micro 80
1550/6 ESD 82
1555 PZ Micro 80
1567 TORX PLUS® IPR 81
1567 TORX® BO 81
1567 TORX® HF Micro 80
1567 TORX® Micro 81
1569 ESD 82
1572 ESD 82
1578 A Micro 80
1578 A/6 82

2

247 101
247 SB 101
2035 Micro 66
2035/6 A 71
2035/6 B 72
2050 PH Micro 66
2050/6 72
2052 Micro 68
2052/6 72
2054 Micro 68
2055 PZ 66
2067 IPR Micro 68
2067 TORX® 67
2067 TORX® BO Micro 67

2067 TORX® HF 66
2067/6 TORX® BO 73
2069 Micro 69
2069/6 73
2072 68
2090 90 Nm 511
2090/17 511

3

300 Hex 486
300 Hex Pistole / Pistol 486
300 IP 486
300 IP Pistole / Pistol 487
300 TX 486
300 TX Pistole / Pistol 487
334 34
334 SB 35
334 SK 34
334 SK/6 48
334/355 SK/6 48
334/355/6 Rack 48
334/368/6 51
334/6 48
335 34
335/350/355/3 49
335/350/355/4 50
335/350/355/6 49
335/350/367/7 Lasertip 50
336 Stubby 44
350 PH 36
350 PH SB 36
350 SK PH 36
352 38
354 Hex-Plus 38
355 PZ 37
355 SB 37
355 SK PZ 37
367 K TORX® 40
367 SB 39
367 TORX PLUS® 40
367 TORX® 39
367 TORX® BO 40
367 TORX® HF 38
367/4 TORX HF extra lang / long 50
367/6 TORX® 51
367/6 TORX® BO 51
367/6 TORX® HF 50
367/7 TORX® HF 50
368 41
368 SB 41
371 TORQ-SET® Mplus 40
375 TRI-WING® 42
378 B 35
391 42
392 287
395 42
395 HO 43
395 HO/7 SM 51
3160 i VDE 90
3160 i/7 Rack 91
3162 i VDE 90
3165 i PZ VDE 90
3165 i/6 Rack 91
3334 22
3334/3350/3355/6 25
3334/3355/6 24
3334/6 24
3335 22
3350 PH 22
3355 PZ 22
3367 TX 23
3368 23
3800/1 TS 376
3800/4 378
3816 R 284
3840/1 TS 380
3840/4 Hex-Plus 382
3851/1 TS PH 316
3851/4 326
3855/1 TS PZ 338
3855/4 344
3867/1 TS SB SiS 352
3867/1 TS TORX® 352
3867/4 TORX® 358
3867/4 TORX® BO 367
3868/1 TS 388
3868/4 Square-Plus 390
3869/4 401
3888/4/1 K 414
3888/4/1 K SB SiS 414
3950 PKL 246
3950 PKL inch 246
3950 SPKL Multicolour 246
3950/9 Hex-Plus Imperial Stainless 1 239
3950/9 Hex-Plus Multicolour Stainless 1 238
3950/9 Hex-Plus Stainless 1 238
3950/9 Hex-Plus Stainless 1 SB 238
3950/9 Hex-Plus Stainless 1 SB 238

Article No. Index

4

454 76
454 inch 76
467 TORX® 76
489 R 77
495 77

6

68 294

7

700 A HTS 397
700 B HTS 397
700 C HTS 397
712 293
780 A 428
780 B 428
780 C 428
784 A/1 428
784 B 428
784 C 428
797 A/4/1 B 418
797 B/4/1 B 418
7400 472
7400 ESD 473
7400 ESD Halfmoon 475
7400 ESD inch 474
7400 ESD vor Halfmoon 483
7400 inch 474
7400 Pistole / Pistol 472
7400 Pistole / Pistol inch 474
7400 Pistole / Pistol pre-set 480
7400 Pistole pre-set inch 482
7400 VDE 114
7400 pre-set 480
7400 pre-set ESD 481
7400 pre-set inch 482
7440/41 476
7440/41/42 476
7443/12 477
7443/61/9 476
7445/46/47 476
7770 502
7771 503
7772 A 504
7772 B 504
7772 C 504
7773 A 504
7773 B 505
7773 C 505
7774/1 505
7774/2 505
7774/3 506
7775 506
7776 506
7779/1 507
7779/2 507
7780 502
7781 503
7782 C 504
7782 E 504
7783 C 505
7783 E 505
7786 506
7790/1 507
7790/2 507

8

80 292
80 RA 289
81 293
82 293
83 294
84 294
85 294
86 294
87 294
88/1 292
800/1 BDC 376
800/1 BTZ 376
800/1 HTN 397
800/1 TZ 376
800/1 Z 377
800/1 Z Set D 377
800/1 Z Set SB 377

800/2 Z 379
800/4 Z 378
800/9 C 379
807/4 Z 379
810/1 ESD 85
810/1 Vario 287
811/1 ESD 85
811/1 Vario 287
812/1 Vario 287
813 287
813 R 284
813 R ESD 84
816 R 284
816 R ESD 83
816 RA 288
817 R 285
817 R SB SiS 285
817 VDE 114
819/1 Vario 286
819/1/6 286
819/1/6 PH 286
820/1/6 286
830 292
840/1 BTZ Hex-Plus 380
840/1 IMP DC 380
840/1 IMP DC Impaktor Bits SB 380
840/1 Z Hex-Plus 381
840/1 Z Hex-Plus BO 387
840/1 Z Set SB SiS 381
840/2 Z 385
840/4 IMP DC 382
840/4 IMP DC SB 382
840/4 Z Hex-Plus 383
840/4 Z Hex-Plus BO 387
840/9 C 386
842/1 Z 381
842/4 384
843 461
844 461
844/7 461
845 461
845/8 462
846 HSS 462
846/8 462
847 HSS 462
847/7 HSS 463
848 HSS 463
848/851/867/19 463
849 HSS 463
849/855/867/18 465
851/1 A PH 318
851/1 ADC PH 318
851/1 AH 319
851/1 BDC PH 317
851/1 BDC SB 317
851/1 BTH PH 318
851/1 BTZ PH 318
851/1 IMP DC 316
851/1 IMP DC SB 316
851/1 J 325
851/1 RDC PH 319
851/1 RH 319
851/1 RZ PH 321
851/1 RZ SB 321
851/1 TH PH 322
851/1 TiN PH 322
851/1 TiN SB 322
851/1 TZ PH 323
851/1 TZ SB 323
851/1 Z DIY 100 324
851/1 Z DIY 324
851/1 Z PH 324
851/1 Z SB 324
851/11 PH 333
851/12 PH 333
851/15 PH 334
851/16 PH 334
851/2 Z PH 332
851/21 J 335
851/22 336
851/23 PH 332
851/25 H 336
851/4 A PH 328
851/4 ADC PH 328
851/4 BDC PH 326
851/4 BTH PH 327
851/4 BTZ PH 327
851/4 IMP DC 326
851/4 IMP DC SB 326
851/4 J 330
851/4 PH/S 350
851/4 R PH 329
851/4 RH 328
851/4 TH PH 329
851/4 TZ PH 330
851/4 TZ SB 330
851/4 Z PH 330
851/4 Z SB 330

Article No. Index

8

851/9 C 335
853/1 TZ ACR PH 323
853/4 ACR 331
853/4 Harpoon ACR 331
855/1 BDC PZ 339
855/1 BDC SB 339
855/1 BTH PZ 340
855/1 BTZ PZ 340
855/1 IMP DC 338
855/1 IMP DC SB 338
855/1 RZ PZ 340
855/1 TH PZ 341
855/1 TiN PZ 341
855/1 TiN SB 341
855/1 TZ PZ 342
855/1 Z DIY 100 343
855/1 Z DIY 343
855/1 Z PZ 342
855/1 Z SB 342
855/11 PZ 348
855/12 PZ 349
855/15 PZ 349
855/2 Z PZ 348
855/4 BDC PZ 346
855/4 BTH PZ 346
855/4 BTZ PZ 346
855/4 IMP DC 344
855/4 IMP DC SB 344
855/4 PZ/S 351
855/4 TH PZ 347
855/4 TZ PZ 347
855/4 TZ SB 347
855/4 Z PZ 347
855/4 Z SB 347
856/1 TZ ACR PZ 342
857/1 Z 400
857/4 Z 400
860/1 XZN 396
860/4 XZN 396
864/1 BTZ 375
864/1 Z 375
867/1 BDC SB 353
867/1 IMP DC 352
867/1 IMP DC SB 352
867/1 IP TORX PLUS® 368
867/1 IPR 372
867/1 TORX® 356
867/1 TORX® BDC 353
867/1 TORX® BTZ 354
867/1 TZ TORX® 355
867/1 Z TORX® BO 366
867/1 Z TORX® HF 354
867/1 Z TORX® W 357
867/1 ZA TORX® 357
867/11 TORX® 362
867/12 TORX® 362
867/15 TORX® 363
867/16 TORX® 363
867/2 Z TORX® 361
867/21 IPR TORX® PLUS 374
867/21 TORX PLUS® 370
867/21 TORX® 364
867/22 TORX PLUS® 370
867/22 TORX® 365
867/4 H TORX® 359
867/4 IMP DC 358
867/4 IMP DC SB 358
867/4 IP TORX PLUS® 369
867/4 IPR 373
867/4 KK 358
867/4 TORX® HF 359
867/4 Z TORX® 360
867/4 Z TORX® BO 367
867/9 C TORX PLUS® 370
867/9 C TORX® 364
867/9 IPR TORX® PLUS 373
868/1 BTZ Square-Plus 388
868/1 IMP DC 388
868/1 IMP DC SB 388
868/1 V 389
868/1 Z 389
868/4 BTZ Square-Plus 390
868/4 IMP DC 390
868/4 IMP DC SB 390
868/4 Square-Plus 391
868/4 V 391
869/4 401
869/4 M 402
869/4 M SB 402
869/4 M Set A SB 402
869/9 402
870/1 426
870/14 427

870/2 426
870/4 427
870/4 A 426
870/4/7 Set A SB 427
870/7 427
8700 A FL 165
871/1 DC TORQ-SET® Mplus 392
871/1 TORQ-SET® Mplus 25 mm 392
871/1 TORQ-SET® Mplus 32 mm 392
871/19 TORQ-SET® Mplus 394
871/2 TORQ-SET® Mplus 394
871/4 DC TORQ-SET® Mplus 393
871/4 TORQ-SET® Mplus 393
871/6 TORQ-SET® Mplus 394
871/7 TORQ-SET® Mplus 394
872/21 398
872/9 398
875/1 TRI-WING® 25 mm 395
875/1 TRI-WING® 32 mm 395
875/4 TRI-WING® 395
875/6 TRI-WING® 395
879/4 403
887/4 RR 417
887/4 RR SB 417
888/4/1 K 416
889/4 R 416
889/4/1 416
889/4/1 K 415
890/00/0 421
890/4/1 421
890/6/1 421
890/7/1 421
890/7/2 421
891/4/1 424
891/8/1 424
893/4/1 K 422
893/4/1 K SB 422
894/14/1 419
894/4/1 419
894/4/1 K 419
895/14/1 420
895/4/1 420
895/4/1 K 419
895/4/1 K SB 419
896/4/1 SB 425
897/4 Impaktor Impaktor 410
897/4 Impaktor Impaktor R 410
897/4 Impaktor R SB 410
897/4 R 414
897/4 R SB 414
898/21 420
898/4 420
898/9 420
899/14/1 423
899/14/1 SB 423
899/3/1 422
899/4/1 422
899/4/1 S 423
899/4/1 SB 422
899/5/1 423
899/8/1 423
899/8/1 K 423
8000 A 150
8000 A SB 150
8000 B 174
8000 B SB 174
8000 C 192
8000 C SB 192
8000 E 196
8001 A SB 222
8002 C Koloss All Inclusive Set 212
8002 C Koloss 212
8003 A 153
8003 B 177
8003 C 199
8004 A 155
8004 B 179
8004 C 201
8005 222
8006 C 196
8006 SC 1 194
8007 B VDE 126
8100 SA 10 152
8100 SA 11 154
8100 SA 12 HF 155
8100 SA 2 148
8100 SA 4 148
8100 SA 6 144
8100 SA 7 152
8100 SA 8 154
8100 SA 9 145
8100 SA All-In 144
8100 SA/SC 2 149
8100 SB 10 176
8100 SB 11 178
8100 SB 2 173
8100 SB 4 174
8100 SB 6 172

Article No. Index

8

8100 SB 7 176
8100 SB 8 178
8100 SB 9 172
8100 SB HF 1 179
8100 SB VDE 1 129
8100 SC 10 198
8100 SC 11 200
8100 SC 2 191
8100 SC 4 192
8100 SC 6 190
8100 SC 7 198
8100 SC 8 200
8100 SC 9 190
8740 A 162
8740 A HF 162
8740 A HF 1 163
8740 B HF 183
8740 B HF 1 184
8740 B HF Imperial 1 184
8740 C HF 206
8740 C HF 1 205
8740 C HF 2 206
8751 A 164
8755 A 164
8767 A HF 160
8767 A HF 1 161
8767 B HF 182
8767 B HF 1 182
8767 C HF 204
8767 C HF 1 204
8767 C HF 2 204
8767 C HF 3 205
8780 C 212
8781 C 213
8782 C 213
8784 A1 169
8784 B1 186
8784 C2 209
8789 A 166
8789 B 187
8789 C 209
8790 B VDE 126
8790 C HF 1 203
8790 FA 223
8790 HMA 156
8790 HMA HF 156
8790 HMB 180
8790 HMB HF 180
8790 HMC 202
8790 HMC HF 202
8794 A 169
8794 B 187
8794 C 209
8794 LA 166
8794 LB 186
8794 LB VDE 128
8794 LC 208
8794 SA 167
8794 SB 186
8794 SB VDE 128
8794 SC 208
8795 A 169
8795 B 187
8795 C 209
8796 LA 166
8796 LB 186
8796 LC 208
8796 SA 166
8796 SB 186
8796 SC 208
8797 C 196

9

91 292
95 292
917 SPH 28
917 SPH SB 28
917 SPHS 28
918 SPZ 29
918 SPZ SB 29
919 PH 257
919 PZ 257
920 A 257
930 A 60
930/935/6 60
930/955/6 60
932 A 28
932 A SB 28
932 AS 28
932 S/6 30

932/6 30
932/918/6 31
935 SPH 60
950 249
950 BM 249
950 L 248
950 PKL 247
950 PKL BM 247
950 PKL inch 248
950 PKLS 248
950 PKS 248
950 SPKL HF Multicolour 246
950 SPKL inch 247
950 SPKL Multicolour 247
950/13 Hex-Plus Imperial 1 245
950/7 Hex-Plus 1 244
950/7 Hex-Plus Magnet 1 244
950/7 Hex-Plus Multicolour Magnet 1 241
950/9 Hex-Plus 3 242
950/9 Hex-Plus 1 242
950/9 Hex-Plus 1 SB 242
950/9 Hex-Plus 2 242
950/9 Hex-Plus 4 243
950/9 Hex-Plus 5 243
950/9 Hex-Plus 6 244
950/9 Hex-Plus 6 SB 244
950/9 Hex-Plus 7 244
950/9 Hex-Plus Imperial 1 245
950/9 Hex-Plus Imperial 1 SB 245
950/9 Hex-Plus Multicolour 1 240
950/9 Hex-Plus Multicolour 1 SB 240
950/9 Hex-Plus Multicolour HF 1 240
950/9 Hex-Plus Multicolour Imperial 1 241
955 SPZ 60
967 L TORX® HF 256
967 PKL TORX® 256
967 PKXL TORX® 256
967 SL TORX® HF 254
967 SPKL TORX® BO Multicolour 254
967 SPKXL TORX® Multicolour 253
967 SXL HF TORX® Multicolour 253
967 SXL TORX® Multicolour 254
967 TORX® 256
967 XL HF TORX® 254
967 XL TORX® 256
967/9 TX 1 252
967/9 TX BO Multicolour 1 212
967/9 TX HF 1 250
967/9 TX Multicolour HF 1 250
967/9 TX XL Multicolour HF 1 250
967/9 TX XL 1 252
967/9 TX XL HF 1 250
967/9 TX XL Multicolour 1 251
977 TORX® 29
977/6 TORX® 31

ABC

BC 10 Drywall 1 465
Belt A 1 157
Belt A 2 162
Belt A 3 161
Belt A 4 159
Belt A Imperial 1 160
Belt A, 8-teilig / 8 location, unbestückt / unloaded 163
Belt A, 9-teilig / 9 location, unbestückt / unloaded 164
Belt B 1 181
Belt B 2 184
Belt B 3 182
Belt B 4 181
Belt B Imperial 1 184
Belt B, 8-teilig / 8 location, unbestückt / unloaded 185
Belt B, 9-teilig / 9 location, unbestückt / unloaded 185
Big Pack 900 30
Bit-Box 15 Impaktor PH 316
Bit-Box 15 Impaktor PZ 338
Bit-Box 15 Impaktor TX 352
Bit-Box 20 BTH PZ 340
Bit-Box 20 BTZ PH 318
Bit-Box 20 BTZ PZ 340
Bit-Box 20 BTZ TX 354
Bit-Box 20 PH 324
Bit-Box 20 PZ 342
Bit-Box 20 RZ PH 321
Bit-Box 20 TX 356
Bit-Box 20 V Robertson 389
Bit-Check 10 BiTorsion 1 441
Bit-Check 10 BiTorsion 2 441
Bit-Check 10 BiTorsion 3 SB 442
Bit-Check 10 Diamond 1 444
Bit-Check 10 Impaktor 1 434
Bit-Check 10 Impaktor 1 SB 434
Bit-Check 10 Impaktor 2 434
Bit-Check 10 Impaktor 3 434

Article No. Index

ABC

Bit-Check 10 Impaktor 4 435
Bit-Check 10 PZ BiTorsion 1 442
Bit-Check 10 PZ BiTorsion 2 442
Bit-Check 10 PZ Impaktor 1 435
Bit-Check 10 PZ Universal 1 451
Bit-Check 10 PZ Universal 2 451
Bit-Check 10 Stainless 1 438
Bit-Check 10 Stainless 1 SB 438
Bit-Check 10 TX Impaktor 1 435
Bit-Check 10 TX Universal 1 452
Bit-Check 10 TX Universal 2 452
Bit-Check 10 Universal 1 450
Bit-Check 10 Universal 2 450
Bit-Check 10 Universal 3 450
Bit-Check 10 Universal 3 SB 450
Bit-Check 10 Universal 4 450
Bit-Check 10 Universal 5 SB 451
Bit-Check 10 Zyklop Mini 1 220
Bit-Check 10 Zyklop Mini BiTorsion 1 220
Bit-Check 12 BiTorsion 1 440
Bit-Check 12 Diamond 1 444
Bit-Check 12 Metal 1 460
Bit-Check 12 Stainless 1 438
Bit-Check 12 Universal 1 449
Bit-Check 12 Universal 2 449
Bit-Check 12 Wood 1 458
Bit-Check 12 Wood 2 459
Bit-Check 12 Wood 3 459
Bit-Check 12 Wood 4 459
Bit-Check 30 BiTorsion 1 440
Bit-Check 30 Diamond 1 444
Bit-Check 30 Impaktor 1 434
Bit-Check 30 Metal 1 460
Bit-Check 30 Stainless 1 438
Bit-Check 30 TX Universal 1 449
Bit-Check 30 Universal 1 448
Bit-Check 30 Wood 1 458
Bit-Check 30 Wood 2 458
Bit-Check 30 Zyklop Mini 1 216
Bit-Check 30 Zyklop Mini 2 216
Bit-Check 6 Impaktor 1 436
Bit-Check 6 Impaktor 2 436
Bit-Check 6 PH BiTorsion 1 443
Bit-Check 6 PH Diamond 1 447
Bit-Check 6 PH Impaktor 1 436
Bit-Check 6 PZ Diamond 1 447
Bit-Check 6 PZ Impaktor 1 436
Bit-Check 6 PZ Universal 1 456
Bit-Check 6 Stainless 1 SB 439
Bit-Check 6 TX HF 1 457
Bit-Check 6 TX Impaktor 1 436
Bit-Check 6 TX Universal 1 456
Bit-Check 6 TX Universal 1 SB 456
Bit-Check 6 Universal 1 455
Bit-Check 6 Universal 1 SB 455
Bit-Check 6 Universal 2 456
Bit-Check 6 Universal 3 456
Bit-Check 6 V Universal 1 457
Bit-Check 7 Diamond 1 445
Bit-Check 7 Diamond 1 SB 445
Bit-Check 7 Hex-Plus 1 454
Bit-Check 7 PH BiTorsion 1 443
Bit-Check 7 PH Diamond 1 446
Bit-Check 7 PZ BiTorsion 1 442
Bit-Check 7 PZ Diamond 1 446
Bit-Check 7 PZ Diamond 1 SB 446
Bit-Check 7 PZ Universal 1 453
Bit-Check 7 PZ Universal 1 SB 453
Bit-Check 7 PZ Universal 2 453
Bit-Check 7 TiN Universal 1 454
Bit-Check 7 TiN Universal 1 SB 454
Bit-Check 7 TX BO Universal 1 454
Bit-Check 7 TX Diamond 1 446
Bit-Check 7 TX Universal 1 454
Bit-Check 7 TX Universal 1 SB 454
Bit-Check 7 Universal 1 452
Bit-Check 7 Universal 2 453
Bit-Check 7 Universal 3 453
Bit-Check 7 Universal 4 453
Bit-Safe 43 Universal 1 448
Bit-Safe 61 BiTorsion 1 440
Bit-Safe 61 Universal 1 448
Bit-Safe 61 Universal 2 448
Bit-Safe 61 Wood 1 458
Click-Torque A 5 492
Click-Torque A 6 492
Click-Torque B 1 494
Click-Torque B 2 494
Click-Torque C 1 495
Click-Torque C 2 495
Click-Torque C 3 496
Click-Torque C 4 496
Click-Torque C 5 497

Click-Torque E 1 497
Click-Torque X 1 498
Click-Torque X 2 498
Click-Torque X 3 499
Click-Torque X 4 499
Click-Torque X 5 500
Click-Torque X 6 500
Joker 228
Joker Double 228
Joker inch 228
Joker Set 4 230
Joker Set 6 229
Joker Set Switch 231
Joker Switch 230
Joker Switch inch 230
Joker Set 4 inch SB 230
Joker Set switch 4 inch 231
Joker Set 11 228
Joker Set 8 inch 229
Joker Set Switch 11 232
Joker Set Switch 8 232
Kraftform Kompakt 10 262
Kraftform Kompakt 12 262
Kraftform Kompakt 20 264
Kraftform Kompakt 20 A 264
Kraftform Kompakt 22 264
Kraftform Kompakt 25 266
Kraftform Kompakt 26 266
Kraftform Kompakt 27 RA 1 SB 290
Kraftform Kompakt 27 RA 2 SB 290
Kraftform Kompakt 40 268
Kraftform Kompakt 41 268
Kraftform Kompakt 50 269
Kraftform Kompakt 60 272
Kraftform Kompakt 60 ESD 84
Kraftform Kompakt 60 i 114
Kraftform Kompakt 60 Imperial 272
Kraftform Kompakt 60 iS 114
Kraftform Kompakt 60 KK 272
Kraftform Kompakt 60 RA 288
Kraftform Kompakt 60 RA Imperial 288
Kraftform Kompakt 60 Stainless 270
Kraftform Kompakt 60 Stainless Imperial 271
Kraftform Kompakt 60 Torque 270
Kraftform Kompakt 62 273
Kraftform Kompakt 62 i 114
Kraftform Kompakt 62 i PH/S 116
Kraftform Kompakt 62 iS 115
Kraftform Kompakt 62 iS PH/S 116
Kraftform Kompakt 64 i 117
Kraftform Kompakt 65 i PZ 115
Kraftform Kompakt 65 i PZ/S 116
Kraftform Kompakt 65 iS PZ 115
Kraftform Kompakt 65 iS PZ/S 116
Kraftform Kompakt 67 i TORX® 116
Kraftform Kompakt 67 iS TORX® 117
Kraftform Kompakt 68 i 117
Kraftform Kompakt 68 iS 117
Kraftform Kompakt 70 Allround 276
Kraftform Kompakt 71 Security 276
Kraftform Kompakt 96 VK 6,3 118
Kraftform Kompakt 97 VK 8,1 118
Kraftform Kompakt 98 DK 118
Kraftform Kompakt 99 FL 118
Kraftform Kompakt Pistol RA 290
Kraftform Kompakt Pistol RA 4 290
Kraftform Kompakt VDE 15 Torque 1,2-3,0 Nm extra slim 1 108
Kraftform Kompakt VDE 16 extra slim 1 112
Kraftform Kompakt VDE 16 Torque 1,2-3,0 Nm 108
Kraftform Kompakt VDE 16 Universal 1 112
Kraftform Kompakt VDE 17 Universal 1 111
Kraftform Kompakt VDE 18 Imperial 1 110
Kraftform Kompakt VDE 18 Universal 1 109
Kraftform Kompakt VDE 18 Universal 2 110
Kraftform Kompakt VDE 7 Imperial 1 113
Kraftform Kompakt VDE 7 Universal 1 113
Kraftform Kompakt VDE 7 Universal 2 113
Kraftform Kompakt Zyklop Mini 2 217
Klettstreifen / Hook and Loop Fastener Strips 1 303
Klettstreifen Hook and Loop Fastener Strips 2 303
Klettstreifen Hook and Loop Fastener Strips 3 303
Kraftform 2go 100 105
Kraftform 2go 300 46
Kraftform Big Pack 100 VDE 102
Kraftform Big Pack 300 45
Kraftform Kompakt 100 278
Kraftform Kompakt 20 Tool Finder 1 264
Kraftform Kompakt 28 mit Tasche / with pouch 267
Kraftform Kompakt 28 SB 267
Kraftform Kompakt H1 Holz 280
Kraftform Kompakt M1 Metall 281
Kraftform Kompakt Micro 11 Electronics 1 71

Article No. Index

ABC

Kraftform Kompakt Micro 11 ESD 1 85
Kraftform Kompakt Micro 11 Universal 1 71
Kraftform Kompakt Micro 20 ESD 1 85
Kraftform Kompakt Micro 21 ESD 1 84
Kraftform Kompakt SH 1 282
Kraftform Kompakt Vario RA 289
Kraftform Kompakt W1 Wartung 280
Kraftform Kompakt Zyklop 150
Kraftform Kompakt Zyklop MS1 Metal/Speed 1/4 146
Kraftform Micro 12 Electronics 1 70
Kraftform Micro 12 Universal 1 70
Kraftform XXL 45
Kraftform XXL 2 46
Kraftform XXL 3 46
Mutterentnahme-Werkzeug / Nut Extructor 159
Rack 63
Rack Micro 62
Stubby PH 44
Stubby PZ 44
Tool-Check 1 SB 219
Tool-Check Automotive 1 220
Tool-Check PLUS 218
Tool-Check PLUS Imperial 218
Wera 2go 1 300
Wera 2go 2 300
Wera 2go 3 300
Wera 2go 4 300
Wera 2go 5 301
Wera 2go 6 301
Wera Star 62
Zyklop Hybrid Set 194

Alphabetical Index
All products from A to Z

A

Adaptors 292, 426, 427, 428
Assembly set for tyre pressure control systems 476, 477
ASSY®
- Bits 375

Awl 62

B

Ballhead
- Bits 272, 358, 381, 384
- Screwdrivers 38, 40

Belts 157, 159, 160, 161, 162, 163, 164, 181, 182, 184, 185
Bit-Box 316, 318, 321, 324, 338, 340, 342, 352, 354, 356, 389
Bit-Checks 216, 220, 434, 435, 436, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 465
Bit-Safes 440, 448, 458
Bitholding Kraftform Micro Screwdrivers 70
Bitholding Screwdrivers 77, 83, 84, 85, 284, 285, 286, 287
BiTorsion
- Bits 317, 318, 326, 327, 339, 340, 346, 353, 354, 375, 376 380, 388, 390, 440, 441, 442, 443
- Bit Holder 418
- Bit Sets 440, 441, 442, 443

Bits
- ACR (Anti Cam-Out Ribs) 323, 331, 342
- ASSY® 375
- BiTorsion 317, 318, 326, 327, 339, 340, 346, 353, 354, 375, 376, 380, 388, 390, 440, 441, 442, 443
- Countersink Bits 461, 462
- Diamond-coated 317, 318, 319, 326, 328, 339, 346, 353, 376, 392, 393, 444, 445, 446, 447
- Double-ended Bits 332
- Drill bits 462, 463, 465
- Halfmoon 335, 364, 370, 373, 379, 386
- Hex-Plus 380, 381, 382, 383, 384, 385, 386, 387
- Hexagon socket screws 380, 381, 382, 383, 384, 385, 386
- Hexagon socket screws BO 387

Alphabetical Index
All products from A to Z

B

Bits

Hi-TORQUE	397
HIOS	335, 336, 364, 365, 370, 398
Impaktor	316, 326, 338, 344, 352, 358, 380, 382, 387, 388, 390, 434, 435, 436
Microstix®	398
Multipoint	396
Phillips PH	316, 317, 318, 319, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 347
pias	375
PlusMinus PH-S	350
PlusMinus PZ-S	351
Pozidriv PZ	321, 338, 339, 340, 341, 342, 343, 344, 346, 347, 348, 349
Reduced shank diameter	319, 321, 340
Single Tap Bits	461
Slotted	376, 377, 378, 379
Snake Eye	400
Spanner	400
Square socket screws	388, 389, 390, 391
Stainless Steel	316, 326, 338, 344, 352, 358, 367, 376, 378, 380, 382, 388, 390, 438, 439
Stepped drill bits	461
TiN-coated	322, 341, 454
TORQ-SET®	392, 393, 394
TORX®	352, 353, 354, 355, 356, 358, 359, 360, 361, 362, 363, 364, 365
TORX® BO	366, 367
TORX® Wedge	357
TORX® with Safety Pin	357
TORX PLUS®	368, 369, 370
TORX PLUS® IPR	372, 373, 374
TRI-WING®	395

Bits with Holding Function

TORX®	354, 359

Bit Holder

Adjustable depth stop	425
BiTorsion	418
Combination HIOS&Halfmoon	420
Copper Beryllium Sleeve	424
Impaktor	410, 414

Bit Holder
- Quick Release Chuck 419, 420
- Rapidaptor 414, 415, 416, 417
- Rapidaptor Ring Magnet 417
- Rapidaptor Stainless Steel 414
- Retaining Ring 421
- Stainless Steel Sleeve 422, 423

Bit Sets
- Bit-Checks 216, 220, 434, 435, 436, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 465
- Bit-Safes 440, 448, 458
- BiTorsion 440, 441, 442, 443
- Diamond 444, 445, 446, 447
- Impaktor 434, 435, 436
- Metal 460
- Stainless 438, 439
- Universal 448, 449, 450, 451, 452, 453, 454, 455456, 457
- Wood 458, 459

Bit Sockets
- Hexagon socket 162
- Hexagon socket screws with Holding Function 162, 163, 183, 184, 205, 206
- Slotted 165
- TORX® with Holding Function 160, 161, 182, 204, 205

C

Chip lifter 69
Chiseldriver 28, 29, 30, 31, 60
Countersink Bits 461, 462

D

Diamond-coated Bits 317, 318, 319, 326, 328, 339, 346, 353, 376, 392, 393, 444, 445, 446, 447
Double-ended Bits 332
Drill bits 462, 463, 465

Alphabetical Index
All products from A to Z

E

Electronics Screwdrivers 66, 67, 68, 69, 70, 71, 72, 73, 80, 81, 82, 84
ESD Tools 82, 83, 84, 85, 473, 474, 475, 481, 483

F

Flagdrivers
- TORX® 61
- TORX PLUS® 61

G

Guide Sleeves 379

H

Halfmoon
- Bits 335, 364, 370, 373, 379, 386

Hex-Plus
- Bit Sockets 162
- Bit Sockets with Holding Function 162, 163, 183, 184, 205, 206
- Bits 380, 381, 382, 383, 384, 385, 386, 387
- L-Keys 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 256
- Screwdrivers 38

Hexagon socket screws
- Bits 380, 381, 382, 383, 384, 385, 386
- Bit Sockets 162
- Bit Sockets with Holding Function 162, 163, 183, 184, 205, 206
- L-Keys 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 256
- L-Keys extra short arm 243, 248
- Screwdrivers 38

Hexagon socket screws BO
- Bits 387

Hi-TORQUE
- Bits 397

HIOS
Bits 335, 336, 364, 365, 370, 398
Hose Clamp Screwdrivers 42

I

Impact Drivers 511
Impaktor
Bits 316, 326, 338, 344, 352, 358, 380, 382, 387, 388, 390, 434, 435, 436
Bit Holder 410, 414
Bit Sets 434, 435, 436
Insulated Tools 94, 95, 96, 97, 98, 99, 100, 102, 103, 104, 108, 109, 110, 111, 112, 113, 114, 122, 123, 126, 128, 129
with reduced blade diameter 94, 96, 97, 98, 104, 111, 112, 114, 115, 116, 117
Internal thread insertion tools 403

J

Joker 228, 229, 230, 231, 232

K

Koloss 212, 213
Kraftform Kompakt 10 262
Kraftform Kompakt 20 264, 266, 267, 290
Kraftform Kompakt 40 268
Kraftform Kompakt 50 269
Kraftform Kompakt 60 270, 271, 272, 273
Kraftform Kompakt 70 276
Kraftform Kompakt 100 278
Kraftform Kompakt Ratchet 288, 289, 290
Kraftform Kompakt user-specific sets 280, 281, 282
Kraftform Kompakt Vario 289, 292, 293, 294
Kraftform Kompakt VDE (insulated) 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118
Kraftform Micro 66, 67, 68, 69, 70, 71, 72, 73, 80, 81, 82, 84

Alphabetical Index
All products from A to Z

L

L-Keys
- extra short arm — 243, 248
- Hex-Plus — 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 256
- Hexagon socket screws — 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 256
- TORX® — 212, 250, 251, 252, 253, 254, 256
- TORX® BO — 212, 254
- with Holding Function TORX® — 240, 246, 250, 254, 256

M

Magnetizer
- Demagnetizer — 62

Microstix®
- Bits — 398
- Screwdrivers — 68, 82

Multipoint
- Bits — 396

N

Nutsetters — 42, 43, 51, 401, 402

O

Offset Screwdrivers — 257

P

Phillips PH
- Bits: 316, 317, 318, 319, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 347
- Bit Sockets: 164
- Screwdrivers: 22, 36, 54, 90

pias
- Bits: 375

PlusMinus PH-S
- Bits: 350
- Screwdrivers: 97, 98, 116

PlusMinus PZ-S
- Bits: 351
- Screwdrivers: 98, 116

Pozidriv PZ
- Bits: 321, 338, 339, 340, 341, 342, 343, 344, 346, 347, 348, 349
- Bit Sockets: 164
- Screwdrivers: 22, 37, 54, 90

R

Rack
- Kraftform: 63
- Kraftform Micro: 62

Rapidaptor
- Bit Holder: 414, 415, 416, 417
- Bit Holder Ring Magnet: 417
- Stainless Steel: 414

Ratchets
- Koloss: 212
- Koloss Accessories: 213
- Zyklop Accessories: 156, 166, 167, 169, 180, 186, 187, 196, 202, 203, 204, 205, 206, 208, 209
- Zyklop Hybrid: 194, 196
- Zyklop Metal: 144, 146, 152, 153, 154, 155, 176, 177, 178, 179, 198, 199, 200, 201
- Zyklop Mini: 216, 217, 218, 219, 220, 222
- Zyklop Mini Accessories: 223
- Zyklop Speed: 126, 144, 145, 146, 148, 149, 150, 155, 172, 173, 174, 190, 191, 192
- Zyklop VDE: 126, 128, 129

Alphabetical Index
All products from A to Z

R

Ratchet Wrenches 228, 229, 230, 231, 232
Reamer 62

S

Screwdrivers
- Hex-Plus 38
- Hexagon socket screws 38
- Phillips PH 22, 36, 54, 90
- PlusMinus PH-S 97, 98, 116
- Pozidriv PZ 22, 37, 54, 90
- Slotted 22, 34, 35, 54, 60, 90
- Square socket screws 23, 41
- TORQ-SET® 40
- TORX® 23, 39, 40, 51, 55
- TORX® BO 40, 51
- TORX PLUS® 40
- TORX PLUS® IPR 68, 81
- TRI-WING® 42
- Wood 60

Screwdrivers PlusMinus PH-S 97, 98
Screwdrivers PlusMinus PZ-S 98, 116
Screwdrivers with Holding Function
- TORX® 38, 50, 66, 80

Screwdriver Sets 45, 46, 48, 49, 50, 51, 56
Screwdriver Sets Big Pack 30, 45, 102
Screwdriver Sets Kraftform 2go 46, 102
Screwdriver Sets XXL 45, 46
Screw Gripper 63
Single Tap Bits 461
Slotted
- Bits 376, 377, 378, 379
- Bit Sockets 165
- Screwdrivers 22, 34, 35, 54, 60, 90

Snake Eye
- Bits 400

Sockets
with Holding Function 144, 155, 179, 202, 203
Soft-faced Hammers 514, 515
Spanner
Bits 400
Square socket screws
Bits 388, 389, 390, 391
Screwdrivers 23, 41
Stainless Steel Tools
Bitholding Screwdrivers 284
Bits 316, 326, 338, 344, 352, 358, 367, 376, 378, 380, 382, 388, 390, 438, 439
Bit Sets 438, 439
Kraftform Kompakt 270, 271
L-Keys 238, 239, 246
Nutsetters 401
Screwdrivers 22, 23, 24, 25, 90, 91
Stepped drill bits 461
Stubbies
Carburettor Screwdrivers 44
T-Handle Screwdrivers 76, 77
Thread drive Bits 333, 334, 348, 349, 362, 363
Tool-Check 218, 219, 220
Toolfinder Take it easy
Bit-Checks 434, 435, 436, 438, 440, 441, 442, 443, 444, 445, 446, 447
Bit-Safes 440
Bits 264, 316, 317, 318, 326, 327, 338, 339, 340, 344, 346, 352, 353, 354, 358, 376, 380, 382, 387
Bit Sockets 204, 205, 206
Joker 228, 229, 230, 231, 232
L-Keys 212, 238, 240, 241, 246, 247, 250, 251, 252, 253, 254
Ratchet Sets 144, 145, 146, 148, 149, 150, 152, 153, 154, 155, 172, 173, 174, 176, 177, 178, 179, 190, 191, 192, 194, 196, 198, 199, 200, 201, 216, 217, 218, 219, 220
Screwdrivers 22, 23, 24, 25, 34, 35, 36, 37, 38, 39, 45, 44, 45, 46, 48, 49, 50, 51, 90, 91, 94, 95, 96, 97, 98, 99102, 103, 104, 105
Sockets 156, 180, 202, 203

Alphabetical Index
All products from A to Z

T

TORQ-SET®
- Bits 392, 393, 394
- Screwdrivers 40

Torque Tools
- ESD 473, 474, 475, 481, 483
- Insert Tools 502, 503, 504, 505, 506, 507
- Torque-indicators 486, 487
- Torque Screwdrivers 108, 270, 472, 474, 476, 480, 482
- Torque Wrenches Click-Torque 492, 494, 495, 496, 497, 498, 499, 500
- VDE 108, 114

TORX®
- Bits 352, 353, 354, 355, 356, 358, 359, 360, 361, 362, 363, 364, 365
- Bits with Holding Function 354, 359
- Bits with Safety Pin 357
- Bit Sockets with Holding Function 160, 161, 182, 204, 205
- Flagdrivers 61
- L-Keys 212, 250, 251, 252, 253, 254, 256
- L-Keys with holding Function 240, 246, 250, 254, 256
- Screwdrivers 23, 39, 40, 51, 55
- Screwdrivers with holding Function 38, 50, 66, 80

TORX® BO
- Bits 366, 367
- L-Keys 212, 254
- Screwdrivers 40, 51

TORX PLUS®
- Bits 368, 369, 370
- Flagdrivers 61
- Screwdrivers 40

TORX PLUS® IPR
- Bits 372, 373, 374
- Screwdrivers 68, 81

TRI-WING®
- Bits 395
- Screwdrivers 42

U

Unlocking pin 196, 213

V

Vario 289, 292, 293, 294
Voltage tester 101

W

Wera 2go 300, 301, 303
Wera Star 62
Wooden Handle Screwdrivers 60

Z

Zyklop
- Accessories 156, 166, 167, 169, 180, 186, 187, 196, 202, 203, 204, 205, 206, 208, 209
- Hybrid 194, 196
- Metal 144, 146, 152, 153, 154, 155, 176, 177, 178, 179, 198, 199, 200, 201
- Mini 216, 217, 218, 219, 220, 222
- Mini Accessories 223
- Speed 126, 144, 145, 146, 148, 149, 150, 155, 172, 173, 174, 190, 191, 192
- VDE 126, 128, 129

Notes

Notes

Notes

Notes

Notes

Notes

Notes

Notes

Regional Contacts

Wera Werkzeuge GmbH

Korzerter Straße 21-25
42349 Wuppertal

+49 / (0)202 / 40 45 - 311
Fax: +49 / (0)202 / 40 36 34

E-Mail: info@wera.de

Germany

04654 Frohburg
Industrievertretung Jens Hiensch
+49 / (0)157 / 71 90 78 21
E-Mail: jens.hiensch@iv-hiensch.de

09326 Geringswalde
IMS Lonthoff
+49 / (0)1525 / 39 81 570
E-Mail: info@ims-lonthoff.de

10961 Berlin
Werksvertretung Peter Raschke
+49 / (0)177 / 74 90 484
E-Mail: raschke@wv-raschke.de

21465 Reinbek
Rosendahl & Koppel
Inh. Mark Petersen e.K.
+49 / (0)40 / 23 41 47
E-Mail: mark.petersen@roko-petersen.de

26160 Bad Zwischenahn
Ralf Saul
+49 / (0)4403 / 91 00 972
E-Mail: r.saul@wera.de

42111 Wuppertal
HKL Industrievertretungen GmbH
+49/(0)202 / 47 00 01
E-Mail: hkl@wera.de

42349 Wuppertal
Dirk Blasius - Verkaufsleiter NRW
+49 / (0)202 / 40 45 204
E-Mail: blasius@wera.de

58256 Ennepetal
Ulrich Hesselmann
+49 / (0)2333 / 83 92 37
E-Mail: ulrich.hesselmann@wera.de

64342 Seeheim-Jugenheim
Layer OHG
+49 / (0)6257 / 86 96 0
E-Mail: info@layer-ohg.de

78132 Hornberg
Industrievertretung Markus Haberstroh
+49 / (0)7833 / 955 54 86
E-Mail: m.haberstroh@haberstroh-industrievertretung.de

88489 Wain
Thorsten Schilder Handelsvertretung
+49 / (0)7353 / 528 48 74
E-Mail: thorsten.schilder@wera.de

90455 Nürnberg
Dietz OHG
+49 / (0)9129 / 90 57 50
E-Mail: dietz@wera.de

Europe

AT - 5412 Puch
Alpen-MayKestag GmbH
+43 / (0)662 / 44 901-0
E-Mail: verkauf@a-mk.com

B - 1600 Sint-Pieters-Leeuw
Beltracy S.A.
+32 / (0)2 / 54 36 890
E-Mail: info@beltracy.be

BG - 1421 Sofia
Mr. Nikola Ivanov
+359 / (0)2 / 96 31 900
E-Mail: weraw@mail.bg

CH - 1026 Denges
Metalsa SA
+41 / (0)21 / 80 45 050
E-Mail: info@metalsa.ch

CZ - 180 82 Praha 8
ABQ AGENCY s.r.o.
+420 / (0)2 / 28 38 41 981
E-Mail: info@abefekt.cz

DK - 2730 Herlev
HJS Værktøj A/S
+45 / 44 84 40 44
E-Mail: hjs@hjs.dk

Wera Iberia
C./Mogoda, 1-5 (Edificio Nodus)
Pno. Ind. Can Salvatella
E - 08210 Barberà del Vallès / Barcelona
+34 / 93 / 7 29 7-2 40
Fax: +34 / 93 / 7 29 7-2 41
E-Mail: juan.pires@weraspain.com

EST - 1415 Tallinn
AS Stokker
+372 / 6/20 11 11
E-Mail: timmo.eenmaa@stokker.com

EST - 12618 Tallinn
Toolmarketing OÜ
+372/6/09 64 36
E-Mail: info@toolmarketing.eu

Wera Outillages S.A.S.
13, rue Ampère
F - 67500 Haguenau
+33 9 72 61 16 52
E-Mail: info@wera-outillages.fr

FIN - 01511 Vantaa
Wihuri Oy Technical Trade
+358 / (0)20 / 51 02 364
E-Mail: info@wihuri.fi

Wera Tools UK Ltd.
Units 1 & 2, McGregor´s Way
Turnoaks Business Park
GB - Chesterfield S40 2WB
+44 / (0)1246 / 27 77 56
Fax: +44 / (0)1246 / 27 33 35
E-Mail: queries@wera-tools.co.uk

GR - 166 72 Vari
Costas J. Kessissoglou
+30 / 210 / 96 37 521
E-Mail: kessi@hol.gr

I - 20097 San Donato Milanese
Carlo Stechel & Figli srl
+39 / 02 52 77 71
E-Mail: wera@stechel.it

For more regional contacts please see
www.wera.de, www.weratools.com and www.wera-tools.co.uk

Regional Contacts

Europe

LT-69320 Klaipėdos raj.
UAB GITANA
+370 / 46 / 410881
E-Mail: info@gitana.lt

N - 0787 Oslo
MORGENSTIERNE verktøy AS
+47 / (0)22 / 49 28 00
E-Mail: tools@morgenstierne.no

NL - Nord
Gerard Kluck
+31 / 65 28 52 622
E-Mail: kluck@wera.de

NL - Süd
Wouter Steijvers
+31 / 65 28 50 162
E-Mail: steijvers@wera.de

PL - 61-306 Poznań
Agentools Sp. z o.o. Sp. k.
+48 / (0)61 / 87 19 000
E-Mail: info@agentools.pl

RO-400441 Cluj-Napoca
Mr. Victor Martes
+40 / 741 / 072 479
E-Mail: rominfocom@gmail.com

RUS - 119454 Moskau
KNIPEX OOO
+7 / 495 / 73 73 497
E-Mail: info@knipex.ru

RUS-143581 Moskau
ООО „ЦИТ“ ЦЕНТРОИНСТРУМЕНТ
+7- / 495 / 789 73 14/15
E-Mail: wera@centro-i.ru

S - 163 53 Spånga
Hansson & Frife AB
+46 / (0)8 / 76 02 510
E-Mail: hansson.frife@esma.se

SRB-11030 Beograd
ELTEC Export-Import d.o.o
+381 / 11 / 3555 - 065
E-Mail: E-Mail: info@eltec.rs

North America (Canada, USA, Mexico)

CA - Burlington, Ontario
Wera Tools Inc.
1 – 800 – 267 – 5541
E-Mail: info@weratools.com

CA - Burlington, Ontario
Wera Tools Inc.
1 – 800 – 267 – 5541
E-Mail: info@weratools.com

CA - Burlington, Ontario
Wera Tools Inc.
+ 1 – 905 – 637 – 0003
E-Mail: info@weratools.com

South America

AR - 1879 Buenos Aires
Quilmes Neumática S.A.
+54 / 11 42 50 03 65 int.21
E-Mail: rudi@quilmesneumatica.com

BR - 09601-000 São Bernardo do Campo-SP
DFG Comércio Importação
Exportação e Representação Ltda
+55 / 11 49 41 21 51
E-Mail: www.dfgferramentas.com.br

CL - Santiago de Chile
Comercial e Industrial Isesa S.A.
+56 / 23 62 70 00

Australia and Oceania

AU - Australia - 2147 Seven Hills
Cabac
+61 / 13 31 22
E-Mail: sales@cabac.com.au

NZ – 1060 Auckland
Ecco Pacific Ltd.
+64 0800 77 6969
E-Mail: sales@cabac.co.nz

NZ – 8023 Christchurch
Blacks Fasteners
+64-3-3652460
E-Mail: sydenham@blacksfasteners.co.nz

Asia

CN - 201206 Shanghai
KNIPEX Tools Co., Ltd.
+86 / 21 58 99 80 10
E-Mail: info@knipex.com.cn

Matfron Industrial Automatic
(Shanghai) Co., Ltd
+86 / 021 / 66 24 91 22
E-Mail: service@matfron.com

KR - 10463 Gyunggi-Do
LnJ Korea
+82 / 31 / 96 61 429
E-Mail: LNJ2100@ymail.com

KR - 08531 Seoul
Protool Co., LTD.
E-Mail: sejin@protool.co.kr

Wera Tools Japan G.K.
+81 70 4813 1142
E-Mail: frank.yang@wera.de

IN - 411001 Pune
Nikita Distributors & Extreme
Adventure Sports
+91 / 20 30 50 06 14
E-Mail: raman.jpa@gmail.com

IN – 600 125 Chennai
Rapidtec Enterprises
+91 994 036 6621
E-Mail: rapidtec2011@gmail.com

SG - 575625 Singapore
Wing Poh Hardware Pte Ltd
+65 / 62 50 05 23

TW - 114 Taipei City / Taiwan R.O.C
Inhand Corporation
+886 / 2 / 63 19 53 8

TW - 11483 Taipei / Taiwan R.O.C.
Duramet Corporation
+886 / 2 / 26 32 24 88

VN - Ho Chi Minh City, Vietnam
THE GIOI MOI EQUIPMENT AND ENGINEERING SOLUTION JOINT STOCK COMPANY (THE GIOI MOI JSC)
+84-28-66 80 88 75
E-Mail: thegioimoijscvn@gmail.com

Middle East

IL - Tel-Aviv 61573
Tenegal Agencies Ltd.
+972 / (0)3 / 56 17 411
E-Mail: menahem@tenegal.com

JO, LB, IR, SY, KW, BH, QA, OM, AE, SA, JE
KNIPEX Tools Middle East FZE
+971 / 48 87 85 56
E-Mail: info@knipex-tools.com

IR - 15866-45915 Tehran / Iran
Abzarsara Co.
+98 / 21 88 81 31 20
E-Mail: info@abzarsara.com

IR - 15866-45915 Tehran / Iran
FourSat Kish Co Ltd.
+98 / 21 88 60 24 84
E-Mail: arash.etminan@foursat.com

Which type of bit is needed for which job?



Impaktor-Bits

Impact-Bits are needed when a strong power tool (e.g. 18 volt impact screwdriver) is used. Impact bits were specifically developed to withstand high power tool forces.



TH-Bits

TH-Bits are hard bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.



Stainless Steel-Bits

Wera stainless steel bits are manufactured out of stainless steel so unsightly rust can be avoided. The stainless steel bits from Wera are vacuum ice-hardened and have the hardness and strength needed for screw connections. There are no limitations to the industrial applications they are suitable for.



J-Bits

J stands for Japan. J bits have been optimised to suit Asian PH screws. In particular, they are for use with very small dimensions as set out in the Japanese Camera Standard.



BDC-Bits

BDC-Bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits. The diamond coating lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head. B stands for BiTorsion. DC stands for diamond coated.



ACR®-Bits

ACR® stands for “anti-cam-out ribs”. ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® is a registered trademark of Phillips Screw Company.



BTH-Bits

BTH-Bits have an additional tempered BiTorsion zone, which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits.



TiN-Bits

TiN stands for titanium-nitrite. An extremely hard coating to withstand permanent loads such as during continual screwdriving operations in series manufacturing.



BTZ-Bits

BTZ-Bits have an additional tempered BiTorsion zone, which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone – something which enhances the service life of the bits.



DC-Bits

The diamond coating of the DC bits lowers the danger of slipping as the minute diamond particles literally “bite” themselves into the screw head.



TZ-Bits

TZ-Bits are tough bits with a torsion zone. Torsion bits absorb the damaging peak torque loads in the torsion zone. This prevents premature wear and enhances the service life of the bits.



Bits with reduced shaft diameter

Bits with reduced shaft diameter ensure that screws can be sunk without damaging the surface. This is particularly necessary in drywall construction applications.



A-Bits

A stands for aviation. A bits are particularly hard bits with a sharp-edged profile which e.g. penetrates screw profiles full of paint (such as on fuselage panels) ensuring a dependable transfer of force between the bit and the screw.

Imprint

Subject to technical modifications!
Any reprinting – even only excerpts – shall only be permissible with the prior written consent of the company Wera Werkzeuge GmbH.

Edition: EN 2018
Printed in Germany

Trademarks used:

ACR	Phillips Screw Company
ASSY	Adolf Würth GmbH & Co. KG
AW	Adolf Würth GmbH & Co. KG
HIOS	Totsu, Katsuyuki
Microstix	OSG System Products Co. Ltd.
Phillips Recess	Phillips Screw Company
Pozidriv	registered trademark for Phillips Screw Company in Canada, Mexico and in the USA; for Trifast plc in the UK
PZ	registered trademark for Phillips Screw Company in Canada, Mexico and in the USA
PZ1, PZ2, PZ3	registered trademark in the USA for Phillips Screw Company
Robertson	British Robertson S.L.U.
SDS plus	Robert Bosch GmbH
SIT	Adolf Würth GmbH & Co. KG
SPAX	SPAX International GmbH & Co. KG
T-STAR plus	SPAX International GmbH & Co. KG
TORQ-SET	Phillips Screw Company
TORX	Acument Intellectual Properties, LLC, Troy, Mich., US
TORX PLUS	Acument Intellectual Properties, LLC, Troy, Mich., US
TRI-WING	Phillips Screw Company

We reserve the right to modify without prior notification any details stated in this catalogue regarding product features, versions and designs.
No liability for printing errors or mistakes shall be assumed.



Contact us

All regions (except for North America, UK and Republic of Ireland)

Wera Werkzeuge GmbH · Germany
Korzerter Straße 21–25
D-42349 Wuppertal

Phone: +49 (0) 202 / 40 45-0
Fax: +49 (0) 202 / 40 36 34
E-Mail: info@wera.de

Internet:
www.wera.de

North America

Wera Tools Inc.
4129 Harvester Rd, Unit H
Burlington, Ontario
Canada, L7L 5M3

Phone: 1-800-267-55 41
E-Mail: info@weratools.com

Internet:
www.weratools.com

UK & Republic of Ireland

Wera Tools UK LTD
Units 1 & 2, McGregor‘s Way
Turnoaks Business Park, Chesterfield
Derbyshire, S40 2WB
Great Britain

Phone: +44 / (0) 12 46 / 27 77 56
E-Mail: queries@wera-tools.co.uk

Internet:
www.wera-tools.co.uk

05000001018

EN 05 500001 018 - 0052570 - 01

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Spanners ***category:***

Click to view products by Wera ***manufacturer:***

Other Similar products are found below :

74005 74008 1406504-3 1406504-4 1406504-5 1406504-7 1725859-2 9965 999-16625-001 G70515-18 1055265-1 1055267-1 1-1406504-0 1055787-1 DCH.91.251.PA TG70-18 TG70 G62748-11 DPH.99.005.2K DCP.91.045.TN 1055512-1 1055276-1 R282303020 TA-0456 DCA.91.149.0TN TA-0436 TA-0398 TOL-222901 74_Z-0-0-193 294GB-5069-17-N 74_Z-0-0-2 523200-4 294GB-5070-25-A 74_Z-0-0-79 294GB-5070-17-A 74_Z-0-0-321 TOL-171801 PR23350 1490262-2 9968 AC24VS 80117 DCN.91.149.0TK BT-A-6010CAGE R282340000 BT-BS-609WT BT-A-6000B R282303000 BT-BS-610R BT-BS-610RT