

**General Description**

The WSD3056DN is the highest performance trench Dual N-Ch MOSFET with extreme high cell density, which provide excellent  $R_{DS(on)}$  and gate charge for most of the synchronous buck converter applications.

The WSD3056DN meet the RoHS and Green Product requirement 100% EAS guaranteed with full function reliability approved.

**Features**


- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent  $CdV/dt$  effect decline
- 100% EAS Guaranteed
- Green Device Available

**Product Summary**

$B_{VDS}$	$R_{DS(on)}$	$I_D$
30V	13m $\Omega$	35A

**Applications**

- POL Applications
- MB / VGA / Vcore
- Load Switch
- SMPS 2nd SR

**DFN3X3 Dual Pin Configuration**

**Absolute Maximum Ratings @TA=25°C unless otherwise noted**

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	30	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current (Continuous) *AC	$T_C=25^\circ C$	35
		$T_C=100^\circ C$	22
$I_{DM}$	Drain Current (Pulse) *B	140	A
$P_D$	Power Dissipation	$T_C=25^\circ C$	27
EAS	Single Pulse Avalanche Energy	13	mJ
$R_{\theta JA}$	Thermal Resistance Junction to ambient	62	$^\circ C/W$
$R_{\theta JC}$	Thermal Resistance Junction to Case	4.6	$^\circ C/W$
$T_I/T_{STG}$	Operating Temperature/ Storage Temperature	-55~150	$^\circ C$


**Electrical Characteristics @ $T_A=25^{\circ}\text{C}$  unless otherwise noted**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
<b>Static</b>						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	30			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 30V, V_{GS} = 0V$			1	$\mu A$
$I_{GSS}$	Gate Leakage Current	$V_{GS} = \pm 20V, V_{DS} = 0V$			100	nA
<b>On Characteristics</b>						
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}, I_{DS} = 250\mu A$	1.2	1.8	2.5	V
$R_{DS(on)}$	Drain-Source On-state Resistance	$V_{GS} = 10V, I_D = 10A$		10	13	$m\Omega$
		$V_{GS} = 4.5V, I_D = 8A$		14	18	$m\Omega$
gFS	Forward Transconductance	$V_{DS} = 5V, I_D = 5A$		6		S
<b>Switching</b>						
Qg	Total Gate Charge	$V_{GS}=10V, V_{DS}=15V, I_D=5A$		7.2		nC
Qgs	Gate-Source Charge			2.3		nC
Qgd	Gate-Drain Charge			3		nC
td (on)	Turn-on Delay Time	$V_{GS}=10V, V_{DD}=15V, I_D=1A, R_G=6\Omega$		3.8		ns
tr	Turn-on Rise Time			10		ns
td(off)	Turn-off Delay Time			22		ns
tf	Turn-off Fall Time			6.6		ns
Rg	Gate resistance	$V_{GS}=0V, V_{DS}=0V, f=1MHz$		2.8		$\Omega$
<b>Dynamic</b>						
Ciss	Input Capacitance	$V_{GS}=0V, V_{DS}=15V, f=1MHz$		620		pF
Coss	Output Capacitance			85		pF
Crss	Reverse Transfer Capacitance			30		pF
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>						
$I_S$	Continuous Source Current	$V_G=V_D=0V, \text{ Force Current}$			35	A
$I_{SM}$	Pulsed Source Current <sup>3</sup>				70	A
$V_{SD}$	Diode Forward Voltage	$I_{SD} = 1A, V_{GS}=0V$			1.2	V


Note :

- 1, Repetitive Rating : Pulsed width limited by maximum junction temperature.
- 2,  $V_{DD}=25V, V_{GS}=10V, L=0.1mH, I_{AS}=16A, R_G=25$  ,Starting  $T_J=25^{\circ}\text{C}$ .
- 3, The data tested by pulsed , pulse width  $\cong 300us$  , duty cycle  $\cong 2\%$ .
- 4, Essentially independent of operating temperature.


**Typical Characteristics**




**Fig1.** Typical Output Characteristics




**Fig2.** Threshold Voltage Vs. Temperature




**Fig3.** Typical Transfer Characteristics



**Fig4.** Normalized On-Resistance Vs. Temperature




**Fig5.** Typical Source-Drain Diode Forward Voltage




**Fig6.** Maximum Safe Operating Area


**Typical Characteristics**




**Fig7.** Typical Capacitance Vs.Drain-Source Voltage




**Fig8.** Typical Gate Charge Vs.Gate-Source Voltage



**Fig9.** T1, Transient Thermal Response Curve



**Fig10.** Unclamped Inductive Test Circuit and waveforms



**Fig11.** Switching Time Test Circuit and waveforms



## Attention

- 1, Any and all Winsok power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Winsok power representative nearest you before using any Winsok power products described or contained herein in such applications.
- 2, Winsok power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Winsok power products described or contained herein.
- 3, Specifications of any and all Winsok power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- 4, Winsok power Semiconductor CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- 5, In the event that any or all Winsok power products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- 6, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Winsok power Semiconductor CO., LTD.
- 7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. Winsok power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- 8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the Winsok power product that you intend to use.
- 9, this catalog provides information as of Sep. 2014. Specifications and information herein are subject to change without notice.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [Winsok](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [NTNS3A92PZT5G](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#)  
[AOD464](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [751625C](#)  
[IPS70R2K0CEAKMA1](#) [BSF024N03LT3 G](#) [PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#)  
[EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMC2700UDMQ-7](#)  
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#)  
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [IRF40H233XTMA1](#) [IPSA70R950CEAKMA1](#) [IPSA70R2K0CEAKMA1](#) [STU5N65M6](#)  
[C3M0021120D](#) [DMN6022SSD-13](#)