





PARAMETER		TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-5	@20°C	0.035 ohms ±20%
D.C. RESISTANCE	2-3	@20°C	2.15 ohms ±10%
D.C. RESISTANCE	7–8	@20°C	0.025 ohms ±20%
INDUCTANCE	2-3	10kHz, 100mVAC, Ls	2.28mH ±10%
SATURATION CURRENT		20% rolloff from initial	300mA
LEAKAGE INDUCTANCE	2-3	tie(1+5, 7+8), 100kHz, 100mVAC, Ls	30uH typ., 45.0uH max.
DIELECTRIC RAIING	1-8	4500VAC, 1 second	4500VAC, 1 minute
DIELECTRIC RATING	2-8	4500VAC, 1 second	4500VAC, 1 minute
DIELECTRIC RATING	1-2	625VAC, 1 second	500VAC, 1 minute
TURNS RATIO		(2-3):(1-5)	12:1, ±2%
TURNS RATIO		(2-3):(8-7)	10.8:1, ±2%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC61558-2-17: - Reinforced insulation for a primary circuit at a working voltage of 400VDC.

PART MUST INSERT FULLY TO SURFACE A IN RECOMMENDED GRID #0.025 SQ.(9) [.64] .118/.158 [3.00/4.00] .630 MAX. [16.00]	DOT LOCATES TERM. #1 .960 MAX. [24.38] 750811023 WE-MIDCOM [20.32]
TERM. NO.'s FOR REF. ONLY	LOT CODE & DATE CODE
PRI 120-375V 66kHz	[1.42] [17.00] [5.00]
CANCEL 8V, 300mA	.138(4)
AUX	RECOMMENDED P.C. PATTERN, COMPONENT SIDE

REV. Packaging Specifications DATE Method: Tray PKG-0058 www.midcom-inc.com

3/09

CUSTOMER TERMINAL

Sn96%, Ag4%

RoHS

Yes

LEAD(Pb)-FREE

Yes

CONVENTION PLACEMENT SEE REVISION SHEET FOR REVISION LEVEL Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64

Decimals: ±.005 [.13] Footprint: ±.005 [.127] This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE

TRANSFORMER

eiSos p/n: **750811023**

PART NO.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Transformers category:

Click to view products by Wurth manufacturer:

Other Similar products are found below:

ET-030A F-102X F-120X F-14X-1 F-181U F-18A F-199U F-19X F-202U F-204U F-206U F-227X F-238U F-239U-1 F-23U F24-250-B
F-242U F-245U F-264U F-265U F-267U F-281U F-283U F-290X F-295Z F-296Z F-298Z F-3143P F-3298Z F-33U F-346X F-35U F364U F-392A F-395X F-397U F-412X F-47U F-55X-1 F-60U F-68U F-71U F-72Z F-74U F-83A F-84AC F-85U F-86U F-9U PCT-02