








RoHS

REV	ECN NO.	DESRPTION	DESIGN	APPROVAL	DATE
A1	NEW	更换图框			2024.04.17

SPECIFICATIONS
Current Rating: 10 Amps @ 500V AC
Temperature Rating: -40 °C to 125 °C
Insulator: Nylon , UL 94V-0
Contacts: Brass
Finish: Tin plated over Nickel
Fuse Size: 5.2x20mm FUSE BLOCK



PCB板



X.±0.50	X.°±	PART NO: XF-656		XFCN 兴飞连接器	
.X±0.25	.X°±				
.XX±0.15	.XX°±	TITLE: 5.2x20mm 保险丝座		0769-82001899	
.XXX±0.10	.XXX°±			www.xfconn.com	
UNITS:	mm			DWG NO: /	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF XFCN AND SHALL NOT BE REPRODUCED, COPIED OR CUED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF XFCN		APPD	Chen ZhiQiang		
		CHKD	Liu Wei	VIEW	
		DRAW	Chen HongJiang	SCALE	SHEET
		DATE	2024.08.26	NONE	REV
					1/1 A1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fuse Holder](#) category:

Click to view products by [XFCN](#) manufacturer:

Other Similar products are found below :

[0031.1351.01](#) [6SC30A2IC](#) [F30A3S](#) [F600A3B](#) [80910030](#) [80910080](#) [9-3557-GP REV A](#) [HFH-1](#) [RF30A1S](#) [RF30A2B](#) [RF30A3SP](#)
[15602-04-08-21](#) [HTJ-LES-FUSE](#) [2193](#) [2602](#) [2650](#) [F60A2SQ](#) [T30A2B](#) [G4PB8](#) [2660](#) [HKP-CCHH](#) [341001A](#) [348670](#) [CVRMCC](#) [4202](#) [4537](#)
[HPC](#) [55900008011](#) [345602-010](#) [345603-010](#) [345612](#) [345903A](#) [3833-5](#) [3833-7](#) [3992](#) [4393](#) [4409](#) [CCM630](#) [6SM30A1IC](#) [6T30A2S](#)
[T100A1B](#) [CJ630](#) [T400A1B](#) [BP/HHA-RP](#) [74-FH6](#) [6611HPJ](#) [E92/30CC](#) [03450632H](#) [BK/HTB-68M-R](#) [0101590](#)